
ztd.text

Release 0.0.0

ThePhD & Shepherd's Oasis, LLC

Jan 15, 2024

CONTENTS:

1 Who Is This Library For?	3
2 Indices & Search	461
Index	463

The premiere library for handling text in different encoding forms and reducing transcoding bugs in your C++ software.

WHO IS THIS LIBRARY FOR?

If:

- you want to convert from one Unicode encoding to another Unicode encoding;
- you want a no-overhead way to track and keep data in a specific encoding (Unicode-based or not);
- you want a no-memory-overhead way to archive;
- you want to prevent data in the wrong encoding from infiltrating your application and causing [Mojibake](#);
- you want to work with higher-level primitives (code points, graphemes) when iterating text that do not break your text apart;
- you want safe defaults for working with text;

then `ztd.text` is for you!

1.1 Quick ‘n’ Dirty Tutorial

1.1.1 Setup

Use of this library is officially supported through the use of [CMake](#). Getting an updated CMake is difficult on non-Windows machines, especially if they come from your system’s package manager distribution which tends to be several (dozen?) minor revisions out of date, or an entire major revision behind on CMake. To get a very close to up-to-date CMake, Python maintains a version that works across all systems. You can get it (and the ninja build system) by using the following command in your favorite command line application (assuming Python is already installed):

```
python -m pip install --user --update cmake ninja
```

If you depend on calling these executables using shorthand and not their full path, make sure that the Python “downloaded binaries” folder is contained with the `PATH` environment variable. Usually this is already done, but if you have trouble invoking `cmake --version` on your typical command line, please see the [Python pip install documentation for more details](#) for more information, in particular about the `--user` option.

If you do not have Python or CMake/ninja, you must get a recent enough version [directly from CMake](#) and build/install it.

1.1.2 Using CMake

Here's a sample of the `CMakeLists.txt` to create a new project and pull in `ztd.text` in the simplest possible way:

```

1 project(my_app
2     VERSION 1.0.0
3     DESCRIPTION "My application."
4     HOMEPAGE_URL "https://ztdtext.readthedocs.io/en/latest/quick.html"
5     LANGUAGES C CPP
6 )
7
8 include(FetchContent)
9
10 FetchContent_Declare(ztd.text
11     GIT_REPOSITORY https://github.com/soasis/text.git
12     GIT_SHALLOW    ON
13     GIT_TAG         main)
14 FetchContent_MakeAvailable(ztd.text)

```

This will automatically download and set up all the dependencies `ztd.text` needs (in this case, simply `ztd.cmake`, `ztd.platform`, `ztd.idk`, and `ztd.cuneicode`). You can override how `ztd.text` gets these dependencies using the standard `FetchContent` described in the [CMake `FetchContent` Documentation](#). One that happens, simply use CMake's `target_link_libraries(...)` to add it to the code:

```

1 # ...
2
3 file(GLOB_RECURSE my_app_sources
4     LIST_DIRECTORIES OFF
5     CONFIGURE_DEPENDS
6     source/*.cpp
7 )
8
9 add_executable(my_app ${my_app_sources})
10
11 target_link_libraries(my_app PRIVATE ztd::text)

```

Once you have everything configured and set up the way you like, you can then use `ztd.text` in your code, as shown below:

```

1 #include <ztd/text.hpp>
2
3 int main(int, char*[]) {
4     // overlong encoded null
5     // (https://ztdtext.rtf.d.io/en/latest/api/encodings/mutf8.html)
6     const char mutf8_text[]
7         = { 'm', 'e', 'o', 'w', '\xc0', '\x80', 'm', 'e', 'o', 'w', '!' };
8     const auto is_valid_mutf8_text
9         = ztd::text::validate_decodable_as(mutf8_text, ztd::text::compat_mutf8);
10
11     std::cout << "The input text is "
12               << (is_valid_mutf8_text.valid ? "valid " : "not valid ")
13               << "MUTF-8 text!" << std::endl;
14
15     return 0;

```

(continues on next page)

(continued from previous page)

}

Let's get started by digging into some examples!

Note: If you would like to see more examples and additional changes besides what is covered below, please do feel free to make requests for them [here!](#) This is not a very full-on tutorial and there is a lot of functionality that, still, needs explanation!

1.1.3 Transcoding

Transcoding is the action of taking data in one encoding and transforming it to another. `ztd.text` offers many ways to do this; here are a few different ways that have different expectations, needs, meanings, and tradeoffs.

Transcode between Unicode Encodings

Going from a Unicode Encoding to another Unicode Encoding just requires going through the `ztd::text::transcode` API. All you have to do after that is provide the appropriate `ztd::text::utf8`, `ztd::text::utf16`, or `ztd::text::utf32` encoding object:

```

1  #include <ztd/text.hpp>
2
3  #include <string>
4
5  int main(int, char*[]) {
6      constexpr const auto& input      = U"";
7      constexpr const auto& wide_input = L"";
8      // properly-typed input picks the right encoding automatically
9      std::u16string utf16_emoji_string
10         = ztd::text::transcode(input, ztd::text::utf16);
11     // explicitly pick the input encoding
12     std::u16string utf16_emoji_string_explicit
13         = ztd::text::transcode(input, ztd::text::utf32, ztd::text::utf16);
14     // must use explicit handler because "wide execution" may be
15     // a lossy encoding! See:
16     // https://ztdtext.rtf.io/en/latest/design/error%20handling/lossy%20protection.
17     ↪html
18     std::u16string utf16_korean_string_explicit
19         = ztd::text::transcode(wide_input, ztd::text::wide_execution,
20                                ztd::text::utf16, ztd::text::replacement_handler);
21     // result in the same strings, but different encodings!
22     ZTD_TEXT_ASSERT(utf16_emoji_string == utf16_emoji_string_explicit);
23     ZTD_TEXT_ASSERT(utf16_emoji_string == u "");
24     ZTD_TEXT_ASSERT(utf16_korean_string_explicit == u "");
25     return 0;
26 }

```

Transcode from Execution Encoding to UTF-8

The *execution encoding* is the encoding that comes with the system. It is typically the encoding that all locale data comes in, especially for e.g. command line parameters on Windows. To encode from such an encoding to the highly successful and popular UTF-8, you may use the same `ztd::text::transcode` as above with the appropriate `ztd::text::(compat_)utf8:`

```

1 #include <ztd/text.hpp>
2
3 #include <string>
4 #include <string_view>
5 #include <iostream>
6
7 int main(int argc, char* argv[]) {
8     if (argc < 1) {
9         return 0;
10    }
11    for (int i = 0; i < argc; ++i) {
12        // print each argument as its UTF-8 version
13        // the default error handler is the "replacement" error handler:
14        // anything unrecognized will use the usual replacement "".
15        std::string_view input = argv[i];
16        std::string utf8_string
17            = ztd::text::transcode(input, ztd::text::compat_utf8,
18                                   ztd::text::execution, ztd::text::replacement_handler);
19        // directly write to ouput (terminal) to prevent any internal conversions
20        // to/from an internal encoding while writing output
21        std::cout.write(utf8_string.data(), utf8_string.size());
22        // newline + flush
23        std::cout << std::endl;
24    }
25    return 0;
26 }
```

The `compat_` prefix is to make sure we are using the typedef definition of the templated `ztd::text::basic_utf8` that uses `char` units. This is helpful for working with legacy data streams. We use `std::cout.write(...)` explicitly to prevent as much direct interface from the terminal or locales as possible to write the data to the terminal, ensuring that on competent systems with reasonably up-to-date terminals will display out UTF-8 data untouched (and, hopefully, properly).

Transcoding with Output Container Controls

Occasionally, you need to:

- serialize to a container that isn't a `std::basic_string/std::(u8/16/32)string`;
- OR, you need to serialize to a container but you need to know if anything went wrong.

This is where the functions that are suffixed `_to` come into play, and where the template argument provided to the non-suffixed `ztd::text::transcode<...>(...)` come into play.

```

1 #include <ztd/text.hpp>
2
3 #include <vector>
4 #include <list>
```

(continues on next page)

(continued from previous page)

```

5 #include <deque>
6 #include <string>
7 #include <string_view>
8
9 int main(int, char*[]) {
10     constexpr const char32_t input[] = U"";
11     constexpr const std::u16string_view utf16_expected_output = u"";
12
13     // a vector instead of a std::u16string
14     std::vector<char16_t> utf16_emoji_vector
15         = ztd::text::transcode<std::vector<char16_t>>(input, ztd::text::utf16);
16
17     // a list (doubly-linked list) instead of a std::u16string
18     std::list<char16_t> utf16_emoji_list
19         = ztd::text::transcode<std::list<char16_t>>(input, ztd::text::utf16);
20
21     // insert into a std::deque, with additional return information
22     auto utf16_emoji_deque_result
23         = ztd::text::transcode_to<std::deque<char16_t>>(input, ztd::text::utf16);
24     // transcode_into_raw returns a ztd::text::transcode_result<...>
25     // which we can inspect for error codes and more!
26     // the error_code should be "ok"
27     ZTD_TEXT_ASSERT(
28         utf16_emoji_deque_result.error_code == ztd::text::encoding_error::ok);
29     // No errors should have occurred, even if they were "handled" and still
30     // returned "ok"
31     ZTD_TEXT_ASSERT(!utf16_emoji_deque_result.errors_were_handled());
32     // The input should be completely empty
33     ZTD_TEXT_ASSERT(utf16_emoji_deque_result.input.empty());
34
35     // The results should all be the same, despite the container!
36     ZTD_TEXT_ASSERT(
37         ztd::ranges::equal(utf16_emoji_vector, utf16_expected_output));
38     ZTD_TEXT_ASSERT(ztd::ranges::equal(utf16_emoji_list, utf16_expected_output));
39     ZTD_TEXT_ASSERT(ztd::ranges::equal(
40         utf16_emoji_deque_result.output, utf16_expected_output));
41     return 0;
42 }

```

The returned `ztd::text::transcode_result` from the `_to`-suffixed function gives more information about what went wrong, including the error count and any other pertinent information.

Transcoding into any Output View/Range

Sometimes, just picking the container to serialize into isn't enough. After all, in the above examples, space will be automatically allocated as the container is added to. This may not be desirable for memory-constrained environments, for places with strict performance requirements that cannot risk touching an allocator, and within tight loops even under normal desktop and server environments.

Therefore, the `_into` suffixed functions allow explicitly passing in a range to be written into that will keep writing into the available space between the range's begin and end (e.g., from a `std::vector`'s `.data()` to its `.data() + .size()`).

```

1  #include <ztd/text.hpp>
2
3  #include <ztd/idk/span.hpp>
4
5  #include <string>
6  #include <string_view>
7  #include <deque>
8
9  int main(int, char*[]) {
10     constexpr const ztd_char8_t input[] = u8"barkbark!";
11     constexpr const std::u16string_view expected_output = u"barkbark!";
12
13     // Get a deque with a pre-ordained size.
14     std::deque<char16_t> utf16_deque(expected_output.size());
15     // Subrange indicating available space to write into
16     auto utf16_deque_output_view
17         = ztd::ranges::make_subrange(utf16_deque.begin(), utf16_deque.end());
18     // SAFE by default: if the container runs out of space, will not write more!
19     auto utf16_deque_result = ztd::text::transcode_into(input, ztd::text::utf8,
20         utf16_deque_output_view, ztd::text::utf16, ztd::text::pass_handler,
21         ztd::text::pass_handler);
22
23     // Ensure that the error code indicates success.
24     ZTD_TEXT_ASSERT(
25         utf16_deque_result.error_code == ztd::text::encoding_error::ok);
26     // there were no errors handled for us while processing
27     ZTD_TEXT_ASSERT(!utf16_deque_result.errors_were_handled());
28     // We had (exactly enough) space.
29     ZTD_TEXT_ASSERT(ztd::ranges::equal(expected_output, utf16_deque));
30     // There is no more input or output space left
31     ZTD_TEXT_ASSERT(ztd::ranges::empty(utf16_deque_result.input));
32     ZTD_TEXT_ASSERT(ztd::ranges::empty(utf16_deque_result.output));
33
34     return 0;
35 }

```

The returned `ztd::text::transcode_result` from the `_into`-suffixed function gives more information about what went wrong, including the error count and any other pertinent information. If a pivot is not used (described in a below section), it will return a `ztd::text::pivotless_transcode_result` or a `ztd::text::stateless_transcode_result`, which just has a few less data members to describe what happened.

If there is not enough space, then extra writing will not be done and it will stop and return an error of `ztd::text::encoding_error::insufficient_output_space`:

```

1  #include <ztd/text.hpp>
2
3  #include <ztd/idk/span.hpp>
4
5  #include <string>
6  #include <string_view>
7
8  int main(int, char*[]) {
9     constexpr const ztd_char8_t input[] = u8"barkbark!";

```

(continues on next page)

(continued from previous page)

```

10  constexpr std::size_t input_last_exclamation_mark_index
11      = ztdc_c_string_array_size(input) - 1;
12  constexpr const std::u16string_view full_expected_output
13      = u"barkbark!";
14  constexpr std::size_t truncated_input_size = 15;
15  // string_view containing: "barkbark" (no ending exclamation point)
16  constexpr const std::u16string_view truncated_expected_output
17      = full_expected_output.substr(0, truncated_input_size);
18
19  // SAFE by default: if the string runs out of space, will not write more!
20  std::u16string truncated_utf16_string(truncated_input_size, u'\0');
21  // Span indicating available space to write into
22  ztd::span<char16_t> truncated_utf16_string_output(truncated_utf16_string);
23  auto truncated_utf16_string_result = ztd::text::transcode_into(input,
24      ztd::text::compat_utf8, truncated_utf16_string_output, ztd::text::utf16,
25      ztd::text::pass_handler, ztd::text::pass_handler);
26
27  // We only had space for sixteen UTF-16 code units; expect as much from output
28  ZTD_TEXT_ASSERT(truncated_expected_output == truncated_utf16_string);
29  // The sequence was correct, but there wasn't enough output space for the full
30  // sequence!
31  ZTD_TEXT_ASSERT(truncated_utf16_string_result.error_code
32      == ztd::text::encoding_error::insufficient_output_space);
33  ZTD_TEXT_ASSERT(truncated_utf16_string_result.errors_were_handled());
34  // There is no more output space
35  ZTD_TEXT_ASSERT(ztd::ranges::empty(truncated_utf16_string_result.output));
36  // There is still input left
37  ZTD_TEXT_ASSERT(!ztd::ranges::empty(truncated_utf16_string_result.input));
38  // We left only enough space for everything except the last '\0':
39  // check to see if that's what happened in the input
40  ZTD_TEXT_ASSERT(truncated_utf16_string_result.input[0] == '!');
41  ZTD_TEXT_ASSERT(truncated_utf16_string_result.input[0]
42      == input[input_last_exclamation_mark_index]);
43  // No copies of the input were made:
44  // points to the same data as it was given.
45  ZTD_TEXT_ASSERT(&truncated_utf16_string_result.input[0]
46      == &input[input_last_exclamation_mark_index]);
47
48  return 0;
49 }

```

Transcoding with Errors

Very often, text contains errors. Whether it's being interpreted as the wrong encoding or it contains file names or data mangled during a system crash, or it's just plain incorrect, bad data is a firm staple and constant reality for text processing. `ztd.text` offers many kinds of *error handlers*. They have many different behaviors, from doing nothing and stopping the desired encoding operation, to skipping over bad text and not doing anything, to adding replacement characters, and more.

The `ztd::text::default_handler`, unless configured differently, is to use replacement characters:

```

1  #include <ztd/text.hpp>
2
3  #include <string>
4  #include <string_view>
5
6  int main(int, char*[]) {
7      constexpr const char32_t input[] = U"Ba\xD800rk!";
8      // Equivalent to: u8"Bark!"
9      constexpr const char expected_default_output[] = "Ba\xef\xbf\xbdrk!";
10
11     std::string utf8_string_with_default
12         = ztd::text::transcode(input, ztd::text::compat_utf8);
13
14     ZTD_TEXT_ASSERT(utf8_string_with_default == expected_default_output);
15
16     auto utf8_string_with_default_result
17         = ztd::text::transcode_to(input, ztd::text::compat_utf8);
18     ZTD_TEXT_ASSERT(utf8_string_with_default_result.error_code
19         == ztd::text::encoding_error::ok);
20     ZTD_TEXT_ASSERT(utf8_string_with_default_result.errors_were_handled());
21     ZTD_TEXT_ASSERT(utf8_string_with_default_result.error_count == 1);
22     ZTD_TEXT_ASSERT(
23         utf8_string_with_default_result.output == expected_default_output);
24     ZTD_TEXT_ASSERT(ztd::ranges::empty(utf8_string_with_default_result.input));
25
26     return 0;
27 }

```

The `ztd::text::replacement_handler` explicitly inserts replacement characters where the failure occurs:

```

1  #include <ztd/text.hpp>
2
3  #include <string>
4  #include <string_view>
5
6  int main(int, char*[]) {
7      constexpr const char32_t input[] = U"Ba\xD800rk!";
8      constexpr const char expected_replacement_output[] = "Ba\xef\xbf\xbdrk!";
9
10     std::string utf8_string_with_replacement
11         = ztd::text::transcode(input, ztd::text::utf32, ztd::text::compat_utf8,
12             ztd::text::replacement_handler);
13
14     ZTD_TEXT_ASSERT(utf8_string_with_replacement == expected_replacement_output);
15
16     auto utf8_string_with_replacement_result
17         = ztd::text::transcode_to(input, ztd::text::utf32,
18             ztd::text::compat_utf8, ztd::text::replacement_handler);
19
20     ZTD_TEXT_ASSERT(utf8_string_with_replacement_result.error_code
21         == ztd::text::encoding_error::ok);
22     ZTD_TEXT_ASSERT(utf8_string_with_replacement_result.errors_were_handled());
23     ZTD_TEXT_ASSERT(utf8_string_with_replacement_result.error_count == 1);

```

(continues on next page)

(continued from previous page)

```

24     ZTD_TEXT_ASSERT(utf8_string_with_replacement_result.output
25         == expected_replacement_output);
26     ZTD_TEXT_ASSERT(
27         ztd::ranges::empty(utf8_string_with_replacement_result.input));
28
29     return 0;
30 }

```

To simply skip over bad input without outputting any replacement characters, use `ztd::text::skip_handler`:

```

1  #include <ztd/text.hpp>
2
3  #include <string>
4  #include <string_view>
5
6  int main(int, char*[]) {
7      constexpr const char32_t input[]          = U"Ba\xD800rk!";
8      constexpr const char expected_skip_output[] = "Bark!";
9
10     std::string utf8_string_with_skip = ztd::text::transcode(input,
11         ztd::text::utf32, ztd::text::compat_utf8, ztd::text::skip_handler);
12     ZTD_TEXT_ASSERT(utf8_string_with_skip == expected_skip_output);
13
14     auto utf8_string_with_skip_result = ztd::text::transcode_to(input,
15         ztd::text::utf32, ztd::text::compat_utf8, ztd::text::skip_handler);
16     ZTD_TEXT_ASSERT(utf8_string_with_skip_result.error_code
17         == ztd::text::encoding_error::ok);
18     ZTD_TEXT_ASSERT(utf8_string_with_skip_result.errors_were_handled());
19     ZTD_TEXT_ASSERT(utf8_string_with_skip_result.error_count == 1);
20     ZTD_TEXT_ASSERT(utf8_string_with_skip_result.output == expected_skip_output);
21     ZTD_TEXT_ASSERT(ztd::ranges::empty(utf8_string_with_skip_result.input));
22
23     return 0;
24 }

```

To stop in the middle of the operation and return immediately, employ the `ztd::text::pass_handler`. This will leave text unprocessed, but offer a chance to inspect what is left and any corrective action that might need to be taken afterwards:

```

1  #include <ztd/text.hpp>
2
3  #include <string>
4  #include <string_view>
5
6  int main(int, char*[]) {
7      constexpr const char32_t input[]          = U"Ba\xD800rk!";
8      constexpr const char expected_pass_output[] = "Ba";
9      constexpr const char32_t expected_pass_leftover_input[] = U"\xD800rk!";
10
11     std::string utf8_string_with_pass = ztd::text::transcode(input,
12         ztd::text::utf32, ztd::text::compat_utf8, ztd::text::pass_handler);
13

```

(continues on next page)

(continued from previous page)

```

14     ZTD_TEXT_ASSERT(utf8_string_with_pass == expected_pass_output);
15
16     auto utf8_string_with_pass_result = ztd::text::transcode_to(input,
17         ztd::text::utf32, ztd::text::compat_utf8, ztd::text::pass_handler);
18
19     ZTD_TEXT_ASSERT(utf8_string_with_pass_result.error_code
20         == ztd::text::encoding_error::invalid_sequence);
21     ZTD_TEXT_ASSERT(utf8_string_with_pass_result.errors_were_handled());
22     ZTD_TEXT_ASSERT(utf8_string_with_pass_result.error_count == 1);
23     ZTD_TEXT_ASSERT(utf8_string_with_pass_result.output == expected_pass_output);
24     ZTD_TEXT_ASSERT(ztd::ranges::equal(utf8_string_with_pass_result.input,
25         std::u32string(expected_pass_leftover_input)));
26
27     return 0;
28 }

```

Error handlers like the `ztd::text::skip_handler` and `ztd::text::replacement_handler` (and potentially the `ztd::text::default_handler`) are smart enough to not output multiple replacement characters for every single 8, 16, or 32-bit unit that contains an error, folding them down into one replacement character per distinct failure location:

```

1  #include <ztd/text.hpp>
2
3  #include <vector>
4  #include <list>
5  #include <deque>
6  #include <string>
7  #include <string_view>
8
9  int main(int, char*[]) {
10     // Scuffed UTF-8 input: 'C0' is not a legal sequence starter
11     // for regular, pure UTF-8
12     constexpr const char input[] = "Me\xC0\x9F\x90\xB1ow!";
13     constexpr const char32_t expected_skip_output[] = U"Meow!";
14
15     std::u32string utf32_string_with_skip = ztd::text::transcode(input,
16         ztd::text::compat_utf8, ztd::text::utf32, ztd::text::skip_handler);
17
18     ZTD_TEXT_ASSERT(utf32_string_with_skip == expected_skip_output);
19
20     auto utf32_string_with_skip_result = ztd::text::transcode_to(input,
21         ztd::text::compat_utf8, ztd::text::utf32, ztd::text::skip_handler);
22     ZTD_TEXT_ASSERT(utf32_string_with_skip_result.error_code
23         == ztd::text::encoding_error::ok);
24     ZTD_TEXT_ASSERT(utf32_string_with_skip_result.errors_were_handled());
25     ZTD_TEXT_ASSERT(utf32_string_with_skip_result.error_count == 1);
26     ZTD_TEXT_ASSERT(utf32_string_with_skip_result.output == expected_skip_output);
27     ZTD_TEXT_ASSERT(ztd::ranges::empty(utf32_string_with_skip_result.input));
28
29     return 0;
30 }

```

```

1  #include <ztd/text.hpp>

```

(continues on next page)

(continued from previous page)

```

2
3 #include <vector>
4 #include <list>
5 #include <deque>
6 #include <string>
7 #include <string_view>
8
9 int main(int, char*[]) {
10     // Scuffed UTF-8 input: 'C0' is not a legal sequence starter
11     // for regular, pure UTF-8!
12     constexpr const char input[] = "Me\xC0\x9F\x90\xB1ow!";
13     constexpr const char32_t expected_default_output[] = U"Meow!";
14
15     std::u32string utf32_string_with_default
16         = ztd::text::transcode(input, ztd::text::compat_utf8, ztd::text::utf32);
17
18     ZTD_TEXT_ASSERT(utf32_string_with_default == expected_default_output);
19
20     auto utf32_string_with_default_result = ztd::text::transcode_to(
21         input, ztd::text::compat_utf8, ztd::text::utf32);
22     ZTD_TEXT_ASSERT(utf32_string_with_default_result.error_code
23         == ztd::text::encoding_error::ok);
24     ZTD_TEXT_ASSERT(utf32_string_with_default_result.errors_were_handled());
25     ZTD_TEXT_ASSERT(utf32_string_with_default_result.error_count == 1);
26     ZTD_TEXT_ASSERT(
27         utf32_string_with_default_result.output == expected_default_output);
28     ZTD_TEXT_ASSERT(ztd::ranges::empty(utf32_string_with_default_result.input));
29
30     return 0;
31 }

```

```

1 #include <ztd/text.hpp>
2
3 #include <vector>
4 #include <list>
5 #include <deque>
6 #include <string>
7 #include <string_view>
8
9 int main(int, char*[]) {
10     // Scuffed UTF-8 input: 'C0' is not a legal sequence starter
11     // for regular, pure UTF-8
12     constexpr const char input[] = "Me\xC0\x9F\x90\xB1ow!";
13     constexpr const char32_t expected_replacement_output[] = U"Meow!";
14
15     std::u32string utf32_string_with_replacement
16         = ztd::text::transcode(input, ztd::text::compat_utf8, ztd::text::utf32,
17             ztd::text::replacement_handler);
18
19     ZTD_TEXT_ASSERT(utf32_string_with_replacement == expected_replacement_output);
20
21     auto utf32_string_with_replacement_result

```

(continues on next page)

(continued from previous page)

```

22     = ztd::text::transcode_to(input, ztd::text::compat_utf8,
23         ztd::text::utf32, ztd::text::replacement_handler);
24     ZTD_TEXT_ASSERT(utf32_string_with_replacement_result.error_code
25         == ztd::text::encoding_error::ok);
26     ZTD_TEXT_ASSERT(utf32_string_with_replacement_result.errors_were_handled());
27     ZTD_TEXT_ASSERT(utf32_string_with_replacement_result.error_count == 1);
28     ZTD_TEXT_ASSERT(utf32_string_with_replacement_result.output
29         == expected_replacement_output);
30     ZTD_TEXT_ASSERT(
31         ztd::ranges::empty(utf32_string_with_replacement_result.input));
32
33     return 0;
34 }

```

Compared to the `ztd::text::pass_handler`, which will stop at the first potential error:

```

1  #include <ztd/text.hpp>
2
3  #include <vector>
4  #include <list>
5  #include <deque>
6  #include <string>
7  #include <string_view>
8
9  int main(int, char*[]) {
10     // Scuffed UTF-8 input: 'C0' is not a legal sequence starter
11     // for regular, pure UTF-8
12     constexpr const char input[] = "Me\xC0\x9F\x90\xB1ow!";
13     constexpr const char32_t expected_pass_output[] = U"Me";
14     constexpr const char expected_pass_leftover_input[] = "\xC0\x9F\x90\xB1ow!";
15
16     std::u32string utf32_string_with_pass = ztd::text::transcode(input,
17         ztd::text::compat_utf8, ztd::text::utf32, ztd::text::pass_handler);
18
19     ZTD_TEXT_ASSERT(utf32_string_with_pass == expected_pass_output);
20
21     auto utf32_string_with_pass_result = ztd::text::transcode_to(input,
22         ztd::text::compat_utf8, ztd::text::utf32, ztd::text::pass_handler);
23     ZTD_TEXT_ASSERT(utf32_string_with_pass_result.error_code
24         == ztd::text::encoding_error::invalid_sequence);
25     ZTD_TEXT_ASSERT(utf32_string_with_pass_result.errors_were_handled());
26     ZTD_TEXT_ASSERT(utf32_string_with_pass_result.error_count == 1);
27     ZTD_TEXT_ASSERT(utf32_string_with_pass_result.output == expected_pass_output);
28     ZTD_TEXT_ASSERT(ztd::ranges::equal(utf32_string_with_pass_result.input,
29         std::string_view(expected_pass_leftover_input)));
30
31     return 0;
32 }

```

You can even *write your own custom error handlers*.

Transcoding with Input, Output and Pivot Controls

Occasionally, you need to perform a transcoding operation that has no extension point and needs to go through an intermediate transition phase first (like UTF-8 Intermediate UTF-32 Shift-JIS). Normally, ztd.text will create an internal, stack-based buffer (controllable with *preprocessor definitions*) to use as the intermediate. But sometimes you need to exercise control over even that, to keep memory usage predictable and stable in all situations. Enter the pivot parameter, which a user can use to give a custom buffer (any custom range) as the intermediate data holder:

```

1  #include <ztd/text.hpp>
2
3  #include <string>
4  #include <iterator>
5
6  int main(int, char*[]) {
7      constexpr const char16_t u16_data[]
8          = u""
9            u""
10           u""
11           u""
12           u""
13           u"1";
14
15     // must provide all arguments to get to the "pivot" part.
16     // decode and encode states to use
17     auto utf16_decode_state = ztd::text::make_decode_state(ztd::text::utf16);
18     auto shift_jis_encode_state
19         = ztd::text::make_encode_state(ztd::text::shift_jis_x0208);
20     // the output we're going to serialize into! We're using a std::back_inserter
21     // to just fill up our desired container (in this case, a std::string)
22     std::string shift_jis_string;
23     auto output_view
24         = ztd::ranges::unbounded_view(std::back_inserter(shift_jis_string));
25     // we're going to use a static buffer, but anything
26     // would work just fine, really, as the "pivot"
27     char32_t my_intermediate_buffer[256];
28     ztd::span<char32_t> pivot(my_intermediate_buffer);
29
30     // Perform the conversion!
31     auto shift_jis_result = ztd::text::transcode_into(u16_data, ztd::text::utf16,
32         output_view, ztd::text::shift_jis_x0208, ztd::text::replacement_handler,
33         ztd::text::replacement_handler, utf16_decode_state,
34         shift_jis_encode_state, pivot);
35
36
37     // Verify everything is in a state we expect it to be in!
38     // A Shift-JIS encoded character string.
39     constexpr const char expected_shift_jis_string[]
40         = "\x82\xb1\x82\xcc\x8d\x91\x82\xcc\x97\xf0\xe\x6a\x82\xcd\x90\xa2\xa"
41           "\x45\x82\xaa\x82\xdc\x82\xbe\x96\xa2\xa\xae\x90\xac\x82\xc5\x81\x41"
42           "\x90\x5f\x97\x6c\x82\xb7\x82\xe7\x82\xa2\x82\xc8\x82\xa9\x82\xc1\x82"
43           "\xbd\x82\xc6\x82\xb1\x82\xeb\x82\xa9\x82\xe7\x8e\x6e\x82\xdc\x82\xe9"
44           "\x81\x42\x8c\xbb\x8d\xdd\x82\xcc\x93\xfa\x96\x7b\x82\xcd\x81\x77\x90"
45           "\x5f\x97\x6c\x82\xcc\x8f\x5a\x82\xde\x93\x56\x8a\x45\x81\x78\x81\x77"

```

(continues on next page)

(continued from previous page)

```

46     "\x90\x6c\x8a\xd4\x82\xcc\x8f\x5a\x82\xde\x92\x6e\x8f\xe3\x81\x78\x81"
47     "\x77\x8e\x80\x8e\xd2\x82\xcc\x8f\x5a\x82\xde\x96\xbb\x8a\x45\x81\x78"
48     "\x82\xcc\x8e\x4f\x91\x77\x82\x99\x95\xaa\x82\xa9\x82\xea\x82\xc4\x82"
49     "\xa2\x82\xe9\x82\xaf\x82\xea\x82\xc7\x81\x41\x82\xbb\x82\xcc\x8d\xa0"
50     "\x82\xcd\x82\xdc\x82\xbe\x8b\x43\x91\xcc\x82\xc6\x8c\xc5\x91\xcc\x82"
51     "\xb7\x82\xe7\x95\xaa\x82\xa9\x82\xea\x82\xc4\x82\xa2\x82\xc8\x82\xad"
52     "\x82\xc4\x81\x41\x83\x4a\x83\x49\x83\x58\x8f\xf3\x91\xd4\x82\xcc\x90"
53     "\xa2\x8a\x45\x82\xaa\x82\xc7\x82\xb1\x82\xdc\x82\xc5\x82\xe0\x82\xc7"
54     "\x82\xb1\x82\xdc\x82\xc5\x82\xe0\x8d\x4c\x82\xaa\x82\xc1\x82\xc4\x82"
55     "\xa2\x82\xe9\x82\xbe\x82\xaf\x82\xbe\x82\xc1\x82\xbd\x81\x42\x82\xbb"
56     "\x82\xea\x82\xa9\x82\xe7\x92\xb7\x81\x5b\x81\x5b\x82\xa2\x92\xb7\x81"
57     "\x5b\x81\x5b\x81\x5b\x82\xa2\x8e\x9e\x8a\xd4\x82\xaa\x8c\x6f\x82\xc1"
58     "\x82\xbd\x82\xa0\x82\xe9\x93\xfa\x81\x41\x82\xd3\x82\xa2\x82\xc9\x93"
59     "\x56\x82\xc6\x92\x6e\x82\xaa\x95\xaa\x82\xa9\x82\xea\x82\xbd\x81\x42"
60     "\x82\xb7\x82\xe9\x82\xc6\x81\x41\x82\xc7\x82\xb1\x82\xa9\x82\xe7\x82"
61     "\xc6\x82\xe0\x82\xc8\x82\xad\x93\x56\x82\xc9\x31\x90\x6c\x82\xcc\x90"
62     "\x5f\x97\x6c\x82\xaa\x81\x41\x82\xc8\x82\xe8\x82\xc8\x82\xe8\x82\xc6"
63     "\x90\xb6\x82\xdc\x82\xea\x82\xc4\x82\xab\x82\xbd\x81\x42";
64
65     ZTD_TEXT_ASSERT(shift_jis_result.error_code == ztd::text::encoding_error::ok);
66     ZTD_TEXT_ASSERT(!shift_jis_result.errors_were_handled());
67     ZTD_TEXT_ASSERT(
68         shift_jis_result.pivot_error_code == ztd::text::encoding_error::ok);
69     ZTD_TEXT_ASSERT(shift_jis_result.pivot_error_count == 0);
70     ZTD_TEXT_ASSERT(ztd::ranges::empty(shift_jis_result.input));
71     ZTD_TEXT_ASSERT(shift_jis_string == expected_shift_jis_string);
72     return 0;
73 }

```

Here, we use an **exceptionally** small buffer to keep memory usage down. Note that the buffer should be at least as large as `ztd::text::max_code_points_v<FromEncoding>` (`FromEncoding` in this case being the `ztd::text::compat_utf8` encoding) so that no *"insufficient output size" errors* occur during translation. (For `ztd::text::encode` operations, the buffer should be at least as large as `ztd::text::max_code_units_v<FromEncoding>`) If the pivot buffer is too small this can produce unpredictable failures and unexpected behavior from unanticipated errors, so make sure to always provide a suitably-sized pivot buffer! Or, alternatively, just let the implementation use its defaults, which are (generally) tuned to work out well enough for most conversion routines and platforms.

1.1.4 Encoding & Decoding

Encoding and decoding look identical to *Transcoding*, just using the functions `ztd::text::decode` and `ztd::text::encode` functions. `ztd::text::decode` will always produce a sequence of the encoding's code point type (`ztd::text::code_point_t<some_encoding_type>`). `ztd::text::encode` will always produce a sequence of the encoding's code unit type (`ztd::text::code_unit_t<some_encoding_type>`), and the lower-level functions ending in `_to` and `_into` will produce a `ztd::text::encode_result` (for encoding) or `ztd::text::decode_result` (for decoding):

```

1 #include <ztd/text.hpp>
2
3 #include <string>
4
5 int main(int, char* []) {

```

(continues on next page)

(continued from previous page)

```

6     const char input[]
7         = "\xbe\x8\xb3\xe7\x2c\x20\xbf\x0\xb4\xc3\xc0\xba\x20\xc1\xc1\xc0\xba"
8           "\x20\xb3\xaf\x0\xc\xbf\xa1\xbf\xe4\x21";
9
10    // Decode, with result to check!
11    auto korean_decoded_output_result
12        = ztd::text::decode_to(input, ztd::text::euc_kr_uhc);
13    ZTD_TEXT_ASSERT(korean_decoded_output_result.error_code
14                    == ztd::text::encoding_error::ok);
15    ZTD_TEXT_ASSERT(!korean_decoded_output_result.errors_were_handled());
16    ZTD_TEXT_ASSERT(ztd::ranges::empty(korean_decoded_output_result.input));
17    const std::u32string& korean_decoded_output
18        = korean_decoded_output_result.output;
19
20    // Take decoded Unicode code points and encode it into UTF-8
21    auto korean_utf8_output_result
22        = ztd::text::encode_to(korean_decoded_output, ztd::text::compat_utf8);
23    ZTD_TEXT_ASSERT(
24        korean_utf8_output_result.error_code == ztd::text::encoding_error::ok);
25    ZTD_TEXT_ASSERT(!korean_utf8_output_result.errors_were_handled());
26    ZTD_TEXT_ASSERT(ztd::ranges::empty(korean_utf8_output_result.input));
27    const std::string& korean_utf8_output = korean_utf8_output_result.output;
28    // verify that what we got out in UTF-8 would be the same if we converted
29    // it back to EUC-KR.
30    ZTD_TEXT_ASSERT(ztd::ranges::equal(std::string_view(input),
31        ztd::text::transcode(korean_utf8_output, ztd::text::compat_utf8,
32        ztd::text::euc_kr_uhc, ztd::text::pass_handler)));
33    // A korean greeting!
34    std::cout.write(korean_utf8_output.data(), korean_utf8_output.size());
35    std::cout << std::endl;
36
37    return 0;
38 }

```

Encode and decode operations are part of each encoding, represented by its encoding type. Every encoding object natively understands how to go from a sequence of its encoded data to its decoded data, and vice-versa, with the `encode_one` and `decode_one` functions. One should not call these functions directly, however, and instead used the above-provided functions. Because decode and encode operations do not feature intermediate steps, there is no `ztd::text::pivot<...>` for these functions.

1.1.5 Counting

Counting is done using the `ztd::text::count_as_decoded`, `ztd::text::count_as_encoded`, and `ztd::text::count_as_transcoded`. As the names imply, it yields the number of code points or code units that will result from an attempted encode, decode, or transcode operation in a sequence of text. It will return a `ztd::text::count_result` detailing that information:

```

1 #include <ztd/text.hpp>
2
3 #include <iostream>
4

```

(continues on next page)

```

5  int main(int, char*[]) {
6      const char input[]
7          = " OSSL  s s RFC ss  "
8            "-cqj0qgheba6zgdehbb85bfc31d5m2evf4423k0a7nd6abq3flcampfa17ac5froq64c0"
9            "a2a7nbcyjnb1b7yp96t0e31nkf95i";
10     std::vector<char32_t> output(256);
11     auto counting_result
12         = ztd::text::count_as_decoded(input, ztd::text::punycode);
13     ZTD_TEXT_ASSERT(counting_result.error_code == ztd::text::encoding_error::ok);
14     ZTD_TEXT_ASSERT(!counting_result.errors_were_handled());
15     if (counting_result.count > 256) {
16         std::cerr << "The input punycode exceeds the IDNA limited size buffer: "
17                   "change parameters to allocate a larger one!"
18                   << std::endl;
19         return 1;
20     }
21     output.resize(counting_result.count);
22     auto decoding_result = ztd::text::decode_into_raw(
23         input, ztd::text::punycode, ztd::span<char32_t>(output));
24     std::size_t decoding_result_count
25         = decoding_result.output.data() - output.data();
26     ZTD_TEXT_ASSERT(decoding_result.error_code == ztd::text::encoding_error::ok);
27     ZTD_TEXT_ASSERT(!decoding_result.errors_were_handled());
28     ZTD_TEXT_ASSERT(ztd::ranges::empty(decoding_result.input));
29     ZTD_TEXT_ASSERT(decoding_result_count == counting_result.count);
30
31     // Show decoded punycode (translate to UTF-8 to print to console)
32     std::cout << "Decoded punycode code points:\n\t";
33     for (const auto& code_point : output) {
34         std::cout << std::hex << std::showbase
35                   << static_cast<uint_least32_t>(code_point) << " ";
36     }
37     std::cout << "\n" << std::endl;
38
39     std::cout << "Decoded punycode as UTF-8:\n\t";
40     ztd::text::encode_view<ztd::text::utf8_t> print_view(
41         std::u32string_view(output.data(), decoding_result_count));
42     for (auto u8_code_unit : print_view) {
43         std::cout.write(reinterpret_cast<const char*>(&u8_code_unit), 1);
44     }
45     std::cout << std::endl;
46
47     return 0;
48 }

```

Getting counts is essential to being able to size allocated buffers for exactly what is necessary, or make use of small buffer optimizations by checking sizes before potentially spilling over into larger allocations.

1.1.6 Validation

Validation is checking whether or not the input sequence can be encoded, decoded, or transcoded to by (and to) the given encoding. It works through the `ztd::text::validate_decodable`, `ztd::text::validate_encodable`, and `ztd::text::validate_transcodable` functions.

```

1  #include <ztd/text.hpp>
2
3  #include <string_view>
4
5  int main(int, char*[]) {
6      constexpr const std::u32string_view input = U"meowmoew!";
7
8      // At compile-time: returns a structure with (explicit) operator bool
9      // to allow it to be used with ! and if() statements
10     static_assert(!ztd::text::validate_encodable_as(input, ztd::text::ascii),
11                  "Unfortunately, ASCII does not support emoji.");
12
13     // At run-time: returns a structure
14     auto validate_result
15         = ztd::text::validate_encodable_as(input, ztd::text::ascii);
16
17     // Check if the result is valid (should not be valid).
18     if (validate_result) {
19         // Everything was verified (not expected! )
20         std::cerr << "Unexpectedly, the input text was all valid ASCII."
21                 << std::endl;
22         return 1;
23     }
24
25     // Otherwise, everything was not verified (expected! )
26     std::cout << "As expected, the input text was not valid ASCII."
27              << "\n"
28              << "Here are the unicode hex values of the unvalidated UTF-32 code "
29              << "points:\n\t";
30     // use the structure to know where we left off.
31     std::u32string_view unused_input(
32         validate_result.input.data(), validate_result.input.size());
33     for (const auto& u32_codepoint : unused_input) {
34         std::cout << "0x" << std::hex
35                 << static_cast<uint_least32_t>(u32_codepoint);
36         if (&u32_codepoint != &unused_input.back()) {
37             std::cout << " ";
38         }
39     }
40     std::cout << std::endl;
41     return 0;
42 }

```

1.1.7 There's More!

There is more you can do with this library, from *authoring your own encoding objects/types* to *taking control of the performance of conversions*. More will be added to this Getting Started as time goes on, but if you have any inkling of something that should work, give it a try! If it fails in a way you don't think is helpful, please let us know through any of our available communication channels so we can assist you!

1.2 Users in the Wild

None have come and told us about their usage, yet!

If you use the library to any success, please do not hesitate to reach out to opensource@soasis.org!

1.3 Glossary of Terms & Definitions

Occasionally, we may need to use precise language to describe what we want. This contains a list of definitions that can be linked to from the documentation to help describe key concepts that are useful for the explication of the concepts and ideas found in this documentation.

character

This word carries with it 2 meanings, thanks to C-style languages and their predecessors. Sometimes, `chars`, `wchar_ts`, `char8_ts`, and similar are called “narrow character”s, “wide character”s, “UTF-8 characters” and similar. This is the result of a poor legacy in software and hardware nomenclature. These are not character types, but rather types that `_may_` represent the abstract notion of a character but frequently, and often, do not. After all, you wouldn't be here reading this if it did and non-English wasn't busted in your application, now would you?

The other definition is just an abstract unit of information in human languages and writing. The closest approximation that Unicode has for the human language/writing character is a *Grapheme Cluster*.

code point

A single unit of decoded information. Most typically associated with *unicode code points*, but they can be other things such as *unicode scalar values* or even a 13-bit value.

Note that a single code point does not imply a “*character*”, as that is a complex entity in human language and writing that cannot be mapped easily to a single unit of decoded information.

code unit

A single unit of encoded information. This is typically, 8-, 16-, or 32-bit entities arranged in some sequential fashion that, when read or treated in a certain manner, end up composing higher-level units which make up readable text. Much of the world's most useful encodings that encode text use multiple code units in sequence to give a specific meaning to something, which makes most encodings variable length encodings.

decode

Converting from a stream of input, typically code units, to a stream of output, typically code points. The output is generally in a form that is more widely consumable or easier to process than when it started. Frequently, this library expects and works with the goal that any decoding process is producing *unicode code points* or *unicode scalar values* from some set of *code units*.

encode

Converting from a stream of input, typically code points, to a stream of output, typically code units. The output may be less suitable for general interchange or consumption, or is in a specific interchange format for the interoperation. Frequently, this library expects and works with the goal that any decoding process is producing *unicode code points* or *unicode scalar values* from some set of *code units*.

encoding

A set of functionality that includes an encode process or a decode process (or both). The encode process takes in a stream of code points and puts out a stream of code units. The decode process takes in a stream of code units and puts out a stream of code points. In a concrete sense, there are a number of additional operations an encoding needs: see the *Lucky 7 design concept*.

execution encoding

The locale-based encoding related to “multibyte characters” (C and C++ magic words) processed during program evaluation/execution. It is directly related to the `std::set_locale(LC_CTYPE, ...)` calls. Note that this is different from *literal encoding*, which is the encoding of string literals. The two may not be (and many times, are not) the same.

grapheme cluster

The closest the Unicode Standard gets to recognizing a *human-readable and writable character*, grapheme cluster’s are arbitrarily sized bundles of *unicode code points* that compose of a single concept that might match what a “*character*” is in any given human language.

indivisible unit of work

A single unit of transcoding effort when going from one encoding to another that consumes the smallest possible input to produce an output, to change the state, to both produce an output and change the state, or to produce an error. Unlike *unicode code points* or *unicode scalar values*, indivisible units of work do not have a fixed width or fixed definition and are dependent on the two encodings involved in the transcoding operation being performed.

injective

An operation which can map all input information to an output. This is used for this library, particularly, to determine whether an operation is lossy (loses information) or not. For example, UTF-8 to UTF-32 is an injective operation because the values in a UTF-8 encoding are preserved in a UTF-32 encoding. UTF-16 to GB18030 is also an injective operation. But, converting something like Latin-1 to ASCII is a lossy operation, or UTF-8 to SHIFT-JIS.

literal encoding

The encoding of string literals (“”) during constant evaluation. This is usually controlled by command line arguments (MSVC and GCC) or fixed during compilation (Clang as UTF-8, *though that may change*). Typically defaults to the system’s “locale” setting.

mojibake

(Japanese: Pronunciation: [modibake] “unintelligible sequence of characters”.) From Japanese (moji), meaning “character” and (bake), meaning change, is an occurrence of incorrect unreadable characters displayed when computer software fails to render text correctly to its associated character encoding.

transcode

Converting from one form of encoded information to another form of encoded information. In the context of this library, it means going from an input in one *encoding*’s code units to an output of another encoding’s code units. Typically, this is done by invoking the *decode* of the original encoding to reach a common interchange format (such as *unicode code points*) before taking that intermediate output and piping it through the *encode* step of the other encoding. Different transcode operations may not need to go through a common interchange, and may transcode “directly”, as a way to improve space utilization, time spent, or both.

unicode code point

A single unit of decoded information for Unicode. It represents the smallest, non-encoded, and indivisible piece of information that can be used to talk about higher level algorithms, properties, and more from the Unicode Standard.

A unicode code point has been reserved to take at most 21 bits of space to identify itself.

A single unicode code point is NOT equivalent to a *character*, and multiple of them can be put together or taken apart and still have their sequence form a “*character*”. For a more holistic, human-like interpretation of code points or other data, see *grapheme clusters*.

unicode scalar value

A single unit of decoded information for Unicode. It's definition is identical to that of *unicode code points*, with the additional constraint that every unicode scalar value may not be a "Surrogate Value". Surrogate values are non-characters used exclusively for the purpose of encoding and decoding specific sequences of code units, and therefore carry no useful meaning in general interchange. They may appear in text streams in certain encodings: see *Wobbly Transformation Format-8 (WTF-8)* for an example.

wide execution encoding

The locale-based encoding related to "wide characters" (C and C++ magic words) processing during program evaluation/execution. It is directly related to the `std::set_locale(LC_CTYPE, ...)` calls. Note that this is different from the *wide literal encoding*, which is the encoding of wide string literals. The two may not be (and many times, are not) the same. Nominally, wide string literals are usually not like this, but there are a handful of compilers where they use neither UTF-16 or UTF-32 as the wide execution encoding, and instead use, for example, [EUC-TW](#).

wide literal encoding

The encoding of wide string literals (L"") during constant evaluation. This is usually controlled by command line arguments (GCC) or fixed during compilation (Clang as UTF-32, [though that may change](#)). Typically defaults to the system's "locale" setting.

1.4 Design Goals and Philosophy

The goal of this library are to

- enable people to write new code that can properly handle encoded information, specifically text;
- offer them effective means to convert that information in various ways;
- impose no run-time overhead compared to writing the code by hand; and
- statically track encodings, where possible, to make lossless or bad conversions a compile time error rather than a runtime problem;

These four goals inform the design of the library to its deepest levels and helps us go through the following important tenets:

1.4.1 First Principles - "Lucky 7" and a Liberation-First Design

One of the core premises of this library is that any text in one encoding can be converted to another, without having to know anything about external encodings. This is how the library achieves infinite extensibility! We start by noting that almost any encoding conversion can be done so long as there is an intermediary that exists between the source and the destination. For encoded text, this is the line between code units (`code_unit` for code) and code points (`code_point` for code).

Code units are single elements of a linear sequence of encoded information. That could be a sequence of bytes, a sequence of 16-bit numbers, and more. A sequence of code units is typically specific to the encoding it has and is generally impossible to reason about in a general or generic sense.

Code points are single elements of a linear sequence of information that have been decoded. They are far more accessible because they are generally an agreed upon interchange point that most others can access and reason about.

We leverage that, for text, **Unicode Code Points** are an agreed upon interchange format, giving rise to this general framework for encoding and decoding text:

The way to tap into this concept is to create an object that models an encoding concept, which is commonly referred to as the "Lucky 7" concept. The concept leverages a technique that has been used at least since the early days of Bruno Haible's and Daiko Ueno's `iconv` library, but formalizes it for interacting between 2 encodings.




Fig. 1: The generic pathway from one encoding to another for most (all?) text Encodings.

We call this concept the **Lucky 7**.

Lucky 7

Lucky 7 is a conceptual idea a single encoding object is all you need to write to fulfill your end of the encoding bargain. It is called the Lucky 7 because only 7 things are required from you, as the author of the encoding object, to get started:

- 3 type definitions (`code_point`, `code_unit`, `state`)
- 2 static member variables (`max_code_points`, `max_code_units`)
- 2 functions (`encode_one`, `decode_one`)

```

1 #include <cstdint>
2 #include <span>
3
4 struct empty_struct {};
5
6 struct utf_ebcdic {
7     // (1)
8     using code_unit = char;
9     // (2)
10    using code_point = char32_t;
11    // (3)
12    using state      = empty_struct;
13
14    // (4)
15    static constexpr inline std::size_t max_code_points = 1;
16    // (5)
17    static constexpr inline std::size_t max_code_units  = 6;
18
19    // (6)
20    ue_encode_result encode_one(
21        ztd::span<const code_point> input,
22        ztd::span<code_unit> output,
23        state& current,
24        ue_encode_error_handler error_handler
25    );
26
27    // (7)
28    ue_decode_result decode_one(
29        ztd::span<const code_unit> input,
30        ztd::span<code_point> output,
31        state& current,
32        ue_decode_error_handler error_handler
33    );
34 };

```

There are some supporting structures here that we will explain one by one, but this is the anatomy of a simple encoding object that you and others can define to do this job. This anatomy explicitly enables some basic work:

- encoding a single indivisible unit of work from *code points* to *code units*
- decoding a single indivisible unit of work from *code units* to *code points*
- transcoding a single indivisible unit of work from the source encoding's *code units* to the destination encoding's *code code units*, if they share a common *code point type*.

From these 3 operations above, everything else on this library can be built.

Breaking it Down

The first three typedefs are what let internal and external machinery know what kind of values you expect out of the ranges that go into the `decode_one` and `encode_one` function calls:

- `code_unit` - the input for decoding (`decode_one`) operations and the output for encode operations.
- `code_point` - the input for encode operations and the output for decoding (`decode_one`) operations.

`char` is the code unit type that the ranges work with for incoming and outgoing encoded data. `char32_t` is the code point type that the ranges use for incoming and outgoing decoded data. Given those, that gives us the ability to define the result types we will be working with.

Result Types

Result types are specific structs in the library that mark encode and decode operations. They can be used by composing with the templated type `ztd::text::decode_result` and `ztd::text::encode_result`.

```

1 #include <ztd/text/encode_result.hpp>
2 #include <ztd/text/decode_result.hpp>
3
4 using ue_decode_result = ztd::text::decode_result<
5     ztd::span<const char>,
6     ztd::span<char32_t>,
7     empty_struct
8 >;
9
10 using ue_encode_result = ztd::text::encode_result<
11     ztd::span<const char32_t>,
12     ztd::span<char>,
13     empty_struct
14 >;

```

These result structures are returned from the lowest level encode and decode operations. They contain:

- An `input` member, which is the range that is passed into the `decode_one` and `encode_one` functions;
- An `output` member;
- A `state` member, which is a reference to the state that was passed in to the `decode_one` or `encode_one` functions;
- An `error_code` member, which is an enumeration value from `ztd::text::encoding_error`; and
- An `error_count` member, which is an unsigned integral (`std::size_t`) value that says whether or not the given `error_handler` was invoked and how many times
- An `errors_were_handled()` member function, which returns a boolean value indicating whether `error_count` is greater than 0.

These variables can be used to query what exactly happened during the operation (`error_code` and `error_count`), inspect any state passed into encodings (not used for an encoding such as `utf_ebcdic`), and how much input and output has been read/what is left (by checking the `input` and `output` ranges whose `.begin()` value has been incremented compared to the input values). Understanding the result types now, we move to the error handler:

Error Handlers

The only other thing we need is the error handler, now. Generally, this is a template argument, but for the sake of illustration we use a concrete type here:

```

1  #include <functional>
2
3  using ue_decode_error_handler = std::function<
4      ue_decode_result(
5          const utf_ebcdic&,
6          ue_decode_result,
7          ztd::span<char>,
8          ztd::span<char32_t>
9      )
10 >;
11
12 using ue_encode_error_handler = std::function<
13     ue_encode_result(
14         const utf_ebcdic&,
15         ue_encode_result,
16         ztd::span<char32_t>,
17         ztd::span<char>
18     )
19 >;

```

The error handlers use a result-in, result-out design. The parameters given are:

0. The encoding which triggered the error. This allows you to access any information about the encoding object type or any values stored on the encoding object itself.
1. The result object. This object has the `error_code` member set to what went wrong (see `ztd::text::encoding_error`), and any other changes made to the input or output during the operation.
2. A contiguous range (`ztd::span`) of `code_units` or `code_points` that were already read by the algorithm. This is useful for when the input range uses input iterators, which sometimes cannot be “rolled back” after something is read (e.g., consider `std::istream_iterator`).
3. A contiguous range (`ztd::span`) of `code_units` or `code_points` that were already read by the algorithm. This is useful for when the output range uses output iterators, which sometimes cannot be “rolled back” after something is written (e.g., consider `std::ostream_iterator`).

It returns the same type as the result object. Within this function, anyone can perform any modifications they like to the type, before returning it. This is an incredibly useful behavior that comes in handy for defining custom error handling behaviors, as shown in *the Error Handling Design section*. For example, this allows us to do things like insert **REPLACEMENT_CHARACTER** `\uFFFD` () into a encoding through the `ztd::text::replacement_handler_t` or enable speedy encoding for pre-validated text using `ztd::text::assume_valid_handler`. When writing your `encode_one` or `decode_one` function, it is your responsibility to invoke the error handler (or not, depending on the value of `ztd::text::is_ignorable_error_handler`).

Liberation Achieved

If you achieve all these things, then we can guarantee that you can implement all of the desired functionality of an encoding library. This is the core design that underpins this whole library, and how it frees both Library Developers from needing to manically provide every possible encoding to end-users, and end-users from having to beg library developers to add support for a particular encoding.



There is more depth one can add to an encoding object, but this is the base, required set of things to know and handle when it comes to working with ztd.text. You can build quite a complex set of features from this functionality, and we encourage you to keep reading through more of the design documentation to get an understanding for how this works!

1.4.2 Bulk vs. Single Conversions

There is some wonder as to whether it is prudent for the Lucky 7 to be based on bulk conversions rather than the *indivisible unit of work* it is based on right now. In general, if you have either a bulk or a single conversion, you can go from one to the other. However, while going from a single *indivisible unit of work* to a bulk conversion by looping is a sound operation, trying to back-engineer a single indivisible unit of work from only a bulk conversion is not only an entirely unsound operation (it does not generalize to all cases), it is also has horrible performance unless intermediate buffers or allocations are deployed (and even then, **still** runs into soundness issues). Briefly:

Single Conversions

Single conversions are, effectively, doing “one unit of work” at a time. Whether converting Unicode one code point at a time or making iterators/views to go over a range of UTF-8 one bundle of non-error code units at a time, the implication here is that it uses minimal memory while guaranteeing that forward progress is made/work is done. It is absolutely not the most performant way of encoding, but it makes all other operations possible out of the composition of this single unit of work, so there’s that. If a single conversion is the only thing you have, you can typically build up the bulk conversion from it.

In the opposite case, where only a bulk conversion API is available, single conversion API may still be implemented. Just take a bulk API, break the input off into a subrange of size 1 from the beginning of the input. Then, call the bulk

API. If it succeeds, that is all that needs to be done. If not, take the subrange and make it a subrange of size 2 from the start of the input. Keep looping up until the bulk API successfully converts that sub-chunk of input, or until input exhaustion. There are, unfortunately, several problems with this methodology.

- It is horrifically inefficient. It is inadvisable to do this, feature set is literally the only goal of a given API.
- It is **unsound**, especially in the presence of optimizations. Consider a valid UTF-8 string consisting of 3 bytes: E2 81 87. If `ztd::text::assume_valid_handler` is used, or any similar “assume validity” flag is set, then when the input is shortened to a length of 1, it will assume the 3-part UTF-8 character is actually a single, valid UTF-8 character. This will propagate through any system where that faux-“single” conversion API based off this bulk conversion will present an invalid single UTF-8 byte as a valid code point.

The above is just a few ways a bulk-only conversion that tries to simulate a single conversion API can go wrong. Pressuring a user to provide a single conversion first, and then a bulk conversion, will provide far better performance metrics and safety. For this library, we focus on providing a *Lucky 7* that focuses on the single case and then allows the user to extrapolate outside of that.

These performance metrics are documented in the *benchmarks of internal routines for ztd.text and ztd.cuneicode*, where there is a special category of cuneicode using SIMD optimizations that then deploys the “single from bulk” conversion talked about below.

Bulk Conversions

Bulk conversions are a way of converting as much input as possible to fill up as much output as possible. The only stopping conditions for bulk conversions are exhausted input (success), not enough room in the output, an illegal input sequence, or an incomplete sequence (but only at the very end of the input when the input is exhausted). Bulk conversions open the door to using Single Instruction Multiple Data (SIMD) CPU instructions, GPU processing, parallel processing, and more, to convert large regions of text at a time.

More notably, given a stable single conversion function, running that conversion in a loop would produce the same effect, but may be slower due to various reasons (less able to optimize the loop, cannot be easily restructured to use SIMD, and more). Bulk conversions get around that by stating up-front they will process as much data as possible. A bulk conversion, derived from a properly-behaving conversion that works solely on a single indivisible unit of work, can not malfunction.

1.4.3 Lost Information

One of the biggest problems facing text processing in programming languages today is the loss of information as its carried through any given system. In C and C++, this comes in the form of all strings - especially multibyte strings - being given the same type. For example:

```
1 void read_name(const char* name) {  
2     // (1)  
3 }
```

As the maintainer of code inside of the function `read_name`, what is the encoding of “name” at (1)? What is its normalization form? What system did it originate from? The function written in C++ form offers very little benefit either:

```
1 void read_name(std::string_view name) {  
2     // (1)  
3 }
```

Even here, we’ve only made marginal improvements. We know the string is stored in some heap by the default allocator, we have the size of the string, but that only tells us how many char units are stored, not how many conceptual, human-

readable *characters* there are or any other pertinent information. Is this information encoded? Is it UTF-8? Maybe it's EBCDIC Code Page 833. Maybe it's UTF-7-IMAP. You don't know, and by the time you start inspecting or poking at the individual `char` *code units*, who knows what can happen? To make matters worse, even C++ and its Standard Library have poor support for encoding/decoding, let alone Unicode in general. These problems have been explained in quite a lot of detail up to this point, but the pitfalls are many:

... Where are potential problems?

All over the place? Let's see...

—R. Martinho Fernandes, last edited April 20th, 2018

Some proponents say that if we just change everything to mean “UTF-8” (*const char**, *std::string*, and more), then we can just assume UTF-8 throughout the entire application and only accept UTF-8 and that will end all our encoding problems. Typically, these people read [UTF-8 Everywhere](#) and then just go all-in on the philosophy, all the time.

“UTF-8 Everywhere!!”


There are many in the programming space that believe that just switching everything to UTF-8 everywhere will solve the problem. This is, unfortunately, greatly inadequate as a solution. For those who actually read the entire UTF-8 Everywhere manifesto in its fullness, they will come across this FAQ entry:

Q: Why not just let any programmer use their favorite encoding internally, as long as they knows how to use it?

A: We have nothing against correct usage of any encoding. However, it becomes a problem when the same type, such as *std::string*, means different things in different contexts. While it is ‘ANSI codepage’ for some, for others, it means ‘this code is broken and does not support non-English text’. In our programs, it means Unicode-aware UTF-8 string. This diversity is a source of many bugs and much misery. ...

—FAQ Entry #6

The core problem with the “*std::string* is always UTF-8” decision (even when they are as big as Google, Apple, Facebook, or Microsoft and own everything from the data center to the browser you work with) is that they live on a planet with other people who do not share the same sweeping generalizations about their application environments. Nor have they invoked the ability to, magically, rewrite everyone's code or the data that's been put out by these programs in the last 50 or 60 years. This results in a gratuitous amount of replacement characters or *Mojibake* when things do not encode or decode properly:



There is a distinct problem that human beings are so used to computers failing them with encoding that they know how to recognize the mistranslated text:

We get so good at it that we can even recognize the bad text . There’s a wiki for it too... . . . It used to be a lot worse. UTF-8 definitely helps a whole lot.

—Elias Daler

So, what do we do from here?

Fighting Code Rot

We need ways to fight bit rot and issues of function invariants – like expected encoding on string objects – from infesting code. While we can’t rewrite every function declaration or wrap every function declaration, one of the core mechanisms this library provides is a way of tracking and tagging this kind of invariant information, particularly at compile time.

We know we can’t solve interchange on a global level (e.g., demanding everyone use UTF-8) because, at some point, there is always going to be some small holdout of legacy data that has not yet been fixed or ported. The start of solving this is by having views and containers that keep encoding information with them after they are first constructed. This makes it possible to not “lose” that information as it flows through your program:

```
1 using utf8_view = ztd::text::decode_view<ztd::text::utf8>;
```

2

(continues on next page)

(continued from previous page)

```

3 void read_name(utf8_view name) {
4     // (1)
5 }

```

Now, we have an *explicit decoding view* into a sequence of UTF-8 code units, that produces `unicode_code_points` that we can inspect and work with. This is much better, as it uses C++’s strong typing mechanisms to give us a useful view. This means that not only does the person outside of the `read_name` function understand that the function expects some UTF-8 encoded text, but the person inside the function knows that they are working with UTF-8 encoded text. This solves both ends of the user and maintainer divide.

Of course, sometimes this is not always possible. ABI stability mandates some functions can’t have their signatures change. Other times, you can’t modify the signature of functions you don’t own. This is still helpful in this case, as you can, at the nearest available point inside the function or outside of it, apply these transformations:

```

1 void read_name(const char* untagged_name) {
2     using utf8_view = ztd::text::decode_view<
3         ztd::text::compat_utf8, // use "char" as the code unit type
4         std::string_view // explicitly use this view type
5     >;
6     // constructs a std::string_view and
7     // stores it in the proper place
8     utf8_view name(untagged_name);
9     // use it...
10 }

```

Because the range and container types are templated on not only encoding, but the underlying storage type, you can wrap up both parameter and return values. You can also access the underlying `std::string_view` using `.base()`, so it remains easy to interop and work with pre-existing systems using newer, more explicit types. Other ranges become possible, including, say, the `__gnu_cxx::rope` class that is part of the GCC Extensions Library. It genuinely doesn’t matter what you pick: we will wrap it up and present the proper interface to you. This also follows UTF-8 Everywhere’s requirements for what it would want out of a C++ Library that does text Correctly™:

If you design a library that accepts strings, the simple, standard and lightweight `std::string` would do just fine. On the contrary, it would be a mistake to reinvent a new string class and force everyone through your peculiar interface. Of course, if one needs more than just passing strings around, he should then use appropriate text processing tools. However, such tools are better to be independent of the storage class used, in the spirit of the container/algorithm separation in the STL.

—UTF-8 Everywhere, FAQ Entry #19

Rather than create new `std::string` or `std::string_view` types, we simply wrap existing storage interfaces and provide specific views or operations on those things. This alleviates the burden of having to reinvent things that already work fine for byte-oriented interfaces, and helps programmers control (and prevent) bugs. They also get to communicate their intent in their APIs if they so desire (“This API takes a `std::string_view`, but with the expectation that it’s going to be decoded as `utf8`”). The wrapped type will always be available by calling `.base()`, which means a developer can drop down to the level they think is appropriate when they want it (with the explicit acknowledgement they’re going to be ruining things).

1.4.4 Error Handling

Text is notorious for being a constant and consistent malformed source of input. From intermediate services mangling encodings and producing *Mojibake* to bungled normalization and bad programs not understanding even the slightest hint of code beyond ASCII, there is a lot of text data that is strictly bad for any program to consume.

When interfacing with range types such as `ztd::text::decode_view`, functions like `ztd::text::transcode`, and individual `.encode_one` or `.decode_one` calls on encoding objects like `ztd::text::utf8`, you can:

- give an error handler type as a template parameter and as part of the constructor; or,
- pass it in as a normal argument to the function to be used.

They can change the conversion and other operations happen works. Consider, for example, this piece of code which translates from Korean UTF-8 to ASCII:

```

1 #include <ztd/text/transcode.hpp>
2
3 #include <iostream>
4
5 int main(int, char* []) {
6     // (1)
7     std::string my_ascii_string = ztd::text::transcode(
8         // input
9         u8"",
10        // from this encoding
11        ztd::text::utf8,
12        // to this encoding
13        ztd::text::ascii);
14
15    std::cout << my_ascii_string << std::endl;
16
17    return 0;
18 }
```

Clearly, the Korean characters present in the UTF-8 string just cannot fit in a strict, 7-bit ASCII encoding. What, then, becomes the printed output from `std::cout` at `// (2)`? The answer is two ASCII question marks, `??`. The `ztd::text::replacement_handler_t` object passed in at `// (1)` substitutes replacement characters (zero or more) into the output for any failed operation. There are multiple kinds of error handlers with varying behaviors:

- `replacement_handler_t`, which inserts a substitution character specified by either the encoding object or some form using the default replacement character `"U+FFFD"` as well as skip over invalid input (either 1 input unit or as dictated by `ztd::text::skip_input_error`);
- `skip_handler_t`, which skips over invalid input (and does not reflect it in the output) by either 1 input unit or as dictated by `ztd::text::skip_input_error`;
- `pass_handler`, which simply returns the error result as it and, if there is an error, halts higher-level operations from proceeding forward;
- `default_handler`, which is just a name for the `replacement_handler_t` or `throw_handler` or some other type based on compile time configuration of the library;
- `throw_handler`, for throwing an exception on any failed operation;
- `incomplete_handler`, which will accumulate 1 `encode_one/decode_one`'s worth of failure and let the end-user do something with it;
- `assume_valid_handler`, which triggers no checking for many error conditions and can leads to Undefined Behavior if used on malformed input.

Warning: For the love of what little remains holy, PLEASE don't use `ztd::text::assume_valid_handler` unless you REALLY know you need it. It is a surefire way to open up vulnerabilities in your text processing algorithm. Not a single line of code using this type should pass code review if there is even the slightest thought that this will be used on any input that is not PERFECTLY under the DIRECT, PERSONAL control of the authors, auditors, and maintainers of the code.

These are all the error handlers that you have at your disposal, but they are just pre-provided types you can instantiate yourself. Nothing stops you from making your own error handling type! In order to do that, however, you need to understand what an error handler is composed of, and what it's got inside of itself.

Error Handler Anatomy

An error handler is just a function (or an object with a function call operator) that takes 3 parameters and returns 1 result:

- takes the encoding that will call it when something goes wrong;
- takes the result object you expect to be working with (specifically, `ztd::text::encode_result` and `ztd::text::decode_result`), which contains the current state of affairs from the encoding operation;
- takes a contiguous range representing any input values that may have been read but will not be used; and,
- returns the same result type with any modifications (or not!) you'd like to make.

They are classes with a function call operator and utilizes a few templates. Here's the skeleton for one:

```

1  #include <ztd/text.hpp>
2
3  struct my_error_handler {
4      // Helper definitions
5      template <typename Encoding>
6      using code_point_span = ztd::span<const ztd::text::code_point_t<Encoding>>;
7      template <typename Encoding>
8      using code_unit_span = ztd::span<const ztd::text::code_unit_t<Encoding>>;
9
10     // Function call operator that returns a "deduced" (auto) type
11     // Specifically, this one is called for encode failures
12     template <typename Encoding, typename Input, typename Output, typename State>
13     auto operator()(
14         // First Parameter
15         const Encoding& encoding,
16         // Second Parameter, encode-specific
17         ztd::text::encode_result<Input, Output, State> result,
18         // Third Parameter
19         code_point_span<Encoding> input_progress,
20         // Fourth Parameter
21         code_unit_span<Encoding> output_progress) const noexcept {
22         // ... implementation here!
23         (void)encoding;
24         (void)input_progress;
25         (void)output_progress;
26         return result;
27     }
28

```

(continues on next page)

(continued from previous page)

```

29 // Function call operator that returns a "deduced" (auto) type
30 // Specifically, this one is called for decode failures
31 template <typename Encoding, typename Input, typename Output, typename State>
32 auto operator()(
33     // First Parameter
34     const Encoding& encoding,
35     // Second Parameter, decode-specific
36     ztd::text::decode_result<Input, Output, State> result,
37     // Third Parameter
38     code_unit_span<Encoding> input_progress,
39     // Fourth Parameter
40     code_point_span<Encoding> output_progress) const noexcept {
41     // ... implementation here!
42     (void)encoding;
43     (void)input_progress;
44     (void)output_progress;
45     return result;
46 }
47 };
48
49 int main(int, char* argv[]) {
50
51     // convert from execution encoding to utf8 encoding,
52     // using our new handler
53     std::string utf8_string = ztd::text::transcode(std::string_view(argv[0]),
54         ztd::text::execution, ztd::text::compat_utf8, my_error_handler {});
55
56     return 0;
57 }

```

This skeleton, by itself, works. It doesn't do anything: it just returns the result object as-is. This will result in the algorithm stopping exactly where the error occurs, and returning back to the user. This is because the result has an `error_code` member variable, and that member variable, when it reaches the higher level algorithms, stops all encoding, decoding, transcoding, counting, validation, and etc. work and exists with the proper information.

First Parameter

The first parameter is simple enough: it is the encoding that is calling this error handler. If you invoke an `encode_one` or `decode_one` (or a higher-level conversion algorithm) on a `ztd::text::utf8` object, then you can expect a first parameter of type `ztd::text::utf8` to be passed to the error handler.

Note: If the function call `.encode_one` or `.decode_one` is a static function that has no instance, then the encoding object will create a temporary instance to pass to the function. This happens with most encodings that do not contain any pertinent information on the encoding object itself, like all the Unicode encodings and the ASCII/locale/string literal encodings.

This can be handy if you need to access information about the encoding object or encoding type. You can get information about the encoding by using:

- `ztd::text::encode_state_t`
- `ztd::text::decode_state_t`

- `ztd::text::code_unit_t<Encoding>`
- `ztd::text::code_point_t<Encoding>`
- `ztd::text::code_unit_v<Encoding>`
- `ztd::text::code_point_v<Encoding>`

Second Parameter

The second parameter is the result object. It is of the type `ztd::text::decode_result` or `ztd::text::encode_result`. The two types have identical information inside of them, but have different names so that a function call operator can tell the difference between the two, if it's necessary.

This contains all of the state and information that the decode operation/encode operation would return, if left unmodified by the error handler. If you don't want to do anything to it, simply pass it through by returning it with `return result;`. Otherwise, you have access to the `input` range, the `output` range, any `.state` relevant to the operation, the `.error_code`, and the `.error_handled` value. You can modify any one of these, or even perform a recovery operation and change the `.error_code` to be `ztd::text::encoding_error::ok`. Literally, anything can be done!

For example, someone can see if there is space left in the `result.output` parameter, and if so attempt to serialize a replacement character in place there (this is what `ztd::text::replacement_handler_t` does).

Third Parameter

The third parameter is a contiguous range of input values that were read. Typically, this is a `ztd::span` handed to you, or something that can construct a `ztd::span` or either code units or code points (whatever the output type has). This is useful for `input_ranges` and `input_iterators` where it is impossible to guarantee a value can be written, as is the case with `istream_iterator` and other I/O-style iterators and ranges.

Fourth Parameter

The fourth parameter is a contiguous range of output values that were almost written to the output, but could not be because the output has no more room left. Typically, this is a `ztd::span` handed to you, or something that can construct a `ztd::span` or either code units or code points (whatever the input type has). This is particularly useful for `output_ranges` and `output_iterators` where there is no way to guarantee all characters will be successfully written, as is the case with `ostream_iterator` and other I/O-style iterators and ranges.

The fourth parameter is only ever filled out if the error returned is `ztd::text::encoding_error::insufficient_output`. It is **very** important for when someone does bulk-buffered writes, since multiple writes are not guaranteed to fit within the given `ztd::text::max_code_points_v` or `ztd::text::max_code_units_v` for a specific encoding. (They only represent the maximum for a single, indivisible operation.)

This is useful for grabbing any would-be-written output data, and storing it for later / completing it. For example, writing to a smaller, contiguous buffer for delivery and looping around that buffer can be faster, but it runs the risk of partial reads/writes on the boundaries of said smaller, contiguous buffer.

Secret Type Definition

There is a type definition you can add to your error handler to signal that it is okay to ignore it's calls. It goes on the struct and looks like:

```
using assume_valid = std::false_type; // or std::true_type
```

This allows any encoding which uses `ztd::text::is_ignorable_error_handler` property on your error handler to know if it's okay to ignore the error handler when bad things happen. Having this functionality means you can create a “debug handler” for text you previously know is valid, but might want to check during a debug or tracing build or something as it encodes and decodes through the system:

```
1 struct my_debug_handler {
2
3     // Assume it's valid if the config value
4     // is explicitly turned off
5     using assume_valid = std::integral_constant<
6         bool, (MY_ENCODING_TRACE_IS_TURNED_OFF != 0)
7     >;
8
9     // rest of the implementation...
10 };
```

Writing A Handler

When put together, it can generally look like this:

```
1 #include <ztd/text/encode.hpp>
2 #include <ztd/text/encoding.hpp>
3
4 #include <iostream>
5
6 using ascii_encode_result = ztd::text::encode_result<
7     // input range type
8     ztd::span<const char32_t>,
9     // output range type; figured out from function call
10    ztd::span<char>,
11    // the state type for encode operations
12    ztd::text::encode_state_t<ztd::text::ascii_t>>;
13
14 ascii_encode_result my_printing_handler(const ztd::text::ascii_t& encoding,
15    ascii_encode_result result, ztd::span<const char32_t> unused_read_characters,
16    ztd::span<const char> unused_write_characters) noexcept {
17     (void)encoding;
18     // just printing some information
19     std::cout << "An error occurred.\n"
20         << "\tError code value: " << ztd::text::to_name(result.error_code)
21         << "\n"
22         << "\t# of code unit spaces left: " << result.output.size() << "\n"
23         << "\t# of unused code points: " << unused_read_characters.size()
24         << "\n"
25         << "\n"
```

(continues on next page)

(continued from previous page)

```

26         << "\t# of unused code units: " << unused_write_characters.size()
27         << "\n"
28         << "\tInput units left: " << result.input.size() << "\n";
29     // setting the error to "ok"
30     // tells the algorithm to keep spinning,
31     // even if nothing gets written to the output
32     result.error_code = ztd::text::encoding_error::ok;
33     return result;
34 }
35
36 int main(int, char*[]) {
37     std::string my_ascii_string = ztd::text::encode(
38         // input
39         U"",
40         // to this encoding
41         ztd::text::ascii,
42         // handled with our function
43         &my_printing_handler);
44
45     ZTD_TEXT_ASSERT(my_ascii_string == "");
46
47     return 0;
48 }

```

The result in `my_ascii_string` should be an empty string: nothing should have succeeded and therefore the function will just return an empty string. The print out will look like this:

```

An error occurred.
  Error code value: invalid_sequence
  # of unused characters: 1
  Input units left: 1
An error occurred.
  Error code value: invalid_sequence
  # of unused characters: 1
  Input units left: 0

```

If you would like the higher-level called function to return more information to you, use the lower level *encode_to/encode_into_raw*, *decode_to/decode_into_raw*, *transcode_to/transcode_into_raw*.

If you need to do more, you can change from concrete types to templates, and work at increasingly higher levels of genericity in order to have the printing handler do more and more.

Lossy Operation Protection

Occasionally, you will end up in a situation where you want to convert some text from its pristine and ideal Unicode form to some other form. Maybe for interoperation purposes, maybe because some function call can't properly handle embedded NULs in the text so you need to *use an overlong sequence to encode the 0 value in your text*. No matter what the case is, you need to leave the world of *Unicode Code Points*, *Unicode Scalar Values*, and all the guarantees they provide you. Let's take an example, going from UTF-8 to 7-bit-clean ASCII:

```

1 #include <ztd/text/transcode.hpp>
2

```

(continues on next page)

(continued from previous page)

```

3 #include <iostream>
4
5 int main(int, char* []) {
6     // (1)
7     std::string my_ascii_string = ztd::text::transcode(
8         // input
9         u8"",
10        // from this encoding
11        ztd::text::utf8,
12        // to this encoding
13        ztd::text::ascii);
14
15    std::cout << my_ascii_string << std::endl;
16
17    return 0;
18 }

```

This will produce a compile time error (with this error number for MSVC as an example):

error C2338: The encode (output) portion of this transcode is a lossy, non-injective operation. This means you may lose data that you did not intend to lose; specify an ‘out_handler’ error handler parameter to `transcode[_to](in, in_encoding, out_encoding, in_handler, out_handler, ...)` or `transcode_into_raw(in, in_encoding, out, out_encoding, in_handler, out_handler, ...)` explicitly in order to bypass this.

The reason this happens is because we can detect, at compile time, that the conversion from Unicode Code Points to ASCII is a lossy transformation. When this happens, we realize the conversion will be a lossy one: therefore, it makes sense that the user cannot perform the encoding or decoding operation without being explicit about how they are going to handle errors because there is such a gigantically enormous possibility that they will mangle incoming text.

Since this library is trying to prevent *Mojibake* and other encoding problems, you are required to tag any potentially-lossy encoding with an error handler, to be explicit and acknowledge that you may or may not be ruining someone’s day:

```

1 #include <ztd/text/transcode.hpp>
2
3 #include <iostream>
4
5 int main(int, char* []) {
6     std::string my_ascii_string = ztd::text::transcode(
7         // input
8         u8"",
9         // from this encoding
10        ztd::text::utf8,
11        // to this encoding
12        ztd::text::ascii,
13        // (1) error handler
14        ztd::text::replacement_handler);
15
16    std::cout << my_ascii_string << std::endl; // (2)
17
18    ZTD_TEXT_ASSERT(my_ascii_string == "??");
19
20    return 0;

```

(continues on next page)

(continued from previous page)

21

}

Any encoding which does not meet the requirements of either `ztd::text::is_encode_injective_v` or `ztd::text::is_decode_injective_v` (or both, for transcoding which uses both an encode and a decode operation) will throw an error if you specify no error handlers in the text. This is done through the *Injectivity Lucky 7 Extensions* that go beyond the *traditional Lucky 7* with 2 `std::true_type/std::false_type` definitions.


1.4.5 Converting, Counting, and Validating Text

Conversions are one of the more important aspects of dealing with textual data. To support this, `ztd.text` contains 7 different methods, each with various overloads and inner groupings of functions to aid in encoding, decoding, transcoding, validating, and counting code points and code units.

As shown in the *Lucky 7 Design*, everything here is supported by just having either the required one or two encoding objects with the designated functions, variables and type definitions. The core of the explanation is in this algorithm:

- Is the `input` value empty? If so, is the `state` finished and have nothing to output? If both are true, return the current results, everything is okay .
- Otherwise,
 0. Set up an `intermediate` buffer of `code_points` using the `max_code_points` of the input encoding count for the next operation.
 1. Do the `decode_one` step from `input` (using its `begin()` and `end()`) into the `intermediate code_point` buffer.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), `output`, and `state`.
 2. Do the `encode_one` step from the `intermediate` into the `output`.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), `output`, and `state`.
- Update `input`'s `begin()` value to point to after what was read by the `decode_one` step.
- Go back to the start.

That's it for the core loop. Failure is determined exclusively by whether or not the `error_code` returned from the decode or encode operation's result object is `ztd::text::encoding_error::ok`. If it is OK, then the loop continues until the `input` is exhausted. Otherwise, it stops. This forms the basis of the library, and will essentially be our version of "Elements of Programming", but for working with Text:



The above algorithm can work for all the below operations:

- **transcoding**: the above loop presented as-is.
- **encoding**: take an input of `code_points`, and simply do not do the decoding step.
- **decoding**: take an input of `code_units`, and simply do not do the encoding step.
- **validating code units**: do the transcoding loop into 2 intermediate buffers, and compare the result of the final intermediate output to the input.
- **validating code points**: do the transcoding loop, but in the reverse direction for an input of `code_points` (encode first, then decode) into 2 intermediate buffers, and compare the result of the final intermediate output to the input.
- **counting code units**: perform the “encoding” operation into an intermediate buffer and repeatedly count the number of buffered writes, discarding or ignoring the actual contents of the buffer each time.
- **counting code points**: perform the “decoding” operation into an intermediate buffer and repeatedly count the number of buffered writes, discarding or ignoring actual the contents of the buffer each time.

This covers the full universe of potential operations you may want to perform on encoded text, for the purposes of input and output. If you implement the *base Lucky 7* or implement the *extended Lucky 7* for an encoding, you can gain access to the full ecosystem of encodings within your application.

Encode

Encoding is the action of converting from one sequence of decoded information to a sequence of encoded information. The formula given for Encoding is effectively just the first half of the diagram shown in the *main Lucky 7 documentation*, reproduced here with emphasis added:




Fig. 2: The generic pathway between 2 encodings, but modified to show the exact difference between the encoding step and the decoding step.

In particular, we are interested in the operation that helps us go from the decoded input to the encoded output, which is the bottom half of the diagram. The input in this case is labeled “intermediate”, because that is often what it is. But, there are many uses for working directly with the encoded data. A lot of the world does not speak directly in 21-bit Unicode Code Points, but instead speaks in UTF-8. Legacy systems are often found communicating with Code Pages (e.g., EBCDIC or SHIFT-JIS); until those systems go down or are replaced, it is imperative to send them well-formed data, whether over a network or across an inter-process communication bridge of any kind.

Thusly, we use the algorithm as below to do the work. Given an input of `code_points` with an `encoding`, a target `output`, and any necessary additional `state`, we can generically convert that sequence of `code_points` into its

encoded form:

- Is the `input` value empty? If so, is the `state` finished and have nothing to output? If both are true, return the current results with the the empty `input`, `output`, and `state`, everything is okay !
- Otherwise,
 0. Do the `encode_one` step from `input` (using its `begin()` and `end()`) into the output `code_unit` storage location.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), `output`, and `states`.
- Update `input`'s `begin()` value to point to after what was read by the `encode_one` step.
- Go back to the start.

This involves a single encoding type, and so does not need any cooperation to go from the `code_point` sequence to the `code_unit` sequence.

Check out the API documentation for [ztd::text::encode](#) to learn more.

Decode

Decoding is the action of converting from one sequence of encoded information to a sequence of decoded information. The formula given for Decoding is effectively just the first half of the diagram shown in the [main Lucky 7 documentation](#), reproduced here with emphasis added:

In particular, we are interested in the operation that helps us go from the encoded input to the decoded output, which is the top half of the diagram. The output we are interested in is labeled as an “intermediate”, because that is often what it is. But, there are many uses for working directly with the decoded data. Many Unicode algorithms are specified to work over *unicode code points* or *unicode scalar values*. In order to identify Word Breaks, classify Uppercase vs. Lowercase, perform Casefolding, Regex over certain properties properly, Normalize text for search + other operations, and many more things, one needs to be working with code points as the basic unit of operation.

Thusly, we use the algorithm as below to do the work. Given an `input` of `code_units` with an `encoding`, a `target output`, and any necessary additional `state`, we can generically bulk convert the input sequence to a form of `code_points` in the output:

- Is the `input` value empty? If so, is the `state` finished and have nothing to output? If both are true, return the current results with the the empty `input`, `output`, and `state`, everything is okay !
- Otherwise,
 0. Do the `decode_one` step from `input` (using its `begin()` and `end()`) into the output `code_point` storage location.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), `output`, and `states`.
- Update `input`'s `begin()` value to point to after what was read by the `decode_one` step.
- Go back to the start.

This involves a single encoding type, and so does not need any cooperation to go from the `code_units` to the `code_points`. Notably, the encoding's `code_point` type will hopefully be some sort of *unicode code point* type (see: [ztd::text::is_code_point](#) for a more code-based classification). Though, it does not have to be for *many different (and very valid) reasons*.

Check out the API documentation for [ztd::text::decode](#) to learn more.




Fig. 3: The generic pathway between 2 encodings, but modified to show the exact difference between the encoding step and the decoding step.

Transcode

Transcoding is the action of converting from one sequence of encoded information to another sequence of (usually differently) encoded information. The formula given for Transcoding is actually exactly the same as the one shown in the *main Lucky 7 documentation*, reproduced here:




Fig. 4: The generic pathway from one encoding to another for all text Encodings.

The core tenant here is that as long as there is a common intermediary between the 2 encodings, you can decode from the given input into that shared common intermediary (e.g., *unicode code points* or *unicode scalar values*), then encode from the common intermediary to the second encoding's output. This is a pretty basic way of translating data and it's not even a particularly new idea (*iconv* has been doing this for well over a decade now, *libogonek* got this core idea rolling in a C++ interface, and in general this is quite literally how all data interchange has been done since forever). The equalizer here is that, unlike other industries that struggle to define an interchange format, Unicode Code Points has become the clear and overwhelming interoperation choice for people handling text all over the world.

Thusly, we use the algorithm as below to do the work. Given an `input` of `code_units` with a `from_encoding`, a `to_encoding` with a target output, and any necessary additional states, we can generically convert that one encoding

to the other so long as those encodings follow the Lucky 7 design:

- Is the `input` value empty? If so, is the `state` finished and have nothing to output? If both are true, return the current results with the the empty `input`, `output`, and `state`, everything is okay !
- Otherwise,
 0. Set up an `intermediate` storage location of `code_points`, using the `max_code_points` of the input encoding as the maximum size of the storage location, for the next operation.
 1. Do the `decode_one` step from `input` (using its `begin()` and `end()`) into the `intermediate` `code_point` storage location.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), `output`, and `states`.
 2. Do the `encode_one` step from the `intermediate` into the `output`.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), `output`, and `states`.
- Update `input`'s `begin()` value to point to after what was read by the `decode_one` step.
- Go back to the start.

This fundamental process works for any 2 encoding pairs, and does not require the first encoding `from_encoding` to know any details about the second encoding `to_encoding`! This means a user is only responsible for upholding their end of the bargain with their encoding object, and can thusly interoperate with every other encoding that speaks in the same intermediate, decoded values (i.e. *unicode code points*).

Check out the API documentation for `ztd::text::transcode` to learn more.

Recode

Transcoding is the action of converting from one sequence of encoded information to another sequence of (usually differently) encoded information. The formula given for Transcoding is actually exactly the same as the one shown in the *main Lucky 7 documentation*, reproduced here:

The core tenant here is that as long as there is a common intermediary between the 2 encodings, you can decode from the given input into that shared common intermediary (e.g., *unicode code points* or *unicode scalar values*), then encode from the common intermediary to the second encoding's output. This is a pretty basic way of translating data and it's not even a particularly new idea (*iconv* has been doing this for well over a decade now, *libgonek* got this core idea rolling in a C++ interface, and in general this is quite literally how all data interchange has been done since forever). The equalizer here is that, unlike other industries that struggle to define an interchange format, Unicode Code Points has become the clear and overwhelming interoperation choice for people handling text all over the world.

Thusly, we use the algorithm as below to do the work. Given an `input` of `code_units` with a `from_encoding`, a `to_encoding` with a target `output`, and any necessary additional `states`, we can generically convert that one encoding to the other so long as those encodings follow the Lucky 7 design:

- Is the `input` value empty? If so, is the `state` finished and have nothing to output? If both are true, return the current results with the the empty `input`, `output`, and `state`, everything is okay !
- Otherwise,
 0. Set up an `intermediate` storage location of `code_points`, using the `max_code_points` of the input encoding as the maximum size of the storage location, for the next operation.
 1. Do the `decode_one` step from `input` (using its `begin()` and `end()`) into the `intermediate` `code_point` storage location.

- If it failed, return with the current `input` (unmodified from before this iteration, if possible), `output`, and `states`.
- 2. Do the `encode_one` step from the `intermediate` into the `output`.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), `output`, and `states`.
- Update `input`'s `begin()` value to point to after what was read by the `decode_one` step.
- Go back to the start.

This fundamental process works for any 2 encoding pairs, and does not require the first encoding `from_encoding` to know any details about the second encoding `to_encoding`! This means a user is only responsible for upholding their end of the bargain with their encoding object, and can thusly interoperate with every other encoding that speaks in the same intermediate, decoded values (i.e. *unicode code points*).

Check out the API documentation for `ztd::text::recode` to learn more.

Validate Encodable

Validation is the way to verify a given sequence of input can have a specific action performed on it. Particularly, we check here if the input of code points can be turned into code units of the given encoding. The way it does this, however, is two-fold:

- it first encodes the input code units, to see if it can do the transformation without loss of information; then,
- it decodes the output from the last step, to see if the final output is equivalent to the input.

The algorithm for this is as follows:

- Is the `input` value empty? If so, is the `state` finished and have nothing to output? If both are true, return the current results with the the empty `input`, `valid` set to `true` and `states`, everything is okay !
- Otherwise,
 0. Set up an `intermediate` storage location of `code_units`, using the `max_code_units` of the input encoding, for the next operations.
 1. Set up an `intermediate_checked_output` storage location of `code_points`, using the `max_code_points` of the input encoding, for the next operations.
 2. Do the `encode_one` step from `input` (using its `begin()` and `end()`) into the `intermediate` `code_unit` storage location.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), `valid` set to `false`, and `states`.
 3. Do the `decode_one` step from the `intermediate` into the `intermediate_checked_output`.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), `valid` set to `false`, and `states`.
 4. Compare the `code_points` of the `input` sequentially against the `code_points` within the `intermediate_checked_output`.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), `valid` set to `false`, and `states`.
- Update `input`'s `begin()` value to point to after what was read by the `decode_one` step.
- Go back to the start.

This fundamental process works for all encoding objects, provided they implement the basic *Lucky 7*. The reason for checking if it can be turned back is to ensure that the input code units actually match up with the output code units. If an encoding performs a lossy transformation in one direction or the other, then validation will fail if it cannot reproduce the input exactly. And, you will know the exact place in the `input` that caused such a failure.

There are extension points used in the API that allow certain encodings to get around the limitation of having to do both the `encode_one` step and the `decode_one` step, giving individual encodings control over the verification of a single unit of input and of bulk validation as well.

Check out the API documentation for `ztd::text::validate_encodable_as` to learn more.

Validate Decodable

Validation is the way to verify a given sequence of input can have a specific action performed on it. Particularly, we check here if the input of code units can be turned into code points of the given encoding. The way it does this, however, is two-fold:

- it first decodes the input code units, to see if it can do the transformation without loss of information; then,
- it encodes the output from the last step, to see if the final output is equivalent to the input.

The algorithm for this is as follows:

- Is the `input` value empty? If so, is the `state` finished and have nothing to output? If both are true, return the current results with the the empty `input`, `valid` set to true, and `states`, everything is okay !
- Otherwise,
 0. Set up an `intermediate` storage location of `code_points`, using the `max_code_points` of the input encoding, for the next operations.
 1. Set up an `intermediate_checked_output` storage location of `code_units`, using the `max_code_units` of the input encoding, for the next operations.
 2. Do the `decode_one` step from `input` (using its `begin()` and `end()`) into the `intermediate` `code_point` storage location.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), `valid` set to false, and `states`.
 3. Do the `encode_one` step from the `intermediate` into the `intermediate_checked_output`.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), `valid` set to false, and `states`.
 4. Compare the `code_units` of the `input` sequentially against the `code_units` within the `intermediate_checked_output`.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), `valid` set to false, and `states`.
- Update `input`'s `begin()` value to point to after what was read by the `decode_one` step.
- Go back to the start.

This fundamental process works for all encoding objects, provided they implement the basic *Lucky 7*. The reason for checking if it can be turned back is to ensure that the input code units actually match up with the output code units. If an encoding performs a lossy transformation in one direction or the other, then validation will fail if it cannot reproduce the input exactly. And, you will know the exact place in the `input` that caused such a failure.

There are extension points used in the API that allow certain encodings to get around the limitation of having to do both the `decode_one` step and the `encode_one` step, giving individual encodings control over the verification of a single unit of input and of bulk validation as well.

Check out the API documentation for `ztd::text::validate_decodable_as` to learn more.

Validate Decodable

Validation is the way to verify a given sequence of input can have a specific action performed on it. Particularly, we check here if the input of code units can be turned into code points of the given encoding. The way it does this, however, is two-fold:

- it first decodes the input code units, to see if it can do the transformation without loss of information; then,
- it encodes the output from the last step.

The algorithm for this is as follows:

- Is the `input` value empty? If so, is the `state` finished and have nothing to output? If both are true, return the current results with the the empty `input`, `valid` set to true, and `states`, everything is okay !
- Otherwise,
 0. Set up an `intermediate` storage location of `code_points`, using the `max_code_points` of the input encoding, for the next operations.
 1. Set up an `intermediate_checked_output` storage location of `code_units`, using the `max_code_units` of the output encoding, for the next operations.
 2. Do the `decode_one` step from `input` (using its `begin()` and `end()`) into the `intermediate` `code_point` storage location.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), `valid` set to false, and `states`.
 3. Do the `encode_one` step from the `intermediate` into the `intermediate_checked_output`.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), `valid` set to false, and `states`.
- Update `input`'s `begin()` value to point to after what was read by the `decode_one` step.
- Go back to the start.

This fundamental process works for all encoding objects, provided they implement the basic *Lucky 7*. Unlike the `encode` and `decode` validation functions, this one does not have anything to compare its output to. By virtue of converting from the source to the destination, it is *transcodable*. Whether or not it can be round-tripped in the other direction isn't particularly of concern, just that it can do so without error. This is the more general purpose forms of the `encode` or `decode` operations.

There are extension points used in the API that allow certain encodings to get around the limitation of having to do both the `decode_one` step and the `encode_one` step, giving individual encodings control over the verification of a single unit of input and of bulk validation as well.

Check out the API documentation for `ztd::text::validate_transcodable_as` to learn more.

Count as Decoded

Counting code units is the action of finding out how many code points will result from a given sequence of encoded information. Essentially, we run the *decoding algorithm* loop, but instead of giving the end user the decoded values, we instead simply provide the count for running that bulk operation.

Thusly, we use the algorithm as below to do the work. Given an input of `code_units` with an `encoding`, an initial count set at 0, and any necessary additional state, we can generically predict how many code units will result from a decoding operation by running the following loop:

- Is the `input` value empty? If so, is the `state` finished and have nothing to output? If both are true, return the current results with the the empty `input`, current count, and `state`, everything is okay !
- Otherwise,
 0. Set up an `intermediate` storage location of `code_points`, using the `max_code_points` of the input `encoding`, for the next operations.
 1. Do the `decode_one` step from `input` (using its `begin()` and `end()`) into the `intermediate` `code_point` storage location, saving the returned `intermediate_output` from the `decode_one` call.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), current count, and `states`.
 2. Compute the difference between the `begin(intermediate)` from the original step, and the `begin(intermediate_output)` returned by `decode_one`; add that difference to the current count.
- Update `input`'s `begin()` value to point to after what was read by the `decode_one` step.
- Go back to the start.

This involves a single encoding type, and so does not need any cooperation to count the `code_units`. Note that this algorithm doesn't show what the error handler does; if the error handler “erases” the failure by setting the result type's `.error_code == ztd::text::encoding_error::ok`, then the algorithm will keep going. This is useful to, for example, detect the maximum size of an operation even if it errors and would result in replacement characters being inserted (e.g., from `ztd::text::replacement_handler_1`).

Check out the API documentation for `ztd::text::count_as_decoded` to learn more.

Count as Encoded

Counting encodable data is the action of finding out how many code units will result from a given sequence of already decoded information, AKA a sequence of code points. Essentially, we run the *encoding algorithm* loop, but instead of giving the end user the encoded values, we instead simply provide the count for running that bulk operation.

Thusly, we use the algorithm as below to do the work. Given an input of `code_units` with an `encoding`, an initial count set at 0, and any necessary additional state, we can generically predict how many code units will result from a decoding operation by running the following loop:

- Is the `input` value empty? If so, is the `state` finished and have nothing to output? If both are true, return the current results with the the empty `input`, current count, and `state`, everything is okay !
- Otherwise,
 0. Set up an `intermediate` storage location of `code_units`, using the `max_code_units` of the input `encoding`, for the next operations.
 1. Do the `encode_one` step from `input` (using its `begin()` and `end()`) into the `intermediate` `code_unit` storage location, saving the returned `intermediate_output` from the `encode_one` call.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), current count, and `states`.

2. Compute the difference between the `begin(intermediate)` from the original step, and the `begin(intermediate_output)` returned by `encode_one`; add that difference to the current count.
- Update `input`'s `begin()` value to point to after what was read by the `encode_one` step.
 - Go back to the start.

This involves a single encoding type, and so does not need any cooperation to count the `code_points`. Note that this algorithm doesn't show what the error handler does; if the error handler "erases" the failure by setting the result type's `.error_code == ztd::text::encoding_error::ok`, then the algorithm will keep going. This is useful to, for example, detect the maximum size of an operation even if it errors and would result in replacement characters being inserted (e.g., from [ztd::text::replacement_handler_1](#)).

Check out the API documentation for [ztd::text::count_as_encoded](#) to learn more.

Count as Transcoded

This operation counts how much text will result from a transcode operation. Essentially, we run the *encoding algorithm* loop, but instead of giving the end user the re-encoded values, we instead simply provide the count for running that bulk operation.

Thusly, we use the algorithm as below to do the work. Given an input of `code_units` with an encoding, an initial count set at 0, and any necessary additional state, we can generically predict how many code units will result from a decoding operation by running the following loop:

- Is the `input` value empty? If so, is the state finished and have nothing to output? If both are true, return the current results with the the empty `input`, current count, and state, everything is okay !
- Otherwise,
 0. Set up an `intermediate` storage location of `code_points` (of the input encoding), using the `max_code_points` of the input encoding; and, set up an `intermediate_output` storage location of `code_units` (of the output encoding), for the next operations.
 1. Do the `decode_one` step from `input` (using its `begin()` and `end()`) into the `intermediate` `code_point` storage location, saving the returned `intermediate_output` from the `decode_one` call.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), current count, and states.
 2. Do the `encode_one` step from `intermediate` (using its `begin()` and `end()`) into the `intermediate_output` `code_unit` storage location, saving the returned `intermediate_output` from the `encode_one` call.
 - If it failed, return with the current `input` (unmodified from before this iteration, if possible), current count, and states.
 3. Compute the difference between the `begin(intermediate_output)` from the original step, and the `begin(result.output)` returned by `encode_one`; add that difference to the current count.
- Update `input`'s `begin()` value to point to after what was read by the `encode_one` step.
- Go back to the start.

This involves a single encoding type, and so does not need any cooperation to count the `code_points`. Note that this algorithm doesn't show what the error handler does; if the error handler "erases" the failure by setting the result type's `.error_code == ztd::text::encoding_error::ok`, then the algorithm will keep going. This is useful to, for example, detect the maximum size of an operation even if it errors and would result in replacement characters being inserted (e.g., from [ztd::text::replacement_handler_1](#)).

Check out the API documentation for [ztd::text::count_as_transcoded](#) to learn more.

1.4.6 Strong vs. Weak Code Units/Points and Legacy Encodings

Every encoding object must have `code_point` and `code_unit` type definitions on it. Typically, this is set to `ztd::text::unicode_code_point`. But, if you go through a Prior Work for this library, you will notice Tom Honermann’s [reference implementation for `text_view`](#) has a concept of even more strictly controlled `code_unit` and `character_type` than this library. From the associated paper:

This library defines a character class template parameterized by character set type used to represent character values. The purpose of this class template is to make explicit the association of a code point value and a character set.

...

It has also been suggested that `char32_t` might suffice as the only character type; that decoding of any encoded string include implicit transcoding to Unicode code points. The author believes that this suggestion is not feasible...

—Tom Honermann, P0244 `text_view`

The Case for Strength

This general philosophy in Honermann’s `text_view` means that you do not just use `unsigned char` or `unicode_code_point` for code unit and code point types, but instead traffic more directly in, for example, `ebcdic_char` and `ebcdic_code_point` types. They are essentially strong type definitions and strong wrappers simpler, “lower level” types like `char32_t` and `char`. It has the following tradeoffs:

- ✓ Can directly connect a range and its `value_type` to a specific encoding (e.g., `default_code_point_encoding_t<ascii_code_point>` means `ascii`, definitively).
- ✓ Actively prevents passing one type of range/view to a function expecting another (e.g., `std::basic_string<ascii_char>` cannot accidentally be given to a function expecting `std::string`, where the expectation might be for an *execution encoded* string.)
- ✓ Easy to strip out all encoding/codec information and the range types themselves can still recover it (e.g. `ascii_code_point* u32_c_str_ptr` can be strongly associated with the `ascii` encoding, whereas `unicode_code_point* u32_c_str_ptr` loses all that information.)
- Requires `reinterpret_cast` or `std::memcpy/std::copy` to work with most existing code that do not have such strongly typed pointers.
- Can generate a lot of template type spam for what are essentially just `char`.
- Not very good in `constexpr`, where `reinterpret_cast` isn’t allowed and there are pre-existing `constexpr` functions that are not templated.

The question boils down to: should we have strong code point and code unit types **by default** in the library?

Henri Sivonen — author of [`encoding_rs`](#) and expert in the text domain — strongly disagrees.

The Counterpoint

In a long piece on P0422, the C and C++ landscape, and Standardization efforts, Henri writes:

I think the C++ standard should adopt the approach of “Unicode-only internally” for new text processing facilities and should not support non-Unicode execution encodings in newly-introduced features. This allows new features to have less abstraction obfuscation for Unicode usage, avoids digging legacy applications deeper into non-Unicode commitment, and avoids the specification and implementation effort of adapting new features to make sense for non-Unicode execution encodings.

—Henri Sivonen, [It’s Time to Stop Adding New Features for Non-Unicode Execution Encodings in C++](#)

This is a different set of choices and a different set of priorities from the outset. Sivonen’s work specifically is that with Browsers and large code bases like Firefox; they are responsible for making very good traction and progress on encoding issues in a world that is filled primarily with Unicode, but still has millions of documents that are not in Unicode and, for the foreseeable future, won’t end up as Unicode.

This is a strong argument for simply channeling `char16_t`, `char32_t`, and — since C++20 — `char8_t` as the only types one would need. Firefox at most deals in UTF-16 (due to the JavaScript engine for legacy reasons) and UTF-8, internally. At the boundaries, it deals with many more text encodings, because it [has to from the world wide web](#). Occasionally, UTF-32 will appear in someone’s codebase for interoperation purposes or algorithms that need to operate on something better than code units.

Unicode is also... well, a [UNI]versal [CODE]. Its purposes are interoperation, interchange, and common ground between all the encodings, and it has been the clear winner for this for quite some time now. Sivonen makes a compelling point for just considering Unicode — and only Unicode — for all future text endeavors.

Do we really need to focus on having support for legacy encodings? Or at least, do we really need support for legacy encodings at the level that Tom Honermann’s `text_view` is trying to achieve?

ztd.text’s answer is simple:




Allow Both, Prefer One

ztd.text prefers Henri Sivonen’s approach to the library in general. The `code_unit` type is generally a weakly-typed choice of one of the 6 viable code unit types in C++ (`char`, `wchar_t`, `unsigned char`, `char8_t`, `char16_t`, and `char32_t`). The `code_point` type is typically just `unicode_code_point` (an alias for `char32_t` *by default*) or `unicode_scalar_value` (a strong type *by default*, because it carries extra pertinent information about itself that can aid the library). Unfortunately, this means that `ztd::text::default_code_point_encoding_t` is not a very rich type mapping (it generally just spits out UTF-8).

This does not mean all future algorithms bear the burden of supporting an infinity of text encodings. But, the work for encoding and decoding text is isolated and constrained specifically to the *encoding objects*, *view types*, and *functions* that power this library. Down-stream algorithms — like those found in Zach Laine’s Boost.Text — work only with range/iterator types whose `value_type` are either `unicode_code_points` or `unicode_scalar_values`.

By having a core, standard ecosystem that works primarily with `unicode_code_point` and `unicode_scalar_value`, we heavily incentivize the use of these two types as the only interchange types. Furthermore, because all of the encodings provided by this library use `unicode_code_point` as their `code_point` type, we set a strong example for the rest of the ecosystem who may work with and look at these files. This is even the case for the default byte-based encoding `ztd::text::any_encoding`, which strongly incentivizes compatibility with the ecosystem by making it clear that there is a preferred default mode of communication (which is, `ztd::text::unicode_code_point`). In effect, we produce The Unicode™ Vortex™:



This might be the perfect world for most people, but even so there's room inside that funneled vortex for more.

Leaving Room

There is room in Sivonen’s world, even with perfectly-consistent and fully-Unicode internals, for Honermann’s dream of never losing encoding information at even the lowest levels. After all, if someone takes the time to wrap up external interfaces (Shared Pipes, Network Connections, Terminal Interfaces, char Devices, and more), they should have the ability to tag these interfaces with either encoding objects or strong, `reinterpret_cast`-able pointer values.

That’s why encodings can still define their own `code_unit` and `code_point` types; even if this library — or the Standard Library — traffics in strictly `unicode_code_points`, it doesn’t mean the user should be forced to do that if they are willing to put in the effort for a more type-safe world.

Being able to know, at compile time, without any objects or markup, that a particular pointer + size pairing is meant for a specific encoding is a powerful way to maintain invariants and track the flow of data without runtime cost through a program. It can also make it easy to find places where external, non-Unicode data is making it “too far” into the system, and try to push a conversion closer to the edges of the program.

While `ztd.text` will traffic and work with `char32_t` and consider it a `unicode_code_point` value *under most circumstances*, users are free to define and extend this classification for their own types and generally create as strict (or loose) as taxonomy as they desire.

In Sum

The library still overwhelmingly traffics in Unicode, and we believe that by making it the default and producing an overwhelming body of code that treats it as such as can push people towards that default. Using `char32_ts`, `unicode_code_points`, and `unicode_scalar_values` as Sivonen advocates should have a very low “activation energy”. Reaching for the strict world envisioned with Honermann’s `text_view` and its associated implementation is still possible, but requires more energy. We do not force the user to put in that energy.

As long as both are possible, users can find satisfaction for both of their use cases. Even if Honermann’s design is more work, it is still quite useful and can lead to a very robust and statically-verifiable design in even huge, complex software systems.

1.4.7 Lucky 7 Extension - Beyond the Basics

While the given *Lucky 7* represents the simplest possible encoding object one can design, there are several more type definitions, member functions, and other things an individual can use to create more complex encoding objects. Below, we are going to review the most pertinent ones that allow for better extensibility of the core design and let you go [Even Further Beyond](#).

State, Completion, Runtime Data, and More

Some states need extra functionality or additional information to function properly. This can manifest as:

- needing extra data on a per-conversion basis that you can maintain yourself;
- needing 2 different types for encode/decode operations;
- OR, needing runtime-dependent, conversion-dependent information for a specific conversion.

Extra Data and Completion

State objects are always passed into the function by non-const l-value reference (e.g. `void f(state_type& state);`). This means that, once a state is created, it can be used to influence how a specific algorithm works. While most encodings strive to have little to no meaningful state, others can have very meaningful state that should not be discarded between function calls or that may contribute meaningfully to the encoding or decoding process.

To aid with this, a state type can have a callable function of the form `is_complete()`:

```

1 class encode_state {
2 public:
3     encode_state_handle_t handle;
4
5     bool is_complete() const noexcept {
6         return state_handle_has_no_more_output(handle);
7     }
8 };

```

The `state_handle_t` and `state_handle_has_no_more_output` are fictitious, but they represent how the given `encode_state` type would signal that it has no more work to be done. This is useful for algorithms which may need to be signaled that a stream has no more data and should thus produce an error if the final bits of data do not form a complete sequence, or if there are encoding algorithms (such as *punycode*) that need to collect all input before doing output operations. When the state has this function present, a user can use `ztd::text::is_state_complete(some_state)` as part of a condition to check if a given conversion sequence and its state have fully serialized all possible data.

Separate Encode/Decode States

It is no secret that encoding and decoding may carry with them separate states. While converting from a legacy encoding to Unicode may require maintenance of a shift state or code unit modifier, the opposite direction may not need any at all. Therefore, as an optimization, an encoding object can define both an `encode_state` and a `decode_state`, separate from each other. As an example, here is a (simplified) version of how `ztd::text::execution`, the encoding for the Locale-based Runtime Execution Encoding, has two separate states that need to be initialized in different manners:

```

1 class runtime_locale {
2 public:
3     struct decode_state {
4         std::mbstate_t c_stdlib_state;
5
6         decode_state() noexcept : c_stdlib_state() {
7             // properly set for mbrtoc32 state
8             code_point ghost_output[2] {};
9             UCHAR_ACCESS mbrtoc32(ghost_output, "\0", 1, &c_stdlib_state);
10        }
11    };
12
13    struct encode_state {
14        std::mbstate_t c_stdlib_state;
15
16        encode_state() noexcept : c_stdlib_state() {
17            // properly set for c32rtomb state
18            code_unit ghost_output[MB_LEN_MAX] {};
19            UCHAR_ACCESS c32rtomb(ghost_output, U'\0', &c_stdlib_state);

```

(continues on next page)

(continued from previous page)

```

20     }
21 };

```

This is the proper way to initialize a `std::mbstate_t` from the C standard library. Then, you can use it! Here's a complete implementation using the new `encode_state` and `decode_state` types:

```

1  class runtime_locale {
2      using rtl_encode_result = ztd::text::encode_result<ztd::span<const code_point>,
3          ztd::span<code_unit>, encode_state>;
4      using rtl_decode_error_handler
5          = std::function<rtl_decode_result(const runtime_locale&, rtl_decode_result,
6          ztd::span<const char>, ztd::span<const char32_t>>>;
7      using rtl_encode_error_handler
8          = std::function<rtl_encode_result(const runtime_locale&, rtl_encode_result,
9          ztd::span<const char32_t>, ztd::span<const char>>>;
10
11     using empty_code_unit_span = ztd::span<const code_unit, 0>;
12     using empty_code_point_span = ztd::span<const code_point, 0>;
13
14 public:
15     rtl_decode_result decode_one(ztd::span<const code_unit> input,
16         ztd::span<code_point> output, rtl_decode_error_handler error_handler,
17         decode_state& current // decode-based state
18     ) const {
19         if (output.size() < 1) {
20             return error_handler(*this,
21                 rtl_decode_result(input, output, current,
22                     ztd::text::encoding_error::insufficient_output_space),
23                 empty_code_unit_span(), empty_code_point_span());
24         }
25         std::size_t result = UCHAR_ACCESS mbrtoc32(
26             output.data(), input.data(), input.size(), &current.c_stdlib_state);
27         switch (result) {
28             case (std::size_t)0:
29                 // '\0' was encountered in the input
30                 // current.c_stdlib_state was "cleared"
31                 // '\0' character was written to output
32                 return rtl_decode_result(
33                     input.subspan(1), output.subspan(1), current);
34                 break;
35             case (std::size_t)-3:
36                 // no input read, pre-stored character
37                 // was written out
38                 return rtl_decode_result(input, output.subspan(1), current);
39             case (std::size_t)-2:
40                 // input was an incomplete sequence
41                 return error_handler(*this,
42                     rtl_decode_result(input, output, current,
43                         ztd::text::encoding_error::incomplete_sequence),
44                     empty_code_unit_span(), empty_code_point_span());
45                 break;
46             case (std::size_t)-1:

```

(continues on next page)

(continued from previous page)

```

47         // invalid sequence!
48         return error_handler(*this,
49             rtl_decode_result(input, output, current,
50                 ztd::text::encoding_error::invalid_sequence),
51             empty_code_unit_span(), empty_code_point_span());
52     }
53     // everything as fine, then
54     return rtl_decode_result(
55         input.subspan(result), output.subspan(1), current);
56 }
57
58 rtl_encode_result encode_one(ztd::span<const code_point> input,
59     ztd::span<code_unit> output, rtl_encode_error_handler error_handler,
60     encode_state& current // encode-based state
61 ) const {
62     // saved, in case we need to go
63     // around multiple times to get
64     // an output character
65     ztd::span<const code_point> original_input = input;
66     // The C standard library assumes
67     // it can write out MB_CUR_MAX characters to the buffer:
68     // we have no guarantee our output buffer is that big, so it
69     // needs to go into an intermediate buffer instead
70     code_unit intermediate_buffer[MB_LEN_MAX];
71
72     for ([[maybe_unused]] int times_around = 0; ++times_around) {
73         if (input.size() < 1) {
74             // no more input: everything is fine
75             return rtl_encode_result(input, output, current);
76         }
77         std::size_t result = UCHAR_ACCESS c32rtomb(
78             intermediate_buffer, *input.data(), &current.c_stdlib_
↳state);
79
80         if (result == (std::size_t)-1) {
81             // invalid sequence!
82             return error_handler(*this,
83                 rtl_encode_result(original_input, output, current,
84                     ztd::text::encoding_error::invalid_sequence),
85                 empty_code_point_span(), empty_code_unit_span());
86         }
87         else if (result == (std::size_t)0) {
88             // this means nothing was output
89             // we should probably go-around again,
90             // after modifying input
91             input = input.subspan(1);
92             continue;
93         }
94         // otherwise, we got something written out!
95         if (output.size() < result) {
96             // can't fit!!
97             return error_handler(*this,
98                 rtl_encode_result(original_input, output, current,

```

(continues on next page)

(continued from previous page)

```

98         ztd::text::encoding_error::insufficient_output_
↳space),
99         empty_code_point_span(), empty_code_unit_span());
100     }
101     ::std::memcpy(output.data(), intermediate_buffer,
102         sizeof(*intermediate_buffer) * result);
103     input = input.subspan(1);
104     output = output.subspan(result);
105     break;
106 }
107 return rtl_encode_result(input, output, current);
108 }
109 };
110
111 int main(int argc, char* argv[]) {
112     if (argc < 1) {
113         return 0;
114     }
115     // Text coming in from the command line / program arguments
116     // is (usually) encoded by the runtime locale
117     runtime_locale encoding {};
118     std::string_view first_arg = argv[0];
119     std::u32string decoded_first_arg = ztd::text::decode(
120         first_arg, encoding, ztd::text::replacement_handler_t {});

```

This allows you to maintain 2 different states, initialized in 2 different ways, one for each of the `encode_one` and `decode_one` function paths.

Encoding-Dependent States

Some states need additional information in order to be constructed and used properly. This can be the case when the encoding has stored some type-erased information, as `ztd::text::any_encoding` does, or as if you wrote a `variant_encoding<utf8le, utf16be, ...>`. For example, given a `type_erased_encoding` like so:

```

1 class type_erased_encoding {
2 private:
3     struct erased_state {
4         virtual ~erased_state () {}
5     };
6
7     struct erased_encoding {
8         virtual std::unique_ptr<erased_state> create_decode_state() = 0;
9         virtual std::unique_ptr<erased_state> create_encode_state() = 0;
10
11         virtual ~erased_encoding () {}
12     };
13
14     template <typename Encoding>
15     struct typed_encoding : erased_encoding {
16         Encoding encoding;
17

```

(continues on next page)

```

18     struct decode_state : erased_state {
19         using state_type = ztd::text::decode_state_t<Encoding>;
20         state_type state;
21
22         decode_state(const Encoding& some_encoding)
23             : state(ztd::text::make_decode_state(some_encoding)) {
24             // get a decode state from the given encoding
25         }
26     };
27
28     struct encode_state : erased_state {
29         using state_type = ztd::text::encode_state_t<Encoding>;
30         state_type state;
31
32         decode_state(const Encoding& some_encoding)
33             : state(ztd::text::make_encode_state(some_encoding)) {
34             // get a decode state from the given encoding
35         }
36     };
37
38     typed_encoding(Encoding&& some_encoding)
39         : encoding(std::move(some_encoding)) {
40         // move encoding in
41     }
42
43     typed_encoding(const Encoding& some_encoding)
44         : encoding(some_encoding) {
45         // copy encoding in
46     }
47
48     virtual std::unique_ptr<erased_state> create_decode_state() override {
49         return std::make_unique<decode_state>(encoding);
50     }
51
52     virtual std::unique_ptr<erased_state> create_encode_state() override {
53         return std::make_unique<encode_state>(encoding);
54     }
55 };
56
57 std::unique_ptr<erased_encoding> stored;
58
59 public:
60     template <typename AnyEncoding>
61     type_erased(AnyEncoding&& some_encoding)
62         : stored_ptr(std::make_unique<typed_encoding<std::remove_cvref_t<AnyEncoding>>>(
63             std::forward<AnyEncoding>(some_encoding))
64         ) {
65         // store any encoding in the member unique pointer
66     }
67
68     // ... rest of the implementation
69 };

```

We can see that creating a state with a default constructor no longer works, because the state itself requires more information than can be known by just the constructor itself. It needs access to the wrapped encoding. The solution to this problem is an opt-in when creating your state types by giving your *state* type a constructor that takes the encoding type:

```

1 class type_erased_encoding {
2     // from above, etc. ...
3 public:
4     // public-facing wrappers
5     struct type_erased_decode_state {
6     public:
7         // special constructor!!
8         type_erased_state (const type_erased_encoding& encoding)
9             : stored(encoding.stored->create_decode_state()) {
10
11     }
12 private:
13     std::unique_ptr<erased_state> stored;
14 };
15
16 struct type_erased_encode_state {
17 public:
18     // special constructor!!
19     type_erased_state (const type_erased_encoding& encoding)
20         : stored(encoding.stored->create_encode_state()) {
21         // hold onto type-erased state
22     }
23 private:
24     std::unique_ptr<erased_state> stored;
25 };
26
27 using decode_state = type_erased_state;
28 using encode_state = type_erased_state;
29
30 // ... rest of the Lucky 7 members
31 };

```

These special constructors will create the necessary state using information from the `type_erased_encoding` to do it properly. This will allow us to have states that properly reflect what was erased when we perform a given higher-level *conversion operation or algorithm*.

This encoding-aware state-construction behavior is detected by the `ztd::text::is_state_independent`, `ztd::text::is_decode_state_independent`, and `ztd::text::is_encode_state_independent` classifications.

These classifications are used in the `ztd::text::make_decode_state` and `ztd::text::make_encode_state` function calls to correctly construct a state object, which is what the API uses to make states for its higher-level function calls. If you are working in a generic context, you should use these functions too when working in this minute details. However, if you're not working with templates, consider simply using the already-provided `ztd::text::any_encoding` to do exactly what this example shows, with some extra attention to detail and internal optimizations done on your behalf.

Skip Input on Error

Some encodings know how to find the next valid sequence after they encounter an error. Many of these encodings are *self synchronizing codes*, but yet still others may have enough information on their (encode/decode) state to skip additional invalid input. This is where the function `ztd::text::skip_input_error` comes in, and the Lucky 7 Extension hook that allows an encoding to define the function. There are 2 versions of this function that are optional and can be written by an encoding author:

- `decode_result<...> skip_input_error(decode_result<...> result)`, which is meant to skip over bad input from a failed decode operation;
- and, `encode_result<...> skip_input_error(encode_result<...> result)`, which is meant to skip over bad input from a failed encode operation.

They can appear in a normal encoding like so:

```

1  #include <ztd/text.hpp>
2
3
4  class my_encoding {
5  public:
6      struct empty { };
7      // the regular Lucky 7 members
8      static inline constexpr std::size_t max_code_points = 1;
9      static inline constexpr std::size_t max_code_units  = 1;
10     using state                                     = empty;
11     using code_point                               = char32_t;
12     using code_unit                                = char;
13
14     template <typename Input, typename Output, typename ErrorHandler>
15     constexpr static auto decode_one(Input&& input, Output&& output,
16         state& current_state, ErrorHandler&& error_handler) noexcept {
17         // decoding implementation here !
18         return decode_result<ztd::remove_cvref_t<Input>,
19             ztd::remove_cvref_t<Output>, state>(
20             input, output, current_state, ztd::text::encoding_error::ok);
21     }
22
23     template <typename Input, typename Output, typename ErrorHandler>
24     static constexpr auto decode_one(Input&& input, Output&& output,
25         state& current_state, ErrorHandler&& error_handler) noexcept {
26         // encoding implementation here !
27         return encode_result<ztd::remove_cvref_t<Input>,
28             ztd::remove_cvref_t<Output>, state>(
29             input, output, current_state, ztd::text::encoding_error::ok);
30     }
31
32     // Special input skip member here
33     template <typename Input, typename Output, typename State>
34     static constexpr auto skip_input_error(
35         decode_result<Input, Output, State> result) noexcept {
36         // manipulate "result" here,
37         // for any failures in the decode routine.
38         return result;
39     }

```

(continues on next page)

(continued from previous page)

```

40
41     template <typename Input, typename Output, typename State>
42     static constexpr auto skip_input_error(
43         encode_result<Input, Output, State> result) noexcept {
44         // manipulate "result" here,
45         // for any failures in the encode routine.
46         return result;
47     }
48 };

```

The `ztd::text::decode_result` and `ztd::text::encode_result` contain all of the necessary information to perform the skip (input, output, error_code, state, and error_count fields) that could be needed. For example, on a hypothetical UTF-16 encoding, one could define a `skip_input_error` function that behaves like so:

```

1  #include <ztd/text.hpp>
2
3  #include <utility>
4
5  class my_utf16 : private ztd::text::utf16_t {
6  private:
7      using base_t = ztd::text::utf16_t;
8
9  public:
10     // Lucky 7 Members
11     static inline constexpr std::size_t max_code_points = 1;
12     static inline constexpr std::size_t max_code_units = 2;
13     using state = ztd::text::decode_state_t<ztd::text::utf16_t>;
14     using code_point = char32_t;
15     using code_unit = char16_t;
16     // Extension definitions
17     using is_unicode_encoding = std::true_type; // UTF-16 is Unicode
18     using is_injective = std::true_type; // conversion is not lossy
19
20     // Import base implementation here,
21     // to save on the implementation work!
22     using base_t::decode_one;
23     using base_t::encode_one;
24
25     // Import additional methods
26     using base_t::replacement_code_points;
27     using base_t::replacement_code_units;
28
29     // Special input skip member!!
30     // If this function is present and callable, it will
31     // allow us to skip over bad input.
32     template <typename Input, typename Output, typename State, typename InputRead,
33             typename OutputWritten>
34     constexpr auto skip_input_error(
35         ztd::text::decode_result<Input, Output, State> result,
36         const InputRead& input_already_read,
37         [[maybe_unused]] const OutputWritten& output_already_read) const noexcept {
38         // If we are decoding a UTF-16 sequence,

```

(continues on next page)

(continued from previous page)

```

39     // we can have 1 or 2 UTF-16 code units.
40     // they are identifiable as leading and trailing surrogates
41     constexpr char16_t last_utf16_lead_surrogate = 0xDBFF;
42     auto it = ztd::ranges::begin(result.input);
43     auto last = ztd::ranges::end(result.input);
44     if (it != last) {
45         if (ztd::ranges::empty(input_already_read)) {
46             // if no input was already read (e.g. partial read from a
47             // `std::istreambuf_iterator<...>`, then we should
48             // increment the iterator at **least** once! this will
↳prevent us
49             // from constantly erroring over the same stuff.
50             ++it;
51         }
52
53         for (; it != last; ++it) {
54             // We can skip all trailing surrogates, until we find a
↳leading
55             // one.
56             const bool is_good_utf16_stop_point
57                 = *it > last_utf16_lead_surrogate;
58             if (is_good_utf16_stop_point) {
59                 // we found a good place to stop: get out of
↳here!
60                 break;
61             }
62             // if we do not break, we go around the
63             // for loop again, increment the iterator
64         }
65     }
66     // put input range back together, return in constructed result object
67     using SubInput = ztd::ranges::subrange_for_t<Input>;
68     using Result = ztd::text::decode_result<SubInput, Output, State>;
69     return Result(
70         // subrange of input
71         SubInput(std::move(it), std::move(last)),
72         // move the output
73         std::move(result.output),
74         // pass state along
75         result.state,
76         // existing error code
77         result.error_code,
78         // existing error count
79         result.error_count);
80     }
81 };

```

Assuming, briefly, that this was all put into a file called `my_utf16.hpp`, it can be used like this:

```

1 #include "my_utf16.hpp"
2
3 #include <ztd/text.hpp>

```

(continues on next page)

(continued from previous page)

```

4
5 #include <iostream>
6
7 int main(int, char* []) {
8
9     std::string utf8_string = ztd::text::transcode(
10         u"\xD801\xD802\xD803", my_utf16 {}, ztd::text::compat_utf8);
11
12     std::cout.write(utf8_string.data(), utf8_string.size());
13     std::cout << std::endl;
14     return 0;
15 }

```

This will come in handy when defining other Unicode variants that may need to skip multiple bits of bad input rather than just passing over 1 code unit. `ztd::text::replacement_handler` and `ztd::text::skip_handler` will both try to use these extension points to skip over bad input.

Injective: Promoting Safety in Encodings

As detailed in the *Lossy Operation Protection* section, `is_encode_injective` and `is_decode_injective` help the library understand when a conversion you are doing cannot be guaranteed at compile time to be lossless. *Injectivity* is a high-brow mathematical term:

In mathematics, an injective function (also known as injection, or one-to-one function) is a function that maps distinct elements of its domain to distinct elements of its codomain.

—Wikipedia, February 2nd, 2021

This is very fancy speak for the fact that for every complete, well-formed input value, there is a well-formed, distinct output value. It does not have to cover all of the potential output values: so long as there is a one-to-one mapping that is unambiguous for all the input values, it is injective. For practical purposes, it means that all of the code unit sequences that are valid can produce a unique code point sequence (“the decode operation is injective”). And, in the reverse case, it means that all the code point sequences that are valid can produce a unique code unit sequence (“the encode operation is injective”).

These two properties appear on the type itself, and is a way to opt-in to saying that a conversion is not lossy (e.g., it preserves information perfectly if the input is well-formed). You can define them by placing them on your Encoding Object Type’s definition:

```

1 struct any_unicode_byte_encoding {
2     using is_decode_injective = std::true_type;
3     using is_encode_injective = std::true_type;
4     using code_unit = std::byte;
5     using code_point = ztd::text::unicode_scalar_value;
6     // ...
7 };

```

This signals that the `encode_one` and `decode_one` functions — if they are given well-formed input — will never be lossy between their `code_point` type and their `code_unit` types when performing the desired operation. If only one half of that equation is lossy, then you can mark only one, or the other. For example, `ztd::text::ascii` is lossy only in for the `encode_one` operation, so it has `is_decode_injective = std::true_type;` for decode operations, but `is_encode_injective = std::false_type;` for encode operations:

```

1      /// because one type suffices for both.
2      using state = __txt_detail::__empty_state;
3      //
4      /// @brief A range of code units representing the values to use when a
↳ replacement happen. For ASCII, this
5      /// must be '?' instead of the usual Unicode Replacement Character U".
6      static constexpr ::ztd::span<const code_unit, 1> replacement_code_
↳ units() noexcept {
7          return __txt_detail::__question_mark_replacement_units<code_unit>
↳ ;
8      }
9
10     //
11     /// @brief Decodes a single complete unit of information as code points,
↳ and produces a result with the
12     /// input and output ranges moved past what was successfully read and
↳ written; or, produces an error and
13     /// returns the input and output ranges untouched.
14     ///
15     /// @param[in] __input The input view to read code units from.
16     /// @param[in] __output The output view to write code points into.
17 #include <ztd/epilogue.hpp>

```

If the type definition is not present and is not `std::true_type`, then the implementation assumes that this is false for a given encoding. See `ztd::text::is_decode_injective` and `ztd::text::is_encode_injective` for more information.

Replacement Characters

Replacement characters are a way to communicate to the end-user that something went wrong, without having to throw an exception that may stop the world or stop the encoding/decoding process altogether. The default error handler for text (`ztd::text::default_handler`, unless *configured* otherwise) provides room for you to provide your own encoding types, and it does so in two ways that is recognized by the library:

Always Has A Replacement

If your type always has a replacement character, regardless of the situation, it can signal this by writing one of two functions:

- `replacement_code_units()` (for any failed encode step)
- `replacement_code_points()` (for any failed decode step)

These functions return a contiguous range of either `code_units` or `code_points`, typically a `std::span<const code_unit>` or a `std::span<const code_point>`.

```

1 class runtime_locale {
2 public:
3     ztd::span<const code_unit> replacement_code_units() const noexcept {
4         if (this->contains_unicode_encoding()) {
5             // Probably CESU-8 or UTF-8!
6             static const char replacement[3] = { '\xEF', '\xBF', '\xBD' };
7             return replacement;
8         }

```

(continues on next page)

(continued from previous page)

```

9         else {
10             // Uh... well, it probably has this? \_O_/
11             static const char replacement[1] = { '?' };
12             return replacement;
13         }
14     }

```

If the given replacement range is empty, then nothing is inserted at all (as this is a deliberate choice from the user. See the next section for how to have this function but graciously return “no replacements” for given runtime conditions).

This is employed, for example, in the `ztd::text::ascii` encoding, which uses a ‘?’ as its replacement `code_unit` and `code_point` value.

Maybe Has A Replacement

If your type might not have a range of replacement characters but you will not know that until run time, regardless of the situation, the encoding type can signal this by writing different functions:

- `maybe_replacement_code_units()` (for any failed encode step)
- `maybe_replacement_code_points()` (for any failed decode step)

These functions return a `std::optional` of a contiguous range of either `code_units` or `code_points`, typically a `std::optional<std::span<const code_unit>>` or a `std::optional<std::span<const code_point>>`. If the `optional` is not engaged (it does not have a value stored), then the replacement algorithm uses its default logic to insert a replacement character, if possible. Otherwise, if it does have a value, it uses that range. If it has a value but the range is empty, it uses that empty range (and inserts nothing).

This is useful for encodings which provide runtime-erased wrappers or that wrap platform APIs like Win32, whose `CPINFOEXW` structure contains both a `WCHAR UnicodeDefaultChar;` and a `BYTE DefaultChar[MAX_DEFAULTCHAR];`. These can be provided as the range values after being stored on the encoding, or similar.

The Default

When none of the above can happen, the `ztd::text::replacement_handler_t` will attempt to insert a Unicode Replacement Character (, U'\uFFFD') or the ‘?’ character into the stream, in various ways. See `ztd::text::replacement_handler_t` for more details on that process!

Marking an encoding as Unicode-Capable

Sometimes, you need to make your own encodings. Whether for legacy reasons or for interoperability reasons, you need the ability to write an encoding that can losslessly handle all 2^{21} code points. Whether it’s writing a variant of UTF-7, or dealing with a very specific legacy set like Unicode v6.0 with the Softbank Private Use Area, you are going to need to be able to say “hey, my encoding can handle all of the code points and therefore deserves to be treated like a Unicode encoding”. There are 2 ways to do this, one for decisions that can be made at compile time, and one for decisions that can be made at runtime (e.g., over a `variant_encoding<X, Y, Z>`).

compile time

The cheapest way to tag an encoding as Unicode Capable and have the library recognize it as such when `ztd::text::is_unicode_encoding` is used is to just define a member type definition:

```
class utf8_v6_softbank {
public:
    // ...
    using is_unicode_encoding = std::true_type;
    // ...
};
```

That is all you have to write. Both `ztd::text::is_unicode_encoding` and `ztd::text::contains_unicode_encoding` will detect this and use it.

Run-time

If your encoding cannot know at compile time whether or not it is a unicode encoding (e.g., for type-erased encodings, complex wrapping encodings, or encodings which rely on external operating system resources), you can define a method instead. When applicable, this will be picked up by the `ztd::text::contains_unicode_encoding` function. Here is an example of a runtime, locale-based encoding using platform-knowledge to pick up what the encoding might be, and determine if it can handle working in Unicode:

```
1  #endif
2
3      struct encode_state {
4          std::mbstate_t c_stdlib_state;
5
6          encode_state() noexcept : c_stdlib_state() {
7              // properly set for c32rtomb state
8              code_unit ghost_output[MB_LEN_MAX] {};
9              UCHAR_ACCESS c32rtomb(ghost_output, U'\0', &c_stdlib_state);
10         }
11     };
12
13     bool contains_unicode_encoding() const noexcept {
14 #if defined(_WIN32)
15         CPINFOEXW cp_info {};
16         BOOL success = GetCPInfoExW(CP_THREAD_ACP, 0, &cp_info);
17         if (success == 0) {
18             return false;
19         }
20         switch (cp_info.CodePage) {
21             case 65001: // UTF-8
22                 // etc. etc. ...
23                 return true;
24             default:
25                 break;
26         }
27 #else
28     }
```

That is it. `ztd::text::contains_unicode_encoding` will detect this and use your function call, so you should never

be calling this or accessing the above compile time classification if necessary and always delegating to the `ztd::text::contains_unicode_encoding` function call.

Need for Speed: Extension Points

The core encoding/decoding loops and the *Lucky 7 design*, while flexible, can come with performance degradation due to its one-by-one nature. There are many well-researched speedups to validating, counting, and converting UTF and other kinds of text. In order to accommodate these, `ztd.text` has a number of places to overload the core behavior by way of named Argument Dependent Lookup (ADL or Koenig Lookup, named after Andrew Koenig) functions that serve as extension points. They are listed, with their expected argument forms / counts, here.

Extension points: Arguments

For all extension points, arguments are given based on what was input to one of the original higher-level functions. They have these forms and general requirements:

- `tag` - The first argument to every extension point that takes a single encoding. The tag type is `ztd::tag<...>` with any `const`, `volatile`, or references (`&` and `&&`) removed from the `decltype` of the encoding.
- `duo_tag` - The first argument to every extension point that takes 2 encodings. The tag type is `ztd::tag<...>` with any `const`, `volatile`, or references (`&` and `&&`) removed from the `decltype` of the two encodings.
- `encoding` - The encoding used to perform the operation. Can be prefixed with `from_` or `to_` in the argument list to show it is one of two encodings used to perform e.g. a transcode operation.
- `input` - The input range. Can be of any type. Most encodings should at the very least handle basic iterator-iterator pairs correctly. These are allowed to have `const`-correct iterators that produce `const`-correct references, so never assume you can write to the input, and appropriately `const`-qualify any `std::spans` you use.
- `output` - The output range. Can be of any output range type, such as a `unbounded_view<>` with a `back_inserter` or a `std::span` for direct memory writes. The types only requirement is that you can write to it by getting an iterator from `begin(...)`, and calling `*it = value;`
- `handler` - The error handler used to perform the operation. Can be prefixed with `from_` or `to_` in the argument list to show it is one of two error handlers used to perform e.g. a transcode operation.
- `state` - The state objects used to perform the operation. States are always passed by non-`const`, l-value reference. Can be prefixed with `from_` or `to_` in the argument list to show it is one of two states associated with an encoding with the same prefix.
- `pivot` - The *pivot range* that can be used for any intermediary storage; should be used in place of allocating data within a routine so an end-user can avoid allocation if he/she desires for any intermediate productions.

Extension Points: Forms & Return Types

Overriding any one of these extension points allows you to hook that behavior. It is very much required that you either use concrete types to provide these ADL extension points, or heavily constrain them using `SFINAE` (preferred for C++17 and below) or `Concepts` (only C++20 and above).

text_decode

Form: `text_decode(tag, input, encoding, output, handler, state)`.

An extension point to speed up decoding operations for a given encoding, its input and output ranges, and the associated error handler and state. This can be helpful for encodings which *may need to hide certain parts of their state*.

Must return a `ztd::text::decode_result`.

text_encode

Form: `text_encode(input, encoding, output, handler, state)`.

An extension point to speed up encoding operations for a given encoding, its input and output ranges, and the associated error handler and state. This can be helpful for encodings which *may need to hide certain parts of their state*.

Must return a `ztd::text::encode_result`.

text_transcode

Form: `text_transcode(input, from_encoding, output, to_encoding, from_handler, to_handler, from_state, to_state, pivot)`

An extension point to speed up transcoding in bulk, for a given encoding pair, its input and output ranges, and its error handlers and states. Useful for known encoding pairs that have faster conversion paths between them.

Must return a `ztd::text::transcode_result`.

text_transcode_one

Form: `text_transcode_one(input, from_encoding, output, to_encoding, from_handler, to_handler, from_state, to_state)`

An extension point to provide faster one-by-one encoding transformations for a given encoding pair, its input and output ranges, and its error handlers and states. This is **not** a bulk extension point conversion. It is used in the `ztd::text::transcode_view` type to increase the speed of iteration, where possible.

Must return a `ztd::text::transcode_result`.

text_validate_encodable_as_one

Form: `text_validate_encodable_as_one(input, encoding, state)`

An extension point to provide faster one-by-one validation. Provides a shortcut to not needing to perform both a `decode_one` and an `encode_one` step during the basic validation loop.

Must return a `ztd::text::validate_result`.

text_validate_decodable_as_one

Form: `text_validate_decodable_as_one(input, encoding, state)`

An extension point to provide faster one-by-one validation. Provides a shortcut to not needing to perform both a `encode_one` and a `decode_one` step during the basic validation loop.

Must return a *ztd::text::validate_result*.

text_validate_transcodable_as_one

Form: `text_validate_transcodable_as_one(input, from_encoding, to_encoding, decode_state, encode_state, pivot)`

An extension point to provide faster one-by-one validation. Provides a shortcut to not needing to perform both a `encode_one` and a `decode_one` step during the basic validation loop.

Must return a *ztd::text::validate_transcode_result*.

text_validate_encodable_as

Form: `text_validate_encodable_as(input, encoding, state)`

An extension point to provide faster bulk code point validation. There are many tricks to speed up validating of text using bit twiddling of the input sequence and more.

Must return a *ztd::text::validate_result*.

text_validate_decodable_as

Form: `text_validate_decodable_as(input, encoding, state)`

An extension point to provide faster bulk code unit validation. There are many tricks to speed up validating of text using bit twiddling of the input sequence and more.

Must return a *ztd::text::validate_result*.

text_count_as_encoded_one

Form: `text_count_as_encoded_one(input, encoding, handler, state, pivot)`

An extension point to provide faster one-by-one counting. Computation cycles can be saved by only needing to check a subset of things. For example, specific code point ranges can be used to get a count for UTF-16 faster than by encoding into an empty buffer.

Must return a *ztd::text::count_result*.

`text_count_as_decoded_one`

Form: `text_count_as_decoded_one(input, encoding, handler, state)`

An extension point to provide faster one-by-one counting. Computation cycles can be saved by only needing to check a subset of things. For example, the leading byte in UTF-8 can provide an immediate count for how many trailing bytes, leading to a faster counting algorithm.

Must return a `ztd::text::count_result`.

`text_count_as_encoded`

Form: `text_count_as_encoded(input, encoding, handler, state)`

An extension point for faster bulk code point validation.

Must return a `ztd::text::count_result`.

`text_count_as_decoded`

Form: `text_count_as_decoded(input, encoding, handler, state)`

An extension point for faster bulk code point validation.

Must return a `ztd::text::count_result`.

That's All of Them

Each of these extension points are important to one person, or another. For example, Daniel Lemire spends a lot of time optimizing *UTF-8 routines for fast validation* or *Fast Deterministic Finite Automata (DFA) decoding of UTF-8 and more*. There are many more sped up counting, validating, encoding, and decoding routines: therefore it is critical that any library writer or application developer can produce those for their encodings and, on occasion, override the base behavior and implementation-defined internal speed up written by `ztd.text` itself.

1.5 Available Encodings

Below is a table of encodings. Here, we track which encodings can be represented using the *Lucky 7* technique, whether or not we have produced such an implementation, and (if applicable) a link to said implementation.

Most are table-driven encodings, but a select few are not. Tables and data for this are included as part of the [Encoding Tables repository](#).

As a general point, we hope to support almost all of the encodings here in one form or another! If you'd like to request prioritization of a certain encoding, let us know.

Table 1: **Encoding Progress Table**

Name	Stateful	<i>Implementable?</i>	Implemented
UTF-8	No	Yes	<i>Yes</i>
UTF-16	No	Yes	<i>Yes</i>
UTF-32	No	Yes	<i>Yes</i>

continues on next page

Table 1 – continued from previous page

Name	Stateful	Implementable?	Implemented
Modified UTF-8 (MUTF-8)	No	Yes	<i>Yes</i>
Wobbly Transformation Format-8 (WTF-8)	No	Yes	<i>Yes</i>
ASCII	No	Yes	<i>Yes</i>
C Locale	Yes (std::mbstate_t)	Yes	<i>Yes</i>
C Locale, Wide	Yes (std::mbstate_t)	Yes	<i>Yes</i>
String Literals	Compiler-Dependent	Yes	<i>Yes</i>
Wide String Literals	Compiler-Dependent	Yes	<i>Yes</i>
“Anything” Wrapper	Typed-Erased	Yes	<i>Yes</i>
Encoding Scheme	Wrapping-Dependent	Yes	<i>Yes</i>
iconv Encoding	Yes	Yes	<i>Yes</i>
cuneicode Encoding	Yes	Yes	<i>Yes</i>
ARMScii-8	Unresearched	Unconfirmed	No
ATARIST	No	Yes	<i>Yes</i>
BIG5	No	Yes	No
BIG5-2003	No	Yes	No
Big5-HKSCS	No	Yes	<i>Yes</i>
Big5-HKSCS:1999	No	Yes	No
Big5-HKSCS:2001	No	Yes	No
Big5-HKSCS:2004	No	Yes	No
CP737	Unresearched	Unconfirmed	No
CP775	Unresearched	Unconfirmed	No
CP850	Unresearched	Unconfirmed	No
CP852	Unresearched	Unconfirmed	No
CP853	Unresearched	Unconfirmed	No
CP855	Unresearched	Unconfirmed	No
CP857	Unresearched	Unconfirmed	No
CP858	Unresearched	Unconfirmed	No
CP860	Unresearched	Unconfirmed	No
CP861	Unresearched	Unconfirmed	No
CP862	Unresearched	Unconfirmed	No
CP863	Unresearched	Unconfirmed	No
CP864	Unresearched	Unconfirmed	No
CP866	Unresearched	Unconfirmed	No
CP869 (Nice)	Unresearched	Unconfirmed	No
CP932	Unresearched	Unconfirmed	No
CP936	Unresearched	Unconfirmed	No
CP949	Unresearched	Unconfirmed	No
CP1125	Unresearched	Unconfirmed	No
CP1131	Unresearched	Unconfirmed	No
CP1133	Unresearched	Unconfirmed	No
CP1250	Unresearched	Unconfirmed	No
EUC-CN	Unresearched	Unconfirmed	No
EUC-JISX0213	Unresearched	Unconfirmed	No
EUC-JP	Unresearched	Unconfirmed	No
EUC-KR	No	Yes	<i>Yes</i>
EUC-TW	Unresearched	Unconfirmed	No

continues on next page

Table 1 – continued from previous page

Name	Stateful	<i>Implementable?</i>	Implemented
GB18030 (Unicode-capable)	No	Yes	<i>Yes</i>
GBK	No	Yes	<i>Yes</i>
Georgian-Academy	Unresearched	Unconfirmed	No
Georgian-PS	Unresearched	Unconfirmed	No
HP-ROMAN8	Unresearched	Unconfirmed	No
HZ	Unresearched	Unconfirmed	No
IBM 424 Hebrew (Bulletin)	No	Yes	<i>Yes</i>
IBM 856 Hebrew	No	Yes	<i>Yes</i>
IBM 866 Cyrillic (Russian)	No	Yes	<i>Yes</i>
IBM 1006 Urdu	No	Yes	<i>Yes</i>
ISO-2022-CN	Unresearched	Unconfirmed	No
ISO-2022-CN-EXT	Unresearched	Unconfirmed	No
ISO-2022-JP	Unresearched	Unconfirmed	No
ISO-2022-JP-1	Unresearched	Unconfirmed	No
ISO-2022-JP-2	Unresearched	Unconfirmed	No
ISO-2022-JP-3	Unresearched	Unconfirmed	No
ISO-2022-JP-MS	Unresearched	Unconfirmed	No
ISO-2022-KR	Unresearched	Unconfirmed	No
ISO-8859-1-1985	Unresearched	Unconfirmed	No
ISO-8859-1 (1998)	Unresearched	Unconfirmed	No
ISO-8859-2	No	Yes	<i>Yes</i>
ISO-8859-3	No	Yes	<i>Yes</i>
ISO-8859-4	No	Yes	<i>Yes</i>
ISO-8859-5	No	Yes	<i>Yes</i>
ISO-8859-6	No	Yes	<i>Yes</i>
ISO-8859-7	No	Yes	<i>Yes</i>
ISO-8859-8	No	Yes	<i>Yes</i>
ISO-8859-9	Unresearched	Unconfirmed	No
ISO-8859-10	No	Yes	<i>Yes</i>
ISO-8859-13	No	Yes	<i>Yes</i>
ISO-8859-14	No	Yes	<i>Yes</i>
ISO-8859-15	No	Yes	<i>Yes</i>
ISO-8859-16	No	Yes	<i>Yes</i>
JOHAB	Unresearched	Unconfirmed	No
Kamenicky	No	Yes	<i>Yes</i>
Kazakh-STRK1048 / KZ-1048	No	Yes	<i>Yes</i>
KOI8-U	No	Yes	<i>Yes</i>
KOI8-R	No	Yes	<i>Yes</i>
MacArabic	Unresearched	Unconfirmed	No
MacCentralEurope	Unresearched	Unconfirmed	No
MacCroatian	Unresearched	Unconfirmed	No
MacCryllic	No	Yes	<i>Yes</i>
MacGreek	Unresearched	Unconfirmed	No
MacHebrew	Unresearched	Unconfirmed	No
MacIceland	Unresearched	Unconfirmed	No
Macintosh	Unresearched	Unconfirmed	No

continues on next page

Table 1 – continued from previous page

Name	Stateful	Implementable?	Implemented
MacRoman	No	Yes	<i>Yes</i>
MacRomania	Unresearched	Unconfirmed	No
MacThai	Unresearched	Unconfirmed	No
MacTurkish	Unresearched	Unconfirmed	No
MacUkraine	Unresearched	Unconfirmed	No
MuleLao-1	Unresearched	Unconfirmed	No
NEXTSTEP	Unresearched	Unconfirmed	No
PETSCII (Shifted and Un-shifted)	No	Yes	<i>Yes</i>
PT154	Unresearched	Unconfirmed	No
RISCOS-LATIN1	Unresearched	Unconfirmed	No
SHIFT-JIS (AKA SHIFT-JISX0208)	No	Yes	<i>Yes</i>
SHIFT-JISX0208	No	Yes	<i>Yes</i>
SHIFT-JISX0213	Yes, shift states	Yes	No
TACE	No	Yes	No
Tatar (IBM/ASCII)	No	Yes	<i>Yes</i>
Tatar (Windows/ANSI)	No	Yes	<i>Yes</i>
TCVN	Unresearched	Unconfirmed	No
TDS565	Unresearched	Unconfirmed	No
TIS-620	Unresearched	Unconfirmed	No
TSCII	No	Yes	No
UTF-EBCDIC	No	No (Licensed)	No
UTF-7	Yes	No (Licensed)	No
UTF-7-IMAP	Yes	No (Licensed)	No
VISCII	Unresearched	Unconfirmed	No
Windows-437 / DOS Latin-US	No	Yes	<i>Yes</i>
Windows-865 / DOS Nordic	No	Yes	<i>Yes</i>
Windows-874	No	Yes	<i>Yes</i>
Windows-1251	No	Yes	<i>Yes</i>
Windows-1252 / Latin-1	No	Yes	<i>Yes</i>
Windows-1253	Yes	Yes	<i>Yes</i>
Windows-1254	No	Yes	<i>Yes</i>
Windows-1255	No	Yes	<i>Yes</i>
Windows-1256	No	Yes	<i>Yes</i>
Windows-1257	No	Yes	<i>Yes</i>
Windows-1258	No	Yes	<i>Yes</i>

If you know of an encoding not listed here, let us know in the issue tracker!

1.6 Known Unicode Encodings

Out of all the encodings listed on the *encodings page*, only a handful are known to be Unicode Encodings. These are as follows:

- UTF-7
- UTF-7-IMAP
- UTF-8
- UTF-16 (All Endiannesses)
- UTF-32 (All Endiannesses)
- GB18030
- CESU-8
- MUTF-8
- WTF-8
- UTF-1
- UTF-EBCDIC

When the encoding is known at compile time (e.g., it is just a plain object), it contains a `is_unicode_encoding` type member that is set to `std::true_type`. Otherwise, it is left off. This is detected by `ztd::text::contains_unicode_encoding` and `ztd::text::is_unicode_encoding`.

If you know of any others, please let us know!

1.7 Configuring the Library

There are various configuration macros and CMake/build-time switches that will change the behavior of the library or attempt to use different

- **ZTD_TEXT_UNICODE_CODE_POINT_DISTINCT_TYPE**
 - Turns `ztd::text::unicode_code_point` from a type definition to `char32_t` to an implementation-defined class type which enforces the various invariants of being a *unicode code point*.
 - Default: off.
 - Not turned on by-default under any conditions.
- **ZTD_TEXT_UNICODE_CODE_POINT_INVARIANT_ABORT**
 - If `ztd::text::unicode_code_point` is a distinct class (as controlled by `ZTD_TEXT_UNICODE_CODE_POINT_DISTINCT_TYPE`), each construction of a *unicode_code_point* object that violates the required invariants of a *unicode code point* will trigger an abort.
 - It is normally a `ZTD_TEXT_ASSERT(...)` or equivalent.
 - Default: off.
 - Not turned on by-default under any conditions.
- **ZTD_TEXT_DEFAULT_HANDLER_THROWS**

- Makes the `ztd::text::default_handler` into a throwing handler rather than a replacement character handler.
- This is not at all recommended since malformed text (or text assumed to be the wrong encoding) is common, and not properly handling a thrown exception can result in what is, effectively, a denial-of-service attack for things which need to continually handle untrusted input.
- Default: off.
- Not turned on by-default under any conditions.
- **ZTD_TEXT_UNICODE_SCALAR_VALUE_DISTINCT_TYPE**
 - Turns `ztd::text::unicode_scalar_value` from a type definition to `char32_t` to an implementation-defined class type which enforces the various invariants of being a *unicode scalar value*.
 - Default: **on**.
 - Not turned off by-default under any conditions.
- **ZTD_TEXT_UNICODE_SCALAR_VALUE_INVARIANT_ABORT**
 - If `ztd::text::unicode_scalar_value` is a distinct class (as controlled by *ZTD_TEXT_UNICODE_SCALAR_VALUE_DISTINCT_TYPE*), each construction of a *unicode_scalar_value* object that violates the required invariants of a *unicode scalar value* will trigger an abort.
 - It is normally a `ZTD_TEXT_ASSERT(...)` or equivalent.
 - Default: off.
 - Not turned on by-default under any conditions.
- **ZTD_CXX_COMPILE_TIME_ENCODING_NAME**
 - Gives the *ztd::text::literal encoding* a name that matches what the encoding of string literals ("") are.
 - Overrides any of library's heuristics and shenanigans to determine the string literal encoding.
 - If this does not match the actual string literal encoding, it can cause Undefined Behavior.
 - Default: A complex set of platform checks. See *ztd::text::literal encoding* for more details.
 - Not turned on normally under any circumstances.
- **ZTD_TEXT_YES_PLEASE_DESTROY_MY_LITERALS_UTTERLY_I_MEAN_IT**
 - Enables ignoring the fact that the string literal ("") encoding cannot be determined/discovered on the given platform for the *ztd::text::literal encoding*.
 - Will cause Undefined Behavior if a string literal or wide string literal is encoded or decoded to/from and the encoding does not match whatever pot-shot guess the system takes.
 - Default: off.
 - Not turned on by-default under any conditions.
 - **Please don't use this unless you have some really, really weird setup that requires messing everything up...**
- **ZTD_CXX_COMPILE_TIME_WIDE_ENCODING_NAME**
 - Gives the *ztd::text::wide_literal encoding* a name that matches what the encoding of wide string literals (L"") are.
 - Overrides any of library's heuristics and shenanigans to determine the wide string literal encoding.

- If this does not match the actual wide string literal encoding, it can cause Undefined Behavior.
- Default: A complex set of platform checks. See *ztd::text::wide_literal_encoding* for more details.
- Not turned on normally under any circumstances.
- **ZTD_TEXT_YES_PLEASE_DESTROY_MY_WIDE_LITERALS_UTTERLY_I_MEAN_IT**
 - Enables ignoring the fact that the wide string literal (L"") encoding cannot be determined/discovered on the given platform for the *ztd::text::wide_literal_encoding*.
 - Will cause Undefined Behavior if a string literal or wide string literal is encoded or decoded to/from and the encoding does not match whatever pot-shot guess the system takes.
 - Default: off.
 - Not turned on by-default under any conditions.
 - **Please don't use this unless you have some really, really weird setup that requires messing everything up...**
- **ZTD_TEXT_INTERMEDIATE_DECODE_BUFFER_BYTE_SIZE**
 - Changes the default intermediate buffer size placed on the stack for temporary operations.
 - Default: a series of compile time platform checking heuristics to determine a generally useful buffer size that will not overflow the stack.
 - Not turned on by default under any conditions.
 - Specify a numeric value for `ZTD_TEXT_INTERMEDIATE_DECODE_BUFFER_BYTE_SIZE` to have it used instead.
 - Will always be used as the input to a function determining the maximum between this type and a buffer size consistent with *ztd::text::max_code_points_v* or *ztd::text::max_code_points_v*.
- **ZTD_TEXT_INTERMEDIATE_ENCODE_BUFFER_BYTE_SIZE**
 - Changes the default intermediate buffer size placed on the stack for temporary operations.
 - Default: a series of compile time platform checking heuristics to determine a generally useful buffer size that will not overflow the stack.
 - Not turned on by default under any conditions.
 - Specify a numeric value for `ZTD_TEXT_INTERMEDIATE_ENCODE_BUFFER_BYTE_SIZE` to have it used instead.
 - Will always be used as the input to a function determining the maximum between this type and a buffer size consistent with *ztd::text::max_code_points_v* or *ztd::text::max_code_points_v*.
- **ZTD_TEXT_INTERMEDIATE_TRANSCODE_BUFFER_BYTE_SIZE**
 - Changes the default intermediate buffer size placed on the stack for temporary operations.
 - Default: a series of compile time platform checking heuristics to determine a generally useful buffer size that will not overflow the stack.
 - Not turned on by default under any conditions.
 - Specify a numeric value for `ZTD_TEXT_INTERMEDIATE_TRANSCODE_BUFFER_BYTE_SIZE` to have it used instead.
 - Will always be used as the input to a function determining the maximum between this type and a buffer size consistent with *ztd::text::max_code_points_v* or *ztd::text::max_code_points_v*.
- **ZTD_TEXT_INTERMEDIATE_RECODE_BUFFER_BYTE_SIZE**

- Changes the default intermediate buffer size placed on the stack for temporary operations.
- Default: a series of compile time platform checking heuristics to determine a generally useful buffer size that will not overflow the stack.
- Not turned on by default under any conditions.
- Specify a numeric value for `ZTD_TEXT_INTERMEDIATE_RECODE_BUFFER_BYTE_SIZE` to have it used instead.
- Will always be used as the input to a function determining the maximum between this type and a buffer size consistent with `ztd::text::max_code_points_v` or `ztd::text::max_code_points_v`.

1.8 API Reference

This is simply a listing of all the available pages containing various APIs, or links to pages that link to API documentation.

1.8.1 Containers

basic_text (In Progress)

Warning: This isn't finished yet! Come check back by the next major or minor version update.

The `basic_text` class provides functionality similar to `std::string` but for performing it on encoded, normalized text.

```
template<typename, typename, typename>
```

```
class basic_text
```

```
using ztd::text::text = u8text
```

A shortcut for `ztd::u8text`.

```
using ztd::text::ntext = basic_text<execution_t>
```

A container for storing text in the locale, runtime-based encoding.

```
using ztd::text::wtext = basic_text<wide_execution_t>
```

A container for storing text in the locale, runtime-based wide encoding.

```
using ztd::text::nltext = basic_text<literal_t>
```

A container for storing text in the string `literal_t` encoding.

```
using ztd::text::wltext = basic_text<wide_literal_t>
```

A container for storing text in the wide string `literal_t` encoding.

```
using ztd::text::u8text = basic_text<utf8_t>
```

A container for storing text in the UTF-8 encoding.

```
using ztd::text::u16text = basic_text<utf16_t>
```

A container for storing text in the UTF-16 encoding.

```
using ztd::text::u32text = basic_text<utf32_t>
```

A container for storing text in the UTF-32 encoding.

1.8.2 Views

basic_text_view (In Progress)

Warning: This isn't finished yet! Come check back by the next major or minor version update.

The `basic_text_view` class provides a one-by-one view of the stored range's code points and other functionality in a more complete form that goes beyond just code point iteration or code unit iteration like `ztd::text::decode_view` or `ztd::text::encode_view`.

Base Template

```
template<typename _Encoding, typename _NormalizationForm = nfkc, typename _Range =  
::std::basic_string_view<code_unit_t<_Encoding>>, typename _ErrorHandler = default_handler_t, typename  
_State = decode_state_t<remove_cvref_t<_Encoding>>>  
class basic_text_view
```

A view over a sequence of code units. The code units are expected to be of the given encoding and normalization form.

Remark

The default type for this is a `basic_string_view` templated on the code unit type from the encoding. The error handler is also the default careless error handler, meaning that any lossy conversions will automatically cause a compile time error.

Template Parameters

- **_Encoding** – The encoding to store any input and presented text as.
- **_NormalizationForm** – The normalization form to impose on the stored text's sequences.
- **_Range** – The range type that will be stored within this `ztd::text::basic_text_view` and examined using the iterators, following the `_Encoding` type decoding procedure.
- **_ErrorHandler** – The default error handler to use for any and all operations on text. Generally, most operations will provide room to override this.

Public Types

using **range_type** = *_Range*

The type that this view is wrapping.

using **encoding_type** = *_Encoding*

The encoding type that this view is using to interpret the underlying sequence of code units.

using **state_type** = *remove_cvref_t<_State>*

The encoding type that this view is using to interpret the underlying sequence of code units.

using **normalization_type** = *_NormalizationForm*

The normalization form type this view is imposing on top of the encoded sequence.

using **error_handler_type** = *_ErrorHandler*

The error handling type used by default for any problems in conversions.

Public Functions

```
template<typename _ViewErrorHandler>
inline constexpr _CodePointView<_ViewErrorHandler> code_points(state_type __state,
                                                             _ViewErrorHandler
                                                             &&__error_handler) const noexcept
```

Returns a view over the code points of this type, decoding “on the fly”/“lazily”.

Remark

Moves the provided `__state` in as the “starting point”.

Template Parameters

_ViewErrorHandler – The type of the passed-in error handler to use for these operations.

Parameters

- **__state** – [in] The state to use for this code point view.
- **__error_handler** – [in] The error handler to look at the code points for this code point view.

```
inline constexpr _CodePointView code_points(state_type __state) const noexcept
```

Returns a view over the code points of this type, decoding “on the fly”/“lazily”.

Remark

Moves the provided `__state` in as the “starting point”.

Parameters

__state – [in] The state to use for this code point view.

```
inline constexpr _CodePointView code_points() const noexcept
```

Returns a view over the code points of this type, decoding “on the fly”/“lazily”.

Remark

Copies the stored `state` within the `ztd::text::basic_text_view` to perform the code point iteration process.

```
inline constexpr range_type &&base() && noexcept
```

Access the storage as an r-value reference.

```
inline constexpr const range_type &base() const & noexcept
```

Access the storage as a const-qualified l-value reference.

```
inline constexpr range_type &base() & noexcept
```

Access the storage as an l-value reference.

Aliases

```
using ztd::text::text_view = u8text_view
```

A shortcut for `u8text_view`.

```
using ztd::text::ntext_view = basic_text_view<execution_t>
```

A view for examining text in the locale, runtime-based wide encoding.

```
using ztd::text::wtext_view = basic_text_view<wide_execution_t>
```

A view for examining text in the locale, runtime-based wide encoding.

```
using ztd::text::nltext_view = basic_text_view<literal_t>
```

A view for examining text in the string `literal_t` encoding.

```
using ztd::text::wltext_view = basic_text_view<wide_literal_t>
```

A view for examining text in the wide string `literal_t` encoding.

```
using ztd::text::u8text_view = basic_text_view<utf8_t>
```

A view for examining text in the UTF-8 encoding.

```
using ztd::text::u16text_view = basic_text_view<utf16_t>
```

A view for examining text in the UTF-16 encoding.

```
using ztd::text::u32text_view = basic_text_view<utf32_t>
```

A view for examining text in the UTF-32 encoding.

decode_view

The `decode_view` class provides a one-by-one view of the stored range's code points as the desired encoding's code units. Dereferencing the iterators returns a single `code_point` value corresponding to the desired encoding's transformation of the internal code units.

The range-based classes are excellent ways to walk over units of information in a low-memory environment, as they only store the minimum amount of data necessary to perform their operations on the fly. This reduces the speed but is fine for one-at-a-time encoding operations. To decode eagerly and in bulk, see *the decode functions*.

```
template<typename _Encoding, typename _Range =
__txt_detail::__default_char_view_t<code_unit_t<_Encoding>>, typename _ErrorHandler = default_handler_t,
typename _State = decode_state_t<_Encoding>>
class decode_view : public view_base
```

A view over a range of code points, presenting the code points as code units. Uses the `_Encoding` specified to do so.

Remark

The view presents code point one at a time, regardless of how many code points are output by one decode operation. This means if, for example, four (4) UTF-8 code units becomes two (2) UTF-16 code points, it will present one code point at a time. If you are looking to explicitly know what a single decode operation maps into as far as number of code points to code units (and vice-versa), you will have to use lower-level interfaces.

Template Parameters

- **_Encoding** – The encoding to read the underlying range of code points as.
- **_Range** – The range of input that will be fed into the `_FromEncoding`'s decode operation.
- **_ErrorHandler** – The error handler for any encode-step failures.
- **_State** – The state type to use for the decode operations to intermediate code points.

Public Types

```
using iterator = decode_iterator<_Encoding, _StoredRange, _ErrorHandler, _State>
```

The iterator type for this view.

```
using sentinel = decode_sentinel_t
```

The sentinel type for this view.

```
using value_type = ranges::iterator_value_type_t<iterator>
```

The value type for this view.

```
using range_type = _Range
```

The underlying range type.

```
using encoding_type = _Encoding
```

The encoding type used for transformations.

using **error_handler_type** = *ErrorHandler*

The error handler when a decode operation fails.

using **state_type** = *decode_state_t<encoding_type>*

The state type used for decode operations.

Public Functions

```
template<typename _ArgRange, ::std::enable_if_t<!::std::is_same_v<remove_cvref_t<_ArgRange>,
decode_view> && !::std::is_same_v<remove_cvref_t<_ArgRange>, iterator>>* = nullptr>
inline constexpr decode_view(_ArgRange &&__range) noexcept(::std::is_nothrow_constructible_v<iterator,
_ArgRange>)
```

Constructs a *decode_view* from the underlying range.

Remark

The stored encoding, error handler, and state type are default-constructed.

Parameters

__range – [in] The input range to wrap and iterate over.

```
inline constexpr decode_view(range_type __range, encoding_type __encoding)
    noexcept(::std::is_nothrow_constructible_v<iterator, range_type,
encoding_type>)
```

Constructs a *decode_view* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__encoding** – [in] The encoding object to call `.decode` or equivalent functionality on.

```
inline constexpr decode_view(range_type __range, encoding_type __encoding, error_handler_type
    __error_handler) noexcept(::std::is_nothrow_constructible_v<iterator,
range_type, encoding_type, error_handler_type>)
```

Constructs a *decode_view* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__encoding** – [in] The encoding object to call `.decode` or equivalent functionality on.
- **__error_handler** – [in] The error handler to store in this view.

```
inline constexpr decode_view(range_type __range, encoding_type __encoding, error_handler_type
    __error_handler, state_type __state)
    noexcept(::std::is_nothrow_constructible_v<iterator, range_type,
encoding_type, error_handler_type, state_type>)
```

Constructs a *decode_view* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__encoding** – [in] The encoding object to call `.decode` or equivalent functionality on.
- **__error_handler** – [in] The error handler to store in this view.
- **__state** – [in] The state to user for the decode operation.

inline constexpr **decode_view**(*iterator* __it) noexcept(::std::is_nothrow_move_constructible_v<*iterator*>)
 Constructs an `encoding_view` from one of its iterators, reconstituting the range.

Parameters

__it – [in] A previously-made `decode_view` iterator.

constexpr **decode_view**() = default
 Default constructor. Defaulted.

constexpr **decode_view**(const *decode_view*&) = default
 Copy constructor. Defaulted.

constexpr **decode_view**(*decode_view*&&) = default
 Move constructor. Defaulted.

constexpr *decode_view* &**operator**=(const *decode_view*&) = default
 Copy assignment operator. Defaulted.

constexpr *decode_view* &**operator**=(*decode_view*&&) = default
 Move assignment operator. Defaulted.

inline constexpr *iterator* **begin**() & noexcept
 The beginning of the range.

inline constexpr *iterator* **begin**() const & noexcept
 The beginning of the range.

inline constexpr *iterator* **begin**() && noexcept
 The beginning of the range.

inline constexpr *sentinel* **end**() const noexcept
 The end of the range. Uses a sentinel type and not a special iterator.

```
template<typename _Encoding, typename _Range, typename _ErrorHandler = default_handler_t, typename
_State = decode_state_t<_Encoding>>
```

```
class decode_iterator : public __txt_detail::__encoding_iterator<__txt_detail::__transaction::__decode,
decode_iterator<_Encoding, _Range, default_handler_t, decode_state_t<_Encoding>>,
__txt_detail::__iterator_storage<_Encoding, _Range, default_handler_t, decode_state_t<_Encoding>>>
```

An iterator over a range of code points, presented as a range of code units, using the `_Encoding` specified to do so.

Remark

This type produces proxies as their reference type, and are only readable, not writable iterators. The iterator presents code point one at a time, regardless of how many code points are output by one decode operation. This means if, for example, four (4) UTF-8 code units becomes two (2) UTF-16 code points, it will present one code point at a time. If you are looking to explicitly know what a single decode operation maps into as far as number of code points to code units (and vice-versa), you will have to use lower-level interfaces.

Template Parameters

- **_Encoding** – The encoding to read the underlying range of code points as.
- **_Range** – The range of input that will be fed into the `_FromEncoding`'s decode operation.
- **_ErrorHandler** – The error handler for any encode-step failures.
- **_State** – The state type to use for the encode operations to intermediate code points.

Public Types

using **range_type** = typename `__iterator_base_it::range_type`

The underlying range type.

using **iterator** = typename `__iterator_base_it::iterator`

The base iterator type.

using **encoding_type** = typename `__iterator_base_it::encoding_type`

The encoding type used for transformations.

using **error_handler_type** = typename `__iterator_base_it::error_handler_type`

The error handler when an encode operation fails.

using **state_type** = typename `__iterator_base_it::state_type`

The state type used for encode operations.

using **iterator_category** = typename `__iterator_base_it::iterator_category`

The strength of the iterator category, as defined in relation to the base.

using **iterator_concept** = typename `__iterator_base_it::iterator_concept`

The strength of the iterator concept, as defined in relation to the base.

using **value_type** = typename `__iterator_base_it::value_type`

The object type that gets output on every dereference.

using **pointer** = typename `__iterator_base_it::pointer`

A pointer type to the `value_type`.

using **reference** = typename `__iterator_base_it::value_type`

The value returned from dereferencing the iterator.

Remark

This is a proxy iterator, so the `reference` is a non-reference `value_type`.

using **difference_type** = typename __iterator_base_it::difference_type

The type returned when two of these pointers are subtracted from one another.

Remark

It's not a very useful type...

Public Functions

constexpr **decode_iterator**() = default

Default constructor. Defaulted.

constexpr **decode_iterator**(const *decode_iterator*&) = default

Copy constructor. Defaulted.

constexpr **decode_iterator**(*decode_iterator*&&) = default

Move constructor. Defaulted.

template<typename **_ArgRange**, ::std::enable_if_t<!::std::is_same_v<remove_cvref_t<*_ArgRange*>, *decode_iterator*>>* = nullptr>

inline constexpr **decode_iterator**(*_ArgRange* &&__range)
noexcept(::std::is_nothrow_constructible_v<__iterator_base_it,
range_type>)

Constructs a *ztd::text::decode_iterator* from the explicitly given __range.

Remark

Each argument is moved/forwarded in.

Parameters

__range – [in] The range value that will be read from.

inline constexpr **decode_iterator**(*range_type* __range, *encoding_type* __encoding)
noexcept(::std::is_nothrow_constructible_v<__iterator_base_it,
range_type, *encoding_type*>)

Constructs a *ztd::text::decode_iterator* from the explicitly given __range, and __encoding.

Remark

Each argument is moved in.

Parameters

- **__range** – [in] The range value that will be read from.
- **__encoding** – [in] The encoding object to use.

```
inline constexpr decode_iterator(range_type __range, error_handler_type __error_handler)
    noexcept(::std::is_nothrow_constructible_v<__iterator_base_it,
        range_type, error_handler_type>)
```

Constructs a `ztd::text::decode_iterator` from the explicitly given `__range`, and `__error_handler`.

Remark

Each argument is moved in.

Parameters

- **__range** – [in] The range value that will be read from.
- **__error_handler** – [in] The error handler to use for reporting errors.

```
inline constexpr decode_iterator(range_type __range, encoding_type __encoding, error_handler_type
    __error_handler)
    noexcept(::std::is_nothrow_constructible_v<__iterator_base_it,
        range_type, encoding_type, error_handler_type>)
```

Constructs a `ztd::text::decode_iterator` from the explicitly given `__range`, `__encoding`, and `__error_handler`.

Remark

Each argument is moved in.

Parameters

- **__range** – [in] The range value that will be read from.
- **__encoding** – [in] The encoding object to use.
- **__error_handler** – [in] The error handler to use for reporting errors.

```
inline constexpr decode_iterator(range_type __range, encoding_type __encoding, error_handler_type
    __error_handler, state_type __state)
    noexcept(::std::is_nothrow_constructible_v<__iterator_base_it,
        range_type, encoding_type, error_handler_type, state_type>)
```

Constructs a `ztd::text::decode_iterator` from the explicitly given `__range`, `__encoding`, `__error_handler` and `__state`.

Remark

Each argument is moved in.

Parameters

- **__range** – [in] The range value that will be read from.

- **__encoding** – [in] The encoding object to use.
- **__error_handler** – [in] The error handler to use for reporting errors.
- **__state** – [in] The current state.

constexpr *decode_iterator* &**operator**=(const *decode_iterator*&) = default

Copy assignment operator. Defaulted.

constexpr *decode_iterator* &**operator**=(*decode_iterator*&&) = default

Move assignment operator. Defaulted.

encode_view

The `encode_view` class provides a one-by-one view of the stored range's code points as the desired encoding's code units. Dereferencing the iterators returns a single `code_unit` value corresponding to the desired encoding's transformation of the internal code points.

The range-based classes are excellent ways to walk over units of information in a low-memory environment, as they only store the minimum amount of data necessary to perform their operations on the fly. This reduces the speed but is fine for one-at-a-time encoding operations. To encode eagerly and in bulk, see *the encode functions*.

```
template<typename _Encoding, typename _Range =
    __txt_detail::__default_char_view_t<code_point_t<_Encoding>>, typename _ErrorHandler = default_handler_t,
    typename _State = encode_state_t<_Encoding>>
class encode_view : public view_base
```

A view over a range of code points, presenting the code points as code units. Uses the `_Encoding` specified to do so.

Remark

The view presents code units one at a time, regardless of how many code units are output by one decode operation. This means if, for example, one (1) UTF-32 code point becomes four (4) UTF-8 code units, it will present each code unit one at a time. If you are looking to explicitly know what a single encode operation maps into as far as number of code points to code units (and vice-versa), you will have to use lower-level interfaces.

Template Parameters

- **_Encoding** – The encoding to read the underlying range of code points as.
- **_Range** – The range of input that will be fed into the `_FromEncoding`'s decode operation.
- **_ErrorHandler** – The error handler for any encode-step failures.
- **_State** – The state type to use for the encode operations to intermediate code points.

Public Types

using **iterator** = *encode_iterator*<*_Encoding*, *_StoredRange*, *_ErrorHandler*, *_State*>

The iterator type for this view.

using **sentinel** = *encode_sentinel_t*

The sentinel type for this view.

using **range_type** = *_Range*

The underlying range type.

using **encoding_type** = *_Encoding*

The encoding type used for transformations.

using **error_handler_type** = *_ErrorHandler*

The error handler when an encode operation fails.

using **state_type** = *encode_state_t*<*encoding_type*>

The state type used for encode operations.

Public Functions

constexpr **encode_view**() = default

Default constructor. Defaulted.

constexpr **encode_view**(const *encode_view*&) = default

Copy constructor. Defaulted.

constexpr **encode_view**(*encode_view*&&) = default

Move constructor. Defaulted.

template<typename **_ArgRange**, ::std::enable_if_t<!::std::is_same_v<remove_cvref_t<*_ArgRange*>, *encode_view*> && !::std::is_same_v<remove_cvref_t<*_ArgRange*>, *iterator*>>* = nullptr>

inline constexpr **encode_view**(*_ArgRange* && __range) noexcept(::std::is_nothrow_constructible_v<*iterator*, *_ArgRange*>)

Constructs an *encode_view* from the underlying range.

Remark

the stored encoding, error handler, and state type are default-constructed.

Parameters

__range – [**in**] The input range to wrap and iterate over.

inline constexpr **encode_view**(*range_type* __range, *encoding_type* __encoding)
noexcept(::std::is_nothrow_constructible_v<*iterator*, *range_type*, *encoding_type*>)

Constructs an *encode_view* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__encoding** – [in] The encoding object to call `.encode` or equivalent functionality on.

```
inline constexpr encode_view(range_type __range, encoding_type __encoding, error_handler_type
    __error_handler) noexcept(::std::is_nothrow_constructible_v<iterator,
    range_type, encoding_type, error_handler_type>)
```

Constructs an *encode_view* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__encoding** – [in] The encoding object to call `.encode` or equivalent functionality on.
- **__error_handler** – [in] A previously-made *encode_view* iterator.

```
inline constexpr encode_view(range_type __range, encoding_type __encoding, error_handler_type
    __error_handler, state_type __state)
    noexcept(::std::is_nothrow_constructible_v<iterator, range_type,
    encoding_type, error_handler_type, state_type>)
```

Constructs an *encode_view* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__encoding** – [in] The encoding object to call `.encode` or equivalent functionality on.
- **__error_handler** – [in] A previously-made *encode_view* iterator.
- **__state** – [in] The state to user for the encode operation.

```
inline constexpr encode_view(iterator __it) noexcept(::std::is_nothrow_move_constructible_v<iterator>)
```

Constructs an *encoding_view* from one of its iterators, reconstituting the range.

Parameters

__it – [in] A previously-made *encode_view* iterator.

```
constexpr encode_view &operator=(const encode_view&) = default
```

Copy assignment operator. Defaulted.

```
constexpr encode_view &operator=(encode_view&&) = default
```

Move assignment operator. Defaulted.

```
inline constexpr iterator begin() & noexcept
```

The beginning of the range.

```
inline constexpr iterator begin() const & noexcept
```

The beginning of the range.

```
inline constexpr iterator begin() && noexcept
```

The beginning of the range.

```
inline constexpr sentinel end() const noexcept
```

The end of the range. Uses a sentinel type and not a special iterator.

```
template<typename _Encoding, typename _Range, typename _ErrorHandler = default_handler_t, typename
_State = encode_state_t<_Encoding>>
class encode_iterator : public __txt_detail::__encoding_iterator<__txt_detail::__transaction::__encode,
encode_iterator<_Encoding, _Range, default_handler_t, encode_state_t<_Encoding>>,
__txt_detail::__iterator_storage<_Encoding, _Range, default_handler_t, encode_state_t<_Encoding>>>
```

An iterator over an iterator of code points, presenting the code points as code units. Uses the `_Encoding` specified to do so.

Remark

This type produces proxies as their reference type, and are only readable, not writable iterators. The iterator presents code units one at a time, regardless of how many code units are output by one decode operation. This means if, for example, one (1) UTF-32 code point becomes four (4) UTF-8 code units, it will present each code unit one at a time. If you are looking to explicitly know what a single encode operation maps into as far as number of code points to code units (and vice-versa), you will have to use lower-level interfaces.

Template Parameters

- **_Encoding** – The encoding to read the underlying range of code points as.
- **_Range** – The range of input that will be fed into the `_FromEncoding`'s decode operation.
- **_ErrorHandler** – The error handler for any encode-step failures.
- **_State** – The state type to use for the encode operations to intermediate code points.

Public Types

using **range_type** = typename __iterator_base_it::range_type

The underlying range type.

using **iterator** = typename __iterator_base_it::iterator

The base iterator type.

using **encoding_type** = typename __iterator_base_it::encoding_type

The encoding type used for transformations.

using **error_handler_type** = typename __iterator_base_it::error_handler_type

The error handler when an encode operation fails.

using **state_type** = typename __iterator_base_it::state_type

The state type used for encode operations.

using **iterator_category** = typename __iterator_base_it::iterator_category

The strength of the iterator category, as defined in relation to the base.

using **iterator_concept** = typename __iterator_base_it::iterator_concept

The strength of the iterator concept, as defined in relation to the base.

using **value_type** = typename __iterator_base_it::value_type

The object type that gets output on every dereference.

using **pointer** = typename __iterator_base_it::pointer

A pointer type to the value_type.

using **reference** = typename __iterator_base_it::value_type

The value returned from dereferencing the iterator.

Remark

This is a proxy iterator, so the **reference** is a non-reference value_type.

using **difference_type** = typename __iterator_base_it::difference_type

The type returned when two of these pointers are subtracted from one another.

Remark

It's not a very useful type...

Public Functions

constexpr **encode_iterator**() = default

Default constructor. Defaulted.

constexpr **encode_iterator**(const *encode_iterator*&) = default

Copy constructor. Defaulted.

constexpr **encode_iterator**(*encode_iterator*&&) = default

Move constructor. Defaulted.

template<typename **ArgRange**, ::std::enable_if_t<!::std::is_same_v<remove_cvref_t<*ArgRange*>, *encode_iterator*>>* = nullptr>

inline constexpr **encode_iterator**(*ArgRange* &&__range)
 noexcept(::std::is_nothrow_constructible_v<__iterator_base_it,
range_type>)

Constructs a *ztd::text::decode_iterator* from the explicitly given __range.

Remark

Each argument is moved/forwarded in.

Parameters

__range – [in] The range value that will be read from.

```
inline constexpr encode_iterator(range_type __range, encoding_type __encoding)
    noexcept(::std::is_nothrow_constructible_v<__iterator_base_it,
    range_type, encoding_type>)
```

Constructs a *ztd::text::encode_iterator* from the explicitly given `__range`, and `__encoding`.

Remark

Each argument is moved in.

Parameters

- `__range` – [in] The range value that will be read from.
- `__encoding` – [in] The encoding object to use.

```
inline constexpr encode_iterator(range_type __range, error_handler_type __error_handler)
    noexcept(::std::is_nothrow_constructible_v<__iterator_base_it,
    range_type, error_handler_type>)
```

Constructs a *ztd::text::encode_iterator* from the explicitly given `__range`, and `__error_handler`.

Remark

Each argument is moved in.

Parameters

- `__range` – [in] The range value that will be read from.
- `__error_handler` – [in] The error handler to use for reporting errors.

```
inline constexpr encode_iterator(range_type __range, encoding_type __encoding, error_handler_type
    __error_handler)
    noexcept(::std::is_nothrow_constructible_v<__iterator_base_it,
    range_type, encoding_type, error_handler_type>)
```

Constructs a *ztd::text::encode_iterator* from the explicitly given `__range`, `__encoding`, and `__error_handler`.

Remark

Each argument is moved in.

Parameters

- `__range` – [in] The range value that will be read from.
- `__encoding` – [in] The encoding object to use.
- `__error_handler` – [in] The error handler to use for reporting errors.

```
inline constexpr encode_iterator(range_type __range, encoding_type __encoding, error_handler_type
    __error_handler, state_type __state)
    noexcept(::std::is_nothrow_constructible_v<__iterator_base_it,
    range_type, encoding_type, error_handler_type, state_type>)
```

Constructs a `ztd::text::encode_iterator` from the explicitly given `__range`, `__encoding`, `__error_handler` and `__state`.

Remark

Each argument is moved in.

Parameters

- `__range` – [in] The range value that will be read from.
- `__encoding` – [in] The encoding object to use.
- `__error_handler` – [in] The error handler to use for reporting errors.
- `__state` – [in] The current state.

```
constexpr encode_iterator &operator=(const encode_iterator&) = default
```

Copy assignment operator. Defaulted.

```
constexpr encode_iterator &operator=(encode_iterator&&) = default
```

Move assignment operator. Defaulted.

recode_view & recode_iterator

The `recode_view` class provides a one-by-one view of the stored range's code units as another encoding's code units. Dereferencing the iterators returns a single `code_unit` value corresponding to the desired encoding's type.

The range-based classes are excellent ways to walk over units of information in a low-memory environment, as they only store the minimum amount of data necessary to perform their operations on the fly. This reduces the speed but is fine for one-at-a-time encoding operations. To decode eagerly and in bulk, see [the recode functions](#). The paired `recode_iterator` class does the bulk of the work and stores all of the information. It is paired with an empty, blank sentinel value so as to decrease the cost of iteration.

```
template<typename _FromEncoding, typename _ToEncoding = utf8_t, typename _Range =
    __txt_detail::__default_char_view_t<code_unit_t<_FromEncoding>>, typename _FromErrorHandler =
    default_handler_t, typename _ToErrorHandler = default_handler_t, typename _FromState =
    decode_state_t<_FromEncoding>, typename _ToState = encode_state_t<_ToEncoding>>
class recode_view : public view_base
```

A recoding iterator that takes an input of code units and provides an output over the code units of the desired `_ToEncoding` after converting from the `_FromEncoding` in a fashion that will never produce a `ztd::text::encoding_error::insufficient_output` error.

Remark

This type produces proxies as their reference type, and are only readable, not writable iterators. The type will also try many different shortcuts for decoding the input and encoding the intermediates, respectively, including invoking a few customization points for either `decode_one` or `encode_one`. It may also call `recode_one` to

bypass having to do the round-trip through two encodings, which an encoding pair that a developer is interested in can use to do the conversion more quickly. The view presents code units one at a time, regardless of how many code units are output by one decode operation. This means if, for example, one (1) UTF-16 code unit becomes two (2) UTF-8 code units, it will present each code unit one at a time. If you are looking to explicitly know each collection of characters, you will have to use lower-level interfaces.

Template Parameters

- **_FromEncoding** – The encoding to read the underlying range of code points as.
- **_ToEncoding** – The encoding to read the underlying range of code points as.
- **_Range** – The range of input that will be fed into the `_FromEncoding`'s decode operation.
- **_FromErrorHandler** – The error handler for any decode-step failures.
- **_ToErrorHandler** – The error handler for any encode-step failures.
- **_FromState** – The state type to use for the decode operations to intermediate code points.
- **_ToState** – The state type to use for the encode operations to intermediate code points.

Public Types

using **iterator** = *recode_iterator*<*_FromEncoding*, *_ToEncoding*, *_Range*, *_FromErrorHandler*, *_ToErrorHandler*, *_FromState*, *_ToState*>

The iterator type for this view.

using **sentinel** = *recode_sentinel_t*

The sentinel type for this view.

using **range_type** = *_Range*

The underlying range type.

using **from_encoding_type** = *_FromEncoding*

The encoding type used for decoding to intermediate code point storage.

using **to_encoding_type** = *_ToEncoding*

The encoding type used for encoding to the final code units storage.

using **from_error_handler_type** = *_FromErrorHandler*

The error handler when a decode operation fails.

using **to_error_handler_type** = *_ToErrorHandler*

The error handler when an encode operation fails.

using **from_state_type** = *_FromState*

The state type used for decode operations.

using **to_state_type** = *_ToState*

The state type used for encode operations.

Public Functions

inline constexpr **recode_view**(*range_type* __range) noexcept

Constructs a *recode_view* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.

inline constexpr **recode_view**(*range_type* __range, *to_encoding_type* __to_encoding) noexcept

Constructs a *recode_view* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__to_encoding** – [in] The encoding object to call `encode_one` or equivalent functionality on.

inline constexpr **recode_view**(*range_type* __range, *from_encoding_type* __from_encoding, *to_encoding_type* __to_encoding) noexcept

Constructs a *recode_view* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__from_encoding** – [in] The encoding object to call `decode_one` or equivalent functionality on.
- **__to_encoding** – [in] The encoding object to call `encode_one` or equivalent functionality on.

inline constexpr **recode_view**(*range_type* __range, *from_encoding_type* __from_encoding, *to_encoding_type* __to_encoding, *from_error_handler_type* __from_error_handler, *to_error_handler_type* __to_error_handler) noexcept

Constructs a *recode_view* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__from_encoding** – [in] The encoding object to call `decode_one` or equivalent functionality on.
- **__to_encoding** – [in] The encoding object to call `encode_one` or equivalent functionality on.
- **__from_error_handler** – [in] The error handler for decode operations to store in this view.
- **__to_error_handler** – [in] The error handler for encode operations to store in this view.

inline constexpr **recode_view**(*range_type* __range, *from_encoding_type* __from_encoding, *to_encoding_type* __to_encoding, *from_error_handler_type* __from_error_handler, *to_error_handler_type* __to_error_handler, *from_state_type* __from_state, *to_state_type* __to_state) noexcept

Constructs a *recode_view* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.

- **__from_encoding** – [in] The encoding object to call `decode_one` or equivalent functionality on.
- **__to_encoding** – [in] The encoding object to call `encode_one` or equivalent functionality on.
- **__from_error_handler** – [in] The error handler for decode operations to store in this view.
- **__to_error_handler** – [in] The error handler for encode operations to store in this view.
- **__from_state** – [in] The state to user for the decode operation.
- **__to_state** – [in] The state to user for the decode operation.

inline constexpr *iterator* **begin**() & noexcept

The beginning of the range.

inline constexpr *iterator* **begin**() const & noexcept

The beginning of the range.

inline constexpr *iterator* **begin**() && noexcept

The beginning of the range.

inline constexpr *sentinel* **end**() const noexcept

The end of the range. Uses a sentinel type and not a special iterator.

```
template<typename _FromEncoding, typename _ToEncoding, typename _Range, typename _FromErrorHandler,
typename _ToErrorHandler, typename _FromState, typename _ToState>
class recode_iterator : private ebco<remove_cvref_t<_FromEncoding>, 1>, private
ebco<remove_cvref_t<_ToEncoding>, 2>, private ebco<remove_cvref_t<_FromErrorHandler>, 3>, private
ebco<remove_cvref_t<_ToErrorHandler>, 4>, private
__txt_detail::__state_storage<remove_cvref_t<_FromEncoding>, remove_cvref_t<_FromState>, 0>, private
__txt_detail::__state_storage<remove_cvref_t<_ToEncoding>, remove_cvref_t<_ToState>, 1>, private
__txt_detail::__cursor_cache<max_code_units_v<unwrap_remove_cvref_t<_ToEncoding>>,
ranges::is_range_input_or_output_range_exactly_v<unwrap_remove_cvref_t<_Range>>>, private
__txt_detail::__error_cache<decode_error_handler_always_returns_ok_v<unwrap_remove_cvref_t<_FromEncoding>,
unwrap_remove_cvref_t<_FromErrorHandler>>> &&
encode_error_handler_always_returns_ok_v<unwrap_remove_cvref_t<_ToEncoding>,
unwrap_remove_cvref_t<_ToErrorHandler>>>, private
ebco<ranges::range_reconstruct_t<unwrap_remove_cvref_t<_Range>>, 4>
```

A recoding iterator that takes an input of code units and provides an output over the code units of the desired `_ToEncoding` after converting from the `_FromEncoding` in a fashion that will never produce a `ztd::text::encoding_error::insufficient_output` error.

Remark

This type produces proxies as their reference type, and are only readable, not writable iterators. The type will also try many different shortcuts for decoding the input and encoding the intermediates, respectively, including invoking a few customization points for either `decode_one` or `encode_one`. It may also call `recode_one` to bypass having to do the round-trip through two encodings, which an encoding pair that a developer is interested in can use to do the conversion more quickly. The view presents code units one at a time, regardless of how many code units are output by one decode operation. This means if, for example, one (1) UTF-16 code unit becomes two (2) UTF-8 code units, it will present each code unit one at a time. If you are looking to explicitly know each collection of characters, you will have to use lower-level interfaces.

Template Parameters

- **_FromEncoding** – The encoding to read the underlying range of code points as.
- **_ToEncoding** – The encoding to read the underlying range of code points as.
- **_Range** – The range of input that will be fed into the `_FromEncoding`'s decode operation.
- **_FromErrorHandler** – The error handler for any decode-step failures.
- **_ToErrorHandler** – The error handler for any encode-step failures.
- **_FromState** – The state type to use for the decode operations to intermediate code points.
- **_ToState** – The state type to use for the encode operations to intermediate code points.

Public Types

using **range_type** = *_Range*

The underlying range type.

using **iterator_type** = *_BaseIterator*

The base iterator type.

using **from_encoding_type** = *_FromEncoding*

The encoding type used for decoding to intermediate code point storage.

using **to_encoding_type** = *_ToEncoding*

The encoding type used for encoding to the final code units storage.

using **from_error_handler_type** = *_FromErrorHandler*

The error handler when a decode operation fails.

using **to_error_handler_type** = *_ToErrorHandler*

The error handler when an encode operation fails.

using **from_state_type** = *remove_cvref_t<_FromState>*

The state type used for decode operations.

using **to_state_type** = *remove_cvref_t<_ToState>*

The state type used for encode operations.

using **iterator_category** =

```
::std::conditional_t<::ztd::ranges::is_iterator_concept_or_better_v<::std::bidirectional_iterator_tag,
_BaseIterator>, ::std::conditional_t<_IsBackwards, ::std::bidirectional_iterator_tag,
::std::forward_iterator_tag>, ranges::iterator_category_t<_BaseIterator>>
```

The strength of the iterator category, as defined in relation to the base.

using **iterator_concept** =

```
::std::conditional_t<::ztd::ranges::is_iterator_concept_or_better_v<::std::bidirectional_iterator_tag,
_BaseIterator>, ::std::conditional_t<_IsBackwards, ::std::bidirectional_iterator_tag,
::std::forward_iterator_tag>, ranges::iterator_concept_t<_BaseIterator>>
```

The strength of the iterator concept, as defined in relation to the base.

```
using value_type = code_unit_t<ToEncoding>
```

The object type that gets output on every dereference.

```
using pointer = value_type*
```

A pointer type to the `value_type`.

```
using reference = value_type
```

The value returned from dereferencing the iterator.

Remark

This is a proxy iterator, so the `reference` is a non-reference `value_type`.

```
using difference_type = ranges::iterator_difference_type_t<BaseIterator>
```

The type returned when two of these pointers are subtracted from one another.

Remark

It's not a very useful type...

Public Functions

```
inline constexpr recode_iterator() noexcept(  
    cept(::std::is_nothrow_default_constructible_v<__base_from_encoding_t>  
    && ::std::is_nothrow_default_constructible_v<__base_to_encoding_t>  
    &&  
    ::std::is_nothrow_default_constructible_v<__base_from_error_handler_t>  
    &&  
    ::std::is_nothrow_default_constructible_v<__base_to_error_handler_t>  
    && ::std::is_nothrow_constructible_v<__base_from_state_t,  
    _FromEncoding> &&  
    ::std::is_nothrow_constructible_v<__base_to_state_t, ToEncoding> &&  
    ::std::is_default_constructible_v<__base_range_t>)
```

Default constructs a `ztd::text::recode_iterator`.

Remark

This can only work if the underlying encodings, error handlers, and states can handle default construction.

constexpr **recode_iterator**(const *recode_iterator*&) = default

Copy constructs a *recode_iterator*.

constexpr **recode_iterator**(*recode_iterator*&&) = default

Move constructs a *recode_iterator*.

```
inline constexpr recode_iterator(range_type __range)
    noexcept(noexcept(recode_iterator(::std::move(__range),
    to_encoding_type{ })))
```

Constructs a *recode_iterator* from the underlying range.

Parameters

__range – [in] The input range to wrap and iterate over.

```
inline constexpr recode_iterator(range_type __range, to_encoding_type __to_encoding)
```

Constructs a *recode_iterator* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__to_encoding** – [in] The encoding object to call `encode_one` or equivalent functionality on.

```
inline constexpr recode_iterator(range_type __range, from_encoding_type __from_encoding,
    to_encoding_type __to_encoding)
```

Constructs a *recode_iterator* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__from_encoding** – [in] The encoding object to call `decode_one` or equivalent functionality on.
- **__to_encoding** – [in] The encoding object to call `encode_one` or equivalent functionality on.

```
inline constexpr recode_iterator(range_type __range, from_encoding_type __from_encoding,
    to_encoding_type __to_encoding, from_error_handler_type
    __from_error_handler, to_error_handler_type __to_error_handler)
```

Constructs a *recode_iterator* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__from_encoding** – [in] The encoding object to call `decode_one` or equivalent functionality on.
- **__to_encoding** – [in] The encoding object to call `encode_one` or equivalent functionality on.
- **__from_error_handler** – [in] The error handler for decode operations to store in this view.
- **__to_error_handler** – [in] The error handler for encode operations to store in this view.

```
inline constexpr recode_iterator(range_type __range, from_encoding_type __from_encoding,
    to_encoding_type __to_encoding, from_error_handler_type
    __from_error_handler, to_error_handler_type __to_error_handler,
    from_state_type __from_state, to_state_type __to_state)
```

Constructs a *recode_iterator* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__from_encoding** – [in] The encoding object to call `decode_one` or equivalent functionality on.
- **__to_encoding** – [in] The encoding object to call `encode_one` or equivalent functionality on.
- **__from_error_handler** – [in] The error handler for decode operations to store in this view.
- **__to_error_handler** – [in] The error handler for encode operations to store in this view.
- **__from_state** – [in] The state to user for the decode operation.
- **__to_state** – [in] The state to user for the decode operation.

constexpr *recode_iterator* &operator=(const *recode_iterator*&) = default

Copy assigns- a *recode_iterator*.

constexpr *recode_iterator* &operator=(*recode_iterator*&&) = default

Move assigns a *recode_iterator*.

inline constexpr const *from_encoding_type* &from_encoding() const

The decoding (“from”) encoding object.

Returns

A const l-value reference to the encoding object used to construct this iterator.

inline constexpr *from_encoding_type* &from_encoding()

The decoding (“from”) encoding object.

Returns

An l-value reference to the encoding object used to construct this iterator.

inline constexpr const *to_encoding_type* &to_encoding() const

The encoding (“to”) encoding object.

Returns

A const l-value reference to the encoding object used to construct this iterator.

inline constexpr *to_encoding_type* &to_encoding()

The encoding (“to”) encoding object.

Returns

An l-value reference to the encoding object used to construct this iterator.

inline constexpr const *from_state_type* &from_state() const

The decoding (“from”) state object.

inline constexpr *from_state_type* &from_state()

The decoding (“from”) state object.

inline constexpr const *to_state_type* &to_state() const

The encoding (“to”) state object.

```
inline constexpr to_state_type &to_state()
```

The encoding (“to”) state object.

```
inline constexpr const from_error_handler_type &from_handler() const
```

The error handler object.

```
inline constexpr from_error_handler_type &from_handler()
```

The error handler object.

```
inline constexpr const to_error_handler_type &to_handler() const & noexcept
```

The error handler object.

```
inline constexpr to_error_handler_type &to_handler() & noexcept
```

The error handler object.

```
inline constexpr to_error_handler_type &&to_handler() && noexcept
```

The error handler object.

```
inline constexpr range_type range() & noexcept(
    ::std::is_copy_constructible_v<range_type> ?
    ::std::is_nothrow_copy_constructible_v<range_type> :
    (::std::is_nothrow_move_constructible_v<range_type>))
```

The input range used to construct this object.

```
inline constexpr range_type range() const & noexcept(
    ::std::is_nothrow_copy_constructible_v<range_type>)
```

The input range used to construct this object.

```
inline constexpr range_type range() && noexcept(
    ::std::is_nothrow_move_constructible_v<range_type>)
```

The input range used to construct this object.

```
inline constexpr encoding_error pivot_error_code() const noexcept
```

Returns whether the last read operation had an encoding error or not.

Remark

If the error handler is identified as an error handler that, if given a suitably sized buffer, will never return an error. This is the case with specific encoding operations with *ztd::text::replacement_handler_t*, or *ztd::text::throw_handler_t*.

Returns

The *ztd::text::encoding_error* that occurred. This can be *ztd::text::encoding_error::ok* for an operation that went just fine.

```
inline constexpr encoding_error error_code() const noexcept
```

Returns whether the last read operation had an encoding error or not.

Remark

If the error handler is identified as an error handler that, if given a suitably sized buffer, will never return an error. This is the case with specific encoding operations with *ztd::text::replacement_handler_t*, or *ztd::text::throw_handler_t*.

Returns

The `ztd::text::encoding_error` that occurred. This can be `ztd::text::encoding_error::ok` for an operation that went just fine.

```
inline constexpr recode_iterator operator++(int)
```

Copy then increment the iterator.

Returns

A copy of iterator, before incrementing.

```
inline constexpr recode_iterator &operator++()
```

Increment the iterator.

Returns

A reference to `*this`, after incrementing the iterator.

```
inline constexpr value_type operator*() const
```

Dereference the iterator.

Remark

This is a proxy iterator, and therefore only returns a `value_type` object and not a reference object. Encoding iterators are only readable, not writable.

Returns

A `value_type` (NOT a reference) of the iterator.

Friends

```
inline friend constexpr friend bool operator== (const recode_iterator &__it,  
const recode_sentinel_t &)
```

Compares whether or not this iterator has truly reached the end.

```
inline friend constexpr friend bool operator== (const recode_sentinel_t &__sen,  
const recode_iterator &__it)
```

Compares whether or not this iterator has truly reached the end.

```
inline friend constexpr friend bool operator!= (const recode_iterator &__it,  
const recode_sentinel_t &)
```

Compares whether or not this iterator has truly reached the end.

```
inline friend constexpr friend bool operator!= (const recode_sentinel_t &__sen,  
const recode_iterator &__it)
```

Compares whether or not this iterator has truly reached the end.

transcode_view & transcode_iterator

The `transcode_view` class provides a one-by-one view of the stored range's code units as another encoding's code units. Dereferencing the iterators returns a single `code_unit` value corresponding to the desired encoding's type.

The range-based classes are excellent ways to walk over units of information in a low-memory environment, as they only store the minimum amount of data necessary to perform their operations on the fly. This reduces the speed but is fine for one-at-a-time encoding operations. To decode eagerly and in bulk, see *the transcode functions*. The paired `transcode_iterator` class does the bulk of the work and stores all of the information. It is paired with an empty, blank sentinel value so as to decrease the cost of iteration.

```
template<typename _FromEncoding, typename _ToEncoding = utf8_t, typename _Range =
__txt_detail::__default_char_view_t<code_unit_t<_FromEncoding>>, typename _FromErrorHandler =
default_handler_t, typename _ToErrorHandler = default_handler_t, typename _FromState =
decode_state_t<_FromEncoding>, typename _ToState = encode_state_t<_ToEncoding>>
class transcode_view : public view_base
```

A transcoding iterator that takes an input of code units and provides an output over the code units of the desired `_ToEncoding` after converting from the `_FromEncoding` in a fashion that will never produce a `ztd::text::encoding_error::insufficient_output` error.

Remark

This type produces proxies as their reference type, and are only readable, not writable iterators. The type will also try many different shortcuts for decoding the input and encoding the intermediates, respectively, including invoking a few customization points for either `decode_one` or `encode_one`. It may also call `transcode_one` to bypass having to do the round-trip through two encodings, which an encoding pair that a developer is interested in can use to do the conversion more quickly. The view presents code units one at a time, regardless of how many code units are output by one decode operation. This means if, for example, one (1) UTF-16 code unit becomes two (2) UTF-8 code units, it will present each code unit one at a time. If you are looking to explicitly know each collection of characters, you will have to use lower-level interfaces.

Template Parameters

- **_FromEncoding** – The encoding to read the underlying range of code points as.
- **_ToEncoding** – The encoding to read the underlying range of code points as.
- **_Range** – The range of input that will be fed into the `_FromEncoding`'s decode operation.
- **_FromErrorHandler** – The error handler for any decode-step failures.
- **_ToErrorHandler** – The error handler for any encode-step failures.
- **_FromState** – The state type to use for the decode operations to intermediate code points.
- **_ToState** – The state type to use for the encode operations to intermediate code points.

Public Types

using **iterator** = *transcode_iterator*<*_FromEncoding*, *_ToEncoding*, *_Range*, *_FromErrorHandler*, *_ToErrorHandler*, *_FromState*, *_ToState*>

The iterator type for this view.

using **sentinel** = *transcode_sentinel_t*

The sentinel type for this view.

using **range_type** = *_Range*

The underlying range type.

using **from_encoding_type** = *_FromEncoding*

The encoding type used for decoding to intermediate code point storage.

using **to_encoding_type** = *_ToEncoding*

The encoding type used for encoding to the final code units storage.

using **from_error_handler_type** = *_FromErrorHandler*

The error handler when a decode operation fails.

using **to_error_handler_type** = *_ToErrorHandler*

The error handler when an encode operation fails.

using **from_state_type** = *_FromState*

The state type used for decode operations.

using **to_state_type** = *_ToState*

The state type used for encode operations.

Public Functions

inline constexpr **transcode_view**(*range_type* __range) noexcept

Constructs a *transcode_view* from the underlying range.

Parameters

__range – [in] The input range to wrap and iterate over.

inline constexpr **transcode_view**(*range_type* __range, *to_encoding_type* __to_encoding) noexcept

Constructs a *transcode_view* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__to_encoding** – [in] The encoding object to call `encode_one` or equivalent functionality on.

```
inline constexpr transcode_view(range_type __range, from_encoding_type __from_encoding,
                                to_encoding_type __to_encoding) noexcept
```

Constructs a *transcode_view* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__from_encoding** – [in] The encoding object to call `decode_one` or equivalent functionality on.
- **__to_encoding** – [in] The encoding object to call `encode_one` or equivalent functionality on.

```
inline constexpr transcode_view(range_type __range, from_encoding_type __from_encoding,
                                to_encoding_type __to_encoding, from_error_handler_type
                                __from_error_handler, to_error_handler_type __to_error_handler)
                                noexcept
```

Constructs a *transcode_view* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__from_encoding** – [in] The encoding object to call `decode_one` or equivalent functionality on.
- **__to_encoding** – [in] The encoding object to call `encode_one` or equivalent functionality on.
- **__from_error_handler** – [in] The error handler for decode operations to store in this view.
- **__to_error_handler** – [in] The error handler for encode operations to store in this view.

```
inline constexpr transcode_view(range_type __range, from_encoding_type __from_encoding,
                                to_encoding_type __to_encoding, from_error_handler_type
                                __from_error_handler, to_error_handler_type __to_error_handler,
                                from_state_type __from_state, to_state_type __to_state) noexcept
```

Constructs a *transcode_view* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__from_encoding** – [in] The encoding object to call `decode_one` or equivalent functionality on.
- **__to_encoding** – [in] The encoding object to call `encode_one` or equivalent functionality on.
- **__from_error_handler** – [in] The error handler for decode operations to store in this view.
- **__to_error_handler** – [in] The error handler for encode operations to store in this view.
- **__from_state** – [in] The state to user for the decode operation.
- **__to_state** – [in] The state to user for the decode operation.

```
inline constexpr iterator begin() & noexcept
```

The beginning of the range.

inline constexpr *iterator* **begin**() const & noexcept

The beginning of the range.

inline constexpr *iterator* **begin**() && noexcept

The beginning of the range.

inline constexpr *sentinel* **end**() const noexcept

The end of the range. Uses a sentinel type and not a special iterator.

```
template<typename _FromEncoding, typename _ToEncoding, typename _Range, typename _FromErrorHandler,
typename _ToErrorHandler, typename _FromState, typename _ToState>
class transcode_iterator : private ebco<remove_cvref_t<_FromEncoding>, 1>, private
ebco<remove_cvref_t<_ToEncoding>, 2>, private ebco<remove_cvref_t<_FromErrorHandler>, 3>, private
ebco<remove_cvref_t<_ToErrorHandler>, 4>, private
__txt_detail::__state_storage<remove_cvref_t<_FromEncoding>, remove_cvref_t<_FromState>, 0>, private
__txt_detail::__state_storage<remove_cvref_t<_ToEncoding>, remove_cvref_t<_ToState>, 1>, private
__txt_detail::__cursor_cache<max_code_units_v<unwrap_remove_cvref_t<_ToEncoding>>>,
ranges::is_range_input_or_output_range_exactly_v<unwrap_remove_cvref_t<_Range>>>, private
__txt_detail::__error_cache<decode_error_handler_always_returns_ok_v<unwrap_remove_cvref_t<_FromEncoding>,
unwrap_remove_cvref_t<_FromErrorHandler>>> &&
encode_error_handler_always_returns_ok_v<unwrap_remove_cvref_t<_ToEncoding>,
unwrap_remove_cvref_t<_ToErrorHandler>>>>, private
ebco<__txt_detail::__span_reconstruct_t<unwrap_remove_cvref_t<_Range>, unwrap_remove_cvref_t<_Range>>>,
5>
```

A transcoding iterator that takes an input of code units and provides an output over the code units of the desired `_ToEncoding` after converting from the `_FromEncoding` in a fashion that will never produce a `ztd::text::encoding_error::insufficient_output` error.

Remark

This type produces proxies as their reference type, and are only readable, not writable iterators. The type will also try many different shortcuts for decoding the input and encoding the intermediates, respectively, including invoking a few customization points for either `decode_one` or `encode_one`. It may also call `transcode_one` to bypass having to do the round-trip through two encodings, which an encoding pair that a developer is interested in can use to do the conversion more quickly. The view presents code units one at a time, regardless of how many code units are output by one decode operation. This means if, for example, one (1) UTF-16 code unit becomes two (2) UTF-8 code units, it will present each code unit one at a time. If you are looking to explicitly know each collection of characters, you will have to use lower-level interfaces.

Template Parameters

- **_FromEncoding** – The encoding to read the underlying range of code points as.
- **_ToEncoding** – The encoding to read the underlying range of code points as.
- **_Range** – The range of input that will be fed into the `_FromEncoding`'s decode operation.
- **_FromErrorHandler** – The error handler for any decode-step failures.
- **_ToErrorHandler** – The error handler for any encode-step failures.
- **_FromState** – The state type to use for the decode operations to intermediate code points.
- **_ToState** – The state type to use for the encode operations to intermediate code points.

Public Types

using **range_type** = *_Range*

The underlying range type.

using **iterator_type** = *_BaseIterator*

The base iterator type.

using **from_encoding_type** = *_FromEncoding*

The encoding type used for decoding to intermediate code point storage.

using **to_encoding_type** = *_ToEncoding*

The encoding type used for encoding to the final code units storage.

using **from_error_handler_type** = *_FromErrorHandler*

The error handler when a decode operation fails.

using **to_error_handler_type** = *_ToErrorHandler*

The error handler when an encode operation fails.

using **from_state_type** = *remove_cvref_t<_FromState>*

The state type used for decode operations.

using **to_state_type** = *remove_cvref_t<_ToState>*

The state type used for encode operations.

using **iterator_category** =

```
::std::conditional_t<::ztd::ranges::is_iterator_concept_or_better_v<::std::bidirectional_iterator_tag,
_BaseIterator>, ::std::conditional_t<_IsBackwards, ::std::bidirectional_iterator_tag,
::std::forward_iterator_tag>, ranges::iterator_category_t<_BaseIterator>>
```

The strength of the iterator category, as defined in relation to the base.

using **iterator_concept** =

```
::std::conditional_t<::ztd::ranges::is_iterator_concept_or_better_v<::std::bidirectional_iterator_tag,
_BaseIterator>, ::std::conditional_t<_IsBackwards, ::std::bidirectional_iterator_tag,
::std::forward_iterator_tag>, ranges::iterator_concept_t<_BaseIterator>>
```

The strength of the iterator concept, as defined in relation to the base.

using **value_type** = *code_unit_t<_ToEncoding>*

The object type that gets output on every dereference.

using **pointer** = *value_type**

A pointer type to the value_type.

using **reference** = *value_type*

The value returned from dereferencing the iterator.

Remark

This is a proxy iterator, so the `reference` is a non-reference `value_type`.

using `difference_type` = `ranges::iterator_difference_type_t<_BaseIterator>`

The type returned when two of these pointers are subtracted from one another.

Remark

It's not a very useful type...

Public Functions

```
inline constexpr transcode_iterator() noexcept
    cept(::std::is_nothrow_default_constructible_v<__base_from_encoding_t>
    &&
    ::std::is_nothrow_default_constructible_v<__base_to_encoding_t>
    &&
    ::std::is_nothrow_default_constructible_v<__base_from_error_handler_t>
    &&
    ::std::is_nothrow_default_constructible_v<__base_to_error_handler_t>
    && ::std::is_nothrow_constructible_v<__base_from_state_t,
    _FromEncoding> &&
    ::std::is_nothrow_constructible_v<__base_to_state_t, _ToEncoding>
    && ::std::is_default_constructible_v<__base_range_t>)
```

Default constructs a `ztd::text::transcode_iterator`.

Remark

This can only work if the underlying encodings, error handlers, and states can handle default construction.

```
constexpr transcode_iterator(const transcode_iterator&) = default
```

Copy constructs a `transcode_iterator`.

```
constexpr transcode_iterator(transcode_iterator&&) = default
```

Move constructs a `transcode_iterator`.

```
inline constexpr transcode_iterator(range_type __range)
    noexcept(noexcept(transcode_iterator::std::move(__range),
    to_encoding_type{ })))
```

Constructs a `transcode_iterator` from the underlying range.

Parameters

`__range` – [in] The input range to wrap and iterate over.

```
inline constexpr transcode_iterator(range_type __range, to_encoding_type __to_encoding)
```

Constructs a `transcode_iterator` from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__to_encoding** – [in] The encoding object to call `encode_one` or equivalent functionality on.

inline constexpr **transcode_iterator**(*range_type* __range, *from_encoding_type* __from_encoding, *to_encoding_type* __to_encoding)

Constructs a *transcode_iterator* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__from_encoding** – [in] The encoding object to call `decode_one` or equivalent functionality on.
- **__to_encoding** – [in] The encoding object to call `encode_one` or equivalent functionality on.

inline constexpr **transcode_iterator**(*range_type* __range, *from_encoding_type* __from_encoding, *to_encoding_type* __to_encoding, *from_error_handler_type* __from_error_handler, *to_error_handler_type* __to_error_handler)

Constructs a *transcode_iterator* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__from_encoding** – [in] The encoding object to call `decode_one` or equivalent functionality on.
- **__to_encoding** – [in] The encoding object to call `encode_one` or equivalent functionality on.
- **__from_error_handler** – [in] The error handler for decode operations to store in this view.
- **__to_error_handler** – [in] The error handler for encode operations to store in this view.

inline constexpr **transcode_iterator**(*range_type* __range, *from_encoding_type* __from_encoding, *to_encoding_type* __to_encoding, *from_error_handler_type* __from_error_handler, *to_error_handler_type* __to_error_handler, *from_state_type* __from_state, *to_state_type* __to_state)

Constructs a *transcode_iterator* from the underlying range.

Parameters

- **__range** – [in] The input range to wrap and iterate over.
- **__from_encoding** – [in] The encoding object to call `decode_one` or equivalent functionality on.
- **__to_encoding** – [in] The encoding object to call `encode_one` or equivalent functionality on.
- **__from_error_handler** – [in] The error handler for decode operations to store in this view.
- **__to_error_handler** – [in] The error handler for encode operations to store in this view.
- **__from_state** – [in] The state to user for the decode operation.

- **__to_state** – [in] The state to user for the decode operation.

constexpr *transcode_iterator* &**operator**=(const *transcode_iterator*&) = default

Copy assigns- a *transcode_iterator*.

constexpr *transcode_iterator* &**operator**=(*transcode_iterator*&&) = default

Move assigns a *transcode_iterator*.

inline constexpr const *from_encoding_type* &**from_encoding**() const

The decoding (“from”) encoding object.

Returns

A const l-value reference to the encoding object used to construct this iterator.

inline constexpr *from_encoding_type* &**from_encoding**()

The decoding (“from”) encoding object.

Returns

An l-value reference to the encoding object used to construct this iterator.

inline constexpr const *to_encoding_type* &**to_encoding**() const

The encoding (“to”) encoding object.

Returns

A const l-value reference to the encoding object used to construct this iterator.

inline constexpr *to_encoding_type* &**to_encoding**()

The encoding (“to”) encoding object.

Returns

An l-value reference to the encoding object used to construct this iterator.

inline constexpr const *from_state_type* &**from_state**() const

The decoding (“from”) state object.

inline constexpr *from_state_type* &**from_state**()

The decoding (“from”) state object.

inline constexpr const *to_state_type* &**to_state**() const

The encoding (“to”) state object.

inline constexpr *to_state_type* &**to_state**()

The encoding (“to”) state object.

inline constexpr const *from_error_handler_type* &**from_handler**() const

The error handler object.

inline constexpr *from_error_handler_type* &**from_handler**()

The error handler object.

inline constexpr const *to_error_handler_type* &**to_handler**() const & noexcept

The error handler object.

inline constexpr *to_error_handler_type* &**to_handler**() & noexcept

The error handler object.

inline constexpr *to_error_handler_type* &&**to_handler**() && noexcept

The error handler object.

```
inline constexpr range_type range() & noexcept(::std::is_copy_constructible_v<range_type> ?
::std::is_nothrow_copy_constructible_v<range_type> :
(::std::is_nothrow_move_constructible_v<range_type>))
```

The input range used to construct this object.

```
inline constexpr range_type range() const & noexcept(::std::is_nothrow_copy_constructible_v<range_type>)
```

The input range used to construct this object.

```
inline constexpr range_type range() && noexcept(::std::is_nothrow_move_constructible_v<range_type>)
```

The input range used to construct this object.

```
inline constexpr encoding_error pivot_error_code() const noexcept
```

Returns whether the last read operation had an encoding error or not.

Remark

If the error handler is identified as an error handler that, if given a suitably sized buffer, will never return an error. This is the case with specific encoding operations with *ztd::text::replacement_handler_t*, or *ztd::text::throw_handler_t*.

Returns

The *ztd::text::encoding_error* that occurred. This can be *ztd::text::encoding_error::ok* for an operation that went just fine.

```
inline constexpr encoding_error error_code() const noexcept
```

Returns whether the last read operation had an encoding error or not.

Remark

If the error handler is identified as an error handler that, if given a suitably sized buffer, will never return an error. This is the case with specific encoding operations with *ztd::text::replacement_handler_t*, or *ztd::text::throw_handler_t*.

Returns

The *ztd::text::encoding_error* that occurred. This can be *ztd::text::encoding_error::ok* for an operation that went just fine.

```
inline constexpr transcode_iterator operator++(int)
```

Copy then increment the iterator.

Returns

A copy of iterator, before incrementing.

```
inline constexpr transcode_iterator &operator++()
```

Increment the iterator.

Returns

A reference to **this*, after incrementing the iterator.

```
inline constexpr value_type operator*() const
```

Dereference the iterator.

Remark

This is a proxy iterator, and therefore only returns a `value_type` object and not a reference object. Encoding iterators are only readable, not writable.

Returns

A `value_type` (NOT a reference) of the iterator.

Friends

```
inline friend constexpr friend bool operator==(const transcode_iterator &__it,  
const transcode_sentinel_t &)
```

Compares whether or not this iterator has truly reached the end.

```
inline friend constexpr friend bool operator==(const transcode_sentinel_t &__sen,  
const transcode_iterator &__it)
```

Compares whether or not this iterator has truly reached the end.

```
inline friend constexpr friend bool operator!=(const transcode_iterator &__it,  
const transcode_sentinel_t &)
```

Compares whether or not this iterator has truly reached the end.

```
inline friend constexpr friend bool operator!=(const transcode_sentinel_t &__sen,  
const transcode_iterator &__it)
```

Compares whether or not this iterator has truly reached the end.

1.8.3 Encodings

See also *the top-level encodings page* for more details about the overall status and known vs. implemented encodings.

`any_encoding`

`any_encoding` is a class type whose sole purpose is to provide a type-generic, byte-based, runtime-deferred way of handling encodings.

Aliases

```
using ztd::text::any_encoding = any_byte_encoding<::std::byte>
```

The canonical erased encoding type which uses a `std::byte` as its code unit type and an `unicode_code_point` as its code point type, with spans for input and output operations.

Remark

If the input encoding does not match `std::byte`, it will be first wrapped in a `ztd::text::encoding_scheme` first.

Base Template

```
template<typename _Byte, typename _CodePoint = unicode_code_point>
```

```
class any_byte_encoding : public ztd::text::any_encoding_with<_Byte, const unicode_code_point, const _Byte,
unicode_code_point>
```

An encoding type that wraps up other encodings to specifically traffic in the given `_Byte` type provided, which is typically set to `std::byte`.

Remark

This type traffics solely in `std::spans`, which for most people is fine. Others may want to interface with different iterator types (e.g., from a custom Rope implementation or other). For those, one must first create ranges that can operate with those iterators, then use them themselves. (It's not an ideal process at the moment, and we are looking to make this experience better.) It is recommended to use the provided `ztd::text::any_encoding` type definition instead of accessing this directly, unless you have a reason for using a different byte type (e.g., interfacing with legacy APIs).

Template Parameters

_Byte – The byte type to use. Typically, this is either `unsigned char` or `std::byte`.

Public Types

```
using decode_state = any_decode_state
```

The state that can be used between calls to `decode`.

Remark

This is an opaque struct with no members. It follows the “encoding-dependent state” model, which means it has a constructor that takes an `ztd::text::any_encoding_with` so it can properly initialize its state.

using **encode_state** = any_encode_state

The state that can be used between calls to **encode**.

Remark

This is an opaque struct with no members. It follows the “encoding-dependent state” model, which means it has a constructor that takes an *ztd::text::any_encoding_with* so it can properly initialize its state.

using **code_unit** = ranges::range_value_type_t<_EncodeCodeUnits>

The individual units that result from an encode operation or are used as input to a decode operation.

using **code_point** = ranges::range_value_type_t<_DecodeCodePoints>

The individual units that result from a decode operation or as used as input to an encode operation.

using **is_encode_injective** = ::std::false_type

Whether or not the encode operation can process all forms of input into code point values.

Remark

This is always going to be false because this is a type-erased encoding; this value is determined by a runtime decision, which means that the most conservative and truthful answer is selected for this property.

using **is_decode_injective** = ::std::false_type

Whether or not the decode operation can process all forms of input into code point values.

Remark

This is always going to be false because this is a type-erased encoding; this value is determined by a runtime decision, which means that the most conservative and truthful answer is selected for this property.

Public Functions

any_byte_encoding() = delete

Cannot default-construct a *ztd::text::any_byte_encoding* object.

```
template<typename _EncodingArg, typename ..._Args,
::std::enable_if_t<!::std::is_same_v<remove_cvref_t<_EncodingArg>, any_byte_encoding> &&
!::std::is_same_v<__txt_detail::__code_unit_or_void_t<remove_cvref_t<_EncodingArg>>, Byte> &&
lis_specialization_of_v<remove_cvref_t<_EncodingArg>, ::ztd::text::any_byte_encoding> &&
!::std::is_same_v<remove_cvref_t<_EncodingArg>, __base_t> &&
lis_specialization_of_v<remove_cvref_t<_EncodingArg>, ::std::in_place_type_t>>* = nullptr>
```

```
inline any_byte_encoding(_EncodingArg &&__encoding, _Args&&... __args)
```

Constructs a *ztd::text::any_byte_encoding* with the encoding object and any additional arguments.

Remark

If the provided encoding does not have a byte *code_unit* type, it is wrapped in an *ztd::text::encoding_scheme* first.

Parameters

- **__encoding** – [in] The encoding object that informs the *ztd::text::any_byte_encoding* what encoding object to store.
- **__args** – [in] Any additional arguments used to construct the encoding in the erased storage.

```
template<typename _EncodingArg, typename ...Args, ::std::enable_if_t<!::std::is_same_v<_Byte,  
code_unit_t<remove_cvref_t<_EncodingArg>>>>* = nullptr>
```

```
inline any_byte_encoding(::std::in_place_type_t<_EncodingArg>, _Args&&... __args)
```

Constructs a *ztd::text::any_byte_encoding* with the encoding object and any additional arguments.

Remark

If the provided encoding does not have a byte *code_unit* type, it is wrapped in an *ztd::text::encoding_scheme* first.

Template Parameters

_EncodingArg – The Encoding specified by the `std::in_place_type<...>` argument.

Parameters

__args – [in] Any additional arguments used to construct the encoding in the erased storage.

```
template<typename _EncodingArg, typename ...Args, ::std::enable_if_t<::std::is_same_v<_Byte,  
code_unit_t<remove_cvref_t<_EncodingArg>>>>* = nullptr>
```

```
inline any_byte_encoding(::std::in_place_type_t<_EncodingArg> __tag, _Args&&... __args)
```

Constructs a *ztd::text::any_byte_encoding* with the encoding object and any additional arguments.

Remark

If the provided encoding does not have a byte *code_unit* type, it is wrapped in an *ztd::text::encoding_scheme* first.

Template Parameters

_EncodingArg – The Encoding specified by the `std::in_place_type<...>` argument.

Parameters

- **__tag** – [in] A tag containing the encoding type.

- `__args` – [in] Any additional arguments used to construct the encoding in the erased storage.

`any_byte_encoding(const any_byte_encoding&) = delete`

Cannot copy-construct a `ztd::text::any_byte_encoding` object.

`any_byte_encoding &operator=(const any_byte_encoding&) = delete`

Cannot copy-assign a `ztd::text::any_byte_encoding` object.

`any_byte_encoding(any_byte_encoding&&) = default`

Move-constructs a `ztd::text::any_byte_encoding` from the provided r-value reference.

Remark

This leaves the passed-in r-value reference without an encoding object. Calling any function on a moved-from `ztd::text::any_byte_encoding`, except for destruction, is a violation and invokes Undefined Behavior (generally, a crash).

`any_byte_encoding &operator=(any_byte_encoding&&) = default`

Move-assigns a `ztd::text::any_byte_encoding` from the provided r-value reference.

Remark

This leaves the passed-in r-value reference without an encoding object. Calling any function on a moved-from `ztd::text::any_byte_encoding`, except for destruction, is a violation and invokes Undefined Behavior (generally, a crash).

`inline ::std::optional<::ztd::span<const code_point>> maybe_replacement_code_points() const noexcept`

Retrieves the replacement code points for when conversions fail and `ztd::text::replacement_handler_t` (or equivalent) needs to make a substitution.

Returns

A `std::optional` of `ztd::span` of const `code_points`. The returned `std::optional` value is engaged (has a value) if the stored encoding has a valid `replacement_code_points` function and it can be called. If it does not, then the library checks to see if the `maybe_replacement_code_points` function exists, and returns the `std::optional` from that type directly. If neither are present, an unengaged `std::optional` is returned.

`inline ::std::optional<::ztd::span<const code_unit>> maybe_replacement_code_units() const noexcept`

Retrieves the replacement code units for when conversions fail and `ztd::text::replacement_handler_t` (or equivalent) needs to make a substitution.

Returns

A `std::optional` of `ztd::span` of const `code_units`. The returned `std::optional` value is engaged (has a value) if the stored encoding has a valid `replacement_code_units` function and it can be called. If it does not, then the library checks to see if the `maybe_replacement_code_units` function exists, and returns the `std::optional` from that type directly. If neither are present, an unengaged `std::optional` is returned.

inline bool **contains_unicode_encoding**() const noexcept

Returns whether or not the encoding stored in this *ztd::text::any_encoding_with* is a Unicode encoding.

Remark

This can be useful to know, in advance, whether or not there is a chance for lossy behavior. Even if, at compile time, various functions will demand you use an error handler, this runtime property can help you get a decent idea of just how bad and lossy this conversion might be compared to normal UTF conversion formats.

inline __decode_result **decode_one**(_DecodeCodeUnits __input, _DecodeCodePoints __output, __decode_error_handler __error_handler, *decode_state* &__state) const

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a *forward_range*). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an *input_range*.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A *ztd::text::decode_result* object that contains the input range, output range, error handler, and a reference to the passed-in state.

inline __encode_result **encode_one**(_EncodeCodePoints __input, _EncodeCodeUnits __output, __encode_error_handler __error_handler, *encode_state* &__state) const

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a *forward_range*). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an *input_range*.

Parameters

- **__input** – [in] The input view to read code points from.
- **__output** – [in] The output view to write code units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::encode_result` object that contains the input range, output range, error handler, and a reference to the passed-in state.

Public Static Attributes

```
static constexpr ::std::size_t max_code_points = _MaxCodePoints
```

The maximum number of code points a single complete operation of decoding can produce. This is 1 for all Unicode Transformation Format (UTF) encodings.

```
static constexpr ::std::size_t max_code_units = _MaxCodeUnits
```

The maximum code units a single complete operation of encoding can produce.

```
static constexpr ::ztd::text_encoding_id decoded_id = ::ztd::text_encoding_id::unknown
```

The decoded id. Because this is a type-erased encoding, anything can come out: therefore, it is set to “unknown” at all times.

```
static constexpr ::ztd::text_encoding_id encoded_id = ::ztd::text_encoding_id::unknown
```

The encoded id. Because this is a type-erased encoding, anything can come out: therefore, it is set to “unknown” at all times.

any_encoding_with

This is the lowest level base template, `any_encoding_with`, that sits beneath *any_encoding* and *any_byte_encoding*. It is recommended for power users with specific goals for the input and output types of the encode and decode operations, where normal buffer-based I/O is unsuitable. In general, you should be relying on *any_encoding* and *any_byte_encoding*.

Base Template

```
template<typename _EncodeCodeUnits, typename _EncodeCodePoints, typename _DecodeCodeUnits,  
typename _DecodeCodePoints, ::std::size_t _MaxCodeUnits =  
__txt_detail::__default_max_code_units_any_encoding, ::std::size_t _MaxCodePoints =  
__txt_detail::__default_max_code_points_any_encoding>  
class any_encoding_with
```

An encoding class which has the given encode output and input, as well as the decode input and output ranges, provided as fixed types alongside the maximum number of code units put in and pushed out.

Remark

This class is generally interacted with by using its derivate class, `ztd::text::any_byte_encoding`, and its convenience alias, `ztd::text::any_encoding`. This class's use is recommended only for power users who have encoding ranges that cannot be interacted with through `ztd::span` and therefore need other ways. We are looking into ways to produce a `ranges::subrange<any_iterator>` as a completely generic range to aid those individuals who do not want to deal in just `ztd::spans`.

Template Parameters

- **_EncodeCodeUnits** – The output of `encode_one` and related operations.
- **_EncodeCodePoints** – The input of `encode_one` and related operations.
- **_DecodeCodeUnits** – The input of `decode_one` and related operations.
- **_DecodeCodePoints** – The output of `decode_one` and related operations.
- **_MaxCodeUnits** – The maximum number of code units that can be output through a given operation. Directly related to the `maximum_code_units` inline constexpr variable definition.
- **_MaxCodePoints** – The maximum number of code points that can be output through a given operation. Directly related to the `maximum_code_points` inline constexpr variable definition.

Subclassed by `any_byte_encoding<_Byte, _CodePoint>`

Public Types

using **decode_state** = `any_decode_state`

The state that can be used between calls to `decode`.

Remark

This is an opaque struct with no members. It follows the “encoding-dependent state” model, which means it has a constructor that takes an `ztd::text::any_encoding_with` so it can properly initialize its state.

using **encode_state** = `any_encode_state`

The state that can be used between calls to `encode`.

Remark

This is an opaque struct with no members. It follows the “encoding-dependent state” model, which means it has a constructor that takes an `ztd::text::any_encoding_with` so it can properly initialize its state.

using **code_unit** = `ranges::range_value_type_t<_EncodeCodeUnits>`

The individual units that result from an encode operation or are used as input to a decode operation.

using **code_point** = ranges::range_value_type_t<*DecodeCodePoints*>

The individual units that result from a decode operation or as used as input to an encode operation.

using **is_encode_injective** = ::std::false_type

Whether or not the encode operation can process all forms of input into code point values.

Remark

This is always going to be false because this is a type-erased encoding; this value is determined by a runtime decision, which means that the most conservative and truthful answer is selected for this property.

using **is_decode_injective** = ::std::false_type

Whether or not the decode operation can process all forms of input into code point values.

Remark

This is always going to be false because this is a type-erased encoding; this value is determined by a runtime decision, which means that the most conservative and truthful answer is selected for this property.

Public Functions

any_encoding_with() = delete

Cannot default-construct a *ztd::text::any_encoding_with* object.

```
template<typename _Encoding, typename ..._Args, ::std::enable_if_t<!::std::is_same_v<Encoding,  
any_encoding_with> && !is_specialization_of_v<remove_cvref_t<Encoding>, ::std::in_place_type_t>*> =  
nullptr>
```

```
inline any_encoding_with(Encoding &&__encoding, Args&&... __args)
```

Constructs a *ztd::text::any_encoding_with* with the encoding object and any additional arguments.

Template Parameters

_Encoding – The Encoding specified by the first argument.

Parameters

- **__encoding** – [in] The encoding object that informs the *ztd::text::any_encoding_with* what encoding object to store.
- **__args** – [in] Any additional arguments used to construct the encoding in the erased storage.

```
template<typename _Encoding, typename ..._Args>
```

```
inline any_encoding_with(::std::in_place_type_t<Encoding> __tag, Args&&... __args)
```

Constructs a *ztd::text::any_encoding_with* with the encoding type specified in the **__tag** argument.

Template Parameters

_Encoding – The Encoding specified by the **__tag** argument.

Parameters

- **__tag** – [in] The type marker that informs the `ztd::text::any_encoding_with` what encoding object to store.
- **__args** – [in] Any additional arguments used to construct the encoding in the erased storage.

any_encoding_with(const *any_encoding_with*&) = delete

Cannot copy-construct a `ztd::text::any_encoding_with` object.

any_encoding_with &**operator**=(const *any_encoding_with*&) = delete

Cannot copy-assign a `ztd::text::any_encoding_with` object.

any_encoding_with(*any_encoding_with*&&) = default

Move-constructs a `ztd::text::any_encoding_with` from the provided r-value reference.

Remark

This leaves the passed-in r-value reference without an encoding object. Calling any function on a moved-from `ztd::text::any_encoding_with`, except for destruction, is a violation and invokes Undefined Behavior (generally, a crash).

any_encoding_with &**operator**=(*any_encoding_with*&&) = default

Move-assigns a `ztd::text::any_encoding_with` from the provided r-value reference.

Remark

This leaves the passed-in r-value reference without an encoding object. Calling any function on a moved-from `ztd::text::any_encoding_with`, except for destruction, is a violation and invokes Undefined Behavior (generally, a crash).

inline ::std::optional<::ztd::span<const *code_point*>> **maybe_replacement_code_points**() const noexcept

Retrieves the replacement code points for when conversions fail and `ztd::text::replacement_handler_t` (or equivalent) needs to make a substitution.

Returns

A `std::optional` of `ztd::span` of const *code_points*. The returned `std::optional` value is engaged (has a value) if the stored encoding has a valid `replacement_code_points` function and it can be called. If it does not, then the library checks to see if the `maybe_replacement_code_points` function exists, and returns the `std::optional` from that type directly. If neither are present, an unengaged `std::optional` is returned.

inline ::std::optional<::ztd::span<const *code_unit*>> **maybe_replacement_code_units**() const noexcept

Retrieves the replacement code units for when conversions fail and `ztd::text::replacement_handler_t` (or equivalent) needs to make a substitution.

Returns

A `std::optional` of `ztd::span` of const *code_units*. The returned `std::optional` value is engaged (has a value) if the stored encoding has a valid `replacement_code_units` function and it can be called. If it does not, then the library checks to see if the `maybe_replacement_code_units` function exists, and returns the `std::optional` from that type directly. If neither are present, an unengaged `std::optional` is returned.

inline bool **contains_unicode_encoding**() const noexcept

Returns whether or not the encoding stored in this *ztd::text::any_encoding_with* is a Unicode encoding.

Remark

This can be useful to know, in advance, whether or not there is a chance for lossy behavior. Even if, at compile time, various functions will demand you use an error handler, this runtime property can help you get a decent idea of just how bad and lossy this conversion might be compared to normal UTF conversion formats.

inline __decode_result **decode_one**(*_DecodeCodeUnits* __input, *_DecodeCodePoints* __output,
__decode_error_handler __error_handler, *decode_state* &__state) const

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A *ztd::text::decode_result* object that contains the input range, output range, error handler, and a reference to the passed-in state.

inline __encode_result **encode_one**(*_EncodeCodePoints* __input, *_EncodeCodeUnits* __output,
__encode_error_handler __error_handler, *encode_state* &__state) const

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code points from.
- **__output** – [in] The output view to write code units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::encode_result` object that contains the input range, output range, error handler, and a reference to the passed-in state.

Public Static Attributes

```
static constexpr ::std::size_t max_code_points = _MaxCodePoints
```

The maximum number of code points a single complete operation of decoding can produce. This is 1 for all Unicode Transformation Format (UTF) encodings.

```
static constexpr ::std::size_t max_code_units = _MaxCodeUnits
```

The maximum code units a single complete operation of encoding can produce.

```
static constexpr ::ztd::text_encoding_id decoded_id = ::ztd::text_encoding_id::unknown
```

The decoded id. Because this is a type-erased encoding, anything can come out: therefore, it is set to “unknown” at all times.

```
static constexpr ::ztd::text_encoding_id encoded_id = ::ztd::text_encoding_id::unknown
```

The encoded id. Because this is a type-erased encoding, anything can come out: therefore, it is set to “unknown” at all times.

```
class any_decode_state
```

Public Functions

```
inline any_decode_state(const any_encoding_with &__encoding)
```

Creates a state properly initialized from the stored encoding.

```
any_decode_state(const any_decode_state&) = delete
```

You cannot copy construct an *any_decode_state*.

```
any_decode_state &operator=(const any_decode_state&) = delete
```

You cannot copy assign an *any_decode_state*.

```
any_decode_state(any_decode_state&&) = default
```

Move constructs an *any_decode_state*.

```
any_decode_state &operator=(any_decode_state&&) = default
```

Move assigns an *any_decode_state*.

```
class any_encode_state
```

Public Functions

`inline any_encode_state(const any_encoding_with &__encoding)`

Creates a state properly initialized from the stored encoding.

`any_encode_state(const any_encode_state&) = delete`

You cannot copy construct an *any_encode_state*.

`any_encode_state &operator=(const any_encode_state&) = delete`

You cannot copy assign an *any_encode_state*.

`any_encode_state(any_encode_state&&) = default`

Move constructs an *any_encode_state*.

`any_encode_state &operator=(any_encode_state&&) = default`

Move assigns an *any_encode_state*.

ASCII

The American Standard Code for Information Interchange (ASCII). A typical 7-bit encoding that is bitwise-compatible with UTF-8.

Aliases

```
constexpr ascii_t ztd::text::ascii = {}
```

An instance of the *ascii_t* type for ease of use.

```
typedef basic_ascii<char> ztd::text::ascii_t
```

The American Standard Code for Information Exchange (ASCII) Encoding.

Remark

The most vanilla and unimaginative encoding there is in the world, excluding tons of other languages, dialects, and even common English idioms and borrowed words. Please don't pick this unless you have good reason!

Base Template

```
template<typename _CodeUnit, typename _CodePoint = unicode_code_point>
```

```
class basic_ascii
```

The American Standard Code for Information Exchange (ASCII) Encoding.

Remark

The most vanilla and unimaginative encoding there is in the world, excluding tons of other languages, dialects, and even common English idioms and borrowed words. Please don't pick this unless you have good reason!

Template Parameters

_CodeUnit – The code unit type to work over.

Public Types

using **code_unit** = *_CodeUnit*

The individual units that result from an encode operation or are used as input to a decode operation.

using **code_point** = *_CodePoint*

The individual units that result from a decode operation or as used as input to an encode operation. For most encodings, this is going to be a Unicode Code Point or a Unicode Scalar Value.

using **state** = *__txt_detail::__empty_state*

The state that can be used between calls to the encoder and decoder.

Remark

It is an empty struct because there is no shift state to preserve between complete units of encoded information. It is also only *state* and not separately *decode_state* and *encode_state* because one type suffices for both.

using **is_decode_injective** = *::std::true_type*

Whether or not the decode operation can process all forms of input into code point values.

Remark

ASCII can decode from its 7-bit (unpacked) code units to Unicode Code Points. Since the conversion is lossless, this property is true.

using **is_encode_injective** = *::std::false_type*

Whether or not the encode operation can process all forms of input into code unit values. This is not true for ASCII, as many Unicode Code Point and Unicode Scalar Values cannot be represented in ASCII. Since the conversion is lossy, this property is false.

Public Static Functions

static inline constexpr *::ztd::span<const code_unit, 1>* **replacement_code_units**() noexcept

A range of code units representing the values to use when a replacement happen. For ASCII, this must be ‘?’ instead of the usual Unicode Replacement Character U’.

```
template<typename _Input, typename _Output, typename _ErrorHandler>
static inline constexpr auto decode_one(_Input && __input, _Output && __output, _ErrorHandler
&& __error_handler, state & __s)
```

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code uunits from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A *ztd::text::decode_result* object that contains the input range, output range, error handler, and a reference to the passed-in state.

```
template<typename _Input, typename _Output, typename _ErrorHandler>  
static inline constexpr auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler  
    &&__error_handler, state &__s)
```

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code points from.
- **__output** – [in] The output view to write code units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A *ztd::text::encode_result* object that contains the input range, output range, error handler, and a reference to the passed-in state.

Public Static Attributes

```
static constexpr const ::std::size_t max_code_units = 1
```

The maximum code units a single complete operation of encoding can produce.

```
static constexpr const ::std::size_t max_code_points = 1
```

The maximum number of code points a single complete operation of decoding can produce. This is 1 for all Unicode Transformation Format (UTF) encodings.

basic_iconv

This encoding is only available if the configuration macro/build option for ZTD_PLATFORM_LIBICONV is turned on.

This encoding is tied to the [iconv library](#). It will attempt to use the header and the functions directly, and if not otherwise bootstrap iconv on first use of the encoding through `GetProcAddress/dlsym` and related. If it cannot find it will either assert, abort, or loudly annoy the user in some way. The code is retrieved dynamically where possible unless the user explicitly defines the build option for ZTD_TEXT_USE_STATIC_LIBICONV (for CMake), as iconv is under a LGPL/GPL licensed and cannot be traditionally built / statically linked with application code (though in the future we may provide a way for software to do that if the software being made with this library is also GPL-compatible software).

iconv has a fixed set of encodings it can be compiled with to support. States are pre-constructed in the encoding itself and copied as necessary when `encode_state` or `decode_states` are being created to call the iconv functions. The user can inspect the output error parameter from the `basic_iconv` constructor to know of failure, or not pass in the output error parameter and instead take one of a `assert`, thrown exception, or `abort` (preferred invocation in that order).

Base Template

```
template<typename _CodeUnit, typename _CodePoint = unicode_code_point>
```

```
class basic_iconv : public ztd::text::basic_no_encoding<_CodeUnit, unicode_code_point>
```

An encoding which is templated on code unit and code point and provides access to the iconv library.

Remark

The type is created with a name and provides a conversion routine when used. Because it is all done at runtime, it is considered a lossy conversion and thus requires prolific use of error handlers. If libiconv cannot be found, this type will produce a hard error on use.

Template Parameters

- **_CodeUnit** – The code unit type.
- **_CodePoint** – The code point type.

Big5 Hong Kong Supplementary Character Set (HKSCS)

The Big5 encoding, with the Hong Kong Supplementary Character Set (HKSCS) included with it. This is the most prevalent encoding besides GBK in use for Chinese languages (though there exist many subsets captured by other variants and encodings that may use the same name).

Alias

```
constexpr basic_big5_hkscs<char> ztd::text::big5_hkscs = {}
```

An instance of `basic_big5-hkscs` for ease of use.

Base Templates

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_big5_hkscs
```

The Big5-HKSCS (Hong Kong Supplementary Character Set) encoding, standardized around 2001.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

Public Types

```
using code_unit = _CodeUnit
```

Shift-JIS is generally stored as minimum-8-bit values in a sequence.

```
using code_point = _CodePoint
```

Shift-JIS outputs Unicode Scalar Values.

```
using state = __txt_detail::__empty_state
```

Shift-JIS requires no state.

```
using is_decode_injective = std::true_type
```

Marks this encoding as injective for the decode portion of its encoding actions.

Public Functions

```
inline constexpr ztd::span<const code_unit, 1> replacement_code_units() const noexcept
```

A fixed-size 1-element span with the `__code_point` unit “?”.

Public Static Functions

```
template<typename _Input, typename _Output, typename _ErrorHandler>
static inline constexpr auto decode_one(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, state &__state) noexcept
```

Decodes a single complete unit of information as `__code_point` points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- **__input** – [in] The input view to read `__code_point` units from.
- **__output** – [in] The output view to write `__code_point` points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::decode_result` object that contains the input range, output range, error handler, and a reference to the passed-in state.

```
template<typename _Input, typename _Output, typename _ErrorHandler>
static inline constexpr auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, state &__state) noexcept
```

Encodes a single complete unit of information as `__code_point` units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- **__input** – [in] The input view to read `__code_point` points from.
- **__output** – [in] The output view to write `__code_point` units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::encode_result` object that contains the input range, output range, error handler, and a reference to the passed-in state.

Public Static Attributes

```
static constexpr std::size_t max_code_points = 2
```

The Shift-JIS encoding can put out at most 1 `__code_point` point per decoding action.

```
static constexpr std::size_t max_code_units = 2
```

The Shift-JIS encoding can put out at most 2 `__code_point` units per encoding action.

cuneicode_registry_encoding (In Progress)

This encoding is tied to the [cuneicode library](#). The cuneicode library is a C library for validation, counting, and transcoding between a fixed set of encodings, with an additional plug for arbitrary encodings that can be added at run-time. This is in opposition to *iconv*, where additional encodings can only be added by-hand through recompiling the code or hooking specific system configuration points.

cuneicode has a variable number of encodings it can be compiled with to support. States are pre-constructed in the encoding itself and copied as necessary when `encode_state` or `decode_states` are being created to call the desired conversion functions. The user can inspect the output error parameter from the `cuneicode_registry_encoding` constructor to know of failure, or not pass in the output error parameter and instead take one of a `assert`, thrown exception, or `abort` (preferred invocation in that order).

Encoding Scheme

The `encoding_scheme` template turns any encoding into a byte-based encoding capable of reading and writing those bytes into and out of `byte_value_type` ranges. It prevents duplicating effort to read encodings as little endian or big endian, allowing composition for any desired encoding to interface with e.g. a UTF-16 Big Endian blob of data coming over a network or shared pipe.

Aliases

```
template<typename _Byte>
```

```
using ztd::text::basic_utf16_le = encoding_scheme<utf16_t, endian::little, _Byte>
```

A UTF-16 encoding, in Little Endian format, with inputs as a sequence of bytes.

Template Parameters

_Byte – The byte type to use. Typically, this is `std::byte` or `uchar`.

```
using ztd::text::utf16_le_t = basic_utf16_le<::std::byte>
```

A UTF-16 encoding, in Little Endian format, with inputs as a sequence of bytes.

```
template<typename _Byte>
```

```
using ztd::text::basic_utf16_be = encoding_scheme<utf16_t, endian::big, _Byte>
```

A UTF-16 encoding, in Big Endian format, with inputs as a sequence of bytes.

Template Parameters

_Byte – The byte type to use. Typically, this is `std::byte` or `unsigned char`.

```
using ztd::text::utf16_be_t = basic_utf16_be<::std::byte>
```

A UTF-16 encoding, in Big Endian format, with inputs as a sequence of bytes.

```
template<typename _Byte>
```

```
using ztd::text::basic_utf16_ne = encoding_scheme<utf16_t, endian::native, _Byte>
```

A UTF-16 encoding, in Native Endian format, with inputs as a sequence of bytes.

Template Parameters

_Byte – The byte type to use. Typically, this is `std::byte` or `unsigned char`.

```
using ztd::text::utf16_ne_t = basic_utf16_ne<::std::byte>
```

A UTF-16 encoding, in Native Endian format, with inputs as a sequence of bytes.

```
template<typename _Byte>
```

```
using ztd::text::basic_utf32_le = encoding_scheme<utf32_t, endian::little, _Byte>
```

A UTF-32 encoding, in Little Endian format, with inputs as a sequence of bytes.

Template Parameters

_Byte – The byte type to use. Typically, this is `std::byte` or `unsigned char`.

```
using ztd::text::utf32_le_t = basic_utf32_le<::std::byte>
```

A UTF-32 encoding, in Little Endian format, with inputs as a sequence of bytes.

```
template<typename _Byte>
```

```
using ztd::text::basic_utf32_be = encoding_scheme<utf32_t, endian::big, _Byte>
```

A UTF-32 encoding, in Big Endian format, with inputs as a sequence of bytes.

Template Parameters

_Byte – The byte type to use. Typically, this is `std::byte` or `unsigned char`.

```
using ztd::text::utf32_be_t = basic_utf32_be<::std::byte>
```

A UTF-32 encoding, in Big Endian format, with inputs as a sequence of bytes.

```
template<typename _Byte>
```

```
using ztd::text::basic_utf32_ne = encoding_scheme<utf32_t, endian::native, _Byte>
```

A UTF-32 encoding, in Native Endian format, with inputs as a sequence of bytes.

Template Parameters

_Byte – The byte type to use. Typically, this is `std::byte` or `unsigned char`.

```
using ztd::text::utf32_ne_t = basic_utf32_ne<::std::byte>
```

A UTF-32 encoding, in Big Endian format, with inputs as a sequence of bytes.

Base Template

```
template<typename _Encoding, endian _Endian = endian::native, typename _Byte = ::std::byte>
```

```
class encoding_scheme : public __txt_detail::__is_unicode_encoding_es<encoding_scheme<_Encoding,  
endian::native, ::std::byte>, unwrap_remove_cvref_t<_Encoding>>, private ebco<_Encoding>
```

Decomposes the provided Encoding type into a specific endianness (big, little, or native) to allow for a single encoding type to be viewed in different ways.

Remark

For example, this can be used to construct a Big Endian UTF-16 by using `encoding_scheme<ztd::text::utf16_t, ztd::endian::big>`. It can be made interoperable with unsigned char buffers rather than `std::byte` buffers by doing: `ztd::text::encoding_scheme<ztd::text::utf32_t, ztd::endian::native, unsigned char>`.

Template Parameters

- **_Encoding** – The encoding type.
- **_Endian** – The endianness to use. Defaults to `ztd::endian::native`.
- **_Byte** – The byte type to use. Defaults to `std::byte`.

Public Types

```
using encoding_type = _Encoding
```

The encoding type. ///.

The encoding type that this scheme wraps.

```
using code_point = code_point_t<_UBaseEncoding>
```

The individual units that result from a decode operation or as used as input to an encode operation. For most encodings, this is going to be a Unicode Code Point or a Unicode Scalar Value.

```
using code_unit = _Byte
```

The individual units that result from an encode operation or are used as input to a decode operation.

Remark

Typically, this type is usually always some kind of byte type (unsigned char or `std::byte` or other `sizeof(obj) == 1` type)./

```
using decode_state = decode_state_t<_UBaseEncoding>
```

The state that can be used between calls to the decode function.

Remark

Even if the underlying encoding only has a single `state` type, we need to separate the two out in order to generically handle all encodings. Therefore, the `encoding_scheme` will always have both `encode_state` and `decode_state`.

using `encode_state = encode_state_t<_UBaseEncoding>`

The state that can be used between calls to the encode function.

Remark

Even if the underlying encoding only has a single `state` type, we need to separate the two out in order to generically handle all encodings. Therefore, the `encoding_scheme` will always have both `encode_state` and `decode_state`.

using `is_encode_injective = ::std::integral_constant<bool, is_encode_injective_v<_UBaseEncoding>>`

Whether or not the encode operation can process all forms of input into code point values.

Remark

Defers to what the underlying `encoding_type` does.

using `is_decode_injective = ::std::integral_constant<bool, is_decode_injective_v<_UBaseEncoding>>`

Whether or not the decode operation can process all forms of input into code point values.

Remark

Defers to what the underlying `encoding_type` does.

Public Functions

`encoding_scheme()` = default

Default constructs a `ztd::text::encoding_scheme`.

```
template<typename _Arg0, typename ..._Args, ::std::enable_if_t<!::std::is_same_v<remove_cvref_t<_Arg0>,
encoding_scheme> && !::std::is_same_v<remove_cvref_t<_Arg0>, ::std::in_place_t>>* = nullptr>
inline constexpr encoding_scheme(_Arg0 &&__arg0, _Args&&... __args)
    noexcept(::std::is_nothrow_constructible_v<_UBaseEncoding, _Arg0,
    _Args...>)
```

Constructs a `ztd::text::encoding_scheme` with the encoding object and any additional arguments.

Parameters

- `__arg0` – [in] The first argument used to construct the stored encoding.

- **__args** – [in] Any additional arguments used to construct the stored encoding.

template<typename ...**Args**>

```
inline constexpr encoding_scheme(::std::in_place_t, Args&&... __args)  
    noexcept(::std::is_nothrow_constructible_v<_UBaseEncoding, Args...>)
```

Constructs a *ztd::text::encoding_scheme* with the encoding object and any additional arguments.

Remark

If the provided encoding does not have a byte *code_unit* type, it is wrapped in an *ztd::text::encoding_scheme* first.

Parameters

- **__args** – [in] Any additional arguments used to construct the encoding in the erased storage.

encoding_scheme(const *encoding_scheme*&) = default

Cannot copy-construct a *ztd::text::encoding_scheme* object.

encoding_scheme &**operator**=(const *encoding_scheme*&) = default

Cannot copy-assign a *ztd::text::encoding_scheme* object.

encoding_scheme(*encoding_scheme*&&) = default

Move-constructs a *ztd::text::encoding_scheme* from the provided r-value reference.

Remark

This leaves the passed-in r-value reference without an encoding object. Calling any function on a moved-from *ztd::text::encoding_scheme*, except for destruction, is a violation and invokes Undefined Behavior (generally, a crash).

encoding_scheme &**operator**=(*encoding_scheme*&&) = default

Move-assigns a *ztd::text::encoding_scheme* from the provided r-value reference.

Remark

This leaves the passed-in r-value reference without an encoding object. Calling any function on a moved-from *ztd::text::encoding_scheme*, except for destruction, is a violation and may invoke Undefined Behavior (generally, a crash).

inline constexpr *encoding_type* &**base**() & noexcept

Retrieves the underlying encoding object.

Returns

An l-value reference to the encoding object.

inline constexpr const *encoding_type* &**base**() const & noexcept

Retrieves the underlying encoding object.

Returns

An l-value reference to the encoding object.

```
inline constexpr encoding_type &&base() && noexcept
```

Retrives the underlying encoding object.

Returns

An l-value reference to the encoding object.

```
template<typename _Unused = encoding_type, ::std::enable_if_t<is_code_units_replaceable_v<_Unused>>*  
= nullptr>
```

```
inline constexpr decltype(auto) replacement_code_units() const noexcept
```

Returns, the desired replacement code units to use.

Remark

This is only callable if the function call exists on the wrapped encoding. It is broken down into a contiguous view type formulated from bytes if the wrapped code unit types do not match.

```
template<typename _Unused = encoding_type, ::std::enable_if_t<is_code_points_replaceable_v<_Unused>>*  
= nullptr>
```

```
inline constexpr decltype(auto) replacement_code_points() const noexcept
```

Returns the desired replacement code points to use.

Remark

Is only callable if the function call exists on the wrapped encoding.

```
template<typename _Unused = encoding_type,  
::std::enable_if_t<is_code_units_maybe_replaceable_v<_Unused>>* = nullptr>
```

```
inline constexpr decltype(auto) maybe_replacement_code_units() const noexcept
```

Returns the desired replacement code units to use, or an empty optional-like type if there is nothing present.

Remark

This is only callable if the function call exists on the wrapped encoding. It is broken down into a contiguous view type formulated from bytes if the wrapped code unit types do not match.

```
template<typename _Unused = encoding_type,  
::std::enable_if_t<is_code_points_maybe_replaceable_v<_Unused>>* = nullptr>
```

```
inline constexpr decltype(auto) maybe_replacement_code_points() const noexcept
```

Returns the desired replacement code units to use.

Remark

This Is only callable if the function call exists on the wrapped encoding.

```
inline constexpr bool contains_unicode_encoding() const noexcept
```

Whether or not this encoding is some form of Unicode encoding.

```
template<typename _Result, typename _InputProgress, typename _OutputProgress,  
::std::enable_if_t<is_input_error_skippable_v<const encoding_type&, _Result, const _InputProgress&, const  
_OutputProgress&>>* = nullptr>
```

```
inline constexpr decltype(auto) skip_input_error(_Result &&__result) const noex-  
cept(::ztd::text::is_nothrow_skip_input_error_v<const  
encoding_type&, _Result, const _InputProgress&, const  
_OutputProgress&>)
```

Skips any consecutive input errors in the encoded input, where possible.

Remark

This Is only callable if the function call exists on the wrapped encoding.

```
template<typename _Input, typename _Output, typename _ErrorHandler>  
inline constexpr auto decode_one(_Input &&__input, _Output &&__output, _ErrorHandler  
&&__error_handler, decode_state &__s) const
```

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A *ztd::text::decode_result* object that contains the input range, output range, error handler, and a reference to the passed-in state.

```
template<typename _Input, typename _Output, typename _ErrorHandler>  
inline constexpr auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler  
&&__error_handler, encode_state &__s) const
```

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code points from.
- **__output** – [in] The output view to write code units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::encode_result` object that contains the input range, output range, error handler, and a reference to the passed-in state.

Public Static Attributes

```
static constexpr const ::std::size_t max_code_points = max_code_points_v<_UBaseEncoding>
```

The maximum number of code points a single complete operation of decoding can produce. This is 1 for all Unicode Transformation Format (UTF) encodings.

```
static constexpr const ::std::size_t max_code_units = (max_code_units_v<_UBaseEncoding> *
sizeof(_BaseCodeUnit)) / (sizeof(_Byte))
```

The maximum code units a single complete operation of encoding can produce.

```
static constexpr const ::ztd::text_encoding_id decoded_id = decoded_id_v<_UBaseEncoding>
```

The id representing the decoded text.

```
static constexpr const ::ztd::text_encoding_id encoded_id =
::ztd::to_byte_text_encoding_id(encoded_id_v<_UBaseEncoding>, Endian,
sizeof(code_unit_t<_UBaseEncoding>))
```

The id representing the encoded text.

EUC-KR (Unified Hangul Code)

The Extended Unix Code (EUC) encoding for Korean (KR), for the Unified Hangul Code (UHC) variant. This is the same encoding that is present for the WHATWG Encoding Specification.

Alias

```
constexpr basic_euc_kr_uhc<char> ztd::text::euc_kr_uhc = {}
```

An instance of `euc_kr_uhc` for ease of use.

Base Templates

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_euc_kr_uhc
```

The EUC-KR (Unified Hangul Code) encoding.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

Public Types

```
using code_unit = _CodeUnit
```

Shift-JIS is generally stored as minimum-8-bit values in a sequence.

```
using code_point = _CodePoint
```

Shift-JIS outputs Unicode Scalar Values.

```
using state = __txt_detail::__empty_state
```

Shift-JIS requires no state.

```
using is_decode_injective = std::true_type
```

Marks this encoding as injective for the decode portion of its encoding actions.

Public Functions

```
inline constexpr ztd::span<const code_unit, 1> replacement_code_units() const noexcept
```

A fixed-size 1-element span with the `__code_point` unit “?”.

Public Static Functions

```
template<typename _Input, typename _Output, typename _ErrorHandler>
```

```
static inline constexpr auto decode_one(_Input &&__input, _Output &&__output, _ErrorHandler  
    &&__error_handler, state &__state) noexcept
```

Decodes a single complete unit of information as `__code_point` points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- **__input** – [in] The input view to read `__code_point` units from.
- **__output** – [in] The output view to write `__code_point` points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::decode_result` object that contains the input range, output range, error handler, and a reference to the passed-in state.

```
template<typename _Input, typename _Output, typename _ErrorHandler>
static inline constexpr auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, state &__state) noexcept
```

Encodes a single complete unit of information as `__code_point` units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- **__input** – [in] The input view to read `__code_point` points from.
- **__output** – [in] The output view to write `__code_point` units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::encode_result` object that contains the input range, output range, error handler, and a reference to the passed-in state.

Public Static Attributes

```
static constexpr std::size_t max_code_points = 1
```

The Shift-JIS encoding can put out at most 1 `__code_point` point per decoding action.

```
static constexpr std::size_t max_code_units = 2
```

The Shift-JIS encoding can put out at most 2 `__code_point` units per encoding action.

Execution

This is the locale-based, runtime encoding. It uses a number of compile-time and runtime heuristics to eventually be resolved to an implementation-defined encoding. It is not required to work in constant expressions either: for this, use `ztd::text::literal`, which represents the compile-time string (e.g. "my string") encoding.

Currently, the hierarchy of behaviors is like so:

- If the platform is MacOS, then it assumes this is *UTF-8*;
- Otherwise, if the *cuneicode*, then Cuneicode will be used.

Warning: The C Standard Library has many design defects in its production of code points, which may make it unsuitable even if your C Standard Library recognizes certain locales (e.g., Big5-HKSCS). The runtime will always attempt to load `iconv` if the definition is turned on, since it may do a better job than the C Standard Library's interfaces until C23.

Even if, on a given platform, it can be assumed to be a static encoding (e.g., Apple/MacOS where it always returns the "C" Locale but processes text as UTF-8), `ztd::text::execution` will always present itself as a runtime and unknowable encoding. This is to prevent portability issues from relying on, e.g., `ztd::text::is_decode_injective_v<ztd::text::execution>` being true during development and working with that assumption, only to have it break when ported to a platform where that assumption no longer holds.

Aliases

```
constexpr execution_t ztd::text::execution = {}
```

An instance of the `execution_t` type for ease of use.

```
class execution_t : public ztd::text::basic_no_encoding<char, unicode_code_point>
```

The Encoding that represents the "Execution" (narrow locale-based) encoding. The encoding is typically associated with the locale, which is tied to the C standard library's `setlocale` function.

Remark

Use of this type is subject to the C Standard Library or platform defaults. Some locales (such as the Big5 Hong King Supplementary Character Set (Big5-HKSCS)) are broken due to fundamental design issues in the C Standard Library and bugs in `glibc/musl` libe's current locale encoding support. On Apple, this is currently assumed to be UTF-8 since they do not support the `<cuchar>` or `<uchar.h>` headers.

Internal Types

Warning: Names with double underscores, and within the `__*detail` and `__*impl` namespaces are reserved for the implementation. Referencing this entity directly is bad, and the name/functionality can be changed at any point in the future. Relying on anything not guaranteed by the documentation is Undefined Behavior.

MacOS-based

```
class __execution_mac_os : private __utf8_with<__execution_mac_os, char, ztd_char32_t>
```

The default (“locale”) encoding for Mac OS.

Remark

Note that for all intents and purposes, Mac OS demands that all text is in UTF-8. However, on Big Sur, Catalina, and a few other platforms locale functionality and data has been either forgotten/left behind or intentionally kept in place on these devices. It may be possible that with very dedicated hacks one can still change the desired default encoding from UTF-8 to something else in the majority of Apple text. Their documentation states that all text “should” be UTF-8, but very explicitly goes out of its way to not make that hard guarantee. Since it is a BSD-like system and they left plenty of that data behind from C libraries, this may break in extremely obscure cases. Please be careful on Apple machines!

Public Types

```
using code_point = code_point_t<__base_t>
```

The code point type that is decoded to, and encoded from.

```
using code_unit = code_unit_t<__base_t>
```

The code unit type that is decoded from, and encoded to.

```
using decode_state = decode_state_t<__base_t>
```

The associated state for decode operations.

```
using encode_state = encode_state_t<__base_t>
```

The associated state for encode operations.

```
using is_unicode_encoding = ::std::integral_constant<bool, is_unicode_encoding_v<__base_t>>
```

Whether or not this encoding is a unicode encoding or not.

```
using is_decode_injective = ::std::false_type
```

Whether or not this encoding’s `decode_one` step is injective or not.

```
using is_encode_injective = ::std::false_type
```

Whether or not this encoding’s `encode_one` step is injective or not.

Public Static Functions

```
template<typename _Input, typename _Output, typename _ErrorHandler>
static inline constexpr auto decode_one(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, decode_state &__s)
```

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. Most encodings have no state, but because this is effectively a runtime encoding and therefore it is important to preserve and manage this state.

Returns

A *ztd::text::decode_result* object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

```
template<typename _Input, typename _Output, typename _ErrorHandler>
static inline constexpr auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, encode_state &__s)
```

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. Most encodings have no state, but because this is effectively a runtime encoding and therefore it is important to preserve and manage this state.

Returns

A *ztd::text::encode_result* object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

Public Static Attributes

```
static constexpr ::std::size_t max_code_points = 8
```

The maximum code units a single complete operation of encoding can produce.

Remark

There are encodings for which one input can produce 3 code points (some Tamil encodings) and there are rumours of an encoding that can produce 7 code points from a handful of input. We use a protective/conservative 8, here, to make sure ABI isn't broken later.

```
static constexpr ::std::size_t max_code_units = MB_LEN_MAX
```

The maximum number of code points a single complete operation of decoding can produce.

Remark

This is bounded by the platform's `MB_LEN_MAX` macro, which is an integral constant expression representing the maximum value of output all C locales can produce from a single complete operation.

Private Static Functions

```
static inline constexpr auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler
    &&__error_handler, encode_state &__s)
```

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code points from.
- **__output** – [in] The output view to write code units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::encode_result` object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

```
static inline constexpr auto decode_one(_Input &&__input, _Output &&__output, _ErrorHandler
    &&__error_handler, decode_state &__s)
```

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::decode_result` object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

GB18030

An encoding capable of handling all known Unicode-encoded characters, and occasionally a few more (the most recent version of Unicode covers all values available in the most up-to-date GB-18030).

Alias

```
constexpr basic_gb18030<char> ztd::text::gb18030 = {}
```

An instance of `basic_gb18030` for ease of use.

Base Templates

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_gb18030 : public __basic_gb18030<basic_gb18030<char, unicode_code_point>, char,  
unicode_code_point, false>
```

The GB18030 encoding, which can encode all of Unicode (and occasionally adds characters that exist outside of Unicode, but are still Unicode-compatible).

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

Public Types

using **code_unit** = char

Shift-JIS is generally stored as minimum-8-bit values in a sequence.

using **code_point** = *unicode_code_point*

Shift-JIS outputs Unicode Scalar Values.

using **state** = __txt_detail::__empty_state

Shift-JIS requires no state.

using **is_decode_injective** = ::std::true_type

Marks this encoding as injective for the decode portion of its encoding actions.

using **is_encode_injective** = ::std::integral_constant<bool, !_IsGbk>

Marks this encoding as injective for the encode portion of its encoding actions. This is true for GB18030, and not true for pure GBK.

using **is_unicode_encoding** = ::std::integral_constant<bool, !_IsGbk>

GB18030-style encodings are Unicode Encodings (can encode all Unicode code points). GBK cannot.

Public Functions

inline constexpr ztd::span<const *code_unit*, _IsGbk ? 1 : 4> **replacement_code_units**() const noexcept

A fixed-size replacement for either the GBK or GB18030 encoding.

inline constexpr ztd::span<const *code_point*, 1> **replacement_code_points**() const noexcept

A fixed-size replacement for either the GBK or GB18030 encoding.

Public Static Functions

static inline constexpr auto **decode_one**(_Input &&__input, _Output &&__output, _ErrorHandler &&__error_handler, *state* &__state) noexcept

Decodes a single complete unit of information as __code_point points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read __code_point units from.

- **__output** – [in] The output view to write `__code_point` points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::decode_result` object that contains the input range, output range, error handler, and a reference to the passed-in state.

```
static inline constexpr auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler  
    &&__error_handler, state &__state) noexcept
```

Encodes a single complete unit of information as `__code_point` units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- **__input** – [in] The input view to read `__code_point` points from.
- **__output** – [in] The output view to write `__code_point` units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::encode_result` object that contains the input range, output range, error handler, and a reference to the passed-in state.

Public Static Attributes

```
static constexpr std::size_t max_code_points
```

The Shift-JIS encoding can put out at most 1 `code_point` units per decoding action.

```
static constexpr std::size_t max_code_units
```

The Shift-JIS encoding can put out at most 4 `code_point` units per encoding action.

GBK

A legacy encoding typically for Chinese languages.

Alias

```
constexpr basic_gbk<char> ztd::text::gbk = {}
```

An instance of *basic_gbk* for ease of use.

Base Templates

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_gbk : public __basic_gb18030<basic_gbk<char, unicode_code_point>, char, unicode_code_point, true>
```

The single-byte GBK encoding, primarily for use with Chinese text.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

Public Types

```
using code_unit = char
```

Shift-JIS is generally stored as minimum-8-bit values in a sequence.

```
using code_point = unicode_code_point
```

Shift-JIS outputs Unicode Scalar Values.

```
using state = __txt_detail::__empty_state
```

Shift-JIS requires no state.

```
using is_decode_injective = ::std::true_type
```

Marks this encoding as injective for the decode portion of its encoding actions.

```
using is_encode_injective = ::std::integral_constant<bool, !_IsGbk>
```

Marks this encoding as injective for the encode portion of its encoding actions. This is true for GB18030, and not true for pure GBK.

```
using is_unicode_encoding = ::std::integral_constant<bool, !_IsGbk>
```

GB18030-style encodings are Unicode Encodings (can encode all Unicode code points). GBK cannot.

Public Functions

inline constexpr ztd::span<const *code_unit*, *IsGbk* ? 1 : 4> **replacement_code_units**() const noexcept
A fixed-size replacement for either the GBK or GB18030 encoding.

inline constexpr ztd::span<const *code_point*, 1> **replacement_code_points**() const noexcept
A fixed-size replacement for either the GBK or GB18030 encoding.

Public Static Functions

static inline constexpr auto **decode_one**(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, *state* &__state) noexcept

Decodes a single complete unit of information as `__code_point` points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- **__input** – [in] The input view to read `__code_point` units from.
- **__output** – [in] The output view to write `__code_point` points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::decode_result` object that contains the input range, output range, error handler, and a reference to the passed-in state.

static inline constexpr auto **encode_one**(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, *state* &__state) noexcept

Encodes a single complete unit of information as `__code_point` units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- **__input** – [in] The input view to read `__code_point` points from.
- **__output** – [in] The output view to write `__code_point` units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::encode_result` object that contains the input range, output range, error handler, and a reference to the passed-in state.

Public Static Attributes

static constexpr std::size_t **max_code_points**

The Shift-JIS encoding can put out at most 1 `code_point` units per decoding action.

static constexpr std::size_t **max_code_units**

The Shift-JIS encoding can put out at most 4 `code_point` units per encoding action.

Literal

The `literal` encoding handles C and C++ string literals (""") used at compile time and stored in the binary. The library uses a number of heuristics to determine with any degree of certainty what the encoding of string literals are, but in some cases it is not explicitly possible to achieve this goal.

If the library cannot figure out the literal encoding, the code will typically error with a `static_assert`, loudly, that it cannot use the functions on the type when you attempt to do anything with them because it may mangle whatever input or output you are expecting.

If you know the encoding of literals for your project (you provide the command line switch, or similar), then you can define a *configuration macro named* `ZTD_CXX_COMPILE_TIME_ENCODING_NAME` to be a string literal of your type, such as "UTF-8" or "ISO-8859-1".

If the library does not recognize the encoding and cannot transcode it properly, it will also loudly warn you that it does not understand the encoding of the literal (in which case, file an issue about it and we will add it to the list of acceptable literal encodings).

If you like to live dangerously and do not care for the warnings, you can define a *configuration macro named* `ZTD_TEXT_YES_PLEASE_DESTROY_MY_LITERALS_UTTERLY_I_MEAN_IT` and it will just blindly go with whatever weird default it ended up deciding on.

(This is usually a catastrophically terrible idea, but let it be said that we didn't give you the power to do great things, even if it cost you your foot.)

Alias

```
constexpr literal_t ztd::text::literal = {}
```

An instance of the *literal_t* type for ease of use.

Base Type

```
class literal_t : public __literal
```

The encoding of string literal_ts (e.g. "") at compile time.

Public Types

```
using is_unicode_encoding = ::std::integral_constant<bool,  
is_unicode_encoding_id(__txt_detail::__literal_id)>
```

Whether or not this *literal_t* encoding is a Unicode Transformation Format, such as UTF-8, UTF-EBCDIC, or GB18030.

```
using code_unit = code_unit_t<__base_t>
```

The individual units that result from an encode operation or are used as input to a decode operation.

```
using code_point = code_point_t<__base_t>
```

The individual units that result from a decode operation or as used as input to an encode operation. For most encodings, this is going to be a Unicode Code Point or a Unicode Scalar Value.

```
using encode_state = encode_state_t<__base_t>
```

The state that can be used between calls to `encode_one`.

```
using decode_state = decode_state_t<__base_t>
```

The state that can be used between calls to `decode_one`.

```
using is_decode_injective = ::std::integral_constant<bool, is_decode_injective_v<__base_t>>
```

Whether or not the decode operation can process all forms of input into code point values.

Remark

The decode step should always be injective because every encoding used for literal_ts in C++ needs to be capable of being represented by UCNs. Whether or not a platform is a jerk, who knows?

```
using is_encode_injective = ::std::integral_constant<bool, is_encode_injective_v<__base_t>>
```

Whether or not the encode operation can process all forms of input into code unit values.

Remark

This is absolutely not guaranteed to be the case, and as such we must check the provided encoding name for us to be sure.

Public Functions

constexpr **literal_t**() noexcept = default

Default constructs a *ztd::text::literal*.

constexpr **literal_t**(const *literal_t*&) noexcept = default

Copy constructs a *ztd::text::literal*.

constexpr **literal_t**(*literal_t*&&) noexcept = default

Move constructs a *ztd::text::literal*.

constexpr *literal_t* &**operator**=(const *literal_t*&) noexcept = default

Copy assigns into a *ztd::text::literal_t* object.

constexpr *literal_t* &**operator**=(*literal_t*&&) noexcept = default

Move assigns into a *ztd::text::literal_t* object.

template<typename **_Input**, typename **_Output**, typename **_ErrorHandler**>

inline constexpr auto **decode_one**(*_Input* &&__input, *_Output* &&__output, *_ErrorHandler* &&__error_handler, *decode_state* &__state) const

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A *ztd::text::decode_result* object that contains the input range, output range, error handler, and a reference to the passed-in state.

template<typename **_Input**, typename **_Output**, typename **_ErrorHandler**>

inline constexpr auto **encode_one**(*_Input* &&__input, *_Output* &&__output, *_ErrorHandler* &&__error_handler, *encode_state* &__state) const

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code points from.
- **__output** – [in] The output view to write code units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A *ztd::text::encode_result* object that contains the input range, output range, error handler, and a reference to the passed-in state.

Public Static Attributes

```
static constexpr const ::ztd::text_encoding_id decoded_id = decoded_id_v<__base_t>
```

The id representing the decoded text.

```
static constexpr const ::ztd::text_encoding_id encoded_id = encoded_id_v<__base_t>
```

The id representing the encoded text.

```
static constexpr ::std::size_t max_code_points = 16
```

The maximum number of code points a single complete operation of decoding can produce.

```
static constexpr ::std::size_t max_code_units = 32
```

The maximum code units a single complete operation of encoding can produce.

Modified UTF-8

Modified Unicode Transformation Format 8 (MUTF-8) is a UTF-8 format employed by some Android components and other ecosystems. It's special property is that it encodes the NULL character in C-style strings ('\0') as an overlong sequence. This is normally illegal in UTF-8, but allowed here to allow easier interoperation with these systems.

Aliases

```
constexpr mutf8_t ztd::text::mutf8 = {}
```

An instance of the MUTF-8 type for ease of use.

```
using ztd::text::mutf8_t = basic_mutf8<uchar8_t>
```

A Modified UTF-8 Encoding that traffics in `char8_t`. See `ztd::text::basic_mutf8` for more details.

Base Template

```
template<typename _CodeUnit, typename _CodePoint = unicode_code_point>
```

```
class basic_mutf8 : public __utf8_with<basic_mutf8<_CodeUnit, unicode_code_point>, _CodeUnit,
unicode_code_point, __txt_detail::_empty_state, __txt_detail::_empty_state, true, false, true>
```

A Modified UTF-8 Encoding that traffics in, specifically, the desired code unit type provided as a template argument.

Remark

This type as a maximum of 6 input code points and a maximum of 1 output code point. Null values are encoded as an overlong sequence to specifically avoid problems with C-style strings, which is useful for working with bad implementations sitting on top of POSIX or other Operating System APIs. For a strict, Unicode-compliant UTF-8 Encoding, see `ztd::text::basic_utf8`.

Template Parameters

- **_CodeUnit** – The code unit type to use.
- **_CodePoint** – The code point type to use.

Public Types

```
using is_unicode_encoding = ::std::true_type
```

Whether or not this encoding that can encode all of Unicode.

```
using self_synchronizing_code = ::std::true_type
```

The start of a sequence can be found unambiguously when dropped into the middle of a sequence or after an error in reading as occurred for encoded text.

Remark

Unicode has definitive bit patterns which resemble start and end sequences. The bit pattern `0xxxxxxx` indicates a lone bit, and `1xxxxxx` indicates a potential start bit for UTF-8. In particular, if 0 is not the first bit, it must be a sequence of 1s followed immediately by a 0 (e.g., `10xxxxxx`, `110xxxxx`, `1110xxxx`, or `11110xxx`).

using **decode_state** = __txt_detail::__empty_state

The state that can be used between calls to the encoder and decoder. It is normally an empty struct because there is no shift state to preserve between complete units of encoded information.

using **encode_state** = __txt_detail::__empty_state

The state that can be used between calls to the encoder and decoder. It is normally an empty struct because there is no shift state to preserve between complete units of encoded information.

using **code_unit** = *CodeUnit*

The individual units that result from an encode operation or are used as input to a decode operation. For UTF-8 formats, this is usually `char8_t`, but this can change (see *ztd::text::basic_utf8*).

using **code_point** = *unicode_code_point*

The individual units that result from a decode operation or as used as input to an encode operation. For most encodings, this is going to be a Unicode Code Point or a Unicode Scalar Value.

using **is_decode_injective** = ::std::true_type

Whether or not the decode operation can process all forms of input into code point values. This is true for all Unicode Transformation Formats (UTFs), which can encode and decode without a loss of information from a valid collection of code units.

using **is_encode_injective** = ::std::true_type

Whether or not the encode operation can process all forms of input into code unit values. This is true for all Unicode Transformation Formats (UTFs), which can encode and decode without loss of information from a valid input code point.

Public Static Functions

static inline constexpr ::ztd::span<const *code_unit*, 3> **replacement_code_units**() noexcept

Returns the replacement code units to use for the *ztd::text::replacement_handler_t* error handler.

static inline constexpr ::ztd::span<const *code_point*, 1> **replacement_code_points**() noexcept

Returns the replacement code point to use for the *ztd::text::replacement_handler_t* error handler.

static inline constexpr auto **skip_input_error**(*decode_result*<_Input, _Output, _State> __result, const _InputProgress &__input_progress, const _OutputProgress &__output_progress) noexcept

Allows an encoding to discard input characters if an error occurs, taking in both the state and the input sequence to modify through the result type.

Remark

This will skip every input value until a proper starting byte is found.

static inline constexpr auto **skip_input_error**(*encode_result*<_Input, _Output, _State> __result, const _InputProgress &__input_progress, const _OutputProgress &__output_progress) noexcept

Allows an encoding to discard input characters if an error occurs, taking in both the state and the input sequence (by reference) to modify.

Remark

This will skip every input value until a proper UTF-32 unicode scalar value (or code point) is found.

```
static inline constexpr auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, encode_state &__s)
```

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- **__input** – [in] The input view to read code points from.
- **__output** – [in] The output view to write code units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::encode_result` object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

```
static inline constexpr auto decode_one(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, decode_state &__s)
```

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- **__input** – [in] The input view to read code uunits from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A *ztd::text::decode_result* object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

Public Static Attributes

static constexpr ::std::size_t **max_code_points**

The maximum number of code points a single complete operation of decoding can produce. This is 1 for all Unicode Transformation Format (UTF) encodings.

static constexpr ::std::size_t **max_code_units**

The maximum code units a single complete operation of encoding can produce. If overlong sequence allowed, this is 6: otherwise, this is 4.

static constexpr ::ztd::text_encoding_id **encoded_id**

The encoding ID for this type. Used for optimization purposes.

static constexpr ::ztd::text_encoding_id **decoded_id**

The encoding ID for this type. Used for optimization purposes.

PETSCII (Shifted & Unshifted, Combined) / CBM ASCII

PET Standard Code of Information Interchange (PETSCII) was used for Commodore Business Machines and then moved into other Commodore machines (and adjacent machines). It has a “shifted” version (when the shift key was held) and an “unshifted” version (when the shift key was not being held).

The state object for this encoding contains an enumeration that allows the user to select the shifted or unshifted versions at-will.

Aliases

class **petscii_state**

The state associated with an ongoing PETSCII encoding operation.

enum class ztd::text::**petscii_shift**

The current shift state of a PETSCII encoding object and it’s associated state during an encoding operation.

Values:

enumerator **unshifted**

The SHIFT button is not pressed, and character codes should be interpreted as not being “shifted”.

enumerator **shifted**

The SHIFT button is pressed, and character codes should be interpreted as being “shifted”.

```
constexpr basic_petscii<char> ztd::text::petscii = {}
```

An instance of *basic_petscii* for ease of use.

Base Templates

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_petscii
```

The encoding that matches the PETSCII (CBM ASCII) encoding specification, for shifted characters (when the SHIFT button was pressed on a PET/CBM device).

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

punycode

Punycode is an encoding that turns Unicode-encoded text into a sequence of ASCII code units, making it readily inspectable by simple systems and human eyes to see differences between text even if confusable characters are used in the Unicode text.

It is most frequently used in the Internationalized Domain Name in Applications system, specifically for DNS purposes. Despite it’s unfriendliness to stream-based, one-at-a-time interfaces, sufficiently heap-based state allows encoding and decoding in a useful manner.

It is also used as Rust’s choice encoding for its symbol names when stored in binary form for use with any given platform’s library/executable’s linker and loader.

Aliases

```
constexpr punycode_t ztd::text::punycode = punycode_t{}
```

A preexisting object of type *ztd::text::punycode_t* for ease-of-use.

```
constexpr punycode_idna_t ztd::text::punycode_idna = punycode_idna_t{}
```

A preexisting object of type *ztd::text::punycode_idna_t* for ease-of-use.

```
using ztd::text::punycode_t = basic_punycode<char, unicode_code_point>
```

A *ztd::text::basic_any_punycode* type using `char` and *ztd::text::unicode_code_point*.

```
using ztd::text::punycode_idna_t = basic_punycode_idna<char, unicode_code_point>
```

A *ztd::text::basic_any_punycode* type using `char` and *ztd::text::unicode_code_point*.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
using ztd::text::basic_punycode = basic_any_punycode<idna::no, _CodeUnit, _CodePoint>
```

A convenience typedef for `ztd::text::basic_any_punycode` with the `ztd::text::idna::no` provided.

Template Parameters

- **_CodeUnit** – The code unit type for encoded text.
- **_CodePoint** – The code point type for decoded text.

```
template<typename _CodeUnit, typename _CodePoint>
```

```
using ztd::text::basic_punycode_idna = basic_any_punycode<idna::yes, _CodeUnit, _CodePoint>
```

A convenience typedef for `ztd::text::basic_any_punycode` with the `ztd::text::idna::yes` provided.

Template Parameters

- **_CodeUnit** – The code unit type for encoded text.
- **_CodePoint** – The code point type for decoded text.

Base Template

```
template<idna _IsIdna, typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_any_punycode : public __fixed_cuneicode<basic_any_punycode<_IsIdna, char, unicode_code_point>, char, unicode_code_point, 1, 1, decltype(_IsIdna == idna::yes ? &::cnc_mcnrtoc32n_punycode_idna : &::cnc_mcnrtoc32n_punycode), (_IsIdna == idna::yes ? &::cnc_mcnrtoc32n_punycode_idna : &::cnc_mcnrtoc32n_punycode), decltype(_IsIdna == idna::yes ? &::cnc_c32nrtomcn_punycode_idna : &::cnc_c32nrtomcn_punycode), (_IsIdna == idna::yes ? &::cnc_c32nrtomcn_punycode_idna : &::cnc_c32nrtomcn_punycode), cnc_pny_decode_state_t, decltype(&::cnc_pny_decode_state_is_complete), &::cnc_pny_decode_state_is_complete, cnc_pny_encode_state_t, decltype(&::cnc_pny_encode_state_is_complete), &::cnc_pny_encode_state_is_complete, true, true, char, ztd_char32_t>
```

The punycode encoding, as envisioned by RFC 3492 and (potentially) influenced by IDNA (RFC 5890).

Remark

See <https://datatracker.ietf.org/doc/html/rfc5890> and <https://datatracker.ietf.org/doc/html/rfc3492>.

Template Parameters

- **_IsIdna** – Whether or not this punycode type looks for IDNA prefixes and obeys its encoding rules.
- **_CodeUnit** – The code unit type for the encoded ASCII text.
- **_CodePoint** – The code point type for the Unicode Code Point decoded text.

Public Types

using **code_unit** = char

The code unit type for encoded text.

using **code_point** = *unicode_code_point*

The code point type for decoded text.

using **is_decode_injective** = ::std::integral_constant<bool, _IsDecodeInjective>

The whether or not the decode portion of this encoding is injective.

using **is_encode_injective** = ::std::integral_constant<bool, _IsEncodeInjective>

The whether or not the decode portion of this encoding is injective.

Public Static Functions

static inline auto **decode_one**(_Input &&__input, _Output &&__output, _ErrorHandler &&__error_handler, *decode_state* &__state) noexcept

Decodes a provided range of punycode-encoded data and pulls out data.

Remark

This function may need to be called with empty input data repeatedly to fully drain any stored information in the provided `__state`. The entire input may be consumed before any information is output.

Template Parameters

- **_Input** – The input range type.
- **_Output** – The output range type.
- **_ErrorHandler** – The error handler type.

Parameters

- **__input** – The input range.
- **__output** – The output range.
- **__error_handler** – The error handler; this will be called whenever an error occurs during decoding.
- **__state** – A reference to the decode state, which contains most of the running information about a punycode decoding operation. Discarding this between calls is not advised for this encoding type.

Returns

A *ztd::text::decode_result* structure with the appropriate input and output types reconstructed, possibly filtered through an error handler if necessary.

```
static inline auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler &&__error_handler,  
                               encode_state &__state)
```

Encodes a provided range of punycode-encoded data and pulls out data.

Remark

This function may need to be called with empty input data repeatedly to fully drain any stored information in the provided `__state`. The entire input may be consumed before any information is output.

Template Parameters

- **_Input** – The input range type.
- **_Output** – The output range type.
- **_ErrorHandler** – The error handler type.

Parameters

- **__input** – The input range.
- **__output** – The output range.
- **__error_handler** – The error handler; this will be called whenever an error occurs during decoding.
- **__state** – A reference to the encode state, which contains most of the running information about a punycode decoding operation. Discarding this between calls is not advised for this encoding type.

Returns

A `ztd::text::encode_result` structure with the appropriate input and output types reconstructed, possibly filtered through an error handler if necessary.

Public Static Attributes

```
static constexpr ::std::size_t max_code_points
```

The maximum number of code points output by a decode operation. In this case, only 1 code point is output at a time.

```
static constexpr ::std::size_t max_code_units
```

The maximum number of code units output by an encode operation. In this case, only 1 code unit is output at a time.

SHIFT-JISX0208

The version of SHIFT-JIS that corresponds to standard X0208, one of the more prevalent versions.

Note that many versions of SHIFT-JIS do not correspond to one standard and often have different interpretations or characteristics. The communities which use them label them, indiscriminately, as SHIFT-JIS without any kind of specific indicator or even out-of-band modifier. The text community surrounding this is, with all due respect, one gigantic mess. Most industry professionals inside and outside of Japan dealing with such text tend to gravitate towards the SHIFT-JISX0208 release, and simply use replacement characters / invalid indicators for such input text.

As such, it is advisable to perhaps attempt to find some out-of-band data to see if a specific data is, indeed, meant to be SHIFT-JISX0208.

Aliases

```
constexpr basic_shift_jis_x0208<char> ztd::text::shift_jis_x0208 = {}
```

An instance of *basic_shift_jis_x0208* for ease of use.

```
constexpr auto &ztd::text::shift_jis = shift_jis_x0208
```

An instance of *basic_shift_jis* for ease of use.

```
using ztd::text::shift_jis_t = basic_shift_jis_x0208<char>
```

A convenience alias that defaults *shift_jis* to the x0208 version.

```
template<typename _CodeUnit, typename _CodePoint = unicode_code_point>
```

```
using ztd::text::basic_shift_jis = basic_shift_jis_x0208<_CodeUnit, _CodePoint>
```

A convenience alias that defaults *basic_shift_jis* to the x0208 version.

Base Templates

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_shift_jis_x0208
```

The Shift-JIS Encoding (with extensions x0208) for use with most Shift-JIS applications. Identical version of what is a part of the WHATWG encoding standard for Shift-JIS.

Template Parameters

- **_CodeUnit** – The code unit type to use.
- **_CodePoint** – The code point type to use.

Public Types

using **code_unit** = *_CodeUnit*

Shift-JIS is generally stored as minimum-8-bit values in a sequence.

using **code_point** = *_CodePoint*

Shift-JIS outputs Unicode Scalar Values.

using **state** = *__txt_detail::__empty_state*

Shift-JIS requires no state.

using **is_decode_injective** = *std::true_type*

Marks this encoding as injective for the decode portion of its encoding actions.

Public Functions

inline constexpr ztd::span<const *code_unit*, 1> **replacement_code_units**() const noexcept

A fixed-size 1-element span with the *__code_point* unit “?”.

Public Static Functions

template<typename *_Input*, typename *_Output*, typename *_ErrorHandler*>

static inline constexpr auto **decode_one**(*_Input* &&__input, *_Output* &&__output, *_ErrorHandler* &&__error_handler, *state* &__state) noexcept

Decodes a single complete unit of information as *__code_point* points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a *forward_range*). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an *input_range*.

Parameters

- **__input** – [in] The input view to read *__code_point* units from.
- **__output** – [in] The output view to write *__code_point* points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A *ztd::text::decode_result* object that contains the input range, output range, error handler, and a reference to the passed-in state.

```
template<typename _Input, typename _Output, typename _ErrorHandler>
static inline constexpr auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, state &__state) noexcept
```

Encodes a single complete unit of information as `__code_point` units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- **__input** – [in] The input view to read `__code_point` points from.
- **__output** – [in] The output view to write `__code_point` units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::encode_result` object that contains the input range, output range, error handler, and a reference to the passed-in state.

Public Static Attributes

```
static constexpr std::size_t max_code_points = 1
```

The Shift-JIS encoding can put out at most 1 `__code_point` point per decoding action.

```
static constexpr std::size_t max_code_units = 2
```

The Shift-JIS encoding can put out at most 2 `__code_point` units per encoding action.

Single-byte Encodings / Lookup Encodings

These encodings are single-byte encodings that contain no inherent complexity and are driven by high-bit-1, 8-bit lookup tables or direct 8-bit lookup tables. They are all listed below for brevity.

Known Encodings

constexpr *basic_atari_st*<char> ztd::text::atari_st = {}

An instance of *basic_atari_st* for ease of use.

constexpr *basic_atascii*<char> ztd::text::atascii = {}

An instance of *basic_atascii* for ease of use.

constexpr *basic_ibm_424_hebrew_bulletin*<char> ztd::text::ibm_424_hebrew_bulletin = {}

An instance of *basic_ibm_8_424ebrew* for ease of use.

constexpr *basic_ibm_856_hebrew*<char> ztd::text::ibm_856_hebrew = {}

An instance of *basic_ibm_856_hebrew* for ease of use.

constexpr *basic_ibm_866_cyrillic*<char> ztd::text::ibm_866_cyrillic = {}

An instance of *basic_ibm_866_cyrillic* for ease of use.

constexpr *basic_ibm_1006_urdu*<char> ztd::text::ibm_1006_urdu = {}

An instance of *basic_ibm_1006_urdu* for ease of use.

constexpr *basic_iso_8859_1_1985*<char> ztd::text::iso_8859_1_1985 = {}

An instance of *basic_iso_8859_1_1985* for ease of use.

constexpr *basic_iso_8859_1_1998*<char> ztd::text::iso_8859_1_1998 = {}

An instance of *basic_iso_8859_1_1998* for ease of use.

constexpr *basic_iso_8859_1*<char> ztd::text::iso_8859_1 = {}

An instance of the *basic_iso_8859_1* type for ease of use.

constexpr *basic_iso_8859_2*<char> ztd::text::iso_8859_2 = {}

An instance of *basic_iso_8859_2* for ease of use.

constexpr *basic_iso_8859_3*<char> ztd::text::iso_8859_3 = {}

An instance of *basic_iso_8859_3* for ease of use.

constexpr *basic_iso_8859_4*<char> ztd::text::iso_8859_4 = {}

An instance of *basic_iso_8859_4* for ease of use.

constexpr *basic_iso_8859_5*<char> ztd::text::iso_8859_5 = {}

An instance of *basic_iso_8859_5* for ease of use.

constexpr *basic_iso_8859_6*<char> ztd::text::iso_8859_6 = {}

An instance of *basic_iso_8859_6* for ease of use.

```
constexpr basic_iso_8859_7<char> ztd::text::iso_8859_7 = {}
```

An instance of *basic_iso_8859_7* for ease of use.

```
constexpr basic_iso_8859_8<char> ztd::text::iso_8859_8 = {}
```

An instance of *basic_iso_8859_8* for ease of use.

```
constexpr basic_iso_8859_10<char> ztd::text::iso_8859_10 = {}
```

An instance of *basic_iso_8859_10* for ease of use.

```
constexpr basic_iso_8859_13<char> ztd::text::iso_8859_13 = {}
```

An instance of *basic_iso_8859_13* for ease of use.

```
constexpr basic_iso_8859_14<char> ztd::text::iso_8859_14 = {}
```

An instance of *basic_iso_8859_14* for ease of use.

```
constexpr basic_iso_8859_15<char> ztd::text::iso_8859_15 = {}
```

An instance of *basic_iso_8859_15* for ease of use.

```
constexpr basic_iso_8859_16<char> ztd::text::iso_8859_16 = {}
```

An instance of *basic_iso_8859_16* for ease of use.

```
constexpr basic_kamenicky<char> ztd::text::kamenicky = {}
```

An instance of *basic_kamenicky* for ease of use.

```
constexpr basic_kazakh_strk1048<char> ztd::text::kazakh_strk1048 = {}
```

An instance of *basic_kazakh_strk1048* for ease of use.

```
constexpr basic_koi8_r<char> ztd::text::koi8_r = {}
```

An instance of *basic_koi8_r* for ease of use.

```
constexpr basic_koi8_u<char> ztd::text::koi8_u = {}
```

An instance of *basic_koi8_u* for ease of use.

```
constexpr basic_petscii_unshifted<char> ztd::text::petscii_unshifted = {}
```

An instance of *basic_petscii_unshifted* for ease of use.

```
constexpr basic_petscii_shifted<char> ztd::text::petscii_shifted = {}
```

An instance of *basic_petscii_shifted* for ease of use.

```
constexpr basic_tatar_ansi<char> ztd::text::tatar_ansi = {}
```

An instance of *basic_tatar_ansi* for ease of use.

```
constexpr basic_tatar_ascii<char> ztd::text::tatar_ascii = {}
```

An instance of *basic_tatar_ascii* for ease of use.

constexpr *basic_windows_437_dos_latin_us*<char> ztd::text::**windows_437_dos_latin_us** = {}

An instance of *basic_windows_437_dos_latin_us* for ease of use.

constexpr *basic_windows_865_dos_nordic*<char> ztd::text::**windows_865_dos_nordic** = {}

An instance of *basic_windows_865_dos_nordic* for ease of use.

constexpr *basic_windows_874*<char> ztd::text::**windows_874** = {}

An instance of *basic_windows_874* for ease of use.

constexpr *basic_windows_1251*<char> ztd::text::**windows_1251** = {}

An instance of *windows_1251* for ease of use.

constexpr *basic_windows_1252*<char> ztd::text::**windows_1252** = {}

An instance of *basic_windows_1252* for ease of use.

constexpr *basic_windows_1253*<char> ztd::text::**windows_1253** = {}

An instance of *basic_windows_1253* for ease of use.

constexpr *basic_windows_1254*<char> ztd::text::**windows_1254** = {}

An instance of *basic_windows_1254* for ease of use.

constexpr *basic_windows_1255*<char> ztd::text::**windows_1255** = {}

An instance of *basic_windows_1255* for ease of use.

constexpr *basic_windows_1256*<char> ztd::text::**windows_1256** = {}

An instance of *basic_windows_1256* for ease of use.

constexpr *basic_windows_1257*<char> ztd::text::**windows_1257** = {}

An instance of *basic_windows_1257* for ease of use.

constexpr *basic_windows_1258*<char> ztd::text::**windows_1258** = {}

An instance of *basic_windows_1258* for ease of use.

Base Templates

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_atascii : public __single_byte_lookup_encoding<basic_atascii<char, unicode_code_point>, &::ztd::et::atascii_index_to_code_point, &::ztd::et::atascii_code_point_to_index, char, unicode_code_point>
```

Template Parameters

- **_CodeUnit** –
- **_CodePoint** –

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_atari_st : public __single_byte_lookup_encoding<basic_atari_st<char, unicode_code_point>,
&::ztd::et::atari_st_index_to_code_point, &::ztd::et::atari_st_code_point_to_index, char, unicode_code_point>
```

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_ibm_424_hebrew_bulletin : public
__single_byte_lookup_encoding<basic_ibm_424_hebrew_bulletin<char, unicode_code_point>,
&::ztd::et::ibm_424_hebrew_bulletin_index_to_code_point,
&::ztd::et::ibm_424_hebrew_bulletin_code_point_to_index, char, unicode_code_point>
```

The Hebrew encoding that matches IBM's Codepage 424.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_ibm_856_hebrew : public __single_byte_lookup_encoding<basic_ibm_856_hebrew<char,
unicode_code_point>, &::ztd::et::ibm_856_hebrew_index_to_code_point,
&::ztd::et::ibm_856_hebrew_code_point_to_index, char, unicode_code_point>
```

The Hebrew encoding that matches IBM's Codepage 856.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_ibm_866_cyrillic : public
__single_ascii_byte_high_bit_lookup_encoding<basic_ibm_866_cyrillic<char, unicode_code_point>,
&::ztd::et::ibm_866_cyrillic_index_to_code_point, &::ztd::et::ibm_866_cyrillic_code_point_to_index, char,
unicode_code_point>
```

The Cyrillic encoding that matches IBM's Codepage 866.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_ibm_1006_urdu : public __single_byte_lookup_encoding<basic_ibm_1006_urdu<char,
unicode_code_point>, &::ztd::et::ibm_1006_urdu_index_to_code_point,
&::ztd::et::ibm_1006_urdu_code_point_to_index, char, unicode_code_point>
```

The Urdu encoding that matches IBM's Codepage 1006.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_iso_8859_1_1985 : public __single_byte_lookup_encoding<basic_iso_8859_1_1985<char,  
unicode_code_point>, &::ztd::et::iso_8859_1_1985_index_to_code_point,  
&::ztd::et::iso_8859_1_1985_code_point_to_index, char, unicode_code_point>
```

The encoding that matches ISO/IEC 8859-1 specification published in 1985.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_iso_8859_1_1998 : public __single_byte_lookup_encoding<basic_iso_8859_1_1998<char,  
unicode_code_point>, &::ztd::et::iso_8859_1_1998_index_to_code_point,  
&::ztd::et::iso_8859_1_1998_code_point_to_index, char, unicode_code_point>
```

The encoding that matches the ISO/IEC 8859-1 encoding specification published in the year 1998.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit, typename _CodePoint = unicode_code_point>
```

```
class basic_iso_8859_1
```

The ISO/IEC 8859-1 encoding, occasionally referred to as Latin-1 (erroneously). Matches Unicode's encoding of the first 256 bytes one-to-one.

Template Parameters

- **_CodeUnit** – The code unit type to work over.
- **_CodePoint** – The code point type to work over.

Public Types

```
using code_unit = _CodeUnit
```

The individual units that result from an encode operation or are used as input to a decode operation.

```
using code_point = _CodePoint
```

The individual units that result from a decode operation or as used as input to an encode operation. For most encodings, this is going to be a Unicode Code Point or a Unicode Scalar Value.

```
using state = __txt_detail::__empty_state
```

The state that can be used between calls to the encoder and decoder. This is empty for this encoding.

```
using is_decode_injective = ::std::true_type
```

Whether or not the decode operation can process all forms of input into code point values.

Remark

ISO/IEC 8859-1 can decode from its 8-bit (unpacked) code units to Unicode Code Points. Since the conversion is lossless, this property is true.

using **is_encode_injective** = ::std::false_type

Whether or not the encode operation can process all forms of input into code unit values. This is not true for ISO/IEC 8859-1, as many Unicode Code Point and Unicode Scalar Values cannot be represented in ISO/IEC 8859-1. Since the conversion is lossy, this property is false.

Public Static Functions

static inline constexpr ::ztd::span<const *code_unit*, 1> **replacement_code_units**() noexcept

A range of code units representing the values to use when a replacement happens. For ISO/IEC 8859-1, this must be '?' instead of the usual Unicode Replacement Character U'.

template<typename **_Input**, typename **_Output**, typename **_ErrorHandler**>
static inline constexpr auto **decode_one**(*_Input* &&__input, *_Output* &&__output, *_ErrorHandler*
&&__error_handler, *state* &__s)

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A *ztd::text::decode_result* object that contains the input range, output range, error handler, and a reference to the passed-in state.

template<typename **_Input**, typename **_Output**, typename **_ErrorHandler**>
static inline constexpr auto **encode_one**(*_Input* &&__input, *_Output* &&__output, *_ErrorHandler*
&&__error_handler, *state* &__s)

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code points from.
- **__output** – [in] The output view to write code units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::encode_result` object that contains the input range, output range, error handler, and a reference to the passed-in state.

Public Static Attributes

static constexpr const ::std::size_t **max_code_units** = 1

The maximum code units a single complete operation of encoding can produce.

static constexpr const ::std::size_t **max_code_points** = 1

The maximum number of code points a single complete operation of decoding can produce.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_iso_8859_2 : public __single_ascii_byte_high_bit_lookup_encoding<basic_iso_8859_2<char,  
unicode_code_point>, &::ztd::et::iso_8859_2_index_to_code_point, &::ztd::et::iso_8859_2_code_point_to_index,  
char, unicode_code_point>
```

The encoding that matches the ISO/IEC 8859-2 encoding specification.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_iso_8859_3 : public __single_ascii_byte_high_bit_lookup_encoding<basic_iso_8859_3<char,  
unicode_code_point>, &::ztd::et::iso_8859_3_index_to_code_point, &::ztd::et::iso_8859_3_code_point_to_index,  
char, unicode_code_point>
```

The encoding that matches the ISO/IEC 8859-3 encoding specification.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_iso_8859_4 : public __single_ascii_byte_high_bit_lookup_encoding<basic_iso_8859_4<char,
unicode_code_point>, &::ztd::et::iso_8859_4_index_to_code_point, &::ztd::et::iso_8859_4_code_point_to_index,
char, unicode_code_point>
```

The encoding that matches the ISO/IEC 8859-4 encoding specification.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_iso_8859_5 : public __single_ascii_byte_high_bit_lookup_encoding<basic_iso_8859_5<char,
unicode_code_point>, &::ztd::et::iso_8859_5_index_to_code_point, &::ztd::et::iso_8859_5_code_point_to_index,
char, unicode_code_point>
```

The encoding that matches the ISO/IEC 8859-5 encoding specification.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_iso_8859_6 : public __single_ascii_byte_high_bit_lookup_encoding<basic_iso_8859_6<char,
unicode_code_point>, &::ztd::et::iso_8859_6_index_to_code_point, &::ztd::et::iso_8859_6_code_point_to_index,
char, unicode_code_point>
```

The encoding that matches the ISO/IEC 8859-6 encoding specification.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_iso_8859_7 : public __single_ascii_byte_high_bit_lookup_encoding<basic_iso_8859_7<char,
unicode_code_point>, &::ztd::et::iso_8859_7_index_to_code_point, &::ztd::et::iso_8859_7_code_point_to_index,
char, unicode_code_point>
```

The encoding that matches the ISO/IEC 8859-7 encoding specification.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_iso_8859_8 : public __single_ascii_byte_high_bit_lookup_encoding<basic_iso_8859_8<char,
unicode_code_point>, &::ztd::et::iso_8859_8_index_to_code_point, &::ztd::et::iso_8859_8_code_point_to_index,
char, unicode_code_point>
```

The encoding that matches the ISO/IEC 8859-8 encoding specification.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_iso_8859_10 : public __single_ascii_byte_high_bit_lookup_encoding<basic_iso_8859_10<char,  
unicode_code_point>, &::ztd::et::iso_8859_10_index_to_code_point, &::ztd::et::iso_8859_10_code_point_to_index,  
char, unicode_code_point>
```

The encoding that matches the ISO/IEC 8859-10 encoding specification.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_iso_8859_13 : public __single_ascii_byte_high_bit_lookup_encoding<basic_iso_8859_13<char,  
unicode_code_point>, &::ztd::et::iso_8859_13_index_to_code_point, &::ztd::et::iso_8859_13_code_point_to_index,  
char, unicode_code_point>
```

The encoding that matches the ISO/IEC 8859-15 encoding specification.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_iso_8859_14 : public __single_ascii_byte_high_bit_lookup_encoding<basic_iso_8859_14<char,  
unicode_code_point>, &::ztd::et::iso_8859_14_index_to_code_point, &::ztd::et::iso_8859_14_code_point_to_index,  
char, unicode_code_point>
```

The encoding that matches the ISO/IEC 8859-14 encoding specification.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_iso_8859_15 : public __single_ascii_byte_high_bit_lookup_encoding<basic_iso_8859_15<char,  
unicode_code_point>, &::ztd::et::iso_8859_15_index_to_code_point, &::ztd::et::iso_8859_15_code_point_to_index,  
char, unicode_code_point>
```

The encoding that matches the ISO/IEC 8859-15 encoding specification.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_iso_8859_16 : public __single_ascii_byte_high_bit_lookup_encoding<basic_iso_8859_16<char,  
unicode_code_point>, &::ztd::et::iso_8859_16_index_to_code_point, &::ztd::et::iso_8859_16_code_point_to_index,  
char, unicode_code_point>
```

The encoding that matches the ISO/IEC 8859-16 encoding specification.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_kamenicky : public __single_byte_lookup_encoding<basic_kamenicky<char, unicode_code_point>,
&::ztd::et::kamenicky_index_to_code_point, &::ztd::et::kamenicky_code_point_to_index, char,
unicode_code_point>
```

The encoding that matches the KAMENICKY encoding specification.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_kazakh_strk1048 : public __single_byte_lookup_encoding<basic_kazakh_strk1048<char,
unicode_code_point>, &::ztd::et::kazakh_strk1048_index_to_code_point,
&::ztd::et::kazakh_strk1048_code_point_to_index, char, unicode_code_point>
```

The encoding that matches the KZ1048 / Kazakh STRK-1048 encoding specification.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_koi8_r : public __single_ascii_byte_high_bit_lookup_encoding<basic_koi8_r<char,
unicode_code_point>, &::ztd::et::koi8_r_index_to_code_point, &::ztd::et::koi8_r_code_point_to_index, char,
unicode_code_point>
```

The encoding that matches the KOI-8-R (Russian) Cyrillic encoding specification.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_koi8_u : public __single_ascii_byte_high_bit_lookup_encoding<basic_koi8_u<char,
unicode_code_point>, &::ztd::et::koi8_u_index_to_code_point, &::ztd::et::koi8_u_code_point_to_index, char,
unicode_code_point>
```

The encoding that matches the KOI-8 (Ukrainian) encoding specification.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_petscii_unshifted : public __single_byte_lookup_encoding<basic_petscii_unshifted<char,
unicode_code_point>, &::ztd::et::petscii_unshifted_index_to_code_point,
&::ztd::et::petscii_unshifted_code_point_to_index, char, unicode_code_point>
```

The encoding that matches the PETSCII (CBM ASCII) encoding specification, for unshifted characters (when the SHIFT button was NOT pressed on a PET/CBM device).

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.

- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_petscii_shifted : public __single_byte_lookup_encoding<basic_petscii_shifted<char,  
unicode_code_point>, &::ztd::et::petscii_shifted_index_to_code_point,  
&::ztd::et::petscii_shifted_code_point_to_index, char, unicode_code_point>
```

The encoding that matches the PETSCII (CBM ASCII) encoding specification, for shifted characters (when the SHIFT button was pressed on a PET/CBM device).

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_tatar_ansi : public  
__txt_impl::__single_ansi_byte_high_bit_lookup_encoding<basic_tatar_ansi<char, unicode_code_point>,  
&::ztd::et::tatar_ansi_index_to_code_point, &::ztd::et::tatar_ansi_code_point_to_index, char, unicode_code_point>
```

The encoding that matches the TATAR encoding (it's ANSI variant, based on Windows Code Page 1252.)

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_tatar_ascii : public __single_ascii_byte_high_bit_lookup_encoding<basic_tatar_ascii<char,  
unicode_code_point>, &::ztd::et::tatar_ascii_index_to_code_point, &::ztd::et::tatar_ascii_code_point_to_index, char,  
unicode_code_point>
```

The encoding that matches the TATAR encoding specification (based on its “ASCII” variant, IBM Code Page 866).

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_windows_437_dos_latin_us : public  
__single_byte_lookup_encoding<basic_windows_437_dos_latin_us<char, unicode_code_point>,  
&::ztd::et::windows_437_dos_latin_us_index_to_code_point,  
&::ztd::et::windows_437_dos_latin_us_code_point_to_index, char, unicode_code_point>
```

The encoding that matches Microsoft Windows's Codepage 437 (DOS Latin, US).

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_windows_865_dos_nordic : public  
__single_byte_lookup_encoding<basic_windows_865_dos_nordic<char, unicode_code_point>,  
&::ztd::et::windows_865_dos_nordic_index_to_code_point,  
&::ztd::et::windows_865_dos_nordic_code_point_to_index, char, unicode_code_point>
```

The encoding that matches Microsoft Windows’s Codepage 437 (DOS Latin, US).

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_windows_874 : public __single_ascii_byte_high_bit_lookup_encoding<basic_windows_874<char, unicode_code_point>, &::ztd::et::windows_874_index_to_code_point, &::ztd::et::windows_874_code_point_to_index, char, unicode_code_point>
```

The encoding that matches Microsoft Windows’s Codepage 874.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_windows_1251 : public __single_ascii_byte_high_bit_lookup_encoding<basic_windows_1251<char, unicode_code_point>, &::ztd::et::windows_1251_index_to_code_point, &::ztd::et::windows_1251_code_point_to_index, char, unicode_code_point>
```

The encoding that matches Microsoft Windows’s Codepage 1251.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_windows_1252 : public __single_ascii_byte_high_bit_lookup_encoding<basic_windows_1252<char, unicode_code_point>, &::ztd::et::windows_1252_index_to_code_point, &::ztd::et::windows_1252_code_point_to_index, char, unicode_code_point>
```

The encoding that matches Microsoft Windows’s Codepage 1252 (AKA “Latin-1”).

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_windows_1253 : public __single_ascii_byte_high_bit_lookup_encoding<basic_windows_1253<char, unicode_code_point>, &::ztd::et::windows_1253_index_to_code_point, &::ztd::et::windows_1253_code_point_to_index, char, unicode_code_point>
```

The encoding that matches Microsoft Windows’s Codepage 1253.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_windows_1254 : public __single_ascii_byte_high_bit_lookup_encoding<basic_windows_1254<char,
unicode_code_point>, &::ztd::et::windows_1254_index_to_code_point,
&::ztd::et::windows_1254_code_point_to_index, char, unicode_code_point>
```

The encoding that matches Microsoft Windows's Codepage 1254.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_windows_1255 : public __single_ascii_byte_high_bit_lookup_encoding<basic_windows_1255<char,
unicode_code_point>, &::ztd::et::windows_1255_index_to_code_point,
&::ztd::et::windows_1255_code_point_to_index, char, unicode_code_point>
```

The encoding that matches Microsoft Windows's Codepage 1255.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_windows_1256 : public __single_ascii_byte_high_bit_lookup_encoding<basic_windows_1256<char,
unicode_code_point>, &::ztd::et::windows_1256_index_to_code_point,
&::ztd::et::windows_1256_code_point_to_index, char, unicode_code_point>
```

The encoding that matches Microsoft Windows's Codepage 1256.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_windows_1257 : public __single_ascii_byte_high_bit_lookup_encoding<basic_windows_1257<char,
unicode_code_point>, &::ztd::et::windows_1257_index_to_code_point,
&::ztd::et::windows_1257_code_point_to_index, char, unicode_code_point>
```

The encoding that matches Microsoft Windows's Codepage 1257.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

```
template<typename _CodeUnit = char, typename _CodePoint = unicode_code_point>
```

```
class basic_windows_1258 : public __single_ascii_byte_high_bit_lookup_encoding<basic_windows_1258<char,
unicode_code_point>, &::ztd::et::windows_1258_index_to_code_point,
&::ztd::et::windows_1258_code_point_to_index, char, unicode_code_point>
```

The encoding that matches Microsoft Windows's Codepage 1258.

Template Parameters

- **_CodeUnit** – The default code unit type to use when outputting encoded units.
- **_CodePoint** – The code point type to use when outputting decoded units.

UTF-16

Aliases

```
constexpr utf16_t ztd::text::utf16 = {}
```

An instance of the UTF-16 encoding for ease of use.

```
typedef basic_utf16<char16_t, unicode_code_point> ztd::text::utf16_t
```

A UTF-16 Encoding that traffics in char16_t. See *ztd::text::basic_utf16* for more details.

```
constexpr wide_utf16_t ztd::text::wide_utf16 = {}
```

An instance of the UTF-16 that traffics in wchar_t for ease of use.

```
using ztd::text::wide_utf16_t = basic_utf16<wchar_t>
```

A UTF-16 Encoding that traffics in wchar_t. See *ztd::text::basic_utf16* for more details.

Base Template

```
template<typename _CodeUnit, typename _CodePoint = unicode_code_point>
```

```
class basic_utf16 : public __utf16_with<basic_utf16<_CodeUnit, unicode_code_point>, _CodeUnit,  
unicode_code_point>
```

A UTF-16 Encoding that traffics in, specifically, the desired code unit type provided as a template argument.

Remark

This is a strict UTF-16 implementation that does not allow lone, unpaired surrogates either in or out.

Template Parameters

- ***_CodeUnit*** – The code unit type to use.
- ***_CodePoint*** – The code point type to use.

Public Types

```
using is_unicode_encoding = ::std::true_type
```

Whether or not this encoding that can encode all of Unicode.

```
using self_synchronizing_code = ::std::true_type
```

The start of a sequence can be found unambiguously when dropped into the middle of a sequence or after an error in reading as occurred for encoded text.

Remark

Unicode has definitive bit patterns which resemble start and end sequences (“low surrogate” and “high surrogate” for UTF-16).

using **state** = `__txt_detail::__empty_state`

The state that can be used between calls to the encoder and decoder. It is an empty struct because there is no shift state to preserve between complete units of encoded information.

using **code_unit** = `_CodeUnit`

The individual units that result from an encode operation or are used as input to a decode operation. For UTF-16 formats, this is usually `char16_t`, but this can change (see `ztd::text::basic_utf16`).

using **code_point** = `unicode_code_point`

The individual units that result from a decode operation or as used as input to an encode operation. For most encodings, this is going to be a Unicode Code Point or a Unicode Scalar Value.

using **is_decode_injective** = `::std::true_type`

Whether or not the decode operation can process all forms of input into code point values. This is true for all Unicode Transformation Formats (UTFs), which can encode and decode without a loss of information from a valid collection of code units.

using **is_encode_injective** = `::std::true_type`

Whether or not the encode operation can process all forms of input into code unit values. This is true for all Unicode Transformation Formats (UTFs), which can encode and decode without loss of information from a valid input code point.

Public Static Functions

static inline constexpr `::ztd::span<const code_unit, 1>` **replacement_code_units**() noexcept

Returns the replacement code units to use for the `ztd::text::replacement_handler_t` error handler.

static inline constexpr `::ztd::span<const code_point, 1>` **replacement_code_points**() noexcept

Returns the replacement code point to use for the `ztd::text::replacement_handler_t` error handler.

static inline constexpr auto **skip_input_error**(`decode_result<_Input, _Output, _State> __result`, const `_InputProgress &__input_progress`, const `_OutputProgress &__output_progress`) noexcept

Allows an encoding to discard input characters if an error occurs, taking in both the state and the input sequence (by reference) to modify.

Remark

This will skip every input value until a proper UTF-16 starting byte (single or leading surrogate).

Parameters

- **__result** – [in] The decode result being processed by the error handler.
- **__input_progress** – [in] The input that has been read but not committed to consumption.

- **__output_progress** – [in] The output that has been written but could not be committed due to an error.

```
static inline constexpr auto skip_input_error(encode_result<_Input, _Output, _State> __result, const
    _InputProgress &__input_progress, const _OutputProgress
    &__output_progress) noexcept
```

Allows an encoding to discard input characters if an error occurs, taking in both the state and the input sequence (by reference) to modify.

Remark

This will skip every input value until a proper UTF-32 unicode scalar value (or code point) is found.

```
static inline constexpr auto decode_one(_Input &&__input, _Output &&__output, _ErrorHandler
    &&__error_handler, state &__s)
```

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::decode_result` object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

```
static inline constexpr auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler
    &&__error_handler, state &__s)
```

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code points from.
- **__output** – [in] The output view to write code units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::encode_result` object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

Public Static Attributes

static constexpr ::std::size_t **max_code_points**

The maximum number of code points a single complete operation of decoding can produce. This is 1 for all Unicode Transformation Format (UTF) encodings.

static constexpr ::std::size_t **max_code_units**

The maximum code units a single complete operation of encoding can produce.

static constexpr ::ztd::text_encoding_id **encoded_id**

The encoding ID for this type. Used for optimization purposes.

static constexpr ::ztd::text_encoding_id **decoded_id**

The encoding ID for this type. Used for optimization purposes.

UTF-32

Aliases

constexpr *utf32_t* ztd::text::**utf32** = {}

An instance of the UTF-32 encoding for ease of use.

typedef *basic_utf32*<char32_t, *unicode_code_point*> ztd::text::**utf32_t**

A UTF-32 Encoding that traffics in `ztd_char32_t`. See `ztd::text::basic_utf32` for more details.

constexpr *wide_utf32_t* ztd::text::**wide_utf32** = {}

An instance of the UTF-32 that traffics in `wchar_t` for ease of use.

using ztd::text::**wide_utf32_t** = *basic_utf32*<wchar_t>

A UTF-32 Encoding that traffics in `wchar_t`. See `ztd::text::basic_utf32` for more details.

Base Template

```
template<typename _CodeUnit, typename _CodePoint = unicode_code_point>
```

```
class basic_utf32 : public __utf32_with<basic_utf32<_CodeUnit, unicode_code_point>, _CodeUnit,
unicode_code_point>
```

A UTF-32 Encoding that traffics in, specifically, the desired code unit type provided as a template argument.

Remark

This is a strict UTF-32 implementation that does not allow lone, unpaired surrogates either in or out.

Template Parameters

- **_CodeUnit** – The code unit type to use.
- **_CodePoint** – The code point type to use.

Public Types

```
using is_unicode_encoding = ::std::true_type
```

Whether or not this encoding that can encode all of Unicode.

```
using self_synchronizing_code = ::std::true_type
```

The start of a sequence can be found unambiguously when dropped into the middle of a sequence or after an error in reading as occurred for encoded text.

Remark

Unicode has definitive bit patterns which resemble start and end sequences. For UTF-32, there is only 1 code point per fully encoded character.

```
using state = __txt_detail::__empty_state
```

The state that can be used between calls to the encoder and decoder. It is an empty struct because there is no shift state to preserve between complete units of encoded information.

```
using code_unit = _CodeUnit
```

The individual units that result from an encode operation or are used as input to a decode operation. For UTF-32 formats, this is usually `ztd_char32_t`, but this can change (see *ztd::text::basic_utf32*).

```
using code_point = unicode_code_point
```

The individual units that result from a decode operation or as used as input to an encode operation. For most encodings, this is going to be a Unicode Code Point or a Unicode Scalar Value.

using **is_decode_injective** = ::std::true_type

Whether or not the decode operation can process all forms of input into code point values. This is true for all Unicode Transformation Formats (UTFs), which can encode and decode without a loss of information from a valid collection of code units.

using **is_encode_injective** = ::std::true_type

Whether or not the encode operation can process all forms of input into code unit values. This is true for all Unicode Transformation Formats (UTFs), which can encode and decode without loss of information from a valid input code point.

Public Static Functions

```
static inline constexpr auto skip_input_error(_Result &&__result, const _InputProgress  
                                               &__input_progress, const _OutputProgress  
                                               &__output_progress) noexcept
```

Allows an encoding to discard input characters if an error occurs, taking in both the state and the input sequence (by reference) to modify.

Remark

This will skip every input value until a proper UTF-32 unicode scalar value (or code point) is found.

```
static inline constexpr auto decode_one(_Input &&__input, _Output &&__output, _ErrorHandler  
                                         &&__error_handler, state &__s)
```

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::decode_result` object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

```
static inline constexpr auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, state &__s)
```

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code points from.
- **__output** – [in] The output view to write code units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A *ztd::text::encode_result* object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

Public Static Attributes

```
static constexpr ::std::size_t max_code_points
```

The maximum number of code points a single complete operation of decoding can produce. This is 1 for all Unicode Transformation Format (UTF) encodings.

```
static constexpr ::std::size_t max_code_units
```

The maximum code units a single complete operation of encoding can produce.

```
static constexpr ::ztd::text_encoding_id encoded_id
```

The encoding ID for this type. Used for optimization purposes.

```
static constexpr ::ztd::text_encoding_id decoded_id
```

The encoding ID for this type. Used for optimization purposes.

UTF-8

Unicode Transformation Format 8 (UTF-8) is an encoding for text that traffics code units 8-bits at a time. It is ubiquitous amongst web and other shared protocols and the preferred storage format for non-legacy environments and operations. It is preferred that all text is placed in UTF-8 format when working internally in your application, unless you have some special reason (e.g., interoperability with JavaScript or Qt).

Aliases

```
constexpr utf8_t ztd::text::utf8 = {}
```

An instance of the UTF-8 encoding for ease of use.

```
typedef basic_utf8<uchar8_t, unicode_code_point> ztd::text::utf8_t
```

A UTF-8 Encoding that traffics in `uchar8_t`. See `ztd::text::basic_utf8` for more details.

```
constexpr compat_utf8_t ztd::text::compat_utf8 = {}
```

An instance of the compatibility UTF-8 encoding for ease of use.

```
typedef basic_utf8<char, unicode_code_point> ztd::text::compat_utf8_t
```

A UTF-8 Encoding that traffics in `char`, for compatibility purposes with older codebases. See `ztd::text::basic_utf8` for more details.

Base Template

```
template<typename _CodeUnit, typename _CodePoint = unicode_code_point>
```

```
class basic_utf8 : public __utf8_with<basic_utf8<_CodeUnit, unicode_code_point>, _CodeUnit,  
unicode_code_point>
```

A UTF-8 Encoding that traffics in, specifically, the desired code unit type provided as a template argument.

Remark

This type as a maximum of 4 input code points and a maximum of 1 output code point. It strictly follows the Unicode Specification for allowed conversions. For overlong sequences (e.g., similar to Android or Java UTF-8 implementations) and other quirks, see `ztd::text::basic_mutf8` or `ztd::text::basic_wtf8`.

Template Parameters

- **_CodeUnit** – The code unit type to use.
- **_CodePoint** – The code point type to use.

Public Types

using **is_unicode_encoding** = ::std::true_type

Whether or not this encoding that can encode all of Unicode.

using **self_synchronizing_code** = ::std::true_type

The start of a sequence can be found unambiguously when dropped into the middle of a sequence or after an error in reading as occurred for encoded text.

Remark

Unicode has definitive bit patterns which resemble start and end sequences. The bit pattern 0xxxxxxx indicates a lone bit, and 1xxxxxx indicates a potential start bit for UTF-8. In particular, if 0 is not the first bit, it must be a sequence of 1s followed immediately by a 0 (e.g., 10xxxxxx, 110xxxxx, 1110xxxx, or 11110xxx).

using **decode_state** = __txt_detail::__empty_state

The state that can be used between calls to the encoder and decoder. It is normally an empty struct because there is no shift state to preserve between complete units of encoded information.

using **encode_state** = __txt_detail::__empty_state

The state that can be used between calls to the encoder and decoder. It is normally an empty struct because there is no shift state to preserve between complete units of encoded information.

using **code_unit** = *_CodeUnit*

The individual units that result from an encode operation or are used as input to a decode operation. For UTF-8 formats, this is usually `char8_t`, but this can change (see *ztd::text::basic_utf8*).

using **code_point** = *unicode_code_point*

The individual units that result from a decode operation or as used as input to an encode operation. For most encodings, this is going to be a Unicode Code Point or a Unicode Scalar Value.

using **is_decode_injective** = ::std::true_type

Whether or not the decode operation can process all forms of input into code point values. This is true for all Unicode Transformation Formats (UTFs), which can encode and decode without a loss of information from a valid collection of code units.

using **is_encode_injective** = ::std::true_type

Whether or not the encode operation can process all forms of input into code unit values. This is true for all Unicode Transformation Formats (UTFs), which can encode and decode without loss of information from a valid input code point.

Public Static Functions

static inline constexpr ::ztd::span<const *code_unit*, 3> **replacement_code_units**() noexcept

Returns the replacement code units to use for the *ztd::text::replacement_handler_t* error handler.

static inline constexpr ::ztd::span<const *code_point*, 1> **replacement_code_points**() noexcept

Returns the replacement code point to use for the *ztd::text::replacement_handler_t* error handler.

static inline constexpr auto **skip_input_error**(*decode_result*<_Input, _Output, _State> __result, const
_InputProgress &__input_progress, const _OutputProgress
&__output_progress) noexcept

Allows an encoding to discard input characters if an error occurs, taking in both the state and the input sequence to modify through the result type.

Remark

This will skip every input value until a proper starting byte is found.

static inline constexpr auto **skip_input_error**(*encode_result*<_Input, _Output, _State> __result, const
_InputProgress &__input_progress, const _OutputProgress
&__output_progress) noexcept

Allows an encoding to discard input characters if an error occurs, taking in both the state and the input sequence (by reference) to modify.

Remark

This will skip every input value until a proper UTF-32 unicode scalar value (or code point) is found.

static inline constexpr auto **encode_one**(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, *encode_state* &__s)

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a *forward_range*). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an *input_range*.

Parameters

- **__input** – [in] The input view to read code points from.
- **__output** – [in] The output view to write code units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.

- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::encode_result` object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

```
static inline constexpr auto decode_one(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, decode_state &__s)
```

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::decode_result` object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

Public Static Attributes

```
static constexpr ::std::size_t max_code_points
```

The maximum number of code points a single complete operation of decoding can produce. This is 1 for all Unicode Transformation Format (UTF) encodings.

```
static constexpr ::std::size_t max_code_units
```

The maximum code units a single complete operation of encoding can produce. If overlong sequence allowed, this is 6; otherwise, this is 4.

```
static constexpr ::ztd::text_encoding_id encoded_id
```

The encoding ID for this type. Used for optimization purposes.

```
static constexpr ::ztd::text_encoding_id decoded_id
```

The encoding ID for this type. Used for optimization purposes.

Wide Execution

This is the locale-based, wide runtime encoding. It uses a number of compile-time and runtime heuristics to eventually be resolved to an implementation-defined encoding. It is not required to work in constant expressions either: for this, use `ztd::text::wide_literal`, which represents the compile-time wide string (e.g. `L"my string"`) encoding.

Currently, the hierarchy of behaviors is like so:

- If the platform is Windows, then it assumes this is *UTF-16*;
- If the platform is MacOS or `__STDC_ISO10646__`, then it assumed this is *UTF-32* of some kind;
- Otherwise, cuneicode is used.

Warning: The C Standard Library has many design defects in its production of code points, which may make it unsuitable even if your C Standard Library recognizes certain locales (e.g., Big5-HKSCS). The runtime will always attempt to load `iconv` if the definition is turned on, since it may do a better job than the C Standard Library's interfaces until C23.

Even if, on a given platform, it can be assumed to be a static encoding (e.g., Apple/MacOS where it always returns the “C” Locale but processes text as UTF-32), `ztd::text::wide_execution` will always present itself as a runtime and unknowable encoding. This is to prevent portability issues from relying on, e.g., `ztd::text::is_decode_injective_v<ztd::text::wide_execution>` being true during development and working with that assumption, only to have it break when ported to a platform where that assumption no longer holds.

Aliases

```
constexpr wide_execution_t ztd::text::wide_execution = {}
```

An instance of the `wide_execution_t` type for ease of use.

```
class wide_execution_t : public __wide_execution_cwchar
```

The Encoding that represents the “Wide Execution” (wide locale-based) encoding. The wide execution encoding is typically associated with the locale, which is tied to the C standard library's `setlocale` function.

Remark

Windows uses UTF-16, unless you call the C Standard Library directly. This object may use the C Standard Library to perform transcoding if certain platform facilities are disabled or not available. If this is the case, the C Standard Library has fundamental limitations which may treat your UTF-16 data like UCS-2, and result in broken input/output. This object uses UTF-16 directly on Windows when possible to avoid some of the platform-specific shenanigans. It will attempt to do UTF-32 conversions where possible as well, relying on C Standard definitions.

Internal Type

Warning: Names with double underscores, and within the `__*detail` and `__*impl` namespaces are reserved for the implementation. Referencing this entity directly is bad, and the name/functionality can be changed at any point in the future. Relying on anything not guaranteed by the documentation is Undefined Behavior.

<wchar>-based

class `__wide_execution_cwchar`

The Encoding that represents the “Wide Execution” (wide locale-based) encoding. This iteration uses the C Standard Library to do its job.

Remark

Because this encoding uses the C Standard Library’s functions, it is both slower and effectively dangerous because it requires a roundtrip through the encoding to get to UTF-32, and vice-versa. This is only used when `wchar_t` and its locale-based runtime encoding cannot be determined to be UTF-32, UTF-16, or some other statically-known encoding. These conversions may also be lossy.

Subclassed by *wide_execution_t*

Public Types

using `code_unit` = `wchar_t`

The individual units that result from an encode operation or are used as input to a decode operation.

Remark

Please note that `wchar_t` is a variably sized type across platforms and may not represent either UTF-16 or UTF-32, including on *nix or POSIX platforms.

using `code_point` = *unicode_code_point*

The individual units that result from a decode operation or as used as input to an encode operation. For most encodings, this is going to be a Unicode Code Point or a Unicode Scalar Value.

using `decode_state` = `__wide_decode_state`

The state of the wide encoding used between calls, which may potentially manage shift state.

Remark

This type can potentially have lots of state due to the way the C API is specified.

using **encode_state** = __wide_encode_state

The state of the wide encoding used between calls, which may potentially manage shift state.

Remark

This type can potentially have lots of state due to the way the C API is specified.

using **is_decode_injective** = ::std::false_type

Whether or not the decode operation can process all forms of input into code point values.

Remark

All known wide encodings can decode into Unicode just fine.

using **is_encode_injective** = ::std::false_type

Whether or not the encode operation can process all forms of input into code unit values. On Windows, this is guaranteed to be UTF-16 encoding for the platform. Normally, this is UTF-32 on *nix/POSIX machines, but it can (and has been) changed before, sometimes even at runtime.

Remark

IBM encodings/computers make life interesting...

using **is_unicode_encoding** = ::std::false_type

Whether or not this encoding a Unicode encoding of some type.

Remark

On Windows, this is always true. On other platforms, the guarantees are not quite there. IBM encodings/computers make life interesting...

Public Static Functions

static inline bool **contains_unicode_encoding**() noexcept

Returns whether or not this encoding is a unicode encoding.

Remark

This function operates at runtime and queries the existing locale through a variety of platform-specific means (such as `nl_langinfo` for POSIX, ACP probing on Windows, or fallin back to `std::setlocale` name checking otherwise).

```
template<typename _Input, typename _Output, typename _ErrorHandler>
static inline auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler &&__error_handler,
                               encode_state &__s)
```

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

Platform APIs and/or the C Standard Library may be used to properly decode one complete unit of information (alongside `std::mbstate_t` usage). Whether or not the state is used is based on the implementation and what it chooses.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- **__input** – [in] The input view to read code uunits from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. Most encodings have no state, but because this is effectively a runtime encoding and therefore it is important to preserve and manage this state.

Returns

A `ztd::text::encode_result` object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

```
template<typename _Input, typename _Output, typename _ErrorHandler>
static inline auto decode_one(_Input &&__input, _Output &&__output, _ErrorHandler &&__error_handler,
                               decode_state &__s)
```

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

Platform APIs and/or the C Standard Library may be used to properly decode one complete unit of information (alongside `std::mbstate_t` usage). Whether or not the state is used is based on the implementation and what it chooses.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. Most encodings have no state, but because this is effectively a runtime encoding and therefore it is important to preserve and manage this state.

Returns

A `ztd::text::decode_result` object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

Public Static Attributes

```
static constexpr const ::std::size_t max_code_units = 8
```

The maximum code units a single complete operation of encoding can produce.

```
static constexpr const ::std::size_t max_code_points = 8
```

The maximum number of code points a single complete operation of decoding can produce.

MacOS-based / `__STDC_ISO10646__`-based

```
class __wide_execution_iso10646: private __utf32_with<__wide_execution_iso10646, wchar_t, ztd_char32_t>
```

The wide encoding, as envisioned by ISO 10646. Typically UTF-32 with native endianness.

Remark

This is generally only turned on when the Standard Definition is turned on (`__STDC_ISO_10646__`). It effectively uses UTF-32 since that's the only encoding that can meet the original requirement of the C Standard and C Standard Library with respect to what happens with individual `wchar_t` objects.

Public Types

using **code_point** = *code_point_t*<__base_t>

The code point type that is decoded to, and encoded from.

using **code_unit** = *code_unit_t*<__base_t>

The code unit type that is decoded from, and encoded to.

using **decode_state** = *decode_state_t*<__base_t>

The associated state for decode operations.

using **encode_state** = *encode_state_t*<__base_t>

The associated state for encode operations.

using **is_unicode_encoding** = ::std::integral_constant<bool, *is_unicode_encoding_v*<__base_t>>

Whether or not this encoding is a unicode encoding or not.

using **is_decode_injective** = ::std::false_type

Whether or not this encoding's `decode_one` step is injective or not.

using **is_encode_injective** = ::std::false_type

Whether or not this encoding's `encode_one` step is injective or not.

Public Static Functions

```
template<typename _Input, typename _Output, typename _ErrorHandler>
static inline constexpr auto decode_one(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, decode_state &__s)
```

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. Most encodings have no state, but because this is effectively a runtime encoding and therefore it is important to preserve and manage this state.

Returns

A *ztd::text::decode_result* object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

```
template<typename _Input, typename _Output, typename _ErrorHandler>
```

```
static inline constexpr auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, encode_state &__s)
```

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. Most encodings have no state, but because this is effectively a runtime encoding and therefore it is important to preserve and manage this state.

Returns

A *ztd::text::encode_result* object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

Public Static Attributes

```
static constexpr const ::std::size_t max_code_units = 8
```

The maximum code units a single complete operation of encoding can produce.

```
static constexpr const ::std::size_t max_code_points = 8
```

The maximum number of code points a single complete operation of decoding can produce.

Private Static Functions

```
static inline constexpr auto decode_one(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, state &__s)
```

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a *forward_range*). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an *input_range*.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.

- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A *ztd::text::decode_result* object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

```
static inline constexpr auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, state &__s)
```

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- **__input** – [in] The input view to read code points from.
- **__output** – [in] The output view to write code units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A *ztd::text::encode_result* object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

Windows-based

```
class __wide_execution_windows : private basic_utf16<wchar_t>
```

The Encoding that represents the “Wide Execution” (wide locale-based) encoding, as it exists on Windows. The wide encoding is typically associated with the locale, which is tied to the C standard library’s `setlocale` function.

Remark

Windows uses UTF-16, unless you call the C Standard Library directly. This object may use the C Standard Library to perform transcoding if certain platform facilities are disabled or not available (e.g., a Windows-like machine without the Windows SDK). If this is the case, the C Standard Library has fundamental limitations which may treat your UTF-16 data like UCS-2, and result in broken input/output. This object uses UTF-16 directly on Windows when possible to avoid some of the platform-specific shenanigans.

Public Types

using **code_point** = *code_point_t*<__base_t>

The code point type that is decoded to, and encoded from.

using **code_unit** = *code_unit_t*<__base_t>

The code unit type that is decoded from, and encoded to.

using **decode_state** = *decode_state_t*<__base_t>

The associated state for decode operations.

using **encode_state** = *encode_state_t*<__base_t>

The associated state for encode operations.

using **is_unicode_encoding** = ::std::integral_constant<bool, *is_unicode_encoding_v*<__base_t>>

Whether or not this encoding is a unicode encoding or not.

using **is_decode_injective** = ::std::false_type

Whether or not this encoding's `decode_one` step is injective or not.

using **is_encode_injective** = ::std::false_type

Whether or not this encoding's `encode_one` step is injective or not.

Public Static Functions

```
template<typename _Input, typename _Output, typename _ErrorHandler>
static inline constexpr auto decode_one(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, state &__s)
```

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. Most encodings have no state, but because this is effectively a runtime encoding and therefore it is important to preserve and manage this state.

Returns

A *ztd::text::decode_result* object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

```
template<typename _Input, typename _Output, typename _ErrorHandler>
```

```
static inline constexpr auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler
&&__error_handler, state &__s)
```

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. Most encodings have no state, but because this is effectively a runtime encoding and therefore it is important to preserve and manage this state.

Returns

A *ztd::text::encode_result* object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

Public Static Attributes

```
static constexpr const ::std::size_t max_code_units = 8
```

The maximum code units a single complete operation of encoding can produce.

```
static constexpr const ::std::size_t max_code_points = 8
```

The maximum number of code points a single complete operation of decoding can produce.

Wide Literal

The *wide_literal* encoding handles C and C++ wide string literals (L"") used at compile time and stored in the binary. The library uses a number of heuristics to determine with any degree of certainty what the encoding of string literals are, but in some cases it is not explicitly possible to achieve this goal.

If the library cannot figure out the wide literal encoding, the code will typically error with a `static_assert`, loudly, that it cannot use the functions on the type when you attempt to do anything with them because it may mangle whatever input or output you are expecting.

If you know the encoding of wide literals for your project (you provide the command line switch, or similar), then you can define a *configuration macro named ZTD_CXX_COMPILE_TIME_WIDE_ENCODING_NAME* to be a string literal of your type, such as "UTF-16" or "EUC-TW".

If the library does not recognize the encoding and cannot transcode it properly, it will also loudly warn you that it does not understand the encoding of the literal (in which case, file an issue about it and we will add it to the list of acceptable wide literal encodings).

If you like to live dangerously and do not care for the warnings, you can define a *configuration macro named ZTD_TEXT_YES_PLEASE_DESTROY_MY_WIDE_LITERAL_UTTERLY_I_MEAN_IT* and it will just blindly go with whatever weird default it ended up deciding on.

(This is usually a catastrophically terrible idea, but let it not be said that we didn't give you the power to do great things, even if it cost you your foot.)

Alias

```
constexpr wide_literal_t ztd::text::wide_literal = {}
```

An instance of the *wide_literal_t* type for ease of use.

Base Type

```
class wide_literal_t : public __wide_literal
```

The encoding of wide string literal_ts (e.g. "") at compile time.

Public Types

```
using is_unicode_encoding = ::std::integral_constant<bool,  
is_unicode_encoding_id(__txt_detail::__wide_literal_id)>
```

Whether or not this *wide_literal_t* encoding is a Unicode Transformation Format, such as UTF-8, UTF-GB18030, UTF-16, or UTF-32.

```
using code_unit = code_unit_t<__base_t>
```

The individual units that result from an encode operation or are used as input to a decode operation.

```
using code_point = code_point_t<__base_t>
```

The individual units that result from a decode operation or as used as input to an encode operation. For most encodings, this is going to be a Unicode Code Point or a Unicode Scalar Value.

```
using encode_state = encode_state_t<__base_t>
```

The state that can be used between calls to `encode_one`.

```
using decode_state = decode_state_t<__base_t>
```

The state that can be used between calls to `decode_one`.

```
using is_decode_injective = ::std::integral_constant<bool, is_decode_injective_v<__base_t>>
```

Whether or not the decode operation can process all forms of input into code point values.

Remark

The decode step is always injective because every encoding used for literal_ts in C++ needs to be capable of being represented by UCNs.

```
using is_encode_injective = ::std::integral_constant<bool, is_encode_injective_v<__base_t>>
```

Whether or not the encode operation can process all forms of input into code unit values.

Remark

This is absolutely not guaranteed to be the case, and as such we must check the provided encoding name for wide to be sure.

Public Functions

constexpr **wide_literal_t**() noexcept = default

Default constructs a *ztd::text::wide_literal*.

constexpr **wide_literal_t**(const *wide_literal_t*&) noexcept = default

Copy constructs a *ztd::text::wide_literal*.

constexpr **wide_literal_t**(*wide_literal_t*&&) noexcept = default

Move constructs a *ztd::text::wide_literal*.

constexpr *wide_literal_t* &**operator**=(const *wide_literal_t*&) noexcept = default

Copy assigns into a *ztd::text::wide_literal_t* object.

constexpr *wide_literal_t* &**operator**=(*wide_literal_t*&&) noexcept = default

Move assigns into a *ztd::text::wide_literal_t* object.

```
template<typename _Input, typename _Output, typename _ErrorHandler>
inline constexpr auto decode_one(_Input &&__input, _Output &&__output, _ErrorHandler
    &&__error_handler, decode_state &__state) const
```

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code units from.
- **__output** – [in] The output view to write code points into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A *ztd::text::decode_result* object that contains the input range, output range, error handler, and a reference to the passed-in state.

```
template<typename _Input, typename _Output, typename _ErrorHandler>
inline constexpr auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler
    &&__error_handler, encode_state &__state) const
```

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a forward_range). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an input_range.

Parameters

- **__input** – [in] The input view to read code points from.
- **__output** – [in] The output view to write code units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__state** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A *ztd::text::encode_result* object that contains the input range, output range, error handler, and a reference to the passed-in state.

Public Static Attributes

```
static constexpr const ::ztd::text_encoding_id decoded_id = decoded_id_v<__base_t>
```

The id representing the decoded text.

```
static constexpr const ::ztd::text_encoding_id encoded_id = encoded_id_v<__base_t>
```

The id representing the encoded text.

```
static constexpr ::std::size_t max_code_points = 8
```

The maximum number of code points a single complete operation of decoding can produce.

```
static constexpr ::std::size_t max_code_units = 16
```

The maximum code units a single complete operation of encoding can produce.

WTF-8

Wobby Transformat Format 8 (WTF-8) is an encoding scheme that preserves lone-encoded surrogates, which is generally not allowed in streams composed purely of Unicode Scalar Values.

Aliases

```
constexpr wtf8_t ztd::text::wtf8 = {}
```

An instance of the UTF-8 type for ease of use.

```
using ztd::text::wtf8_t = basic_wtf8<uchar8_t>
```

A “Wobbly Transformation Format 8” (UTF-8) Encoding that traffics in `char8_t`. See `ztd::text::basic_wtf8` for more details.

Base Template

```
template<typename _CodeUnit, typename _CodePoint = unicode_code_point>
```

```
class basic_wtf8 : public __utf8_with<basic_wtf8<_CodeUnit, unicode_code_point>, _CodeUnit,
unicode_code_point, __txt_detail::__empty_state, __txt_detail::__empty_state, false, true, false>
```

A “Wobbly Transformation Format 8” (UTF-8) Encoding that traffics in, specifically, the desired code unit type provided as a template argument.

Remark

This type as a maximum of 4 input code points and a maximum of 1 output code point. Unpaired surrogates are allowed in this type, which may be useful for dealing with legacy storage and implementations of the Windows Filesystem (modern Windows no longer lets non-Unicode filenames through). For a strict, Unicode-compliant UTF-8 Encoding, see `ztd::text::basic_utf8`.

Template Parameters

- **_CodeUnit** – The code unit type to use.
- **_CodePoint** – The code point type to use.

Public Types

```
using is_unicode_encoding = ::std::true_type
```

Whether or not this encoding that can encode all of Unicode.

```
using self_synchronizing_code = ::std::true_type
```

The start of a sequence can be found unambiguously when dropped into the middle of a sequence or after an error in reading as occurred for encoded text.

Remark

Unicode has definitive bit patterns which resemble start and end sequences. The bit pattern `0xxxxxxx` indicates a lone bit, and `1xxxxxx` indicates a potential start bit for UTF-8. In particular, if 0 is not the first

bit, it must be a sequence of 1s followed immediately by a 0 (e.g., 10xxxxxx, 110xxxxx, 1110xxxx, or 11110xxx).

using **decode_state** = __txt_detail::__empty_state

The state that can be used between calls to the encoder and decoder. It is normally an empty struct because there is no shift state to preserve between complete units of encoded information.

using **encode_state** = __txt_detail::__empty_state

The state that can be used between calls to the encoder and decoder. It is normally an empty struct because there is no shift state to preserve between complete units of encoded information.

using **code_unit** = *_CodeUnit*

The individual units that result from an encode operation or are used as input to a decode operation. For UTF-8 formats, this is usually `char8_t`, but this can change (see *ztd::text::basic_utf8*).

using **code_point** = *unicode_code_point*

The individual units that result from a decode operation or as used as input to an encode operation. For most encodings, this is going to be a Unicode Code Point or a Unicode Scalar Value.

using **is_decode_injective** = ::std::true_type

Whether or not the decode operation can process all forms of input into code point values. This is true for all Unicode Transformation Formats (UTFs), which can encode and decode without a loss of information from a valid collection of code units.

using **is_encode_injective** = ::std::true_type

Whether or not the encode operation can process all forms of input into code unit values. This is true for all Unicode Transformation Formats (UTFs), which can encode and decode without loss of information from a valid input code point.

Public Static Functions

static inline constexpr ::ztd::span<const *code_unit*, 3> **replacement_code_units**() noexcept

Returns the replacement code units to use for the *ztd::text::replacement_handler_t* error handler.

static inline constexpr ::ztd::span<const *code_point*, 1> **replacement_code_points**() noexcept

Returns the replacement code point to use for the *ztd::text::replacement_handler_t* error handler.

static inline constexpr auto **skip_input_error**(*decode_result*<_Input, _Output, _State> __result, const _InputProgress &__input_progress, const _OutputProgress &__output_progress) noexcept

Allows an encoding to discard input characters if an error occurs, taking in both the state and the input sequence to modify through the result type.

Remark

This will skip every input value until a proper starting byte is found.

```
static inline constexpr auto skip_input_error(encode_result<_Input, _Output, _State> __result, const
    _InputProgress &__input_progress, const _OutputProgress
    &__output_progress) noexcept
```

Allows an encoding to discard input characters if an error occurs, taking in both the state and the input sequence (by reference) to modify.

Remark

This will skip every input value until a proper UTF-32 unicode scalar value (or code point) is found.

```
static inline constexpr auto encode_one(_Input &&__input, _Output &&__output, _ErrorHandler
    &&__error_handler, encode_state &__s)
```

Encodes a single complete unit of information as code units and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- **__input** – [in] The input view to read code points from.
- **__output** – [in] The output view to write code units into.
- **__error_handler** – [in] The error handler to invoke if encoding fails.
- **__s** – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::encode_result` object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

```
static inline constexpr auto decode_one(_Input &&__input, _Output &&__output, _ErrorHandler
    &&__error_handler, decode_state &__s)
```

Decodes a single complete unit of information as code points and produces a result with the input and output ranges moved past what was successfully read and written; or, produces an error and returns the input and output ranges untouched.

Remark

To the best ability of the implementation, the iterators will be returned untouched (e.g., the input models at least a view and a `forward_range`). If it is not possible, returned ranges may be incremented even if an error occurs due to the semantics of any view that models an `input_range`.

Parameters

- `__input` – [in] The input view to read code units from.
- `__output` – [in] The output view to write code points into.
- `__error_handler` – [in] The error handler to invoke if encoding fails.
- `__s` – [inout] The necessary state information. For this encoding, the state is empty and means very little.

Returns

A `ztd::text::decode_result` object that contains the reconstructed input range, reconstructed output range, error handler, and a reference to the passed-in state.

Public Static Attributes

static constexpr ::std::size_t **max_code_points**

The maximum number of code points a single complete operation of decoding can produce. This is 1 for all Unicode Transformation Format (UTF) encodings.

static constexpr ::std::size_t **max_code_units**

The maximum code units a single complete operation of encoding can produce. If overlong sequence allowed, this is 6; otherwise, this is 4.

static constexpr ::ztd::text_encoding_id **encoded_id**

The encoding ID for this type. Used for optimization purposes.

static constexpr ::ztd::text_encoding_id **decoded_id**

The encoding ID for this type. Used for optimization purposes.

1.8.4 Error Handlers

`assume_valid_handler`

The `assume_valid_handler` is a Undefined-Behavior invoking error handler. If an error is encountered, the encoding can legally ignore and never, ever call the error handler at all. This can invoke Undefined Behavior on malformed input.

Warning: This should **only ever be used on the most trusted of input, ever, and that input should never come from a source that is a user or connected to ANY external input sources such as the Network, Shared Pipe, Inter-Procedural Call, or similar.**

Implementers of encodings within templates can check for a potentially ignorable error handler like this one using `ztd::text::is_ignorable_error_handler_v`.

```
constexpr assume_valid_handler_t ztd::text::assume_valid_handler = {}
```

An instance of the `assume_valid_handler_t` type for ease of use.

class `assume_valid_handler_t`

An error handler that tells an encoding that it will pass through any errors, without doing any adjustment, correction or checking.

Remark

This error handler is useful in conjunction with a `ztd::text::ranges::unbounded_view` for the fastest possible encoding and decoding in a general sense. However: IT IS ALSO EXTREMELY DANGEROUS AND CAN INVOKE UNDEFINED BEHAVIOR IF YOUR TEXT IS, IN FACT, MESSED UP. PLEASE DO NOT USE THIS WITHOUT A GOOD REASON!

Public Types

```
using assume_valid = ::std::integral_constant<bool, true>
```

A type that is true when calling code can not call this function and ignore it, and false when it cannot ignore it. See `ztd::text::assume_valid_handler_t` for details.

Public Functions

```
template<typename _Encoding, typename _Result, typename _InputProgress, typename
_OutputProgress>
inline constexpr auto operator() (const _Encoding&, _Result __result, const _InputProgress&, const
_OutputProgress&) const
```

A handler for either decode or encode results that simply passes the result type back through with no changes made.

Parameters

__result – [in] The current state of the encode operation to pass through.

default_handler

The default handler for all operations. A class type that simply wraps `ztd::text::replacement_handler_t` unless configured otherwise. You can change it to throw by default (NOT recommended) by using `ZTD_TEXT_DEFAULT_HANDLER_THROWS`.

Using this type, implicitly or explicitly, signals to `ztd.text` that you would like it to gently admonish you if any part of a conversion could be potentially lossy (valid data is put in, but it cannot be handled by the desired encode/decode/transcode operation).

```
constexpr default_handler_t ztd::text::default_handler = {}
```

An instance of the `default_handler_t` type for ease of use.

```
class default_handler_t : private replacement_handler_t
```

The default error handler for the entire library. Can be configured to use different strategies at build time. Without configuration, it defaults to the `ztd::text::replacement_handler_t`.

Public Types

using **error_handler** = __error_handler_base_t

The underlying error handler type.

basic_incomplete_handler

This error handler takes the `ztd::text::encoding_error::incomplete_sequence` error and uses it to read from the provided “progress” contiguous range provided as the third parameter to any error handler. This can be helpful in situations here incomplete input is not to be interpreted as an error, such as in situations with networking stacks, I/O reads (particularly, non-recoverable streams like `std::istream_iterators` or `std::ostream_iterators`), and other such storage cases.

The data read but not used from an incomplete error during encode and decode operations is stored in the `basic_incomplete_handler` object and can be accessed VIA the `code_points` and `code_units` functions.

```
template<typename _Encoding, typename _ErrorHandler = pass_handler_t>
```

```
class basic_incomplete_handler : private ebco<pass_handler_t>
```

This handler detects if the error code is an incomplete sequence, and sets the error code to being okay before returning.

Remark

This type is often useful in conjunction with an accumulation state or buffer, which can be very handy for I/O (e.g., Networking) operations.

Template Parameters

- **_Encoding** – The encoding type which dictates the `code_unit` and `code_point` buffers to store in the handler to catch unused input from the last parameter of error handler invocations by the encoding.
- **_ErrorHandler** – An error handler to invoke if the encoding error code is **NOT** an incomplete sequence.

Public Types

using **error_handler** = *ErrorHandler*

The underlying error handler type.

Public Functions

inline constexpr **basic_incomplete_handler**()
noexcept(::std::is_nothrow_default_constructible_v<__error_handler_base_t>)

Constructs a *ztd::text::basic_incomplete_handler* with a default-constructed internal error handler.

inline constexpr **basic_incomplete_handler**(const *ErrorHandler* &__error_handler) noexcept
noexcept(::std::is_nothrow_constructible_v<__error_handler_base_t,
const *ErrorHandler*&>)

Constructs a *ztd::text::basic_incomplete_handler* with the provided internal error handler object.

Parameters

__error_handler – The provided error handler object to copy in and use when the error is not an incomplete error.

inline constexpr **basic_incomplete_handler**(*ErrorHandler* &&__error_handler) noexcept
noexcept(::std::is_nothrow_constructible_v<__error_handler_base_t,
ErrorHandler&&>)

Constructs a *ztd::text::basic_incomplete_handler* with the provided internal error handler object.

Parameters

__error_handler – The provided error handler object to move in and use when the error is not an incomplete error.

inline constexpr *ErrorHandler* &base() & noexcept

Returns the base error handler that is called when a non-incomplete error occurs.

inline constexpr const *ErrorHandler* &base() const & noexcept

Returns the base error handler that is called when a non-incomplete error occurs.

inline constexpr *ErrorHandler* &&base() && noexcept

Returns the base error handler that is called when a non-incomplete error occurs.

template<typename **_Result**, typename **_InputProgress**, typename **_OutputProgress**>
inline constexpr auto **operator**() (const *Encoding* &__encoding, *Result* __result, const *InputProgress*
&__input_progress, const *OutputProgress* &__output_progress) const &
noexcept(::std::is_nothrow_invocable_v<*ErrorHandler*, const
Encoding&, *Result*&&, const *InputProgress*&, const
OutputProgress&>)

Checks if the `__result.error_code` is *ztd::text::encoding_error::incomplete_sequence*, it saves the values from `__progress` and returns. Otherwise, invokes the provided error handler this object was constructed with.

Parameters

- **__encoding** – [in] The Encoding that experienced the error.
- **__result** – [in] The current state of the encode operation.
- **__input_progress** – [in] Any code units or code points that were read but not yet used before the failure occurred. These will be stored in this handler.
- **__output_progress** – [in] Any code points or code units that have not yet been written before the failure occurred. These will be stored in this handler.

template<typename **_Result**, typename **_InputProgress**, typename **_OutputProgress**>

```
inline constexpr auto operator() (const _Encoding &__encoding, _Result __result, const _InputProgress
    &__input_progress, const _OutputProgress &__output_progress) &
    noexcept(::std::is_nothrow_invocable_v<_ErrorHandler, const
    _Encoding&, _Result&&, const _InputProgress&, const
    _OutputProgress&>)
```

Checks if the `__result.error_code` is `ztd::text::encoding_error::incomplete_sequence`, it saves the values from `__progress` and returns. Otherwise, invokes the provided error handler this object was constructed with.

Parameters

- **__encoding** – [in] The Encoding that experienced the error.
- **__result** – [in] The current state of the encode operation.
- **__input_progress** – [in] Any code units or code points that were read but not yet used before the failure occurred. These will be stored in this handler.
- **__output_progress** – [in] Any code points or code units that have not yet been written before the failure occurred. These will be stored in this handler.

```
template<typename _Result, typename _InputProgress, typename _OutputProgress>
inline constexpr auto operator() (const _Encoding &__encoding, _Result __result, const _InputProgress
    &__input_progress, const _OutputProgress &__output_progress) &&
    noexcept(::std::is_nothrow_invocable_v<_ErrorHandler, const
    _Encoding&, _Result&&, const _InputProgress&, const
    _OutputProgress&>)
```

Checks if the `__result.error_code` is `ztd::text::encoding_error::incomplete_sequence`, it saves the values from `__progress` and returns. Otherwise, invokes the provided error handler this object was constructed with.

Parameters

- **__encoding** – [in] The Encoding that experienced the error.
- **__result** – [in] The current state of the encode operation.
- **__input_progress** – [in] Any code units or code points that were read but not yet used before the failure occurred. These will be stored in this handler.
- **__output_progress** – [in] Any code points or code units that have not yet been written before the failure occurred. These will be stored in this handler.

```
inline ::ztd::span<_CodeUnit> code_units() const noexcept
```

Returns the code units from the last incomplete decode operations.

```
inline ::ztd::span<_CodePoint> code_points() const noexcept
```

Returns the code points from the last incomplete encode operations.

pass_handler

The `pass_handler` does exactly what its name implies: it passes the error as generated by the encoding object through without touching it. Unlike `ztd::text::assume_valid_handler`, this one does not invoke undefined behavior because it does not meet the requirements for the `ztd::text::is_ignorable_error_handler` trait.

```
constexpr pass_handler_t ztd::text::pass_handler = {}
```

An instance of `pass_handler_t` for ease of use.

```
class pass_handler_t : public __txt_detail::__pass_through_handler_with<false>
```

An error handler that tells an encoding that it will pass through any errors, without doing any adjustment, correction or checking. Does not imply it is ignorable, unlike `ztd::text::assume_valid_handler_t` which can invoke UB if an error occurs.

replacement_handler

The `replacement_handler_t` is the go-to error handling class. It is also the `ztd::text::default_handler` unless configured otherwise.

Replacement works by using several different hooks on the provided encoding objects, or by falling back to some defaults if certain conditions are met. The user-controllable hooks are:

- `encoding.replacement_code_units(...)`, a function (which can be `static` or `constexpr`) that returns a range of code units to insert directly into an output stream on a failed `encode` operation. It can also be called as a secondary backup if an `decode` operation fails, whereupon it will use the values in the range to attempt decoding them into the output if possible. It can be empty, to indicate that nothing is to be inserted.
- `encoding.replacement_code_points(...)`, a function (which can be `static` or `constexpr`) that returns a range of code points to insert directly into an output stream on a failed `decode` operation. It can also be called as a secondary backup if an `encode` operation fails, whereupon it will use the values in the range to attempt encoding them into the output if possible. It can be empty, to indicate that nothing is to be inserted.
- `encoding.maybe_replacement_code_units(...)`, a function (which can be `static` or `constexpr`) that returns a maybe-range. If the expression `if (maybe_returned_range)` evaluates to `true`, it will get the range returned by the function by performing a dereference of `decltype(auto) returned_range = *maybe_returned_range;`. If the conditional expression does not evaluate to `true`, it will assume that nothing can be returned from the function. This is useful for runtime-only encodings or encodings that wrap other encodings and may not have a replacement function. The dereferenced returned range is used exactly as its non-maybe counterpart.
- `encoding.maybe_replacement_code_points(...)`, a function (which can be `static` or `constexpr`) that returns a maybe-range. If the expression `if (maybe_returned_range)` evaluates to `true`, it will get the range returned by the function by performing a dereference of `decltype(auto) returned_range = *maybe_returned_range;`. If the conditional expression does not evaluate to `true`, it will assume that nothing can be returned from the function. This is useful for runtime-only encodings or encodings that wrap other encodings and may not have a replacement function. The dereferenced returned range is used exactly as its non-maybe counterpart.

Each replacement handler can take the current `encode_state/decode_state` parameter for its desired operation, if it so chooses. This will allow replacements to hook into the statefulness of any given encoding operation. It will call `replacement_code_units(state)` first, if it's well-formed. Otherwise, it will call `replacement_code_units()`. It will do this with each of the 4 replacement functions mentioned above.

After a replacement is done (if any), the function will then skip over bad input. The skipping is done by calling `ztd::text::skip_input_error(...)` with the encoding and result object, before returning, and after replacements are done.

```
constexpr replacement_handler_t ztd::text::replacement_handler = {}
```

A convenience variable for passing the *replacement_handler_t* handler to functions.

```
class replacement_handler_t
```

An error handler that replaces bad code points and code units with a chosen code point / code unit sequence.

Remark

This class hooks into the encodings passed as the first parameter to the error handling functions to see if they define either `replacement_code_points()` or `replacement_code_units()` function. If so, they will call them and use the returned contiguous range to insert code points or code units into the function. If neither of these exist, then it checks for a definition of a `maybe_replacement_code_points()` or a `maybe_replacement_code_units()` function. If either is present, they are expected to return a `std::optional` of a contiguous range. If it is engaged (the `std::optional` is filled) it will be used. Otherwise, if it is not engaged, then it will explicitly fall back to attempt to insert the default replacement character U+FFFD (U' ') or ? character. If the output is out of room for the desired object, then nothing will be inserted at all.

Subclassed by *default_handler_t*

Public Functions

```
template<typename _Encoding, typename _Input, typename _Output, typename _State, typename  
_InputProgress, typename _OutputProgress>  
inline constexpr auto operator()(const _Encoding &__encoding, encode_result<_Input, _Output, _State>  
  __result, const _InputProgress &__input_progress, const _OutputProgress  
  &__output_progress) const  
  noexcept(::ztd::text::is_nothrow_skip_input_error_v<const _Encoding&,  
  encode_result<_Input, _Output, _State>, const _InputProgress&, const  
  _OutputProgress&>)
```

The function call for inserting replacement code units at the point of failure, before returning flow back to the caller of the encode operation.

Parameters

- **__encoding** – [in] The Encoding that experienced the error.
- **__result** – [in] The current state of the encode operation.
- **__input_progress** – [in] How much input was (potentially irreversibly) read from the input range before undergoing the attempted encode operation.
- **__output_progress** – [in] How much output was (potentially irreversibly) written to the output range before undergoing the attempted encode operation.

```
template<typename _Encoding, typename _Input, typename _Output, typename _State, typename  
_InputProgress, typename _OutputProgress>  
inline constexpr auto operator()(const _Encoding &__encoding, decode_result<_Input, _Output, _State>  
  __result, const _InputProgress &__input_progress, const _OutputProgress  
  &__output_progress) const  
  noexcept(::ztd::text::is_nothrow_skip_input_error_v<const _Encoding&,  
  decode_result<_Input, _Output, _State>, const _InputProgress&, const  
  _OutputProgress&>)
```

The function call for inserting replacement code points at the point of failure, before returning flow back to the caller of the decode operation.

Parameters

- **__encoding** – [in] The Encoding that experienced the error.
- **__result** – [in] The current state of the encode operation.
- **__input_progress** – [in] How much input was (potentially irreversibly) read from the input range before undergoing the attempted encode operation.
- **__output_progress** – [in] How much output was (potentially irreversibly) written to the output range before undergoing the attempted encode operation.

skip_handler

The `skip_handler`, unlike the `ztd::text::replacement_handler_t`, passes over any malformed input and performs no changes to the output. It is considered a subset of the behavior of the replacement error handler.

The skipping is done by calling `ztd::text::skip_input_error(...)` with the encoding and result.

```
constexpr skip_handler_t ztd::text::skip_handler = { }
```

An instance of `skip_handler_t` for ease of use.

```
class skip_handler_t
```

An error handler that simply skips bad input on error, and performs no replacement.

Remark

If a sequence of text depends on the state of the previous text, and there is an illegal sequence in the middle of such a sequence, using their error handler can cause a cascade of failures as the state may not be prepared for the new input; therefore, it may skip more than a user of this error handler might expect. This is something that may happen due to shift state issues (e.g., when an encoding is not self-synchronizing (`ztd::text::is_self_synchronizing_code`)).

Public Functions

```
template<typename _Encoding, typename _Result, typename _InputProgress, typename
_OutputProgress>
inline constexpr auto operator() (const _Encoding &__encoding, _Result &&__result, const _InputProgress
&__input_progress, const _OutputProgress &__output_progress) const
noexcept(::ztd::text::is_input_error_skippable_v<const _Encoding&,
_&__input_progress, const _OutputProgress&, const _OutputProgress&>)
```

Skips over any input that may produce an error.

Parameters

- **__encoding** – [in] The Encoding that experienced the error.
- **__result** – [in] The current state of the encode operation.

- **__input_progress** – [in] How much input was (potentially irreversibly) read from the input range before undergoing the attempted encode operation.
- **__output_progress** – [in] How much output was (potentially irreversibly) written to the output range before undergoing the attempted encode operation.

throw_handler

The `throw_handler` simply throws a `ztd::text::encoding_error` as an exception. This should only EVER be used for pre-verified, trusted input sources, debugging purposes, or similar; malformed text is a common enough occurrence that throwing errors by default or using this handler by default is a **bad idea** in almost every way.

Throwing on encoding, decoding, and other errors can easily result in Denial of Service target points if this is used in conjunction with user or untrusted input sources.

```
constexpr throw_handler_t ztd::text::throw_handler = {}
```

An instance of `throw_handler_t` for ease of use.

class throw_handler_t

An error handler that throws on any encode operation failure.

Remark

This class absolutely should not be used unless the user is prepared to handle spurious failure, especially for text processing that deals with input vectors. This can result in many exceptions being thrown, which for resource-intensive applications could cause issues and result in Denial of Service by way of repeated, unhandled, and unexpected failure.

Public Functions

```
template<typename _Encoding, typename _Input, typename _Output, typename _State, typename _InputProgress, typename _OutputProgress>
```

```
inline constexpr encode_result<_Input, _Output, _State> operator()(const _Encoding&,
                                                                    encode_result<_Input, _Output,
                                                                    _State> __result, const
                                                                    _InputProgress&, const
                                                                    _OutputProgress&) const
                                                                    noexcept(false)
```

Throws a `ztd::text::encoding_error` as an exception on an encode failure.

```
template<typename _Encoding, typename _Input, typename _Output, typename _State, typename _InputProgress, typename _OutputProgress>
```

```
inline constexpr decode_result<_Input, _Output, _State> operator()(const _Encoding&,
                                                                    decode_result<_Input, _Output,
                                                                    _State> __result, const
                                                                    _InputProgress&, const
                                                                    _OutputProgress&) const
                                                                    noexcept(false)
```

Throws a `ztd::text::encoding_error` code as an exception on a decode failure.

1.8.5 Conversion and Counting Functions

count_as_decoded

`ztd::text::count_as_decoded` is a function that takes an input sequence of `code_units` and attempts to count them, according to the error handler that is given. Because the error handler is included as part of the function call (and is provided by default is one is not passed in), the count operation will also continue to count if the error handler sets the `error_code` member of the result to `ztd::text::encoding_error::ok` but still performs some action. This is, for example, the case with `ztd::text::replacement_handler_t` - output replacement code units or code points will be counted as part of the final count and returned with `result.error_code == ztd::text::encoding_error::ok`. You can differentiate error-less text from non-error text by checking `result.errors_were_handled()`, which will be true if the error handler is called regardless of whether or not the error handler “smooths” the problem over by inserting replacement characters, doing nothing, or otherwise.

The overloads of this function increase the level of control you have with each passed argument. At the last overload with four arguments, the function attempts to work call some extension points or falls back to the base function call in this order:

- The `text_count_as_decoded(input, encoding, handler, state)` extension point, if possible.
- An internal, implementation-defined customization point.
- The `basic_count_as_decoded` base function.

The base function call, `basic_count_as_decoded`, simply performs the *core counting loop* using the *Lucky 7* design.

During the `basic_count_as_decoded` loop, if it detects that there is a preferable `text_count_as_decoded_one`, it will call that method as `text_count_as_decoded_one(input, encoding, handler, state)` inside of the loop rather than doing the core design.

Note: This means that if you implement none of the extension points whatsoever, implementing the basic `decode_one` function on your Encoding Object type will guarantee a proper, working implementation.

Note: If you need to call the “basic” form of this function that takes no secret implementation shortcuts or user-defined extension points, then call `basic_count_as_decoded` directly. This can be useful to stop infinity loops when your extension points cannot handle certain inputs and thereby needs to “delegate” to the basic case.

Functions

```
template<typename _Input, typename _Encoding, typename _ErrorHandler, typename _State>
constexpr auto basic_count_as_decoded(_Input &&__input, _Encoding &&__encoding, _ErrorHandler
&&__error_handler, _State &__state)
```

Counts the number of code units that will result from attempting a decode operation.

Remark

This method does not call ADL extension points. It attempts a combination of implementation techniques to count code units, with a loop over the `.decode` call into an intermediate, unseen buffer being the most basic guaranteed implementation attempt.

Parameters

- **__input** – [in] The input range (of code units) to find out how many code points there are.
- **__encoding** – [in] The encoding to count the input with.
- **__error_handler** – [in] The error handler to invoke when an encode operation fails.
- **__state** – [inout] The state that will be used to count code units.

Returns

A *ztd::text::count_result* that includes information about how many code units are present, taking into account any invoked errors (like replacement from *ztd::text::replacement_handler_t*) and a reference to the provided **__state**.

```
template<typename _Input, typename _Encoding, typename _ErrorHandler, typename _State>  
constexpr auto count_as_decoded(_Input &&__input, _Encoding &&__encoding, _ErrorHandler  
                               &&__error_handler, _State &__state)
```

Counts the number of code units that will result from attempting a decode operation.

Remark

This method will first check if an ADL Extension Point `text_count_as_decoded` is callable with the given arguments. If it is, then that method will be used to do the work after forwarding all four arguments to that function call. Otherwise, it defers to *ztd::text::basic_count_as_decoded*.

Parameters

- **__input** – [in] The input range (of code units) to find out how many code points there are.
- **__encoding** – [in] The encoding to count the input with.
- **__error_handler** – [in] The error handler to invoke when an encode operation fails.
- **__state** – [inout] The state that will be used to count code units.

Returns

A *ztd::text::count_result* that includes information about how many code units are present, taking into account any invoked errors (like replacement from *ztd::text::replacement_handler_t*) and a reference to the provided **__state**.

```
template<typename _Input, typename _Encoding, typename _ErrorHandler>  
constexpr auto count_as_decoded(_Input &&__input, _Encoding &&__encoding, _ErrorHandler  
                               &&__error_handler)
```

Counts the number of code units that will result from attempting a decode operation.

Remark

Calls `ztd::text::count_as_decoded(Input, Encoding, ErrorHandler, State)` with an `state` that is created by `ztd::text::make_decode_state(Encoding)`.

Parameters

- **__input** – [in] The input range (of code units) to find out how many code points there are.

- **__encoding** – [in] The encoding to count the input with.
- **__error_handler** – [in] The error handler to invoke when an encode operation fails.

Returns

A *ztd::text::stateless_count_result* that includes information about how many code units are present, taking into account any invoked errors (like replacement from *ztd::text::replacement_handler_t*).

```
template<typename _Input, typename _Encoding>
constexpr auto count_as_decoded(_Input &&__input, _Encoding &&__encoding)
```

Counts the number of code units that will result from attempting a decode operation.

Remark

Calls *ztd::text::count_as_decoded*(Input, Encoding, ErrorHandler) with an *error_handler* that is similar to *ztd::text::default_handler_t*.

Parameters

- **__input** – [in] The input range (of code units) to find out how many code points there are.
- **__encoding** – [in] The encoding to count the input with.

Returns

A *ztd::text::stateless_count_result* that includes information about how many code units are present, taking into account any invoked errors (like replacement from *ztd::text::replacement_handler_t*).

```
template<typename _Input>
constexpr auto count_as_decoded(_Input &&__input)
```

Counts the number of code units that will result from attempting a decode operation.

Remark

Calls *ztd::text::count_as_decoded*(Input, Encoding) with an *encoding* that is derived from *ztd::text::default_code_unit_encoding*.

Parameters

- **__input** – [in] The input range (of code units) to find out how many code points there are.

Returns

A *ztd::text::stateless_count_result* that includes information about how many code units are present, taking into account any invoked errors (like replacement from *ztd::text::replacement_handler_t*).

count_as_encoded

`ztd::text::count_as_encoded` is a function that takes an input sequence of `code_points` and attempts to count them, according to the error handler that is given. Because the error handler is included as part of the function call (and is provided by default is one is not passed in), the count operation will also continue to count if the error handler sets the `error_code` member of the result to `ztd::text::encoding_error::ok` but still performs some action. This is, for example, the case with `ztd::text::replacement_handler` - output replacement code units or code points will be counted as part of the final count and returned with `result.error_code == ztd::text::encoding_error::ok`. You can differentiate error-less text from non-error text by checking `result.errors_were_handled()`, which will be true if the error handler is called regardless of whether or not the error handler “smooths” the problem over by inserting replacement characters, doing nothing, or otherwise.

The overloads of this function increase the level of control you have with each passed argument. At the last overload with four arguments, the function attempts to work call some extension points or falls back to the base function call in this order:

- The `text_count_as_encoded(input, encoding, handler, state)` extension point, if possible.
- An internal, implementation-defined customization point.
- The `basic_count_as_encoded` base function.

The base function call, `basic_count_as_encoded`, simply performs the *core counting loop* using the *Lucky 7* design.

During the `basic_count_as_encoded` loop, if it detects that there is a preferable `text_count_as_encoded_one`, it will call that method as `text_count_as_encoded_one(input, encoding, handler, state)` inside of the loop rather than doing the core design.

Note: This means that if you implement none of the extension points whatsoever, implementing the basic `encode_one` function on your Encoding Object type will guarantee a proper, working implementation.

Note: If you need to call the “basic” form of this function that takes no secret implementation shortcuts or user-defined extension points, then call `basic_count_as_encoded` directly. This can be useful to stop infinity loops when your extension points cannot handle certain inputs and thereby needs to “delegate” to the basic case.

Functions

count_as_transcoded

`ztd::text::count_as_transcoded` is a function that takes an input sequence of `code_units` and attempts to count them, according to the error handler that is given. Because the error handler is included as part of the function call (and is provided by default is one is not passed in), the count operation will also continue to count if the error handler sets the `error_code` member of the result to `ztd::text::encoding_error::ok` but still performs some action. This is, for example, the case with `ztd::text::replacement_handler_t` - output replacement code units or code points will be counted as part of the final count and returned with `result.error_code == ztd::text::encoding_error::ok`. You can differentiate error-less text from non-error text by checking `result.errors_were_handled()`, which will be true if the error handler is called regardless of whether or not the error handler “smooths” the problem over by inserting replacement characters, doing nothing, or otherwise.

The overloads of this function increase the level of control you have with each passed argument. At the last overload with four arguments, the function attempts to work call some extension points or falls back to the base function call in this order:

- The `text_count_as_transcoded(input, from_encoding, to_encoding, from_handler, to_handler, from_state, to_state)` extension point, if possible.
- An internal, implementation-defined customization point.
- The `basic_count_as_transcoded` base function.

The base function call, `basic_count_as_transcoded`, simply performs the *core counting loop* using the *Lucky 7* design.

During the `basic_count_as_transcoded` loop, if it detects that there is a preferable `text_count_as_transcoded_one`, it will call that method as `text_count_as_transcoded_one(input, encoding, handler, state)` inside of the loop rather than doing the core design.

Note: This means that if you implement none of the extension points whatsoever, implementing the basic `decode_one` and `encode_one` functions on your Encoding Object type will guarantee a proper, working implementation.

Note: If you need to call the “basic” form of this function that takes no secret implementation shortcuts or user-defined extension points, then call `basic_count_as_transcoded` directly. This can be useful to stop infinity loops when your extension points cannot handle certain inputs and thereby needs to “delegate” to the basic case.

Functions

```
template<typename _Input, typename _FromEncoding, typename _ToEncoding, typename _FromErrorHandler,
typename _ToErrorHandler, typename _FromState, typename _ToState, typename _Pivot>
constexpr auto basic_count_as_transcoded(_Input &&__input, _FromEncoding &&__from_encoding,
                                         _ToEncoding &&__to_encoding, _FromErrorHandler
                                         &&__from_error_handler, _ToErrorHandler
                                         &&__to_error_handler, _FromState &__from_state, _ToState
                                         &__to_state, _Pivot &&__pivot)
```

Counts the number of code units that will result from attempting an transcode operation on the input code points.

Remark

This method will not check any ADL extension points. A combination of implementation techniques will be used to count code units, with a loop over the `.encode_one` / `.decode_one` call into an intermediate, unseen buffer being the most basic choice.

Parameters

- **__input** – [in] The input range (of code units) to find out how many code units of the transcoded output there are.
- **__from_encoding** – [in] The encoding that is going to be used to decode the input into an intermediary output.
- **__to_encoding** – [in] The encoding that is going to be used to encode the intermediary output.

- **__from_error_handler** – [in] The error handler to invoke when an intermediary decoding operation fails.
- **__to_error_handler** – [in] The error handler to invoke when the final encoding operation fails.
- **__from_state** – [inout] The state attached to the `__from_encoding` that will be used for the intermediary decode step.
- **__to_state** – [inout] The state related to the `__to_encoding` that will be used for the final encoding step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) pivot range, usually a range of contiguous data from a span provided by the implementation but customizable by the end-user. If the intermediate conversion is what failed, then the `ztd::text::pivot`'s `error_code` member will be set to that error. This only happens if the overall operation also fails, and need not be checked unless to obtain additional information for when a top-level operation fails.

Returns

A `ztd::text::count_result` that includes information about how many code units are present, taking into account any invoked errors (like replacement from `ztd::text::replacement_handler_t`) and a reference to the provided `__from_state` and `__to_state`.

```
template<typename _Input, typename _FromEncoding, typename _ToEncoding, typename _FromErrorHandler,
typename _ToErrorHandler, typename _FromState, typename _ToState, typename _Pivot>
constexpr auto count_as_transcoded(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler, _FromState &__from_state,
_ToState &__to_state, _Pivot &&__pivot)
```

Counts the number of code units that will result from attempting an transcode operation on the input code points.

Remark

This method checks for the ADL extension point `text_count_as_transcoded`. It will be called if it is possible. Otherwise, this function will defer to `ztd::text::basic_count_as_transcoded`.

Parameters

- **__input** – [in] The input range (of code units) to find out how many code units of the transcoded output there are.
- **__from_encoding** – [in] The encoding that is going to be used to decode the input into an intermediary output.
- **__to_encoding** – [in] The encoding that is going to be used to encode the intermediary output.
- **__from_error_handler** – [in] The error handler to invoke when an intermediary decoding operation fails.
- **__to_error_handler** – [in] The error handler to invoke when the final encoding operation fails.
- **__from_state** – [inout] The state attached to the `__from_encoding` that will be used for the intermediary decode step.

- **__to_state** – [inout] The state related to the `__to_encoding` that will be used for the final encoding step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) pivot range, usually a range of contiguous data from a span provided by the implementation but customizable by the end-user. If the intermediate conversion is what failed, then the `ztd::text::pivot`'s `error_code` member will be set to that error. This only happens if the overall operation also fails, and need not be checked unless to obtain additional information for when a top-level operation fails.

Returns

A `ztd::text::count_result` that includes information about how many code units are present, taking into account any invoked errors (like replacement from `ztd::text::replacement_handler_t`) and a reference to the provided `__from_state` and `__to_state`.

```
template<typename _Input, typename _FromEncoding, typename _ToEncoding, typename _FromErrorHandler,
typename _ToErrorHandler, typename _FromState, typename _ToState>
constexpr auto count_as_transcoded(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler, _FromState &__from_state,
_ToState &__to_state)
```

Counts the number of code units that will result from attempting an transcode operation on the input code points.

Remark

This method will call `ztd::text::count_as_transcoded(input, from_encoding, to_encoding, from_error_handler, to_error_handler, from_state, to_state)` with an `to_state` created by `ztd::text::make_encode_state(to_encoding)`.

Parameters

- **__input** – [in] The input range (of code units) to find out how many code units of the transcoded output there are.
- **__from_encoding** – [in] The encoding that is going to be used to decode the input into an intermediary output.
- **__to_encoding** – [in] The encoding that is going to be used to encode the intermediary output.
- **__from_error_handler** – [in] The error handler to invoke when an intermediary decoding operation fails.
- **__to_error_handler** – [in] The error handler to invoke when the final encoding operation fails.
- **__from_state** – [inout] The state attached to the `__from_encoding` that will be used for the intermediary decode step.
- **__to_state** – [inout] The state attached to the `__to_encoding` that will be used for the final encode step.

Returns

A `ztd::text::stateless_count_result` that includes information about how many code units are present, taking into account any invoked errors (like replacement from `ztd::text::replacement_handler_t`).

```
template<typename _Input, typename _FromEncoding, typename _ToEncoding, typename _FromErrorHandler,
typename _ToErrorHandler, typename _FromState>
constexpr auto count_as_transcoded(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler, _FromState &__from_state)
```

Counts the number of code units that will result from attempting an transcode operation on the input code points.

Remark

This method will call `ztd::text::count_as_transcoded(input, from_encoding, to_encoding, from_error_handler, to_error_handler, from_state, to_state)` with an `to_state` created by `ztd::text::make_encode_state(to_encoding)`.

Parameters

- **__input** – [in] The input range (of code units) to find out how many code units of the transcoded output there are.
- **__from_encoding** – [in] The encoding that is going to be used to decode the input into an intermediary output.
- **__to_encoding** – [in] The encoding that is going to be used to encode the intermediary output.
- **__from_error_handler** – [in] The error handler to invoke when an intermediary decoding operation fails.
- **__to_error_handler** – [in] The error handler to invoke when the final encoding operation fails.
- **__from_state** – [inout] The state attached to the `__from_encoding` that will be used for the intermediary decode step.

Returns

A `ztd::text::stateless_count_result` that includes information about how many code units are present, taking into account any invoked errors (like replacement from `ztd::text::replacement_handler_t`).

```
template<typename _Input, typename _FromEncoding, typename _ToEncoding, typename _FromErrorHandler,
typename _ToErrorHandler>
constexpr auto count_as_transcoded(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler)
```

Counts the number of code units that will result from attempting an transcode operation on the input code points.

Remark

This method will call `ztd::text::count_as_transcoded(input, from_encoding, to_encoding, from_error_handler, to_error_handler, from_state)` with an `from_state` created by `ztd::text::make_decode_state(from_encoding)`.

Parameters

- **__input** – [in] The input range (of code units) to find out how many code units of the transcoded output there are.
- **__from_encoding** – [in] The encoding that is going to be used to decode the input into an intermediary output.
- **__to_encoding** – [in] The encoding that is going to be used to encode the intermediary output.
- **__from_error_handler** – [in] The error handler to invoke when the decode portion of the transcode operation fails.
- **__to_error_handler** – [in] The error handler to invoke when the encode portion of the transcode operation fails.

Returns

A *ztd::text::stateless_count_result* that includes information about how many code units are present, taking into account any invoked errors (like replacement from *ztd::text::replacement_handler_t*).

```
template<typename _Input, typename _FromEncoding, typename _ToEncoding, typename
_FromErrorHandler>
constexpr auto count_as_transcoded(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler)
```

Counts the number of code units that will result from attempting an transcode operation.

Remark

This method will call *ztd::text::count_as_transcoded*(input, from_encoding, to_encoding, from_error_handler, to_error_handler) by creating an *to_error_handler* similar to *ztd::text::default_handler_t*.

Parameters

- **__input** – [in] The input range (of code units) to find out how many code units of the transcoded output there are.
- **__from_encoding** – [in] The encoding that is going to be used to decode the input into an intermediary output.
- **__to_encoding** – [in] The encoding that is going to be used to encode the intermediary output.
- **__from_error_handler** – [in] The error handler to invoke when the decode portion of the transcode operation fails.

Returns

A *ztd::text::stateless_count_result* that includes information about how many code units are present, taking into account any invoked errors (like replacement from *ztd::text::replacement_handler_t*).

```
template<typename _Input, typename _FromEncoding, typename _ToEncoding>
constexpr auto count_as_transcoded(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding)
```

Counts the number of code units that will result from attempting an transcode operation.

Remark

This method will call `ztd::text::count_as_transcoded(Input, Encoding, ErrorHandler)` by creating an `error_handler` similar to `ztd::text::default_handler_t`.

Parameters

- **__input** – [in] The input range (of code units) to find out how many code units of the transcoded output there are.
- **__from_encoding** – [in] The encoding that is going to be used to decode the input into an intermediary output.
- **__to_encoding** – [in] The encoding that is going to be used to encode the intermediary output.

Returns

A `ztd::text::stateless_count_result` that includes information about how many code units are present, taking into account any invoked errors (like replacement from `ztd::text::replacement_handler_t`).

```
template<typename _Input, typename _ToEncoding>
```

```
constexpr auto count_as_transcoded(_Input &&__input, _ToEncoding &&__to_encoding)
```

Counts the number of code units that will result from attempting an transcode operation on the input code points.

Remark

Calls `ztd::text::count_as_transcoded(Input, Encoding)` with an `encoding` that is derived from `ztd::text::default_code_unit_encoding`.

Parameters

- **__input** – [in] The input range (of code units) to find out how many code units of the transcoded output there are.
- **__to_encoding** – [in] The encoding that is going to be used to encode the input into an intermediary output.

Returns

A `ztd::text::stateless_count_result` that includes information about how many code units are present, taking into account any invoked errors (like replacement from `ztd::text::replacement_handler_t`).

decode

The `decode` grouping of functions (`decode`, `decode_to`, and `decode_into_raw`) perform the task of doing bulk decoding from an input of `code_units` to the encoding's `code_point` type. They are also accompanied by `decode_one` variants (`decode_one`, `decode_one_to`, `decode_one_into`), which serve the same purpose as their bulk counterparts but only do a single *indivisible unit of work*'s worth of work.

Named Groups

There are 3 named functions for this behavior, and each function comes with several function overloads. Each named function produces increasingly more information, letting you opt into just how much information and control you'd like over the algorithm and behavior. The first one simply returns a container with the transformation applied, discarding much of the operation's result information. This is useful for quick, one-off conversions where you do not care about any errors and would rather let it be handled by the error handler. The second `_to` suffixed functions return a container within a `result` type that contains additional information. The final `_into` suffixed functions take an output range to write into, letting you explicitly control just how much space there is to write into as well as returning a detailed `result` type.

The return type for these function calls is one of:

- the desired output container (highest level);
- `ztd::text::decode_result` or `ztd::text::stateless_decode_result` with the desired output container embedded as the `.output` parameter (mid level); or,
- `ztd::text::decode_result` or `ztd::text::stateless_decode_result` returning just the input and output ranges (lowest level).

decode(...)

This is the highest level bulk function.

This set of function overloads takes the provided `input`, `encoding`, `handler` and `state` and produces an output container type. The default container will either be a `std::basic_string` of the `code_point` type, or a `std::vector` if it is not a known "character" type.

The container type can be specified by passing it as an explicit template parameter to this function, such as `ztd::text::decode<std::vector<char32_t>>("bark", ztd::text::ascii{ })`; The output container is default constructed.

It will either call `push_back/insert` directly on the target container to fill it up, or serialize data to a temporary buffer (controlled by `ZTD_TEXT_INTERMEDIATE_TRANSCODE_BUFFER_BYTE_SIZE`) before then copying it into the desired output container through any available means (bulk `.insert`, repeated `.push_back`, or repeated single `.insert` with the `.end()` iterator in that order).

This is the "fire and forget" version of the `decode` function, returning only the container and not returning any of the result or state information used to construct it.

decode_to(...)

This is the mid level bulk function.

This set of function overloads takes the provided `input`, `encoding`, `handler` and `state` and produces an output container type that is embedded within a `ztd::text::decode_result`, or a `ztd::text::stateless_decode_result`, depending on whether or not you called the version which takes a `ztd::text::decode_state_t<Encoding>` as a parameter or if it had to create one on the stack internally and discard it after the operation was finished.

The container type can be specified by passing it as an explicit template parameter to this function, such as `ztd::text::decode_to<std::u32string>("meow", ztd::text::ascii{})`; . The output container is default constructed.

It will either call `push_back/insert` directly on the target container to fill it up, or serialize data to a temporary buffer (controlled by `ZTD_TEXT_INTERMEDIATE_TRANSCODE_BUFFER_BYTE_SIZE`) before then copying it into the desired output container through any available means (bulk `.insert`, repeated `.push_back`, or repeated single `.insert` with the `.end()` iterator in that order).

If nothing goes wrong or the error handler lets the algorithm continue, `.input` on the result should be empty.

decode_into_raw(...)

This is the lowest level bulk function.

This set of function overloads takes the provided `input`, `encoding`, `output`, `handler`, and `state` and writes data into the output range specified by `output`. The result is a `ztd::text::decode_result`, or a `ztd::text::stateless_decode_result`, depending on whether or not you called the version which takes a `ztd::text::decode_state_t<Encoding>` as a parameter or if it had to create one on the stack internally and discard it after the operation was finished.

It is up to the end-user to provide a suitably-sized output range for `output`, otherwise this operation may return with `ztd::text::encoding_error::insufficient_output` for the result's `error_code` member. The amount of space consumed can be determined by checking the `std::distance` between the `.begin()` of the original output parameter and the `.begin()` of the returned `.output` member. The result also has error information and an `.input` member for checking how much input was consumed.

If nothing goes wrong or the error handler lets the algorithm continue, `.input` on the result should be empty.

For Everything

All named functions have 4 overloads. Each of the “higher level” functions, at the end of their overload call chain, will call the lower-level `decode_into_raw` to perform the work. The final `decode_into_raw` call uses the following ordering of extension points into calling the base implementation:

- `text_decode_into_raw(input, encoding, output, handler, state)`
- An internal, implementation-defined customization point.
- `basic_decode_into_raw`

The base function call, `basic_decode_into_raw`, simply performs the *core decode loop* using the *Lucky 7* design. This design also means minimal stack space is used, keeping the core algorithm suitable for resource-constrained devices.

Note: This means that if you implement none of the extension points whatsoever, implementing the basic `decode_one` function on your Encoding Object type will guarantee a proper, working implementation.

Note: If you need to call the “basic” form of this function that takes no secret implementation shortcuts or user-defined extension points, then call `basic_decode_into_raw` directly. This can be useful to stop infinity loops when your extension points cannot handle certain inputs and thereby needs to “delegate” to the basic case.

Bulk Functions

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler, typename
_State>
constexpr auto basic_decode_into_raw(_Input &&__input, _Encoding &&__encoding, _Output &&__output,
                                     _ErrorHandler &&__error_handler, _State &__state)
```

Converts from the code units of the given `__input` view through the encoding to code points into the `__output` view.

Remark

This function performs the bog-standard, basic loop for decoding. It talks to no ADL extension points.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to decode the input’s code points into output code units.
- **__output** – [in] An `output_view` to write code points to as the result of the decode operation from the intermediate code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__state** – [inout] A reference to the associated state for the `__encoding`’s decode step.

Returns

A `ztd::text::decode_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler, typename
_State>
constexpr auto decode_into_raw(_Input &&__input, _Encoding &&__encoding, _Output &&__output,
                                 _ErrorHandler &&__error_handler, _State &__state)
```

Converts from the code units of the given `__input` view through the encoding to code points into the `__output` view.

Remark

This function detects whether or not the ADL extension point `text_decode` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will

loop over the two encodings and attempt to decode by repeatedly calling the encoding's required `decode_one` function.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to decode the input's code points into output code units.
- **__output** – [in] An `output_view` to write code points to as the result of the decode operation from the intermediate code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__state** – [inout] A reference to the associated state for the `__encoding`'s decode step.

Returns

A `ztd::text::decode_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler>
constexpr auto decode_into_raw(_Input &&__input, _Encoding &&__encoding, _Output &&__output,
                               _ErrorHandler &&__error_handler)
```

Converts from the code units of the given `__input` view through the encoding to code points into the `__output` view.

Remark

Creates a default state using `ztd::text::make_decode_state`.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to decode the input's code points into output code units.
- **__output** – [in] An `output_view` to write code points to as the result of the decode operation from the intermediate code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.

Returns

A `ztd::text::stateless_decode_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output>
constexpr auto decode_into_raw(_Input &&__input, _Encoding &&__encoding, _Output &&__output)
```

Converts from the code units of the given `__input` view through the encoding to code points into the `__output` view.

Remark

Creates a default `error_handler` that is similar to `ztd::text::default_handler_t`, but marked as careless.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to decode the input's code points into output code units.
- **__output** – [in] An `output_view` to write code points to as the result of the decode operation from the intermediate code units.

Returns

A `ztd::text::stateless_decode_result` object that contains references to `__state`.

```
template<typename _Input, typename _Output>
constexpr auto decode_into_raw(_Input &&__input, _Output &&__output)
```

Converts from the code units of the given `__input` view through the encoding to code points into the `__output` view.

Remark

Creates a default `encoding` by figuring out the `value_type` of the `__input`, then passing that type into `ztd::text::default_code_point_encoding_t`. That encoding is that used to decode the input code units, by default.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.
- **__output** – [in] An `output_view` to write code points to as the result of the decode operation from the intermediate code units.

Returns

A `ztd::text::stateless_decode_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler, typename
_State>
constexpr auto basic_decode_into(_Input &&__input, _Encoding &&__encoding, _Output &&__output,
    _ErrorHandler &&__error_handler, _State &__state)
```

Converts from the code units of the given `__input` view through the encoding to code points into the `__output` view.

Remark

This function performs the bog-standard, basic loop for decoding. It talks to no ADL extension points.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to decode the input's code points into output code units.
- **__output** – [in] An `output_view` to write code points to as the result of the decode operation from the intermediate code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__state** – [inout] A reference to the associated state for the `__encoding`'s decode step.

Returns

A `ztd::text::decode_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler, typename _State>
```

```
constexpr auto decode_into(_Input &&__input, _Encoding &&__encoding, _Output &&__output, _ErrorHandler &&__error_handler, _State &__state)
```

Converts from the code units of the given `__input` view through the encoding to code points into the `__output` view.

Remark

This function performs the bog-standard, basic loop for decoding. It talks to no ADL extension points.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to decode the input's code points into output code units.
- **__output** – [in] An `output_view` to write code points to as the result of the decode operation from the intermediate code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__state** – [inout] A reference to the associated state for the `__encoding`'s decode step.

Returns

A `ztd::text::decode_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler>
```

```
constexpr auto decode_into(_Input &&__input, _Encoding &&__encoding, _Output &&__output, _ErrorHandler &&__error_handler)
```

Converts from the code units of the given `__input` view through the encoding to code points into the `__output` view.

Remark

Creates a default `state` using `ztd::text::make_decode_state`.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to decode the input's code points into output code units.
- **__output** – [in] An `output_view` to write code points to as the result of the decode operation from the intermediate code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.

Returns

A `ztd::text::stateless_decode_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output>
constexpr auto decode_into(_Input &&__input, _Encoding &&__encoding, _Output &&__output)
    Converts from the code units of the given __input view through the encoding to code points into the __output view.
```

Remark

Creates a default `error_handler` that is similar to `ztd::text::default_handler_t`, but marked as careless.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to decode the input's code points into output code units.
- **__output** – [in] An `output_view` to write code points to as the result of the decode operation from the intermediate code units.

Returns

A `ztd::text::stateless_decode_result` object that contains references to `__state`.

```
template<typename _Input, typename _Output>
constexpr auto decode_into(_Input &&__input, _Output &&__output)
    Converts from the code units of the given __input view through the encoding to code points into the __output view.
```

Remark

Creates a default encoding by figuring out the `value_type` of the `__input`, then passing that type into `ztd::text::default_code_point_encoding_t`. That encoding is that used to decode the input code units, by default.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.

- **__output** – [in] An `output_view` to write code points to as the result of the decode operation from the intermediate code units.

Returns

A `ztd::text::stateless_decode_result` object that contains references to `__state`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding, typename
_ErrorHandler, typename _State>
constexpr auto decode_to(_Input &&__input, _Encoding &&__encoding, _ErrorHandler &&__error_handler,
_State &__state)
```

Converts the code units of the given `__input` view through the encoding to code points the specified `_OutputContainer` type.

Remark

This function detects creates a container of type `_OutputContainer` and uses a typical `std::back_inserter` or `std::push_back_inserter` to fill in elements as it is written to. The result is then returned, with the `.` output value put into the container.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to decode the input's code points into output code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__state** – [inout] A reference to the associated state for the `__encoding`'s decode step.

Returns

A `ztd::text::decode_result` object that contains references to `__state` and an output of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding, typename
_ErrorHandler>
constexpr auto decode_to(_Input &&__input, _Encoding &&__encoding, _ErrorHandler &&__error_handler)
```

Converts the code units of the given `__input` view through the encoding to code points the specified `_OutputContainer` type.

Remark

This function creates a `state` using `ztd::text::make_decode_state`.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to decode the input's code points into output code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.

Returns

A `ztd::text::stateless_decode_result` object whose output is of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding>
constexpr auto decode_to(_Input &&__input, _Encoding &&__encoding)
```

Converts the code units of the given `__input` view through the encoding to code points the specified `_OutputContainer` type.

Remark

This function creates a handler using `ztd::text::default_handler_t`, but marks it as careless.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to decode the input's code points into output code units.

Returns

A `ztd::text::stateless_decode_result` object whose output is of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input>
constexpr auto decode_to(_Input &&__input)
```

Converts the code units of the given `__input` view through the encoding to code points the specified `_OutputContainer` type.

Remark

This function creates an encoding by using the `value_type` of the `__input` which is then passed through the `ztd::text::default_code_point_encoding` type to get the default desired encoding.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

__input – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.

Returns

A `ztd::text::stateless_decode_result` object whose output is of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding, typename
_ErrorHandler, typename _State>
constexpr auto decode(_Input &&__input, _Encoding &&__encoding, _ErrorHandler &&__error_handler, _State
&__state)
```

Converts the code units of the given `__input` view through the encoding to code points the specified `_OutputContainer` type.

Remark

This function detects creates a container of type `_OutputContainer` and uses a typical `std::back_inserter` or `std::push_back_inserter` to fill in elements as it is written to.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to decode the input's code points into output code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__state** – [inout] A reference to the associated state for the `__encoding`'s decode step.

Returns

An object of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding, typename
_ErrorHandler>
constexpr auto decode(_Input &&__input, _Encoding &&__encoding, _ErrorHandler &&__error_handler)
```

Converts the code units of the given `__input` view through the encoding to code points the specified `_OutputContainer` type.

Remark

This function creates a `state` using `ztd::text::make_decode_state`.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to decode the input's code points into output code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.

Returns

An object of type `_OutputContainer` .

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding>
constexpr auto decode(_Input &&__input, _Encoding &&__encoding)
```

Converts the code units of the given `__input` view through the encoding to code points the specified `_OutputContainer` type.

Remark

This function creates a handler using `ztd::text::default_handler_t`, but marks it as careless.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to decode the input's code points into output code units.

Returns

An object of type `_OutputContainer` .

```
template<typename _OutputContainer = void, typename _Input>
constexpr auto decode(_Input &&__input)
```

Converts the code units of the given `__input` view through the encoding to code points the specified `_OutputContainer` type.

Remark

This function creates an encoding by using the `value_type` of the `__input` which is then passed through the `ztd::text::default_code_point_encoding` type to get the default desired encoding.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

__input – [in] An `input_view` to read code units from and use in the decode operation that will produce code points.

Returns

An object of type `_OutputContainer` .

Single Functions

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler, typename _State>
```

```
constexpr auto decode_one_into_raw(_Input &&__input, _Encoding &&__encoding, _Output &&__output,  
                                     _ErrorHandler &&__error_handler, _State &__state)
```

Converts one indivisible unit of information from the code units of the given `__input` view through the encoding to code points into the `__output` view.

Remark

This function is simply a small wrapper for calling `decode_one` on the `__encoding` object.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the `decode_one` operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to `decode_one` the input's code points into output code units.
- **__output** – [in] An `output_view` to write code points to as the result of the `decode_one` operation from the intermediate code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__state** – [inout] A reference to the associated state for the `__encoding`'s `decode_one` step.

Returns

A `ztd::text::decode_one_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler>  
constexpr auto decode_one_into_raw(_Input &&__input, _Encoding &&__encoding, _Output &&__output,  
                                     _ErrorHandler &&__error_handler)
```

Converts one indivisible unit of information from the code units of the given `__input` view through the encoding to code points into the `__output` view.

Remark

Creates a default `state` using `ztd::text::make_decode_state`.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the `decode_one` operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to `decode_one` the input's code points into output code units.
- **__output** – [in] An `output_view` to write code points to as the result of the `decode_one` operation from the intermediate code units.

- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.

Returns

A `ztd::text::stateless_decode_one_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output>
constexpr auto decode_one_into_raw(_Input &&__input, _Encoding &&__encoding, _Output &&__output)
```

Converts one indivisible unit of information from the code units of the given `__input` view through the encoding to code points into the `__output` view.

Remark

Creates a default `error_handler` that is similar to `ztd::text::default_handler_t`, but marked as `careless`.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the `decode_one` operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to `decode_one` the input's code points into output code units.
- **__output** – [in] An `output_view` to write code points to as the result of the `decode_one` operation from the intermediate code units.

Returns

A `ztd::text::stateless_decode_one_result` object that contains references to `__state`.

```
template<typename _Input, typename _Output>
constexpr auto decode_one_into_raw(_Input &&__input, _Output &&__output)
```

Converts one indivisible unit of information from the code units of the given `__input` view through the encoding to code points into the `__output` view.

Remark

Creates a default encoding by figuring out the `value_type` of the `__input`, then passing that type into `ztd::text::default_code_point_encoding_t`. That encoding is that used to `decode_one` the input code units, by default.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the `decode_one` operation that will produce code points.
- **__output** – [in] An `output_view` to write code points to as the result of the `decode_one` operation from the intermediate code units.

Returns

A `ztd::text::stateless_decode_one_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler, typename _State>
```

```
constexpr auto decode_one_into( _Input &&__input, _Encoding &&__encoding, _Output &&__output,  
                                _ErrorHandler &&__error_handler, _State &__state)
```

Converts one indivisible unit of information from the code units of the given `__input` view through the encoding to code points into the `__output` view.

Remark

This function is simply a small wrapper for calling `decode_one` on the `__encoding` object.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the `decode_one` operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to `decode_one` the input's code points into output code units.
- **__output** – [in] An `output_view` to write code points to as the result of the `decode_one` operation from the intermediate code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__state** – [inout] A reference to the associated state for the `__encoding`'s `decode_one` step.

Returns

A `ztd::text::decode_one_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler>  
constexpr auto decode_one_into( _Input &&__input, _Encoding &&__encoding, _Output &&__output,  
                                _ErrorHandler &&__error_handler)
```

Converts one indivisible unit of information from the code units of the given `__input` view through the encoding to code points into the `__output` view.

Remark

Creates a default `state` using `ztd::text::make_decode_state`.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the `decode_one` operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to `decode_one` the input's code points into output code units.
- **__output** – [in] An `output_view` to write code points to as the result of the `decode_one` operation from the intermediate code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.

Returns

A `ztd::text::stateless_decode_one_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output>
constexpr auto decode_one_into(_Input &&__input, _Encoding &&__encoding, _Output &&__output)
```

Converts one indivisible unit of information from the code units of the given `__input` view through the encoding to code points into the `__output` view.

Remark

Creates a default `error_handler` that is similar to `ztd::text::default_handler_t`, but marked as `careless`.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the `decode_one` operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to `decode_one` the input's code points into output code units.
- **__output** – [in] An `output_view` to write code points to as the result of the `decode_one` operation from the intermediate code units.

Returns

A `ztd::text::stateless_decode_one_result` object that contains references to `__state`.

```
template<typename _Input, typename _Output>
constexpr auto decode_one_into(_Input &&__input, _Output &&__output)
```

Converts one indivisible unit of information from the code units of the given `__input` view through the encoding to code points into the `__output` view.

Remark

Creates a default `encoding` by figuring out the `value_type` of the `__input`, then passing that type into `ztd::text::default_code_point_encoding_t`. That encoding is that used to `decode_one` the input code units, by default.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the `decode_one` operation that will produce code points.
- **__output** – [in] An `output_view` to write code points to as the result of the `decode_one` operation from the intermediate code units.

Returns

A `ztd::text::stateless_decode_one_result` object that contains references to `__state`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding, typename _ErrorHandler, typename _State>
constexpr auto decode_one_to(_Input &&__input, _Encoding &&__encoding, _ErrorHandler &&__error_handler, _State &__state)
```

Converts one indivisible unit of information from the code units of the given `__input` view through the encoding to code points, stored in an object of `_OutputContainer` type.

Remark

This function detects creates a container of type `_OutputContainer` and uses a typical `std::back_inserter` or `std::push_back_inserter` to fill in elements as it is written to. The result is then returned, with the . output value put into the container.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the `decode_one` operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to `decode_one` the input’s code points into output code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__state** – [inout] A reference to the associated state for the `__encoding` ‘s `decode_one` step.

Returns

A `ztd::text::decode_one_result` object that contains references to `__state` and an output of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding, typename
_ErrorHandler>
constexpr auto decode_one_to(_Input &&__input, _Encoding &&__encoding, _ErrorHandler
&&__error_handler)
```

Converts one indivisible unit of information from the code units of the given `__input` view through the encoding to code points, stored in an object of `_OutputContainer` type.

Remark

This function creates a `state` using `ztd::text::make_decode_state`.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the `decode_one` operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to `decode_one` the input’s code points into output code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.

Returns

A `ztd::text::stateless_decode_one_result` object whose output is of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding>
constexpr auto decode_one_to(_Input &&__input, _Encoding &&__encoding)
```

Converts one indivisible unit of information from the code units of the given `__input` view through the encoding to code points, stored in an object of `_OutputContainer` type.

Remark

This function creates a handler using `ztd::text::default_handler_t`, but marks it as careless.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the `decode_one` operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to `decode_one` the input's code points into output code units.

Returns

A `ztd::text::stateless_decode_one_result` object whose output is of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input>
constexpr auto decode_one_to(_Input &&__input)
```

Converts one indivisible unit of information from the code units of the given `__input` view through the encoding to code points, stored in an object of `_OutputContainer` type.

Remark

This function creates an encoding by using the `value_type` of the `__input` which is then passed through the `ztd::text::default_code_point_encoding` type to get the default desired encoding.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

__input – [in] An `input_view` to read code units from and use in the `decode_one` operation that will produce code points.

Returns

A `ztd::text::stateless_decode_one_result` object whose output is of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding, typename
_ErrorHandler, typename _State>
constexpr auto decode_one(_Input &&__input, _Encoding &&__encoding, _ErrorHandler &&__error_handler,
_State &__state)
```

Converts one indivisible unit of information from the code units of the given `__input` view through the encoding to code points, stored in an object of `_OutputContainer` type.

Remark

This function detects creates a container of type `_OutputContainer` and uses a typical `std::back_inserter` or `std::push_back_inserter` to fill in elements as it is written to.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the `decode_one` operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to `decode_one` the input's code points into output code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__state** – [inout] A reference to the associated state for the `__encoding`'s `decode_one` step.

Returns

An object of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding, typename
_ErrorHandler>
constexpr auto decode_one(_Input &&__input, _Encoding &&__encoding, _ErrorHandler &&__error_handler)
    Converts one indivisible unit of information from the code units of the given __input view through the encoding
    to code points, stored in an object of _OutputContainer type.
```

Remark

This function creates a `state` using `ztd::text::make_decode_state`.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the `decode_one` operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to `decode_one` the input's code points into output code units.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.

Returns

An object of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding>
constexpr auto decode_one(_Input &&__input, _Encoding &&__encoding)
    Converts one indivisible unit of information from the code units of the given __input view through the encoding
    to code points, stored in an object of _OutputContainer type.
```

Remark

This function creates a handler using `ztd::text::default_handler_t`, but marks it as careless.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the `decode_one` operation that will produce code points.
- **__encoding** – [in] The encoding that will be used to `decode_one` the input's code points into output code units.

Returns

An object of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input>
constexpr auto decode_one(_Input &&__input)
```

Converts one indivisible unit of information from the code units of the given `__input` view through the encoding to code points, stored in an object of `_OutputContainer` type.

Remark

This function creates an encoding by using the `value_type` of the `__input` which is then passed through the `ztd::text::default_code_point_encoding` type to get the default desired encoding.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

__input – [in] An `input_view` to read code units from and use in the `decode_one` operation that will produce code points.

Returns

An object of type `_OutputContainer`.

encode

The `encode` grouping of functions (`encode`, `encode_to`, and `encode_into_raw`) perform the task of doing bulk decoding from an input of `code_points` to the encoding's `code_unit` type. They are also accompanied by `encode_one` variants (`encode_one`, `encode_one_to`, `encode_one_into`), which serve the same purpose as their bulk counterparts but only do a single *indivisible unit of work*'s worth of work.

Named Groups

There are 3 named functions for this behavior, and each function comes with several function overloads. Each named function produces increasingly more information, letting you opt into just how much information and control you'd like over the algorithm and behavior. The first one simply returns a container with the transformation applied, discarding much of the operation's result information. This is useful for quick, one-off conversions where you do not care about any errors and would rather let it be handled by the error handler. The second `_to` suffixed functions return a container within a `result` type that contains additional information. The final `_into` suffixed functions take an output range to write into, letting you explicitly control just how much space there is to write into as well as returning a detailed `result` type.

The return type for these function calls is one of:

- the desired output container (highest level);
- `ztd::text::encode_result` or `ztd::text::stateless_encode_result` with the desired output container embedded as the `.output` parameter (mid level); or,
- `ztd::text::encode_result` or `ztd::text::stateless_encode_result` returning just the input and output ranges (lowest level).

`encode(...)`

This is the highest level bulk function.

This set of function overloads takes the provided `input`, `encoding`, `handler` and `state` and produces an output container type. The default container will either be a `std::basic_string` of the `code_unit` type, or a `std::vector` if it is not a known “character” type.

The container type can be specified by passing it as an explicit template parameter to this function, such as `ztd::text::encode<std::vector<std::byte>>(U"bark", ztd::text::utf16_be{})`; . The output container is default constructed.

It will either call `push_back/insert` directly on the target container to fill it up, or serialize data to a temporary buffer (controlled by `ZTD_TEXT_INTERMEDIATE_TRANSCODE_BUFFER_BYTE_SIZE`) before then copying it into the desired output container through any available means (bulk `.insert`, repeated `.push_back`, or repeated single `.insert` with the `.end()` iterator in that order).

This is the “fire and forget” version of the `encode` function, returning only the container and not returning any of the result or state information used to construct it.

`encode_to(...)`

This is the mid level bulk function.

This set of function overloads takes the provided `input`, `encoding`, `handler` and `state` and produces an output container type that is embedded within a `ztd::text::encode_result`, or a `ztd::text::stateless_encode_result`, depending on whether or not you called the version which takes a `ztd::text::encode_state_t<Encoding>` as a parameter or if it had to create one on the stack internally and discard it after the operation was finished.

The container type can be specified by passing it as an explicit template parameter to this function, such as `ztd::text::encode_to<std::string>(U"meow", ascii{})`; . The output container is default constructed.

It will either call `push_back/insert` directly on the target container to fill it up, or serialize data to a temporary buffer (controlled by `ZTD_TEXT_INTERMEDIATE_TRANSCODE_BUFFER_BYTE_SIZE`) before then copying it into the desired output container through any available means (bulk `.insert`, repeated `.push_back`, or repeated single `.insert` with the `.end()` iterator in that order).

If nothing goes wrong or the error handler lets the algorithm continue, `.input` on the result should be empty.

`encode_into_raw(...)`

This is the lowest level bulk function.

This set of function overloads takes the provided `input`, `encoding`, `output`, `handler`, and `state` and writes data into the output range specified by `output`. The result is a `ztd::text::encode_result`, or a `ztd::text::stateless_encode_result`, depending on whether or not you called the version which takes a `ztd::text::encode_state_t<Encoding>` as a parameter or if it had to create one on the stack internally and discard it after the operation was finished.

It is up to the end-user to provide a suitably-sized output range for `output`, otherwise this operation may return with `ztd::text::encoding_error::insufficient_output` for the result's `error_code` member. The amount of space consumed can be determined by checking the `std::distance` between the `.begin()` of the original output parameter and the `.begin()` of the returned `.output` member. The result also has error information and an `.input` member for checking how much input was consumed.

If nothing goes wrong or the error handler lets the algorithm continue, `.input` on the result should be empty.

For Everything

All named functions have 4 overloads. Each of the “higher level” functions, at the end of their overload call chain, will call the lower-level `encode_into_raw` to perform the work. The final `encode_into_raw` call uses the following ordering of extension points into calling the base implementation:

- `text_encode_into_raw(input, encoding, output, handler, state)`
- An internal, implementation-defined customization point.
- `basic_encode_into_raw(input, encoding, output, handler, state)`

The final function call, `basic_encode_into_raw`, simply performs the *core encode loop* using the *Lucky 7* design. This design also means minimal stack space is used, keeping the core algorithm suitable for resource-constrained devices.

Note: This means that if you implement none of the extension points whatsoever, implementing the basic `encode_one` function on your Encoding Object type will guarantee a proper, working implementation.

Note: If you need to call the “basic” form of this function that takes no secret implementation shortcuts or user-defined extension points, then call `basic_encode_into_raw` directly. This can be useful to stop infinity loops when your extension points cannot handle certain inputs and thereby needs to “delegate” to the basic case.

Bulk Functions

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler, typename
_State>
constexpr auto basic_encode_into_raw(_Input &&__input, _Encoding &&__encoding, _Output &&__output,
_ErrorHandler &&__error_handler, _State &__state)
```

Converts the code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

This function does not attempt to call any extension points for encoding. It simply uses the encoding and attempts to encode by repeatedly calling the encoding's required `encode_one` function.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to encode the input's code points into output code units.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__state** – [inout] A reference to the associated state for the `__encoding`'s encode step.

Returns

A `ztd::text::encode_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler, typename
_State>
constexpr auto encode_into_raw(_Input &&__input, _Encoding &&__encoding, _Output &&__output,
_ErrorHandler &&__error_handler, _State &__state)
```

Converts the code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

This function detects whether or not the ADL extension point `text_encode` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to encode by repeatedly calling the encoding's required `encode_one` function.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to encode the input's code points into output code units.

- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__state** – [inout] A reference to the associated state for the `__encoding` 's encode step.

Returns

A `ztd::text::encode_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler>
constexpr auto encode_into_raw( _Input &&__input, _Encoding &&__encoding, _Output &&__output,
                                _ErrorHandler &&__error_handler)
```

Converts the code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

Creates a default state using `ztd::text::make_encode_state`.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to encode the input's code points into output code units.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.

Returns

A `ztd::text::stateless_encode_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output>
constexpr auto encode_into_raw( _Input &&__input, _Encoding &&__encoding, _Output &&__output)
```

Converts the code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

Creates a default `error_handler` that is similar to `ztd::text::default_handler_t`, but marked as careless.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to encode the input's code points into output code units.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.

Returns

A `ztd::text::stateless_encode_result` object that contains references to `__state`.

```
template<typename _Input, typename _Output>  
constexpr auto encode_into_raw(_Input &&__input, _Output &&__output)
```

Converts the code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

Creates a default `encoding` by figuring out the `value_type` of the `__input`, then passing that type into `ztd::text::default_code_point_encoding_t`. That encoding is that used to encode the input code points, by default.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.

Returns

A `ztd::text::stateless_encode_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler, typename  
_State>  
constexpr auto basic_encode_into(_Input &&__input, _Encoding &&__encoding, _Output &&__output,  
_ErrorHandler &&__error_handler, _State &__state)
```

Converts the code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

This function detects whether or not the ADL extension point `text_encode` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to encode by repeatedly calling the encoding's required `encode_one` function.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to encode the input's code points into output code units.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__state** – [inout] A reference to the associated state for the `__encoding`'s encode step.

Returns

A *ztd::text::encode_result* object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler, typename
_State>
constexpr auto encode_into(_Input &&__input, _Encoding &&__encoding, _Output &&__output, _ErrorHandler
&&__error_handler, _State &__state)
```

Converts the code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

This function detects whether or not the ADL extension point `text_encode` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to encode by repeatedly calling the encoding's required `encode_one` function.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to encode the input's code points into output code units.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__state** – [inout] A reference to the associated state for the `__encoding`'s encode step.

Returns

A *ztd::text::encode_result* object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler>
constexpr auto encode_into(_Input &&__input, _Encoding &&__encoding, _Output &&__output, _ErrorHandler
&&__error_handler)
```

Converts the code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

Creates a default `state` using *ztd::text::make_encode_state*.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to encode the input's code points into output code units.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.

- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.

Returns

A *ztd::text::stateless_encode_result* object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output>  
constexpr auto encode_into(_Input &&__input, _Encoding &&__encoding, _Output &&__output)
```

Converts the code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

Creates a default `error_handler` that is similar to *ztd::text::default_handler_t*, but marked as careless.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to encode the input's code points into output code units.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.

Returns

A *ztd::text::stateless_encode_result* object that contains references to `__state`.

```
template<typename _Input, typename _Output>  
constexpr auto encode_into(_Input &&__input, _Output &&__output)
```

Converts the code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

Creates a default `encoding` by figuring out the `value_type` of the `__input`, then passing that type into *ztd::text::default_code_point_encoding_t*. That encoding is that used to encode the input code points, by default.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.

Returns

A *ztd::text::stateless_encode_result* object that contains references to `__state`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding, typename  
_ErrorHandler, typename _State>
```

```
constexpr auto encode_to(_Input &&__input, _Encoding &&__encoding, _ErrorHandler &&__error_handler,
    _State &__state)
```

Converts the code points of the given `__input` view through the encoding to code units in the specified `_OutputContainer` type.

Remark

This function detects creates a container of type `_OutputContainer` and uses a typical `std::back_inserter` or `std::push_back_inserter` to fill in elements as it is written to. The result is then returned, with the `.` output value put into the container.

Template Parameters

`_OutputContainer` – The container type to serialize data into.

Parameters

- **`__input`** – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.
- **`__encoding`** – [in] The encoding that will be used to encode the input's code points into output code units.
- **`__error_handler`** – [in] The error handlers for the from and to encodings, respectively.
- **`__state`** – [inout] A reference to the associated state for the `__encoding`'s encode step.

Returns

A `ztd::text::encode_result` object that contains references to `__state` and an output of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding, typename
_ErrorHandler>
```

```
constexpr auto encode_to(_Input &&__input, _Encoding &&__encoding, _ErrorHandler &&__error_handler)
```

Converts the code points of the given `__input` view through the encoding to code units in the specified `_OutputContainer` type.

Remark

This function creates a `state` using `ztd::text::make_encode_state`.

Template Parameters

`_OutputContainer` – The container type to serialize data into.

Parameters

- **`__input`** – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.
- **`__encoding`** – [in] The encoding that will be used to encode the input's code points into output code units.
- **`__error_handler`** – [in] The error handlers for the from and to encodings, respectively.

Returns

A *ztd::text::stateless_encode_result* object whose output is of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding>  
constexpr auto encode_to(_Input &&__input, _Encoding &&__encoding)
```

Converts the code points of the given `__input` view through the encoding to code units in the specified `_OutputContainer` type.

Remark

This function creates a handler using *ztd::text::default_handler_t*, but marks it as careless.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to encode the input's code points into output code units.

Returns

A *ztd::text::stateless_encode_result* object whose output is of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input>  
constexpr auto encode_to(_Input &&__input)
```

Converts the code points of the given `__input` view through the encoding to code units in the specified `_OutputContainer` type.

Remark

This function creates an encoding by using the `value_type` of the `__input` which is then passed through the *ztd::text::default_code_point_encoding* type to get the default desired encoding.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

__input – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.

Returns

A *ztd::text::stateless_encode_result* object whose output is of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding, typename  
_ErrorHandler, typename _State>  
constexpr auto encode(_Input &&__input, _Encoding &&__encoding, _ErrorHandler &&__error_handler, _State  
&__state)
```

Converts the code points of the given `__input` view through the encoding to code units in the specified `_OutputContainer` type.

Remark

This function detects creates a container of type `_OutputContainer` and uses a typical `std::back_inserter` or `std::push_back_inserter` to fill in elements as it is written to.

Template Parameters

`_OutputContainer` – The container type to serialize data into.

Parameters

- `__input` – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.
- `__encoding` – [in] The encoding that will be used to encode the input's code points into output code units.
- `__error_handler` – [in] The error handlers for the from and to encodings, respectively.
- `__state` – [inout] A reference to the associated state for the `__encoding`'s encode step.

Returns

An object of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding, typename
_ErrorHandler>
constexpr auto encode(_Input &&__input, _Encoding &&__encoding, ErrorHandler &&__error_handler)
    Converts the code points of the given __input view through the encoding to code units in the specified
    _OutputContainer type.
```

Remark

This function creates a `state` using `ztd::text::make_encode_state`.

Template Parameters

`_OutputContainer` – The container type to serialize data into.

Parameters

- `__input` – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.
- `__encoding` – [in] The encoding that will be used to encode the input's code points into output code units.
- `__error_handler` – [in] The error handlers for the from and to encodings, respectively.

Returns

An object of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding>
```

```
constexpr auto encode(_Input &&__input, _Encoding &&__encoding)
```

Converts the code points of the given `__input` view through the encoding to code units in the specified `_OutputContainer` type.

Remark

This function creates a handler using `ztd::text::default_handler_t`, but marks it as careless.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to encode the input's code points into output code units.

Returns

An object of type `_OutputContainer` .

```
template<typename _OutputContainer = void, typename _Input>
```

```
constexpr auto encode(_Input &&__input)
```

Converts the code points of the given `__input` view through the encoding to code units in the specified `_OutputContainer` type.

Remark

This function creates an encoding by using the `value_type` of the `__input` which is then passed through the `ztd::text::default_code_point_encoding` type to get the default desired encoding.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

__input – [in] An `input_view` to read code points from and use in the encode operation that will produce code units.

Returns

An object of type `_OutputContainer` .

Single Functions

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler, typename _State>
```

```
constexpr auto encode_one_into_raw(_Input &&__input, _Encoding &&__encoding, _Output &&__output,
                                     _ErrorHandler &&__error_handler, _State &__state)
```

Converts a single indivisible unit of work’s worth of code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

This function takes care of performing some “normalizations” of the output and input range types (like turning them into a span or string_view if at all recognizable or preferable).

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the `encode_one` operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to `encode_one` the input’s code points into output code units.
- **__output** – [in] An `output_view` to write code units to as the result of the `encode_one` operation from the intermediate code points.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__state** – [inout] A reference to the associated state for the `__encoding` ‘s `encode_one` step.

Returns

A `ztd::text::encode_one_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler>
constexpr auto encode_one_into_raw(_Input &&__input, _Encoding &&__encoding, _Output &&__output,
                                     _ErrorHandler &&__error_handler)
```

Converts a single indivisible unit of work’s worth of code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

Creates a default `state` using `ztd::text::make_encode_state`.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the `encode_one` operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to `encode_one` the input’s code points into output code units.

- **__output** – [in] An `output_view` to write code units to as the result of the `encode_one` operation from the intermediate code points.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.

Returns

A `ztd::text::stateless_encode_one_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output>  
constexpr auto encode_one_into_raw(_Input &&__input, _Encoding &&__encoding, _Output &&__output)
```

Converts a single indivisible unit of work's worth of code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

Creates a default `error_handler` that is similar to `ztd::text::default_handler_t`, but marked as `careless`.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the `encode_one` operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to `encode_one` the input's code points into output code units.
- **__output** – [in] An `output_view` to write code units to as the result of the `encode_one` operation from the intermediate code points.

Returns

A `ztd::text::stateless_encode_one_result` object that contains references to `__state`.

```
template<typename _Input, typename _Output>  
constexpr auto encode_one_into_raw(_Input &&__input, _Output &&__output)
```

Converts a single indivisible unit of work's worth of code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

Creates a default `encoding` by figuring out the `value_type` of the `__input`, then passing that type into `ztd::text::default_code_point_encoding_t`. That encoding is that used to `encode_one` the input code points, by default.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the `encode_one` operation that will produce code units.
- **__output** – [in] An `output_view` to write code units to as the result of the `encode_one` operation from the intermediate code points.

Returns

A `ztd::text::stateless_encode_one_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler, typename
_State>
constexpr auto encode_one_into(_Input &&__input, _Encoding &&__encoding, _Output &&__output,
                               _ErrorHandler &&__error_handler, _State &__state)
```

Converts a single indivisible unit of work’s worth of code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

This function takes care of performing some “normalizations” of the output and input range types (like turning them into a span or `string_view` if at all recognizable or preferable).

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the `encode_one` operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to `encode_one` the input’s code points into output code units.
- **__output** – [in] An `output_view` to write code units to as the result of the `encode_one` operation from the intermediate code points.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__state** – [inout] A reference to the associated state for the `__encoding`’s `encode_one` step.

Returns

A `ztd::text::encode_one_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output, typename _ErrorHandler>
constexpr auto encode_one_into(_Input &&__input, _Encoding &&__encoding, _Output &&__output,
                               _ErrorHandler &&__error_handler)
```

Converts a single indivisible unit of work’s worth of code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

Creates a default `state` using `ztd::text::make_encode_state`.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the `encode_one` operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to `encode_one` the input’s code points into output code units.
- **__output** – [in] An `output_view` to write code units to as the result of the `encode_one` operation from the intermediate code points.
- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.

Returns

A `ztd::text::stateless_encode_one_result` object that contains references to `__state`.

```
template<typename _Input, typename _Encoding, typename _Output>  
constexpr auto encode_one_into(_Input &&__input, _Encoding &&__encoding, _Output &&__output)
```

Converts a single indivisible unit of work's worth of code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

Creates a default `error_handler` that is similar to `ztd::text::default_handler_t`, but marked as `careless`.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the `encode_one` operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to `encode_one` the input's code points into output code units.
- **__output** – [in] An `output_view` to write code units to as the result of the `encode_one` operation from the intermediate code points.

Returns

A `ztd::text::stateless_encode_one_result` object that contains references to `__state`.

```
template<typename _Input, typename _Output>  
constexpr auto encode_one_into(_Input &&__input, _Output &&__output)
```

Converts a single indivisible unit of work's worth of code points of the given `__input` view through the encoding to code units into the `__output` view.

Remark

Creates a default encoding by figuring out the `value_type` of the `__input`, then passing that type into `ztd::text::default_code_point_encoding_t`. That encoding is that used to `encode_one` the input code points, by default.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the `encode_one` operation that will produce code units.
- **__output** – [in] An `output_view` to write code units to as the result of the `encode_one` operation from the intermediate code points.

Returns

A `ztd::text::stateless_encode_one_result` object that contains references to `__state`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding, typename  
_ErrorHandler, typename _State>
```

```
constexpr auto encode_one_to(_Input &&__input, _Encoding &&__encoding, _ErrorHandler
    &&__error_handler, _State &__state)
```

Converts a single indivisible unit of work's worth of code points of the given `__input` view through the encoding to code units in the specified `_OutputContainer` type.

Remark

This function detects creates a container of type `_OutputContainer` and uses a typical `std::back_inserter` or `std::push_back_inserter` to fill in elements as it is written to. The result is then returned, with the . output value put into the container.

Template Parameters

`_OutputContainer` – The container type to serialize data into.

Parameters

- **`__input`** – [in] An `input_view` to read code points from and use in the `encode_one` operation that will produce code units.
- **`__encoding`** – [in] The encoding that will be used to `encode_one` the input's code points into output code units.
- **`__error_handler`** – [in] The error handlers for the from and to encodings, respectively.
- **`__state`** – [inout] A reference to the associated state for the `__encoding`'s `encode_one` step.

Returns

A `ztd::text::encode_one_result` object that contains references to `__state` and an output of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding, typename
_ErrorHandler>
constexpr auto encode_one_to(_Input &&__input, _Encoding &&__encoding, _ErrorHandler
    &&__error_handler)
```

Converts a single indivisible unit of work's worth of code points of the given `__input` view through the encoding to code units in the specified `_OutputContainer` type.

Remark

This function creates a `state` using `ztd::text::make_encode_state`.

Template Parameters

`_OutputContainer` – The container type to serialize data into.

Parameters

- **`__input`** – [in] An `input_view` to read code points from and use in the `encode_one` operation that will produce code units.
- **`__encoding`** – [in] The encoding that will be used to `encode_one` the input's code points into output code units.

- **__error_handler** – [in] The error handlers for the from and to encodings, respectively.

Returns

A `ztd::text::stateless_encode_one_result` object whose output is of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding>  
constexpr auto encode_one_to(_Input &&__input, _Encoding &&__encoding)
```

Converts a single indivisible unit of work's worth of code points of the given `__input` view through the encoding to code units in the specified `_OutputContainer` type.

Remark

This function creates a `handler` using `ztd::text::default_handler_t`, but marks it as `careless`.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the `encode_one` operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to `encode_one` the input's code points into output code units.

Returns

A `ztd::text::stateless_encode_one_result` object whose output is of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input>  
constexpr auto encode_one_to(_Input &&__input)
```

Converts a single indivisible unit of work's worth of code points of the given `__input` view through the encoding to code units in the specified `_OutputContainer` type.

Remark

This function creates an `encoding` by using the `value_type` of the `__input` which is then passed through the `ztd::text::default_code_point_encoding` type to get the default desired encoding.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

__input – [in] An `input_view` to read code points from and use in the `encode_one` operation that will produce code units.

Returns

A `ztd::text::stateless_encode_one_result` object whose output is of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding, typename  
_ErrorHandler, typename _State>
```

```
constexpr auto encode_one(_Input &&__input, _Encoding &&__encoding, _ErrorHandler &&__error_handler,
                           _State &__state)
```

Converts a single indivisible unit of work's worth of code points of the given `__input` view through the encoding to code units in the specified `_OutputContainer` type.

Remark

This function detects creates a container of type `_OutputContainer` and uses a typical `std::back_inserter` or `std::push_back_inserter` to fill in elements as it is written to.

Template Parameters

`_OutputContainer` – The container type to serialize data into.

Parameters

- **`__input`** – [in] An `input_view` to read code points from and use in the `encode_one` operation that will produce code units.
- **`__encoding`** – [in] The encoding that will be used to `encode_one` the input's code points into output code units.
- **`__error_handler`** – [in] The error handlers for the from and to encodings, respectively.
- **`__state`** – [inout] A reference to the associated state for the `__encoding`'s `encode_one` step.

Returns

An object of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding, typename
_ErrorHandler>
```

```
constexpr auto encode_one(_Input &&__input, _Encoding &&__encoding, _ErrorHandler &&__error_handler)
```

Converts a single indivisible unit of work's worth of code points of the given `__input` view through the encoding to code units in the specified `_OutputContainer` type.

Remark

This function creates a `state` using `ztd::text::make_encode_state`.

Template Parameters

`_OutputContainer` – The container type to serialize data into.

Parameters

- **`__input`** – [in] An `input_view` to read code points from and use in the `encode_one` operation that will produce code units.
- **`__encoding`** – [in] The encoding that will be used to `encode_one` the input's code points into output code units.
- **`__error_handler`** – [in] The error handlers for the from and to encodings, respectively.

Returns

An object of type `_OutputContainer`.

```
template<typename _OutputContainer = void, typename _Input, typename _Encoding>
constexpr auto encode_one(_Input &&__input, _Encoding &&__encoding)
```

Converts a single indivisible unit of work's worth of code points of the given `__input` view through the encoding to code units in the specified `_OutputContainer` type.

Remark

This function creates a handler using `ztd::text::default_handler_t`, but marks it as careless.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

- **__input** – [in] An `input_view` to read code points from and use in the `encode_one` operation that will produce code units.
- **__encoding** – [in] The encoding that will be used to `encode_one` the input's code points into output code units.

Returns

An object of type `_OutputContainer` .

```
template<typename _OutputContainer = void, typename _Input>
constexpr auto encode_one(_Input &&__input)
```

Converts a single indivisible unit of work's worth of code points of the given `__input` view through the encoding to code units in the specified `_OutputContainer` type.

Remark

This function creates an encoding by using the `value_type` of the `__input` which is then passed through the `ztd::text::default_code_point_encoding` type to get the default desired encoding.

Template Parameters

_OutputContainer – The container type to serialize data into.

Parameters

__input – [in] An `input_view` to read code points from and use in the `encode_one` operation that will produce code units.

Returns

An object of type `_OutputContainer` .

recode

The `recode` grouping of functions (`recode`, `recode_to`, and `recode_into_raw`) perform the task of doing bulk transcoding from an `input` of `code_units` to a second encoding's `code_unit` type. It expects to traffic through the `code_point` type as the intermediary between the two functions. There is also a `recode_one` API as well that does a single indivisible unit of work for both decoding (to a common representation) and then encoding, and has the same variants as the bulk function.

Named Groups

There are 3 named functions for this behavior, and each function comes with several function overloads. Each named function produces increasingly more information, letting you opt into just how much information and control you'd like over the algorithm and behavior. The first one simply returns a container with the transformation applied, discarding much of the operation's result information. This is useful for quick, one-off conversions where you do not care about any errors and would rather let it be handled by the error handler. The second `_to` suffixed functions return a container within a `result` type that contains additional information. The final `_into` suffixed functions take an output range to write into, letting you explicitly control just how much space there is to write into as well as returning a detailed `result` type.

The return type for these function calls is one of:

- the desired output container (highest level);
- `ztd::text::recode_result` or `ztd::text::stateless_recode_result` with the desired output container embedded as the `.output` parameter (mid level); or,
- `ztd::text::recode_result` or `ztd::text::stateless_recode_result` returning just the input and output ranges (lowest level).

recode(...)

This is the highest level bulk function.

This set of function overloads takes the provided `input`, `from_encoding`, `to_encoding`, `from_handler`, `to_handler`, `from_state`, and `to_state` and produces an output container type. The default container will either be a `std::basic_string` of the `code_unit` type, or a `std::vector` if it is not a known "character" type.

The container type can be specified by passing it as an explicit template parameter to this function, such as `ztd::text::recode<std::vector<char16_t>>("bark", ztd::text::utf16{})`;. The output container is default constructed.

It will either call `push_back/insert` directly on the target container to fill it up, or serialize data to a temporary buffer (controlled by `ZTD_TEXT_INTERMEDIATE_RECODE_BUFFER_BYTE_SIZE`) before then copying it into the desired output container through any available means (bulk `.insert`, repeated `.push_back`, or repeated single `.insert` with the `.end()` iterator in that order).

This is the "fire and forget" version of the `recode` function, returning only the container and not returning any of the result or state information used to construct it.

recode_to(...)

This is the mid level bulk function.

This set of function overloads takes the provided `input`, `from_encoding`, `to_encoding`, `from_handler`, `to_handler`, `from_state`, and `to_state` and produces an output container type that is embedded within a `ztd::text::recode_result`, or a `ztd::text::stateless_recode_result`, depending on whether or not you called the version which takes a `ztd::text::decode_state_t<Encoding>` and/or a `ztd::text::encode_state_t<Encoding>` as a parameter or if it had to create one on the stack internally and discard it after the operation was finished.

The container type can be specified by passing it as an explicit template parameter to this function, such as `ztd::text::recode_to<std::string>(U"meow", ascii{ });`. The output container is default constructed.

It will either call `push_back/insert` directly on the target container to fill it up, or serialize data to a temporary buffer (controlled by `ZTD_TEXT_INTERMEDIATE_RECODE_BUFFER_BYTE_SIZE`) before then copying it into the desired output container through any available means (bulk `.insert`, repeated `.push_back`, or repeated single `.insert` with the `.end()` iterator in that order).

If nothing goes wrong or the error handler lets the algorithm continue, `.input` on the result should be empty.

recode_into_raw(...)

This is the lowest level bulk function.

This set of function overloads takes the provided `input`, `from_encoding`, `output`, `to_encoding`, `from_handler`, `to_handler`, `from_state`, and `to_state` to write data into an output range specified by `output`. The result is a `ztd::text::recode_result`, or a `ztd::text::stateless_recode_result`, depending on whether or not you called the version which takes a `ztd::text::decode_state_t<Encoding>` and/or a `ztd::text::encode_state_t<Encoding>` as a parameter or if it had to create one on the stack internally and discard it after the operation was finished.

It is up to the end-user to provide a suitably-sized output range for `output`, otherwise this operation may return with `ztd::text::encoding_error::insufficient_output` for the result's `error_code` member. The amount of space consumed can be determined by checking the `std::distance` between the `.begin()` of the original output parameter and the `.begin()` of the returned `.output` member. The result also has error information and an `.input` member for checking how much input was consumed.

If nothing goes wrong or the error handler lets the algorithm continue, `.input` on the result should be empty.

For Everything

All named functions have 6 overloads. Each of the “higher level” functions, at the end of their overload call chain, will call the lower-level `recode_into_raw` to perform the work. The final `recode_into_raw` call uses the following ordering of extension points into calling the base implementation:

- The `text_recode_into_raw(input, from_encoding, output, to_encoding, ...)` extension point.
- An implementation-defined extension point if any internal optimizations are possible.
- The `basic_recode_into_raw(input, from_encoding, output, to_encoding, ...)` function.

The final function call, `basic_recode_into_raw`, simply performs the *core recode loop* using the *Lucky 7* design. `basic_recode_into_raw` accommodates the lowest level transformation using just `decode_one` into a suitably sized intermediate buffer and then an `encode_one` into the output, calling the relevant error handlers along the way. This design also means minimal stack space is used, keeping the core algorithm suitable for resource-constrained devices.

However, there is a caveat: if there exists a `text_recode_one(input, from_encoding, output, to_encoding, ...)` that is callable then it will be called to perform one unit of complete transformation. Otherwise, `decode_one/encode_one`

The `recode_one` extension point is also used in the `ztd::text::recode_view<...>` to speed up one-by-one translations for iteration-based types, where possible.

Note: This means that if you implement none of the extension points whatsoever, implementing the basic `decode_one` function of the `from_encoding` and the `recode_one` of the `to_encoding` function on your Encoding Object type will guarantee a proper, working implementation.

Note: If you need to call the “basic” form of this function that takes no secret implementation shortcuts or user-defined extension points, then call `basic_recode_into_raw` directly. This can be useful to stop infinity loops when your extension points cannot handle certain inputs and thereby needs to “delegate” to the basic case.

Bulk Functions

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState, typename
_Pivot>
constexpr auto basic_recode_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &&__from_state, _ToState &&__to_state, _Pivot &&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function detects whether or not the ADL extension point `text_recode` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to recode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding` ‘s decode step.

- **__to_state** – [inout] A reference to the associated state for the `__to_encoding` ‘s encode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A `ztd::text::recode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename  
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState, typename  
_Pivot>
```

```
constexpr auto recode_into_raw(_Input &&_input, _FromEncoding &&_from_encoding, _Output  
&&_output, _ToEncoding &&_to_encoding, _FromErrorHandler  
&&_from_error_handler, _ToErrorHandler &&_to_error_handler,  
_FromState &_from_state, _ToState &_to_state, _Pivot &&_pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function detects whether or not the ADL extension point `text_recode` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to recode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding` ‘s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding` ‘s encode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A `ztd::text::recode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState>
constexpr auto recode_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state, _ToState &__to_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function detects whether or not the ADL extension point `text_recode` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to recode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s encode step.

Returns

A `ztd::text::pivotless_recode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState>
constexpr auto recode_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function calls the base reference, the `ztd::text::recode_into_raw` after creating a `to_state` from `ztd::text::make_encode_state`. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.

Returns

A `ztd::text::stateless_recode_result` object.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler>
constexpr auto recode_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates a decode state `from_state` by calling `ztd::text::make_decode_state`. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::pivotless_recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s encode step.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler>
constexpr auto recode_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates an `to_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::pivotless_recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding>
```

```
constexpr auto recode_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
    &&__output, _ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates an `from_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as careless since you did not explicitly provide it. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::pivotless_recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

```
template<typename _Input, typename _ToEncoding, typename _Output>
constexpr auto recode_into_raw(_Input &&__input, _ToEncoding &&__to_encoding, _Output &&__output)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates both: a `from_error_handler` using a `ztd::text::default_handler_t` that is marked as careless to pass to the next function overload; and, a `from_encoding` to interpret the `__input` by checking the `__input`'s `value_type`. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::pivotless_recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState, typename
_Pivot>
```

```
constexpr auto recode_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output &&__output,
_ToEncoding &&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler, _FromState &__from_state, _ToState
&__to_state, _Pivot &&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function detects whether or not the ADL extension point `text_recode` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to recode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s encode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A `ztd::text::pivotless_recode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState>
```

```
constexpr auto recode_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output &&__output,  
    _ToEncoding &&__to_encoding, _FromErrorHandler &&__from_error_handler,  
    _ToErrorHandler &&__to_error_handler, _FromState &__from_state, _ToState  
    &__to_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function detects whether or not the ADL extension point `text_recode` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to recode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s encode step.

Returns

A `ztd::text::pivotless_recode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename  
_FromErrorHandler, typename _ToErrorHandler, typename _FromState>
```

```
constexpr auto recode_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output &&__output,  
    _ToEncoding &&__to_encoding, _FromErrorHandler &&__from_error_handler,  
    _ToErrorHandler &&__to_error_handler, _FromState &__from_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function calls the base reference, the `ztd::text::recode_into` after creating a `to_state` from `ztd::text::make_encode_state`. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::pivotless_recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.

Returns

A `ztd::text::stateless_recode_result` object.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler>
constexpr auto recode_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output &&__output,
    _ToEncoding &&__to_encoding, _FromErrorHandler &&__from_error_handler,
    _ToErrorHandler &&__to_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates a decode state `from_state` by calling `ztd::text::make_decode_state`. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::pivotless_recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.

- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` 's encode step.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename  
_FromErrorHandler>
```

```
constexpr auto recode_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output &&__output,  
                           _ToEncoding &&__to_encoding, _FromErrorHandler &&__from_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates an `to_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::pivotless_recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's decode step.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding>  
constexpr auto recode_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output &&__output,  
                           _ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates an `from_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as careless since you did not explicitly provide it. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::pivotless_recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

```
template<typename _Input, typename _ToEncoding, typename _Output>
constexpr auto recode_into(_Input &&__input, _ToEncoding &&__to_encoding, _Output &&__output)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates both: a `from_error_handler` using a `ztd::text::default_handler_t` that is marked as careless to pass to the next function overload; and, a `from_encoding` to interpret the `__input` by checking the `__input`'s `value_type`. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::pivotless_recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename
_ToState, typename _Pivot>
constexpr auto recode_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler, _ToErrorHandler
&&__to_error_handler, _FromState &__from_state, _ToState &__to_state, _Pivot
&&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s encode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A `ztd::text::recode_result` object that contains references to `__from_state` and `__to_state` and an output parameter that contains the `_OutputContainer` specified. If the container has a `container.reserve` function, it is and some multiple of the input's size is used to pre-size the container, to aid with `push_back` / `insert` reallocation pains.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
    _ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename
    _ToState>
```

```
constexpr auto recode_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
    &&__to_encoding, _FromErrorHandler &&__from_error_handler, _ToErrorHandler
    &&__to_error_handler, _FromState &__from_state, _ToState &__to_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.

- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` ‘s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` ‘s encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding` ‘s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding` ‘s encode step.

Returns

A `ztd::text::pivotless_recode_result` object that contains references to `__from_state` and `__to_state` and an output parameter that contains the `_OutputContainer` specified. If the container has a `container.reserve` function, it is and some multiple of the input’s size is used to pre-size the container, to aid with `push_back` / `insert` reallocation pains.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState>
constexpr auto recode_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler, _ToErrorHandler
&&__to_error_handler, _FromState &__from_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A default state for the encode step of the operation is create using `ztd::text::make_encode_state`. The return type is stateless since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` ‘s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` ‘s encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding` ‘s decode step.

Returns

A `ztd::text::stateless_recode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler>
constexpr auto recode_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler, _ToErrorHandler
&&__to_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A default state for the decode step of the operation is create using `ztd::text::make_decode_state`. The return type is stateless since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s encode step.

Returns

A `ztd::text::stateless_recode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler>
constexpr auto recode_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A `to_error_handler` for the encode step of the operation is created using default construction of a `ztd::text::default_handler_t` that is marked as careless. The return type is stateless since both states must be

passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.

Returns

A `ztd::text::stateless_recode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding>
constexpr auto recode_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A `from_error_handler` for the encode step of the operation is created using default construction of a `ztd::text::default_handler_t` that is marked as `careless`. The return type is `stateless` since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

Returns

A `ztd::text::stateless_recode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _ToEncoding>
constexpr auto recode_to(_Input &&__input, _ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A `from_error_handler` for the encode step of the operation is created using default construction of a `ztd::text::default_handler_t` that is marked as careless. The return type is stateless since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [**in**] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__to_encoding** – [**in**] The encoding that will be used to encode the intermediate code points into the final code units.

Returns

A `ztd::text::stateless_recode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename
_ToState, typename _Pivot>
constexpr auto recode(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding &&__to_encoding,
_FromErrorHandler &&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state, _ToState &__to_state, _Pivot &&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [**in**] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [**in**] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [**in**] The encoding that will be used to encode the intermediate code points into the final code units.

- **__from_error_handler** – [in] The error handler for the `__from_encoding` ‘s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` ‘s encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding` ‘s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding` ‘s encode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::recode_to` or `ztd::text::recode_into_raw`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename
_ToState>
constexpr auto recode(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding &&__to_encoding,
    _FromErrorHandler &&__from_error_handler, _ToErrorHandler &&__to_error_handler,
    _FromState &__from_state, _ToState &__to_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` ‘s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` ‘s encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding` ‘s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding` ‘s encode step.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::recode_to` or `ztd::text::recode_into_raw`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState>
```

```
constexpr auto recode(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding &&__to_encoding,  
                    _FromErrorHandler &&__from_error_handler, _ToErrorHandler &&__to_error_handler,  
                    _FromState &__from_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates an `to_state` for the encoding step of the operation using `ztd::text::make_encode_state`.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::recode_to` or `ztd::text::recode_into_raw`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename  
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler>  
constexpr auto recode(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding &&__to_encoding,  
                    _FromErrorHandler &&__from_error_handler, _ToErrorHandler &&__to_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates an `from_state` for the encoding step of the operation using `ztd::text::make_decode_state`.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` 's encode step.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::recode_to` or `ztd::text::recode_into_raw`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler>
constexpr auto recode(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding &&__to_encoding,
    _FromErrorHandler &&__from_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates a `to_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's decode step.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::recode_to` or `ztd::text::recode_into_raw`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename  
_ToEncoding>  
constexpr auto recode(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding  
                        &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates a `from_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [**in**] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [**in**] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [**in**] The encoding that will be used to encode the intermediate code points into the final code units.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::recode_to` or `ztd::text::recode_into_raw`.

```
template<typename _OutputContainer = void, typename _Input, typename _ToEncoding>  
constexpr auto recode(_Input &&__input, _ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates both: a `from_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it; and, a `from_encoding` derived from the `__input`'s `value_type`. The `careless` marking matters for lossy conversions that are not injective.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [**in**] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.

- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::recode_to` or `ztd::text::recode_into_raw`.

Single Functions

```
template<typename _Input, typename _Output, typename _FromEncoding, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState, typename
_Pivot>
constexpr auto basic_recode_one_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding,
_FromErrorHandler &&__from_error_handler, _ToErrorHandler
&&__to_error_handler, _FromState &__from_state, _ToState
&__to_state, _Pivot &&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view. nly one.

Remark

This function detects whether or not the ADL extension point `text_recode` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to recode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the decode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding` 's encode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding` 's decode step.

- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A *ztd::text::recode_result* object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _Output, typename _FromEncoding, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState, typename
_Pivot>
```

```
constexpr auto recode_one_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state, _ToState &__to_state, _Pivot &&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view. Only performs one distinct unit of encoding.

Remark

This function detects whether or not the ADL extension point `text_recode_one` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to recode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the decode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s encode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s decode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A *ztd::text::recode_result* object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _Output, typename _FromEncoding, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState>
constexpr auto recode_one_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state, _ToState &__to_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view. Only performs one distinct unit of encoding.

Remark

This function detects whether or not the ADL extension point `text_recode_one` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to recode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the decode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s encode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s decode step.

Returns

A `ztd::text::recode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState>
constexpr auto recode_one_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function calls the base reference, the `ztd::text::recode_one_into_raw` after creating a `to_state` from `ztd::text::make_decode_state`. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the decode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s encode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s decode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s encode step.

Returns

A `ztd::text::stateless_recode_result` object.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler>
constexpr auto recode_one_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates a encode state `from_state` by calling `ztd::text::make_encode_state`. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.

- **__from_encoding** – [in] The encoding that will be used to encode the input’s code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the decode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` ‘s encode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` ‘s decode step.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler>
```

```
constexpr auto recode_one_into_raw(Input &&__input, FromEncoding &&__from_encoding, Output
&&__output, ToEncoding &&__to_encoding, FromErrorHandler
&&__from_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates an `to_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input’s code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the decode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` ‘s encode step.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding>
constexpr auto recode_one_into_raw(Input &&__input, FromEncoding &&__from_encoding, Output
&&__output, ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates an `from_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the decode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.

```
template<typename _Input, typename _ToEncoding, typename _Output>  
constexpr auto recode_one_into_raw(_Input &&__input, _ToEncoding &&__to_encoding, _Output  
    &&__output)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates both: a `from_error_handler` using a `ztd::text::default_handler_t` that is marked as `careless` to pass to the next function overload; and, a `from_encoding` to interpret the `__input` by checking the `__input`'s `value_type`. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__output** – [in] An `output_view` to write code units to as the result of the decode operation from the intermediate code points.

```
template<typename _Input, typename _Output, typename _FromEncoding, typename _ToEncoding, typename  
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState, typename  
_Pivot>
```

```
constexpr auto basic_recode_one_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state, _ToState &__to_state, _Pivot &&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view. Only performs one distinct unit of encoding.

Remark

This function detects whether or not the ADL extension point `text_recode_one` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to recode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the decode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s encode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s decode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A `ztd::text::recode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _Output, typename _FromEncoding, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState, typename
_Pivot>
constexpr auto recode_one_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state, _ToState &__to_state, _Pivot &&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view. Only performs one distinct unit of encoding.

Remark

This function detects whether or not the ADL extension point `text_recode_one` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to recode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the decode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s encode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s decode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A `ztd::text::recode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _Output, typename _FromEncoding, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState>
constexpr auto recode_one_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state, _ToState &__to_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view. Only performs one distinct unit of encoding.

Remark

This function detects whether or not the ADL extension point `text_recode_one` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop

over the two encodings and attempt to recode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the decode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s encode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s decode step.

Returns

A `ztd::text::recode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState>
constexpr auto recode_one_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function calls the base reference, the `ztd::text::recode_one_into` after creating a `to_state` from `ztd::text::make_decode_state`. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.

- **__output** – [in] An `output_view` to write code units to as the result of the decode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's encode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` 's decode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding` 's encode step.

Returns

A `ztd::text::stateless_recode_result` object.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler>
constexpr auto recode_one_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates a encode state `from_state` by calling `ztd::text::make_encode_state`. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the decode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's encode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` 's decode step.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler>
```

```
constexpr auto recode_one_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output
    &&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
    &&__from_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates an `to_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the decode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s encode step.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding>
constexpr auto recode_one_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output
    &&__output, _ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates an `from_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.

- **__from_encoding** – [in] The encoding that will be used to encode the input’s code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the decode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.

```
template<typename _Input, typename _ToEncoding, typename _Output>  
constexpr auto recode_one_into(_Input &&__input, _ToEncoding &&__to_encoding, _Output &&__output)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates both: a `from_error_handler` using a `ztd::text::default_handler_1` that is marked as careless to pass to the next function overload; and, a `from_encoding` to interpret the `__input` by checking the `__input`’s `value_type`. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_recode_result` as opposed to a `ztd::text::recode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__output** – [in] An `output_view` to write code units to as the result of the decode operation from the intermediate code points.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename  
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename  
_ToState, typename _Pivot>
```

```
constexpr auto recode_one_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding  
    &&__to_encoding, _FromErrorHandler &&__from_error_handler,  
    _ToErrorHandler &&__to_error_handler, _FromState &__from_state, _ToState  
    &__to_state, _Pivot &&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.

- **__from_encoding** – [in] The encoding that will be used to encode the input’s code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the **__from_encoding** ‘s encode step.
- **__to_error_handler** – [in] The error handler for the **__to_encoding** ‘s decode step.
- **__from_state** – [inout] A reference to the associated state for the **__from_encoding** ‘s encode step.
- **__to_state** – [inout] A reference to the associated state for the **__to_encoding** ‘s decode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A `ztd::text::recode_result` object that contains references to `__from_state` and `__to_state` and an output parameter that contains the `_OutputContainer` specified. If the container has a `container.reserve` function, it is and some multiple of the input’s size is used to pre-size the container, to aid with `push_back` / `insert` reallocation pains.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename
_ToState>
constexpr auto recode_one_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler, _FromState &__from_state, _ToState
&__to_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input’s code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the **__from_encoding** ‘s encode step.
- **__to_error_handler** – [in] The error handler for the **__to_encoding** ‘s decode step.
- **__from_state** – [inout] A reference to the associated state for the **__from_encoding** ‘s encode step.
- **__to_state** – [inout] A reference to the associated state for the **__to_encoding** ‘s decode step.

Returns

A `ztd::text::recode_result` object that contains references to `__from_state` and `__to_state` and an `output` parameter that contains the `_OutputContainer` specified. If the container has a `container.reserve` function, it is and some multiple of the input's size is used to pre-size the container, to aid with `push_back` / `insert` reallocation pains.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState>
constexpr auto recode_one_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler, _FromState &__from_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A default state for the decode step of the operation is create using `ztd::text::make_decode_state`. The return type is stateless since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's encode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` 's decode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding` 's encode step.

Returns

A `ztd::text::stateless_recode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler>
constexpr auto recode_one_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A default state for the encode step of the operation is create using `ztd::text::make_encode_state`. The return type is stateless since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's encode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` 's decode step.

Returns

A `ztd::text::stateless_recode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
    _ToEncoding, typename _FromErrorHandler>
constexpr auto recode_one_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
    &&__to_encoding, _FromErrorHandler &&__from_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A `to_error_handler` for the decode step of the operation is created using default construction of a `ztd::text::default_handler_t` that is marked as `careless`. The return type is stateless since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.

- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's encode step.

Returns

A `ztd::text::stateless_recode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding>
constexpr auto recode_one_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A `from_error_handler` for the decode step of the operation is created using default construction of a `ztd::text::default_handler_t` that is marked as `careless`. The return type is `stateless` since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.

Returns

A `ztd::text::stateless_recode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer, typename _Input, typename _ToEncoding>
constexpr auto recode_one_to(_Input &&__input, _ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A `from_error_handler` for the decode step of the operation is created using default construction of a `ztd::text::default_handler_t` that is marked as `careless`. The return type is `stateless` since both states must be

passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.

Returns

A `ztd::text::stateless_recode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename
_ToState, typename _Pivot>
constexpr auto recode_one( Input &&__input, FromEncoding &&__from_encoding, ToEncoding
&&__to_encoding, FromErrorHandler &&__from_error_handler, ToErrorHandler
&&__to_error_handler, FromState &__from_state, ToState &__to_state, Pivot
&&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s encode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s decode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s encode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s decode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::recode_one_to` or `ztd::text::recode_one_into`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename
_ToState>
constexpr auto recode_one(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler, _ToErrorHandler
&&__to_error_handler, _FromState &__from_state, _ToState &__to_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s encode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s decode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s encode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s decode step.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::recode_one_to` or `ztd::text::recode_one_into`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState>
constexpr auto recode_one(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler, _ToErrorHandler
&&__to_error_handler, _FromState &__from_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates an `to_state` for the encoding step of the operation using `ztd::text::make_decode_state`.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s encode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s decode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s encode step.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::recode_one_to` or `ztd::text::recode_one_into`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler>
constexpr auto recode_one(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler, _ToErrorHandler
&&__to_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates an `from_state` for the encoding step of the operation using `ztd::text::make_encode_state`.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s encode step.

- **__to_error_handler** – [in] The error handler for the `__to_encoding` 's decode step.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::recode_one_to` or `ztd::text::recode_one_into`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler>
constexpr auto recode_one(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates a `to_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as careless since you did not explicitly provide it. This matters for lossy conversions that are not injective.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's encode step.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::recode_one_to` or `ztd::text::recode_one_into`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding>
constexpr auto recode_one(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates a `from_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as careless since you did not explicitly provide it. This matters for lossy conversions that are not injective.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to encode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::recode_one_to` or `ztd::text::recode_one_into`.

```
template<typename _OutputContainer = void, typename _Input, typename _ToEncoding>
constexpr auto recode_one(_Input &&__input, _ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates both: a `from_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as careless since you did not explicitly provide it; and, a `from_encoding` derived from the "`__input`"'s `value_type`. The careless marking matters for lossy conversions that are not injective.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the encode operation that will produce intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to decode the intermediate code points into the final code units.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::recode_one_to` or `ztd::text::recode_one_into`.

transcode

The `transcode` grouping of functions (`transcode`, `transcode_to`, and `transcode_into_raw`) perform the task of doing bulk transcoding from an `input` of `code_units` to a second encoding's `code_unit` type. It expects to traffic through the `code_point` type as the intermediary between the two functions. There is also a `transcode_one` API as well that does a single indivisible unit of work for both decoding (to a common representation) and then encoding, and has the same variants as the bulk function.

Named Groups

There are 3 named functions for this behavior, and each function comes with several function overloads. Each named function produces increasingly more information, letting you opt into just how much information and control you'd like over the algorithm and behavior. The first one simply returns a container with the transformation applied, discarding much of the operation's result information. This is useful for quick, one-off conversions where you do not care about any errors and would rather let it be handled by the error handler. The second `_to` suffixed functions return a container within a `result` type that contains additional information. The final `_into` suffixed functions take an output range to write into, letting you explicitly control just how much space there is to write into as well as returning a detailed `result` type.

The return type for these function calls is one of:

- the desired output container (highest level);
- `ztd::text::transcode_result` or `ztd::text::stateless_transcode_result` with the desired output container embedded as the `.output` parameter (mid level); or,
- `ztd::text::transcode_result` or `ztd::text::stateless_transcode_result` returning just the input and output ranges (lowest level).

transcode(...)

This is the highest level bulk function.

This set of function overloads takes the provided `input`, `from_encoding`, `to_encoding`, `from_handler`, `to_handler`, `from_state`, and `to_state` and produces an output container type. The default container will either be a `std::basic_string` of the `code_unit` type, or a `std::vector` if it is not a known “character” type.

The container type can be specified by passing it as an explicit template parameter to this function, such as `ztd::text::transcode<std::vector<char16_t>>("bark", ztd::text::utf16{})`; . The output container is default constructed.

It will either call `push_back/insert` directly on the target container to fill it up, or serialize data to a temporary buffer (controlled by `ZTD_TEXT_INTERMEDIATE_TRANSCODE_BUFFER_BYTE_SIZE`) before then copying it into the desired output container through any available means (bulk `.insert`, repeated `.push_back`, or repeated single `.insert` with the `.end()` iterator in that order).

This is the “fire and forget” version of the `transcode` function, returning only the container and not returning any of the result or state information used to construct it.

transcode_to(...)

This is the mid level bulk function.

This set of function overloads takes the provided `input`, `from_encoding`, `to_encoding`, `from_handler`, `to_handler`, `from_state`, and `to_state` and produces an output container type that is embedded within a `ztd::text::transcode_result`, or a `ztd::text::stateless_transcode_result`, depending on whether or not you called the version which takes a `ztd::text::decode_state_t<Encoding>` and/or a `ztd::text::encode_state_t<Encoding>` as a parameter or if it had to create one on the stack internally and discard it after the operation was finished.

The container type can be specified by passing it as an explicit template parameter to this function, such as `ztd::text::transcode_to<std::string>(U"meow", ascii{ })`; . The output container is default constructed.

It will either call `push_back/insert` directly on the target container to fill it up, or serialize data to a temporary buffer (controlled by `ZTD_TEXT_INTERMEDIATE_TRANSCODE_BUFFER_BYTE_SIZE`) before then copying it into the desired output container through any available means (bulk `.insert`, repeated `.push_back`, or repeated single `.insert` with the `.end()` iterator in that order).

If nothing goes wrong or the error handler lets the algorithm continue, `.input` on the result should be empty.

transcode_into_raw(...)

This is the lowest level bulk function.

This set of function overloads takes the provided `input`, `from_encoding`, `output`, `to_encoding`, `from_handler`, `to_handler`, `from_state`, and `to_state` to write data into an output range specified by `output`. The result is a `ztd::text::transcode_result`, or a `ztd::text::stateless_transcode_result`, depending on whether or not you called the version which takes a `ztd::text::decode_state_t<Encoding>` and/or a `ztd::text::encode_state_t<Encoding>` as a parameter or if it had to create one on the stack internally and discard it after the operation was finished.

It is up to the end-user to provide a suitably-sized output range for `output`, otherwise this operation may return with `ztd::text::encoding_error::insufficient_output` for the result's `error_code` member. The amount of space consumed can be determined by checking the `std::distance` between the `.begin()` of the original output parameter and the `.begin()` of the returned `.output` member. The result also has error information and an `.input` member for checking how much input was consumed.

If nothing goes wrong or the error handler lets the algorithm continue, `.input` on the result should be empty.

For Everything

All named functions have 6 overloads. Each of the “higher level” functions, at the end of their overload call chain, will call the lower-level `transcode_into_raw` to perform the work. The final `transcode_into_raw` call uses the following ordering of extension points into calling the base implementation:

- The `text_transcode_into_raw(input, from_encoding, output, to_encoding, ...)` extension point.
- An implementation-defined extension point if any internal optimizations are possible.
- The `basic_transcode_into_raw(input, from_encoding, output, to_encoding, ...)` function.

The final function call, `basic_transcode_into_raw`, simply performs the *core transcode loop* using the *Lucky 7* design. `basic_transcode_into_raw` accommodates the lowest level transformation using just `decode_one` into a suitably sized intermediate buffer and then an `encode_one` into the output, calling the relevant error handlers along the way. This design also means minimal stack space is used, keeping the core algorithm suitable for resource-constrained devices.

However, there is a caveat: if there exists a `text_transcode_one(input, from_encoding, output, to_encoding, ...)` that is callable then it will be called to perform one unit of complete transformation. Otherwise, `decode_one/encode_one`

The `transcode_one` extension point is also used in the `ztd::text::transcode_view<...>` to speed up one-by-one translations for iteration-based types, where possible.

Note: This means that if you implement none of the extension points whatsoever, implementing the basic `decode_one` function of the `from_encoding` and the `transcode_one` of the `to_encoding` function on your Encoding Object type will guarantee a proper, working implementation.

Note: If you need to call the “basic” form of this function that takes no secret implementation shortcuts or user-defined extension points, then call `basic_transcode_into_raw` directly. This can be useful to stop infinity loops when your extension points cannot handle certain inputs and thereby needs to “delegate” to the basic case.

Bulk Functions

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState, typename
_Pivot>
constexpr auto basic_transcode_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state, _ToState &__to_state, _Pivot
&&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function detects whether or not the ADL extension point `text_transcode` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to transcode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding` 's decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding` 's encode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A `ztd::text::transcode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState, typename
_Pivot>
```

```
constexpr auto transcode_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state, _ToState &__to_state, _Pivot &&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function detects whether or not the ADL extension point `text_transcode` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to transcode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding` 's decode step.

- **__to_state** – [inout] A reference to the associated state for the `__to_encoding` ‘s encode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A `ztd::text::transcode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState>
constexpr auto transcode_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state, _ToState &__to_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function detects whether or not the ADL extension point `text_transcode` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to transcode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding` ‘s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding` ‘s encode step.

Returns

A `ztd::text::pivotless_transcode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState>
constexpr auto transcode_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function calls the base reference, the `ztd::text::transcode_into_raw` after creating a `to_state` from `ztd::text::make_encode_state`. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` 's encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding` 's decode step.

Returns

A `ztd::text::stateless_transcode_result` object.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler>
constexpr auto transcode_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates a decode state `from_state` by calling `ztd::text::make_decode_state`. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::pivotless_transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s encode step.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler>
constexpr auto transcode_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates an `to_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::pivotless_transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's decode step.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding>
constexpr auto transcode_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates an `from_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::pivotless_transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

```
template<typename _Input, typename _ToEncoding, typename _Output>
constexpr auto transcode_into_raw(_Input &&__input, _ToEncoding &&__to_encoding, _Output &&__output)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates both: a `from_error_handler` using a `ztd::text::default_handler_t` that is marked as `careless` to pass to the next function overload; and, a `from_encoding` to interpret the `__input` by checking the `__input` 's `value_type`. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::pivotless_transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.

- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__output** – [in] An output_view to write code units to as the result of the encode operation from the intermediate code points.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState, typename
_Pivot>
constexpr auto transcode_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output &&__output,
    _ToEncoding &&__to_encoding, _FromErrorHandler &&__from_error_handler,
    _ToErrorHandler &&__to_error_handler, _FromState &__from_state, _ToState
    &__to_state, _Pivot &&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function detects whether or not the ADL extension point `text_transcode` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to transcode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An input_view to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An output_view to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s encode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A `ztd::text::pivotless_transcode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState>
constexpr auto transcode_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output &&__output,
    _ToEncoding &&__to_encoding, _FromErrorHandler &&__from_error_handler,
    _ToErrorHandler &&__to_error_handler, _FromState &__from_state, _ToState
    &__to_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function detects whether or not the ADL extension point `text_transcode` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to transcode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s encode step.

Returns

A `ztd::text::pivotless_transcode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState>
constexpr auto transcode_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output &&__output,
    _ToEncoding &&__to_encoding, _FromErrorHandler &&__from_error_handler,
    _ToErrorHandler &&__to_error_handler, _FromState &__from_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function calls the base reference, the `ztd::text::transcode_into` after creating a `to_state` from `ztd::text::make_encode_state`. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::pivotless_transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.

Returns

A `ztd::text::stateless_transcode_result` object.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler>
constexpr auto transcode_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output &&__output,
                             _ToEncoding &&__to_encoding, _FromErrorHandler &&__from_error_handler,
                             _ToErrorHandler &&__to_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates a decode state `from_state` by calling `ztd::text::make_decode_state`. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::pivotless_transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.

- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` ‘s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` ‘s encode step.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler>
constexpr auto transcode_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output &&__output,
                             _ToEncoding &&__to_encoding, _FromErrorHandler &&__from_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates an `to_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::pivotless_transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` ‘s decode step.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding>
constexpr auto transcode_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output &&__output,
                             _ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates an `from_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::pivotless_transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

```
template<typename _Input, typename _ToEncoding, typename _Output>  
constexpr auto transcode_into(_Input &&__input, _ToEncoding &&__to_encoding, _Output &&__output)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates both: a `from_error_handler` using a `ztd::text::default_handler_t` that is marked as `careless` to pass to the next function overload; and, a `from_encoding` to interpret the `__input` by checking the `__input`'s `value_type`. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::pivotless_transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename  
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename  
_ToState, typename _Pivot>
```

```
constexpr auto transcode_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
    &&__to_encoding, _FromErrorHandler &&__from_error_handler,
    _ToErrorHandler &&__to_error_handler, _FromState &__from_state, _ToState
    &__to_state, _Pivot &&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s encode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A `ztd::text::transcode_result` object that contains references to `__from_state` and `__to_state` and an output parameter that contains the `_OutputContainer` specified. If the container has a `container.reserve` function, it is and some multiple of the input's size is used to pre-size the container, to aid with `push_back` / `insert` reallocation pains.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename
_ToState>
constexpr auto transcode_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
    &&__to_encoding, _FromErrorHandler &&__from_error_handler,
    _ToErrorHandler &&__to_error_handler, _FromState &__from_state, _ToState
    &__to_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.

- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the **__from_encoding** ‘s decode step.
- **__to_error_handler** – [in] The error handler for the **__to_encoding** ‘s encode step.
- **__from_state** – [inout] A reference to the associated state for the **__from_encoding** ‘s decode step.
- **__to_state** – [inout] A reference to the associated state for the **__to_encoding** ‘s encode step.

Returns

A *ztd::text::pivotless_transcode_result* object that contains references to **__from_state** and **__to_state** and an output parameter that contains the **_OutputContainer** specified. If the container has a **container.reserve** function, it is and some multiple of the input’s size is used to pre-size the container, to aid with **push_back** / **insert** reallocation pains.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState>
constexpr auto transcode_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler, _FromState &__from_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A default state for the encode step of the operation is create using *ztd::text::make_encode_state*. The return type is stateless since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the **__from_encoding** ‘s decode step.
- **__to_error_handler** – [in] The error handler for the **__to_encoding** ‘s encode step.

- **__from_state** – [inout] A reference to the associated state for the `__from_encoding` ‘s decode step.

Returns

A `ztd::text::stateless_transcode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler>
constexpr auto transcode_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A default state for the decode step of the operation is create using `ztd::text::make_decode_state`. The return type is stateless since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` ‘s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` ‘s encode step.

Returns

A `ztd::text::stateless_transcode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler>
constexpr auto transcode_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A `to_error_handler` for the encode step of the operation is created using default construction of a `ztd::text::default_handler_t` that is marked as careless. The return type is stateless since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.

Returns

A `ztd::text::stateless_transcode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding>
constexpr auto transcode_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A `from_error_handler` for the encode step of the operation is created using default construction of a `ztd::text::default_handler_t` that is marked as careless. The return type is stateless since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

Returns

A `ztd::text::stateless_transcode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _ToEncoding>
constexpr auto transcode_to(_Input &&__input, ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A `from_error_handler` for the encode step of the operation is created using default construction of a `ztd::text::default_handler_t` that is marked as careless. The return type is stateless since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

Returns

A `ztd::text::stateless_transcode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename
_ToState, typename _Pivot>
constexpr auto transcode(_Input &&__input, _FromEncoding &&__from_encoding, ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler, ToErrorHandler
&&__to_error_handler, _FromState &&__from_state, ToState &&__to_state, Pivot
&&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.

- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the **__from_encoding** ‘s decode step.
- **__to_error_handler** – [in] The error handler for the **__to_encoding** ‘s encode step.
- **__from_state** – [inout] A reference to the associated state for the **__from_encoding** ‘s decode step.
- **__to_state** – [inout] A reference to the associated state for the **__to_encoding** ‘s encode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::transcode_to` or `ztd::text::transcode_into_raw`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename
_ToState>
constexpr auto transcode(_Input &&_input, _FromEncoding &&_from_encoding, _ToEncoding
&&_to_encoding, _FromErrorHandler &&_from_error_handler, _ToErrorHandler
&&_to_error_handler, _FromState &_from_state, _ToState &_to_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the **__from_encoding** ‘s decode step.
- **__to_error_handler** – [in] The error handler for the **__to_encoding** ‘s encode step.
- **__from_state** – [inout] A reference to the associated state for the **__from_encoding** ‘s decode step.
- **__to_state** – [inout] A reference to the associated state for the **__to_encoding** ‘s encode step.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::transcode_to` or `ztd::text::transcode_into_raw`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState>
constexpr auto transcode(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler, _ToErrorHandler
&&__to_error_handler, _FromState &__from_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates an `to_state` for the encoding step of the operation using `ztd::text::make_encode_state`.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::transcode_to` or `ztd::text::transcode_into_raw`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler>
constexpr auto transcode(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler, _ToErrorHandler
&&__to_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates an `from_state` for the encoding step of the operation using `ztd::text::make_decode_state`.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s encode step.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::transcode_to` or `ztd::text::transcode_into_raw`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler>
constexpr auto transcode(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates a `to_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you

are looking for error information and not just a quick one-off conversion function, please use `ztd::text::transcode_to` or `ztd::text::transcode_into_raw`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename _ToEncoding>
```

```
constexpr auto transcode(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates a `from_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::transcode_to` or `ztd::text::transcode_into_raw`.

```
template<typename _OutputContainer = void, typename _Input, typename _ToEncoding>
```

```
constexpr auto transcode(_Input &&__input, _ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates both: a `from_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it; and, a `from_encoding` derived from the `__input`'s `value_type`. The `careless` marking matters for lossy conversions that are not injective.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a `std::basic_string` or a `std::vector` of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::transcode_to` or `ztd::text::transcode_into_raw`.

Single Functions

```
template<typename _Input, typename _Output, typename _FromEncoding, typename _ToEncoding, typename  
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState, typename  
_Pivot>
```

```
constexpr auto basic_transcode_one_into_raw(_Input &&__input, _FromEncoding &&__from_encoding,  
_Output &&__output, _ToEncoding &&__to_encoding,  
_FromErrorHandler &&__from_error_handler,  
_ToErrorHandler &&__to_error_handler, _FromState  
&__from_state, _ToState &__to_state, _Pivot &&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view. nly one.

Remark

This function detects whether or not the ADL extension point `text_transcode` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to transcode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s encode step.

- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A `ztd::text::transcode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _Output, typename _FromEncoding, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState, typename
_Pivot>
```

```
constexpr auto transcode_one_into_raw(_Input &&_input, _FromEncoding &&_from_encoding, _Output
&&_output, _ToEncoding &&_to_encoding, _FromErrorHandler
&&_from_error_handler, _ToErrorHandler &&_to_error_handler,
_FromState &_from_state, _ToState &_to_state, _Pivot &&_pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view. Only performs one distinct unit of encoding.

Remark

This function detects whether or not the ADL extension point `text_transcode_one` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to transcode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s encode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A `ztd::text::transcode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _Output, typename _FromEncoding, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState>
constexpr auto transcode_one_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state, _ToState &__to_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view. Only performs one distinct unit of encoding.

Remark

This function detects whether or not the ADL extension point `text_transcode_one` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to transcode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s encode step.

Returns

A `ztd::text::transcode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState>
constexpr auto transcode_one_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function calls the base reference, the `ztd::text::transcode_one_into_raw` after creating a `to_state` from `ztd::text::make_encode_state`. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.

Returns

A `ztd::text::stateless_transcode_result` object.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler>
constexpr auto transcode_one_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates a decode state `from_state` by calling `ztd::text::make_decode_state`. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.

- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` ‘s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` ‘s encode step.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename  
_FromErrorHandler>
```

```
constexpr auto transcode_one_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output  
                                     &&__output, _ToEncoding &&__to_encoding, _FromErrorHandler  
                                     &&__from_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates an `to_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` ‘s decode step.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding>  
constexpr auto transcode_one_into_raw(_Input &&__input, _FromEncoding &&__from_encoding, _Output  
                                     &&__output, _ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates an `from_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as careless since you did not explicitly provide it. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

```
template<typename _Input, typename _ToEncoding, typename _Output>
constexpr auto transcode_one_into_raw(_Input &&__input, _ToEncoding &&__to_encoding, _Output
&&__output)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates both: a `from_error_handler` using a `ztd::text::default_handler_t` that is marked as careless to pass to the next function overload; and, a `from_encoding` to interpret the `__input` by checking the `__input`'s `value_type`. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.

```
template<typename _Input, typename _Output, typename _FromEncoding, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState, typename
_Pivot>
```

```
constexpr auto basic_transcode_one_into( _Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state, _ToState &__to_state, _Pivot
&&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view. Only performs one distinct unit of encoding.

Remark

This function detects whether or not the ADL extension point `text_transcode_one` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to transcode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s encode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A `ztd::text::transcode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _Output, typename _FromEncoding, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState, typename
_Pivot>
constexpr auto transcode_one_into( _Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state, _ToState &__to_state, _Pivot &&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view. Only performs one distinct unit of encoding.

Remark

This function detects whether or not the ADL extension point `text_transcode_one` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to transcode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s encode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A `ztd::text::transcode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _Output, typename _FromEncoding, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename _ToState>
constexpr auto transcode_one_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state, _ToState &__to_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view. Only performs one distinct unit of encoding.

Remark

This function detects whether or not the ADL extension point `text_transcode_one` can be called with the provided parameters. If so, it will use that ADL extension point over the default implementation. Otherwise, it will loop over the two encodings and attempt to transcode by first decoding the input code units to code points, then encoding the intermediate code points to the desired, output code units.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__to_error_handler** – [in] The error handlers for the from and to encodings, respectively.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s encode step.

Returns

A `ztd::text::transcode_result` object that contains references to `__from_state` and `__to_state`.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler, typename _FromState>
constexpr auto transcode_one_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler,
_FromState &__from_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function calls the base reference, the `ztd::text::transcode_one_into` after creating a `to_state` from `ztd::text::make_encode_state`. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.

- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__output** – [in] An output_view to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the __from_encoding ‘s decode step.
- **__to_error_handler** – [in] The error handler for the __to_encoding ‘s encode step.
- **__from_state** – [inout] A reference to the associated state for the __from_encoding ‘s decode step.

Returns

A *ztd::text::stateless_transcode_result* object.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler, typename _ToErrorHandler>
constexpr auto transcode_one_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler, _ToErrorHandler &&__to_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates a decode state `from_state` by calling *ztd::text::make_decode_state*. The result from this function returns a *ztd::text::stateless_transcode_result* as opposed to a *ztd::text::transcode_result* because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An input_view to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__output** – [in] An output_view to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the __from_encoding ‘s decode step.
- **__to_error_handler** – [in] The error handler for the __to_encoding ‘s encode step.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding, typename
_FromErrorHandler>
```

```
constexpr auto transcode_one_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding, _FromErrorHandler
&&__from_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates an `to_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.

```
template<typename _Input, typename _FromEncoding, typename _Output, typename _ToEncoding>
constexpr auto transcode_one_into(_Input &&__input, _FromEncoding &&__from_encoding, _Output
&&__output, _ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates an `from_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.

- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

```
template<typename _Input, typename _ToEncoding, typename _Output>
constexpr auto transcode_one_into(_Input &&__input, _ToEncoding &&__to_encoding, _Output &&__output)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding into the output view.

Remark

This function creates both: a `from_error_handler` using a `ztd::text::default_handler_1` that is marked as careless to pass to the next function overload; and, a `from_encoding` to interpret the `__input` by checking the `__input`’s `value_type`. This matters for lossy conversions that are not injective. The result from this function returns a `ztd::text::stateless_transcode_result` as opposed to a `ztd::text::transcode_result` because the state information is on the stack, and returning the state in those types by reference will result in references to memory that has already been cleaned up. If you need access to the state parameters, call the lower-level functionality with your own created states.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__output** – [in] An `output_view` to write code units to as the result of the encode operation from the intermediate code points.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename
_ToState, typename _Pivot>
```

```
constexpr auto transcode_one_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler, _FromState &__from_state, _ToState
&__to_state, _Pivot &&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.

- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the **__from_encoding** ‘s decode step.
- **__to_error_handler** – [in] The error handler for the **__to_encoding** ‘s encode step.
- **__from_state** – [inout] A reference to the associated state for the **__from_encoding** ‘s decode step.
- **__to_state** – [inout] A reference to the associated state for the **__to_encoding** ‘s encode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

A `ztd::text::transcode_result` object that contains references to `__from_state` and `__to_state` and an output parameter that contains the `_OutputContainer` specified. If the container has a `container.reserve` function, it is and some multiple of the input’s size is used to pre-size the container, to aid with `push_back` / `insert` reallocation pains.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename
_ToState>
constexpr auto transcode_one_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler, _FromState &__from_state, _ToState
&__to_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An input_view to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input’s code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the **__from_encoding** ‘s decode step.
- **__to_error_handler** – [in] The error handler for the **__to_encoding** ‘s encode step.
- **__from_state** – [inout] A reference to the associated state for the **__from_encoding** ‘s decode step.
- **__to_state** – [inout] A reference to the associated state for the **__to_encoding** ‘s encode step.

Returns

A `ztd::text::transcode_result` object that contains references to `__from_state` and `__to_state` and an `output` parameter that contains the `_OutputContainer` specified. If the container has a `container.reserve` function, it is and some multiple of the input's size is used to pre-size the container, to aid with `push_back` / `insert` reallocation pains.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState>
constexpr auto transcode_one_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler, _FromState &__from_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A default state for the encode step of the operation is create using `ztd::text::make_encode_state`. The return type is stateless since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` 's encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding` 's decode step.

Returns

A `ztd::text::stateless_transcode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler>
constexpr auto transcode_one_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A default state for the decode step of the operation is create using `ztd::text::make_decode_state`. The return type is stateless since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` 's encode step.

Returns

A `ztd::text::stateless_transcode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler>
constexpr auto transcode_one_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A `to_error_handler` for the encode step of the operation is created using default construction of a `ztd::text::default_handler_t` that is marked as `careless`. The return type is stateless since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.

- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's decode step.

Returns

A `ztd::text::stateless_transcode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding>
constexpr auto transcode_one_to(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A `from_error_handler` for the encode step of the operation is created using default construction of a `ztd::text::default_handler_t` that is marked as `careless`. The return type is `stateless` since both states must be passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

Returns

A `ztd::text::stateless_transcode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer, typename _Input, typename _ToEncoding>
constexpr auto transcode_one_to(_Input &&__input, _ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

A `from_error_handler` for the encode step of the operation is created using default construction of a `ztd::text::default_handler_t` that is marked as `careless`. The return type is `stateless` since both states must be

passed in. If you want to have access to the states, create both of them yourself and pass them into a lower-level function that accepts those parameters.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

Returns

A `ztd::text::stateless_transcode_result` object that contains references to an `container.output` parameter that contains the `_OutputContainer` specified.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename  
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename  
_ToState, typename _Pivot>
```

```
constexpr auto transcode_one(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding  
&&__to_encoding, _FromErrorHandler &&__from_error_handler,  
_ToErrorHandler &&__to_error_handler, _FromState &__from_state, _ToState  
&__to_state, _Pivot &&__pivot)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s encode step.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) range as the intermediate pivot, usually a range of contiguous data from a span provided by the implementation but can be passed in here by the user.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::transcode_one_to` or `ztd::text::transcode_one_into`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState, typename
_ToState>
constexpr auto transcode_one(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler, _FromState &__from_state, _ToState
&__to_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding`'s decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding`'s encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding`'s decode step.
- **__to_state** – [inout] A reference to the associated state for the `__to_encoding`'s encode step.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::transcode_one_to` or `ztd::text::transcode_one_into`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler, typename _FromState>
constexpr auto transcode_one(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler, _FromState &__from_state)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates an `to_state` for the encoding step of the operation using `ztd::text::make_encode_state`.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's decode step.
- **__to_error_handler** – [in] The error handler for the `__to_encoding` 's encode step.
- **__from_state** – [inout] A reference to the associated state for the `__from_encoding` 's decode step.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::transcode_one_to` or `ztd::text::transcode_one_into`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler, typename _ToErrorHandler>
constexpr auto transcode_one(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler,
_ToErrorHandler &&__to_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates an `from_state` for the encoding step of the operation using `ztd::text::make_decode_state`.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's decode step.

- **__to_error_handler** – [in] The error handler for the `__to_encoding` 's encode step.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::transcode_one_to` or `ztd::text::transcode_one_into`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding, typename _FromErrorHandler>
constexpr auto transcode_one(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding, _FromErrorHandler &&__from_error_handler)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates a `to_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as `careless` since you did not explicitly provide it. This matters for lossy conversions that are not injective.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.
- **__from_error_handler** – [in] The error handler for the `__from_encoding` 's decode step.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::transcode_one_to` or `ztd::text::transcode_one_into`.

```
template<typename _OutputContainer = void, typename _Input, typename _FromEncoding, typename
_ToEncoding>
constexpr auto transcode_one(_Input &&__input, _FromEncoding &&__from_encoding, _ToEncoding
&&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates a `from_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as careless since you did not explicitly provide it. This matters for lossy conversions that are not injective.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__from_encoding** – [in] The encoding that will be used to decode the input's code units into intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::transcode_one_to` or `ztd::text::transcode_one_into`.

```
template<typename _OutputContainer = void, typename _Input, typename _ToEncoding>  
constexpr auto transcode_one(_Input &&__input, _ToEncoding &&__to_encoding)
```

Converts the code units of the given input view through the from encoding to code units of the to encoding for the output, which is then returned in a result structure with additional information about success.

Remark

This function creates both: a `from_error_handler` from a class like `ztd::text::default_handler_t`, but that is marked as careless since you did not explicitly provide it; and, a `from_encoding` derived from the `"__input"`'s `value_type`. The careless marking matters for lossy conversions that are not injective.

Template Parameters

_OutputContainer – The container to default-construct and serialize data into. Typically, a fixed-size container of some sort.

Parameters

- **__input** – [in] An `input_view` to read code units from and use in the decode operation that will produce intermediate code points.
- **__to_encoding** – [in] The encoding that will be used to encode the intermediate code points into the final code units.

Returns

An `_OutputContainer` with the result, regardless of whether an error occurs or not. If you are looking for error information and not just a quick one-off conversion function, please use `ztd::text::transcode_one_to` or `ztd::text::transcode_one_into`.

validate_decodable_as

`ztd::text::validate_decodable_as` is a function that takes an input sequence of `code_units` and attempts to validate that they can be turned into the `code_points` of the provided encoding. Unlike the `ztd::text::count_as_decoded` function, this does not take an error handler. **Any** error, even if it would be corrected over, produces a stop in the algorithm and a `validate_result/stateless_validate_result` object gets returned with the `.valid` member set to false.

The overloads of this function increase the level of control with each passed argument. At the last overload with four arguments, the function attempts to work call some extension points or falls back to the base function call in this order:

- The `text_validate_decodable_as(input, encoding, decode_state)` extension point, if possible.
- The `text_validate_decodable_as(input, encoding, decode_state, encode_state)` extension point, if possible.
- An internal, implementation-defined customization point.
- The `basic_validate_decodable_as` base function.

The base function call, `basic_validate_decodable_as`, simply performs the *core validating loop* using the *Lucky 7* design. The reason the last overload takes 2 state arguments is due to how the base implementation works from the core validating loop. If during the 3-argument overload it is detected that `text_validate_decodable_as(input, encoding, decode_state)` can be called, it will be called without attempt to create an `encode_state` value with `ztd::text::make_encode_state(...)`.

During the `basic_validate_decodable_as` loop, if it detects that there is a preferable `text_validate_decodable_as_one`, it will call that method as `text_validate_decodable_as_one(input, encoding, decode_state)` inside of the loop rather than doing the core design.

The `ztd::text::validate_result` type only includes the `decode_state` in all cases.

Note: This means that if you implement none of the extension points whatsoever, implementing the basic `decode_one` and `encode_one` functions on your Encoding Object type will guarantee a proper, working implementation.

Note: If you need to call the “basic” form of this function that takes no secret implementation shortcuts or user-defined extension points, then call `basic_validate_decodable_as` directly. This can be useful to stop infinity loops when your extension points cannot handle certain inputs and thereby needs to “delegate” to the basic case.

Functions

```
template<typename __Input, typename __Encoding, typename __DecodeState, typename __EncodeState>
constexpr auto basic_validate_decodable_as(__Input && __input, __Encoding && __encoding, __DecodeState
                                         & __decode_state, __EncodeState & __encode_state)
```

Validates the code units of the `__input` according to the `__encoding` with the given states `__decode_state` and `__encode_state` to see if it can be turned into code points.

Remark

This function explicitly does not call any extension points. It defers to doing a typical loop over the code points to verify it can be decoded into code points, and then encoded back into code units, with no errors and with the exact same value sequence as the original.

Parameters

- **__input** – [in] The input range of code units to validate is possible for encoding into code points.
- **__encoding** – [in] The encoding to verify can properly encode the input of code units.
- **__decode_state** – [in] The state to use for the decoding portion of the validation check.
- **__encode_state** – [in] The state to use for the encoding portion of the validation check.

```
template<typename _Input, typename _Encoding, typename _DecodeState, typename _EncodeState>
constexpr auto validate_decodable_as(_Input &&__input, _Encoding &&__encoding, _DecodeState
                                     &__decode_state, _EncodeState &__encode_state)
```

Validates the code units of the `__input` according to the `__encoding` with the given states `__decode_state` and `__encode_state` to see if it can be turned into code points.

Remark

This functions checks to see if extension points for `text_validate_decodable_as` is available taking the available 4 parameters. If so, it calls this. Otherwise, it defers to `ztd::text::validate_decodable_as`.

Parameters

- **__input** – [in] The input range of code units to validate is possible for encoding into code points.
- **__encoding** – [in] The encoding to verify can properly encode the input of code units.
- **__decode_state** – [in] The state to use for the decoding portion of the validation check.
- **__encode_state** – [in] The state to use for the encoding portion of the validation check.

```
template<typename _Input, typename _Encoding, typename _DecodeState>
constexpr auto validate_decodable_as(_Input &&__input, _Encoding &&__encoding, _DecodeState
                                     &__decode_state)
```

Validates the code units of the `__input` according to the `__encoding` with the given state `__decode_state` to see if it can be turned into code points.

Remark

This functions checks to see if extension points for `text_validate_decodable_as` is available taking the available 3 parameters. If so, it calls this. Otherwise, it creates an encoding state through `ztd::text::make_encode_state` before calling `ztd::text::validate_decodable_as(__input, __encoding, __decode_state, __encode_state)`.

Parameters

- **__input** – [in] The input range of code units to validate is possible for encoding into code points.
- **__encoding** – [in] The encoding to verify can properly encode the input of code units.
- **__decode_state** – [in] The state to use for the decoding portion of the validation check.

```
template<typename _Input, typename _Encoding>
constexpr auto validate_decodable_as(_Input &&__input, _Encoding &&__encoding)
```

Validates the code units of the `__input` according to the `__encoding` to see if they can be turned into code points.

Remark

This functions creates an encoding state through `ztd::text::make_decode_state` before calling the next overload of `ztd::text::validate_decodable_as`.

Parameters

- **__input** – [in] The input range of code units to validate is possible for encoding into code points.
- **__encoding** – [in] The encoding to verify can properly encode the input of code units.

```
template<typename _Input>
constexpr auto validate_decodable_as(_Input &&__input)
```

Validates the code units of the `__input` to see if it can be turned into code points.

Remark

This functions creates an encoding by passing the `value_type` of the `__input` range through `ztd::text::default_code_unit_encoding`.

Parameters

- **__input** – [in] The input range of code units to validate is possible for encoding into code points.

Returns

A `ztd::text::stateless_validate_result` detailing whether or not the input code points can be turned into code units of the corresponding encoding.

validate_encodable_as

`ztd::text::validate_encodable_as` is a function that takes an input sequence of `code_points` and attempts to validate that they can be turned into the `code_units` of the provided encoding. Unlike the `ztd::text::count_as_encoded` function, this does not take an error handler. **Any** error, even if it would be corrected over, produces a stop in the algorithm and a `validate_result/stateless_validate_result` object gets returned with the `.valid` member set to false.

The overloads of this function increase the level of control with each passed argument. At the last overload with four arguments, the function attempts to work call some extension points or falls back to the base function call in this order:

- The `text_validate_encodable_as(input, encoding, encode_state)` extension point, if possible.

- The `text_validate_encodable_as(input, encoding, encode_state, decode_state)` extension point, if possible.
- An internal, implementation-defined customization point.
- The `basic_validate_encodable_as` base function.

The base function call, `basic_validate_encodable_as`, simply performs the *core validating loop* using the *Lucky 7* design. The reason the last overload takes 2 state arguments is due to how the base implementation works from the core validating loop. If during the 3-argument overload it is detected that `text_validate_encodable_as(input, encoding, encode_state)` can be called, it will be called without attempt to create an `decode_state` value with `ztd::text::make_decode_state(...)`.

During the `basic_validate_encodable_as` loop, if it detects that there is a preferable `text_validate_decodable_as_one`, it will call that method as `text_validate_encodable_as_one(input, encoding, encode_state)` inside of the loop rather than doing the core design.

The `ztd::text::validate_result` type only includes the `encode_state` in all cases.

Note: This means that if you implement none of the extension points whatsoever, implementing the basic `decode_one` and `encode_one` functions on your Encoding Object type will guarantee a proper, working implementation.

Note: If you need to call the “basic” form of this function that takes no secret implementation shortcuts or user-defined extension points, then call `basic_validate_encodable_as` directly. This can be useful to stop infinity loops when your extension points cannot handle certain inputs and thereby needs to “delegate” to the basic case.

Functions

```
template<typename _Input, typename _Encoding, typename _EncodeState, typename _DecodeState>
constexpr auto basic_validate_encodable_as(_Input &&__input, _Encoding &&__encoding, _EncodeState
&__encode_state, _DecodeState &__decode_state)
```

Validates the code points of the `__input` according to the `__encoding` with the given states `__encode_state` and `__decode_state`.

Remark

This function explicitly does not check any of the extension points. It defers to doing a typical loop over the code points to verify it can be encoded into code units, and then decoded into code points, with no errors.

Parameters

- **__input** – [in] The input range of code points to validate is possible for encoding into code units.
- **__encoding** – [in] The encoding to verify can properly encode the input of code units.
- **__encode_state** – [in] The state to use for the encoding portion of the validation check.
- **__decode_state** – [in] The state to use for the decoding portion of the validation check, if needed.

```
template<typename _Input, typename _Encoding, typename _EncodeState, typename _DecodeState>
constexpr auto validate_encodable_as(_Input &&__input, _Encoding &&__encoding, _EncodeState
                                     &__encode_state, _DecodeState &__decode_state)
```

Validates the code points of the `__input` according to the `__encoding` with the given states `__encode_state` and `__decode_state`.

Remark

This functions checks to see if extension points for `text_validate_encodable_as` is available taking the available 4 parameters. If so, it calls this. Otherwise, it defers to doing a typical loop over the code points to verify it can be encoded into code units, and then decoded into code points, with no errors.

Parameters

- **__input** – [in] The input range of code points to validate is possible for encoding into code units.
- **__encoding** – [in] The encoding to verify can properly encode the input of code units.
- **__encode_state** – [in] The state to use for the encoding portion of the validation check.
- **__decode_state** – [in] The state to use for the decoding portion of the validation check, if needed.

```
template<typename _Input, typename _Encoding, typename _EncodeState>
constexpr auto validate_encodable_as(_Input &&__input, _Encoding &&__encoding, _EncodeState
                                     &__encode_state)
```

Validates the code points of the `__input` according to the `__encoding` with the given states `"__encode_state"`.

Remark

This functions checks to see if extension points for `text_validate_encodable_as` is available taking the available 3 parameters. If so, it calls this. Otherwise, it defers to `ztd::text::validate_encodable_as`.

Parameters

- **__input** – [in] The input range of code points to validate is possible for encoding into code units.
- **__encoding** – [in] The encoding to verify can properly encode the input of code units.
- **__encode_state** – [in] The state for encoding to use.

```
template<typename _Input, typename _Encoding>
constexpr auto validate_encodable_as(_Input &&__input, _Encoding &&__encoding)
```

Validates the code points of the `__input` according to the `"__encoding"`.

Parameters

- **__input** – [in] The input range of code points to validate is possible for encoding into code units.

- `__encoding` – [in] The encoding to verify can properly encode the input of code units.

```
template<typename _Input>  
constexpr auto validate_encodable_as(_Input &&__input)
```

Validates the code points of the input.

Remark

This passes the default encoding as inferred from the discernible `value_type` of the input range input into the `ztd::text::default_code_point_encoding`.

Parameters

`__input` – [in] The input range of code points to validate is possible for encoding into code units.

validate_transcodable_as

`ztd::text::validate_transcodable_as` is a function that takes an input sequence of `code_units` and attempts to validate that they can be turned into the `code_points` of the provided encoding. Unlike the `ztd::text::count_as_decoded` function, this does not take an error handler. **Any** error, even if it would be corrected over, produces a stop in the algorithm and a `validate_result/stateless_validate_result` object gets returned with the `.valid` member set to false.

The overloads of this function increase the level of control with each passed argument. At the last overload with four arguments, the function attempts to work call some extension points or falls back to the base function call in this order:

- The `text_validate_transcodable_as(input, from_encoding, to_encoding, decode_state, encode_state)` extension point, if possible.
- An internal, implementation-defined customization point.
- The `basic_validate_transcodable_as` base function.

The base function call, `basic_validate_transcodable_as`, simply performs the *core validating loop* using the *Lucky 7* design. The reason the last overload takes 2 state arguments is due to how the base implementation works from the core validating loop. If during the 3-argument overload it is detected that `text_validate_transcodable_as(input, encoding, decode_state)` can be called, it will be called without attempt to create an `encode_state` value with `ztd::text::make_encode_state(...)`.

During the `basic_validate_transcodable_as` loop, if it detects that there is a preferable `text_validate_transcodable_as_one`, it will call that method as `text_validate_transcodable_as_one(input, encoding, decode_state)` inside of the loop rather than doing the core design.

The `ztd::text::validate_result` type only includes the `decode_state` in all cases.

Note: This means that if you implement none of the extension points whatsoever, implementing the basic `decode_one` and `encode_one` functions on your Encoding Object type will guarantee a proper, working implementation.

Note: If you need to call the “basic” form of this function that takes no secret implementation shortcuts or user-defined extension points, then call `basic_validate_transcodable_as` directly. This can be useful to stop infinity loops when your extension points cannot handle certain inputs and thereby needs to “delegate” to the basic case.

Functions

```
template<typename _Input, typename _FromEncoding, typename _ToEncoding, typename _DecodeState,
typename _EncodeState, typename _Pivot>
constexpr auto basic_validate_transcodable_as(_Input &&__input, _FromEncoding &&__from_encoding,
_ToEncoding &&__to_encoding, _DecodeState
&__decode_state, _EncodeState &__encode_state, _Pivot
&&__pivot)
```

Validates the code units of the `__input` according to the `__from_encoding` with the given states `__decode_state` and `__encode_state` to see if it can be turned into code points, and then code units again.

Remark

This function explicitly does not call any extension points. It defers to doing a typical loop over the code points to verify it can be decoded into code points, and then encoded back into code units, with no errors and with the exact same value sequence as the original.

Parameters

- **__input** – [in] The input range of code units to validate is possible for encoding into code points.
- **__from_encoding** – [in] The encoding to verify can properly encode the input of code units.
- **__to_encoding** – [in] The encoding to verify can properly encode the input of code units.
- **__decode_state** – [inout] The state to use for the decoding portion of the validation check.
- **__encode_state** – [inout] The state to use for the encoding portion of the validation check.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) pivot range, usually a range of contiguous data from a span provided by the implementation but customizable by the end-user. If the intermediate conversion is what failed, then the `ztd::text::pivot`'s `error_code` member will be set to that error. This only happens if the overall operation also fails, and need not be checked unless to obtain additional information for when a top-level operation fails.

```
template<typename _Input, typename _FromEncoding, typename _ToEncoding, typename _DecodeState,
typename _EncodeState, typename _Pivot>
constexpr auto validate_transcodable_as(_Input &&__input, _FromEncoding &&__from_encoding,
_ToEncoding &&__to_encoding, _DecodeState &__decode_state,
_EncodeState &__encode_state, _Pivot &&__pivot)
```

Validates the code units of the `__input` according to the `__encoding` with the given states `__decode_state` and `__encode_state` to see if it can be turned into code points.

Remark

This functions checks to see if extension points for `text_validate_transcodable_as` is available taking the available 4 parameters. If so, it calls this. Otherwise, it defers to `ztd::text::validate_transcodable_as`.

Parameters

- **__input** – [in] The input range of code units to validate is possible for encoding into code points.
- **__from_encoding** – [in] The encoding to verify can properly encode the input of code units.
- **__to_encoding** – [in] The encoding to verify can properly encode the input of code units.
- **__decode_state** – [inout] The state to use for the decoding portion of the validation check.
- **__encode_state** – [inout] The state to use for the encoding portion of the validation check.
- **__pivot** – [inout] A reference to a descriptor of a (potentially usable) pivot range, usually a range of contiguous data from a span provided by the implementation but customizable by the end-user. If the intermediate conversion is what failed, then the `ztd::text::pivot`'s `error_code` member will be set to that error. This only happens if the overall operation also fails, and need not be checked unless to obtain additional information for when a top-level operation fails.

```
template<typename _Input, typename _FromEncoding, typename _ToEncoding, typename _DecodeState,
typename _EncodeState>
constexpr auto validate_transcodable_as(_Input &&__input, _FromEncoding &&__from_encoding,
                                     _ToEncoding &&__to_encoding, _DecodeState &__decode_state,
                                     _EncodeState &__encode_state)
```

Validates the code units of the `__input` according to the `__encoding` with the given states `__decode_state` and `__encode_state` to see if it can be turned into code points.

Remark

This functions checks to see if extension points for `text_validate_transcodable_as` is available taking the available 4 parameters. If so, it calls this. Otherwise, it defers to `ztd::text::validate_transcodable_as`.

Parameters

- **__input** – [in] The input range of code units to validate is possible for encoding into code points.
- **__from_encoding** – [in] The encoding to verify can properly encode the input of code units.
- **__to_encoding** – [in] The encoding to verify can properly encode the input of code units.
- **__decode_state** – [inout] The state to use for the decoding portion of the validation check.
- **__encode_state** – [inout] The state to use for the encoding portion of the validation check.

```
template<typename _Input, typename _FromEncoding, typename _ToEncoding, typename _DecodeState>
constexpr auto validate_transcodable_as(_Input &&__input, _FromEncoding &&__from_encoding,
                                     _ToEncoding &&__to_encoding, _DecodeState &__decode_state)
```

Validates the code units of the `__input` according to the `__from_encoding` object with the given state `__decode_state` to see if it can be turned into code units of the `__to_encoding` object.

Remark

This functions will call `ztd::text::make_encode_state` with `__to_encoding` to create a default `encode_state`.

Parameters

- **__input** – [in] The input range of code units to validate is possible for encoding into code points.
- **__from_encoding** – [in] The encoding to verify can properly encode the input of code units.
- **__to_encoding** – [in] The encoding to verify can properly encode the input of code units.
- **__decode_state** – [inout] The state to use for the decoding portion of the validation check.

```
template<typename _Input, typename _FromEncoding, typename _ToEncoding>
constexpr auto validate_transcodable_as(_Input &&__input, _FromEncoding &&__from_encoding,
                                         _ToEncoding &&__to_encoding)
```

Validates the code units of the `__input` according to the `__from_encoding` object to see if it can be turned into code units of the `__to_encoding` object.

Remark

This functions will call `ztd::text::make_decode_state` with the `__from_encoding` object to create a default `decode_state` to use before passing it to the next overload.

Parameters

- **__input** – [in] The input range of code units to validate is possible for encoding into code points.
- **__from_encoding** – [in] The encoding to verify can properly encode the input of code units.
- **__to_encoding** – [in] The encoding to verify can properly encode the input of code units.

```
template<typename _Input, typename _ToEncoding>
constexpr auto validate_transcodable_as(_Input &&__input, _ToEncoding &&__to_encoding)
```

Validates the code units of the `__input` according to the `__from_encoding` object to see if it can be turned into code units of the `__to_encoding` object.

Remark

This functions will call `ztd::text::make_encode_state` with `__to_encoding` to create a default `encode_state`.

Parameters

- **__input** – [in] The input range of code units to validate is possible for encoding into code points.
- **__to_encoding** – [in] The encoding to verify can properly encode the input of code units.

1.8.6 Properties and Classifications

code_point

```
template<typename _Type>
```

```
class code_point
```

Retrieves the code point type for the given type.

Public Types

```
using type = typename remove_cvref_t<Type>::code_point
```

The code point type for the given encoding type. If it does not exist, *ztd::text::unicode_code_point* is assumed.

```
template<typename _Type>
```

```
using ztd::text::code_point_t = typename code_point<Type>::type
```

A typename alias for *ztd::text::code_point*.

code_unit

```
template<typename _Type>
```

```
class code_unit
```

Retrieves the code unit type for the given type.

Public Types

```
using type = typename remove_cvref_t<Type>::code_unit
```

The code unit type for the encoding type.

```
template<typename _Type>
```

```
using ztd::text::code_unit_t = typename code_unit<remove_cvref_t<Type>>::type
```

A typename alias for *ztd::text::code_unit*.

decode_state

```
template<typename _Type>
```

```
class decode_state
```

Retrieves the *decode_state* of the encoding type if it has one, or the state type of the encoding.

Public Types

using **type** = typename __txt_detail::__decode_state<remove_cvref_t<*Type*>>::type

The *decode_state* type or state type on a given encoding type.

template<typename **_Type**>

using ztd::text::**decode_state_t** = typename *decode_state*<*Type*>::type

Typename alias for *ztd::text::decode_state*.

encode_state

template<typename **_Type**>

class **encode_state**

Retrieves the *encode_state* of the encoding type if it has one, or the state type of the encoding.

Public Types

using **type** = typename __txt_detail::__encode_state<remove_cvref_t<*Type*>>::type

The *encode_state* type or state type on a given encoding type.

template<typename **_Type**>

using ztd::text::**encode_state_t** = typename *encode_state*<*Type*>::type

Typename alias for *ztd::text::encode_state*.

max_code_points

The maximum number of code points needed for a given encoding object. This can be used to create a suitably-sized automatic storage duration buffer, e.g.

```
using code_point = ztd::text::code_point_t<ztd::text::utf8>;
constexpr std::size_t max_output_size = ztd::text::max_code_points_v<ztd::text::utf8>;

std::array<code_point, max_output_size> my_cxx_buffer;
code_point my_c_buffer[max_output_size];
```

template<typename **_Type**>

static constexpr ::std::size_t ztd::text::**max_code_points_v** = *Type*::max_code_points

Gets the maximum number of code points that can be produced by an encoding during a decode operation, suitable for initializing a automatic storage duration (“stack-allocated”) buffer.

max_code_units

The maximum number of code units needed for a given encoding object. This can be used to create a suitably-sized automatic storage duration buffer, e.g.

```
using code_unit = ztd::text::code_unit_t<ztd::text::utf8>;
constexpr std::size_t max_output_size = ztd::text::max_code_units_v<ztd::text::utf8>;

// C++-style
std::array<code_unit, max_output_size> my_cxx_buffer;
// or C-style
code_unit my_c_buffer[max_output_size];
```

```
template<typename _Type>
```

```
static constexpr ::std::size_t ztd::text::max_code_units_v = remove_cvref_t<_Type>::max_code_units
```

Gets the maximum number of code units that can be produced by an encoding during an encode operation, suitable for initializing a automatic storage duration (“stack-allocated”) buffer.

max_recode_code_points

The maximum number of code units needed for a given encoding object. This can be used to create a suitably-sized automatic storage duration buffer, e.g.

```
using code_point = ztd::text::code_point_t<ztd::text::utf8>;
constexpr std::size_t max_output_size = ztd::text::max_recode_code_points_v
↳<ztd::text::utf8, ztd::text::utf16>;

// C++-style
std::array<code_point, max_output_size> my_cxx_buffer;
// or C-style
code_point my_c_buffer[max_output_size];
```

```
template<typename _From, typename _To>
```

```
static constexpr ::std::size_t ztd::text::max_recode_code_points_v = max_code_units_v<_From> *
max_code_points_v<_To> * 2
```

Gets the maximum number of code units needed to represent a full *ztd::text::transcode_one* operation without running out of output space.

max_transcode_code_units

The maximum number of code units needed for a given encoding object. This can be used to create a suitably-sized automatic storage duration buffer, e.g.

```
using code_unit = ztd::text::code_unit_t<ztd::text::utf8>;
constexpr std::size_t max_output_size = ztd::text::max_transcode_code_units_v
↳<ztd::text::utf16, ztd::text::utf8>;

// C++-style
std::array<code_unit, max_output_size> my_cxx_buffer;
// or C-style
code_unit my_c_buffer[max_output_size];
```

```
template<typename _From, typename _To>
```

```
static constexpr ::std::size_t ztd::text::max_transcode_code_units_v = max_code_points_v<_From> *
max_code_units_v<_To> * 2
```

Gets the maximum number of code units needed to represent a full *ztd::text::transcode_one* operation without running out of output space.

is_state_independent_v

```
template<typename _Encoding, typename _Type>
```

```
constexpr bool ztd::text::is_state_independent_v = !::std::is_constructible_v<_Type, _Encoding> &&
::std::is_default_constructible_v<_Type>
```

Whether or not the given type can be constructed without information from the encoding itself.

Remark

This value tells users at compile time whether or not they need to be careful with the state. Rather than let users have to work this independently, two functions — *ztd::text::make_encode_state(_Encoding)* and *ztd::text::make_encode_state(_Encoding)* — handle the details here.

Template Parameters

- **_Encoding** – The encoding that may contain necessary information.
- **_Type** – The state type that may need information from the encoding to be successfully constructed.

is_decode_state_independent_v

```
template<typename _Encoding>
```

```
constexpr bool ztd::text::is_decode_state_independent_v = is_state_independent_v<_Encoding,
decode_state_t<_Encoding>>
```

Whether or not the encoding's *decode_state* can be constructed without information from the encoding itself.

is_encode_state_independent_v

```
template<typename _Encoding>
```

```
constexpr bool ztd::text::is_encode_state_independent_v = is_state_independent_v<_Encoding,
encode_state_t<_Encoding>>
```

Whether or not the encoding's *decode_state* can be constructed without information from the encoding itself.

is_decode_injective_v

Looks to see if the `decode_one` operation on a given encoding type is *injective*.

This classification checks whether the given encoding type has a type definition called `is_decode_injective` on it, and if it does checks to see if its `std::true_type`. If it's not present, or if it's `std::false_type`, then the encoding is assumed to NOT be *injective*.

```
template<typename _Type>
```

```
class is_decode_injective : public std::integral_constant<bool,  
__txt_detail::__is_decode_injective_sfinae<::ztd::remove_cvref_t<_Type>>::value ||  
__txt_detail::__is_injective_sfinae<::ztd::remove_cvref_t<_Type>>::value>
```

Checks whether or not the decoding step for `_Type` is injective (cannot possibly lose information regardless of whatever valid input is put in).

Remark

If the encoding object does not define *is_decode_injective*, it is assumed to be false (the safest default).

Template Parameters

`_Type` – The encoding type to check.

```
template<typename _Type>
```

```
constexpr bool ztd::text::is_decode_injective_v =  
is_decode_injective<::ztd::remove_cvref_t<_Type>>::value
```

An alias of the inner value for *ztd::text::is_decode_injective*.

is_encode_injective_v

Looks to see if the `encode_one` operation on a given encoding type is *injective*.

This classification checks whether the given encoding type has a type definition called `is_encode_injective` on it, and if it does checks to see if its `std::true_type`. If it's not present, or if it's `std::false_type`, then the encoding is assumed to NOT be *injective*.

```
template<typename _Type>
```

```
class is_encode_injective : public std::integral_constant<bool,  
__txt_detail::__is_encode_injective_sfinae<_Type>::value || __txt_detail::__is_injective_sfinae<_Type>::value>
```

Checks whether or not the encoding step for `_Type` is injective (cannot possibly lose information regardless of whatever valid input is put in).

Remark

If the encoding object does not define *is_encode_injective*, it is assumed to be false (the safest default).

Template Parameters

`_Type` – The encoding type to check.

```
template<typename _Type>
```

```
constexpr bool ztd::text::is_encode_injective_v = is_encode_injective<_Type>::value
```

An alias of the inner value for *ztd::text::is_encode_injective*.

is_code_units_(maybe_)replaceable

These two traits detect whether or not the given Encoding type have calls on them which return either a replacement range (*is_code_units_replaceable*) or a `std::optional` of a replacement range (*is_code_units_maybe_replaceable*).

The former is useful when it is guaranteed that your encoding will have a replacement range on it and does not need the extra cost of an indirection from not knowing. The latter is useful when something like a wrapped encoding may or may not have a replacement sequence.

```
template<typename _Type, typename ..._Args>
```

```
class is_code_units_replaceable : public is_detected<__txt_detail::__detect_is_code_units_replaceable, _Type, _Args...>
```

Checks whether the given encoding type returns a maybe-replacement range of code units.

Remark

The value boolean is true if the given `_Type` has a function named `replacement_code_units()` on it that can be called from a `const`-qualified `_Type` which returns a contiguous view of code units.

Template Parameters

_Type – The type to check for the proper function call.

```
template<typename _Type, typename ..._Args>
```

```
constexpr bool ztd::text::is_code_units_replaceable_v = is_code_units_replaceable<_Type, _Args...>::value
```

An alias of the inner value for *ztd::text::is_code_units_replaceable*.

```
template<typename _Type, typename ..._Args>
```

```
class is_code_units_maybe_replaceable : public is_detected<__txt_detail::__detect_is_code_units_maybe_replaceable, _Type, _Args...>
```

Checks whether the given encoding type returns a maybe-replacement range of code units.

Remark

The value boolean is true if the given `_Type` has a function named `maybe_replacement_code_units()` on it that can be called from a `const`-qualified `_Type` which returns a `std::optional` containing a contiguous view of code units.

Template Parameters

_Type – The type to check for the proper function call.

```
template<typename _Type, typename ..._Args>
constexpr bool ztd::text::is_code_units_maybe_replaceable_v =
is_code_units_maybe_replaceable<_Type, _Args...>::value
```

An alias of the inner value for *ztd::text::is_code_units_maybe_replaceable*.

is_code_points_(maybe_)replaceable

These two traits detect whether or not the given Encoding type have calls on them which return either a replacement range (*is_code_points_replaceable*) or a `std::optional` of a replacement range (*is_code_points_maybe_replaceable*).

The former is useful when it is guaranteed that your encoding will have a replacement range on it and does not need the extra cost of an indirection from not knowing. The latter is useful when something like a wrapped encoding may or may not have a replacement sequence.

```
template<typename _Type, typename ..._Args>
class is_code_points_replaceable : public is_detected<__txt_detail::__detect_is_code_points_replaceable,
_Type, _Args...>
```

Checks whether the given encoding type returns a maybe-replacement range of code points.

Remark

The value `boolean` is true if the given `_Type` has a function named `replacement_code_points()` on it that can be called from a `const` -qualified `_Type` object which returns a contiguous view of code points.

Template Parameters

_Type – The type to check for the proper function call.

```
template<typename _Type, typename ..._Args>
constexpr bool ztd::text::is_code_points_replaceable_v = is_code_points_replaceable<_Type,
_Args...>::value
```

An alias of the inner value for *ztd::text::is_code_points_replaceable*.

```
template<typename _Type, typename ..._Args>
class is_code_points_maybe_replaceable : public
is_detected<__txt_detail::__detect_is_code_points_maybe_replaceable, _Type, _Args...>
```

Checks whether the given encoding type returns a maybe-replacement range of code points.

Remark

The value `boolean` is true if the given `_Type` has a function named `maybe_replacement_code_points()` on it that can be called from a `const` -qualified `_Type` object which returns a `std::optional` containing a contiguous view of code points.

Template Parameters

_Type – The type to check for the proper function call.

```
template<typename _Type, typename ..._Args>
constexpr bool ztd::text::is_code_points_maybe_replaceable_v =
is_code_points_maybe_replaceable<_Type, _Args...>::value
```

An alias of the inner value for *ztd::text::is_code_points_maybe_replaceable*.

is_ignorable_error_handler

```
template<typename _Type>
class is_ignorable_error_handler : public
__is_ignorable_error_handler_sfinae<::ztd::remove_cvref_t<_Type>>
```

Whether or not the given *_Type* is an error handler that can be ignored.

Remark

An error handler type can mark itself as ignorable by using a `using assume_valid = std::integral_constant<bool, value>` where `value` determines if the type's error handling callback can be ignored. This is what `ztd::text::assume_valid` does. Being configurable means templated error handlers can select whether or not they should be ignorable based on compile time, safe conditions that you can make up (including checking Macros or other environment data as a means of determining whether or not validity should be ignored.) If this results in a type derived from `std::true_type` and the encoder object using it encounters an error, then it is Undefined Behavior what occurs afterwards.

Template Parameters

_Type – the Error Handling type to chec.

```
template<typename _Type>
constexpr bool ztd::text::is_ignorable_error_handler_v =
is_ignorable_error_handler<::ztd::remove_cvref_t<_Type>>::value
```

An alias of the inner value for *ztd::text::is_ignorable_error_handler*.

is_state_complete

```
template<typename _Encoding, typename _State>
constexpr bool ztd::text::is_state_complete(_Encoding &__encoding, _State &__state) noexcept
```

Returns whether or not a state has completed any associated operations and has no more manipulations on the output to perform, even if the input source is empty.

Remark

If the state does not have a member function `is_complete`, then this will simply return `true`. Otherwise, it invokes `__state.is_complete()`.

Parameters

- **__encoding** – [in] The encoding for the state.

- `__state` – [in] The state to check for completion.

is_unicode_encoding

Note: User Specializations: ✓ Okay! You can add other types to this classification by specializing the class template to a definition that derives from `std::true_type`, or turn it off explicitly by having a definition that derives from `std::false_type`. Note that specializing any type not explicitly marked with this notice is Undefined Behavior.

```
template<typename _Type>
class is_unicode_encoding : public __is_unicode_encoding_sfinae<::ztd::remove_cvref_t<_Type>>
    Checks whether or not the encoding has declared it can handle all of Unicode.
```

Remark

If the encoding object does not define `is_unicode_encoding`, it is assumed to be false (the safest default).

Template Parameters

`_Type` – The encoding type to check.

```
template<typename _Type>
constexpr bool ztd::text::is_unicode_encoding_v =
is_unicode_encoding<::ztd::remove_cvref_t<_Type>>::value
    An alias of the inner value for ztd::text::is_unicode_encoding.
```

contains_unicode_encoding

This function determines whether or not the type is or contains a unicode encoding. This means any encoding wherein the entirety of Unicode, all 21 bits, can be represented without loss of information. For a full list of encodings which are considered Unicode Encodings by this library, see *the Known Unicode Encodings list*.

This function checks for 2 things.

- It checks to see if the call `encoding.contains_unicode_encoding()` is well-formed and returns a boolean value. If this is the case, it calls `encoding.contains_unicode_encoding()` and returns that value.
- It looks to see if the provided encoding has a member type called `::is_unicode_encoding`. If this is the case, then it returns `is_unicode_encoding_v<Type>`.

If none of these work, then it returns `false`.

```
template<typename _Encoding>
constexpr bool ztd::text::contains_unicode_encoding(const _Encoding &__encoding) noexcept
    Whether or not the provided encoding is a Unicode encoding.
```

Remark

This function first checks if there is a function called `contains_unicode_encoding`. If it is present, then it returns the value of that function directly. Otherwise, it checks if `ztd::text::is_unicode_encoding_v` is true for the provided `__encoding`. If that's the case, then `true` is returned. Otherwise, it assumes the encoding is not a Unicode-compatible encoding and returns `false`.

Parameters

`__encoding` – [in] The encoding to query.

is_unicode_code_point

This checks if the provided type is a `unicode_code_point`.

Note: User Specializations: ✓ Okay! You can add other types to this classification by specializing the class template to a definition that derives from `std::true_type`, or turn it off explicitly by having a definition that derives from `std::false_type`. Note that specializing any type not explicitly marked with this notice is Undefined Behavior.

Warning: Note there are some *expectations of unicode code points*. If your type violates these expectations then code depending on them is free to execute Undefined Behavior.

```
template<typename _Type>
class is_unicode_code_point : public std::integral_constant<bool,
::std::is_same_v<::ztd::remove_cvref_t<_Type>, char32_t> || ::std::is_same_v<::ztd::remove_cvref_t<_Type>,
__txt_impl::__unicode_code_point> || is_unicode_scalar_value_v<::ztd::remove_cvref_t<_Type>>>
template<typename _Type>
constexpr bool ztd::text::is_unicode_code_point_v =
is_unicode_code_point<::ztd::remove_cvref_t<_Type>>::value
```

is_unicode_scalar_value

This checks if the provided type is a `unicode_scalar_value`.

Note: User Specializations: ✓ Okay! You can add other types to this classification by specializing the class template to a definition that derives from `std::true_type`, or turn it off explicitly by having a definition that derives from `std::false_type`. Note that specializing any type not explicitly marked with this notice is Undefined Behavior.

Warning: Note there are some *expectations of scalar value types*. If your type violates these expectations then code depending on them is free to execute Undefined Behavior.

```
template<typename _Type>
class is_unicode_scalar_value : public std::integral_constant<bool,
::std::is_same_v<::ztd::remove_cvref_t<_Type>, __txt_impl::__unicode_scalar_value>>
template<typename _Type>
```

```
constexpr bool ztd::text::is_unicode_scalar_value_v =  
is_unicode_scalar_value<::ztd::remove_cvref_t<_Type>>::value
```

is_(bitwise_)transcoding_compatible

This classification checks if two encodings are compatible, or bitwise compatible. The heuristic for normal compatibility is simple:

- it checks if the two encodings are identical;
- it checks if the two encodings are near-identical derivations of one another (e.g., *UTF-8* being converted to *MUTF-8* (but not in the other direction)); or,
- it checks if the code point types between the two encodings are the same, or if they are *both some form of unicode code point*.

This type specifically uses the first type as the `From` encoding (e.g., the one to decode the input code unit sequence) and the second type as the `To` encoding (e.g., the one to encode the intermediate decoded code point sequence).

Note: User Specializations: ✓ Okay! You can add other types to this classification by specializing the class template to a definition that derives from `std::true_type`, or turn it off explicitly by having a definition that derives from `std::false_type`. Note that specializing any type not explicitly marked with this notice is Undefined Behavior.

Warning: Specializing this type for types which are not either transcoding compatible or bitwise compatible can result in Undefined Behavior within the library.

```
template<typename _From, typename _To>
```

```
class is_transcoding_compatible : public std::integral_constant<bool,  
__txt_detail::__is_bitwise_transcoding_compatible_v<_From, _To>>
```

Checks whether or not the specified `_From` encoding can be transcoded to the `_To` encoding without invoking a lossy conversion when using the intermediate code points.

Remark

First, it checks if the encodings are bitwise compatible with one another (e.g., transcoding ASCII to UTF-8). If that is not the case, then it checks if the two encodings are just identical. Finally, it checks if the code point types are the same or if it's putting unicode scalar values into unicode code points (which is valid one way, but not the other way since scalar values do not allow surrogates). If none of these are true, then, the intermediate code point likely cannot convert between the two losslessly.

Template Parameters

- `_From` – The encoding that is going to decode the input code units into the intermediate code points.
- `_To` – The encoding that is going to encode the intermediate code points into the final code units.

```
template<typename _From, typename _To>
```

constexpr bool ztd::text::is_transcoding_compatible_v = is_transcoding_compatible<_To, _From>::value
 An alias of the inner value for *ztd::text::is_transcoding_compatible*.

template<typename _From, typename _To>

class **is_bitwise_transcoding_compatible** : public std::integral_constant<bool,
 __txt_detail::__is_bitwise_transcoding_compatible_v<_From, _To>>

Checks whether or not the specified _From encoding can be transcoded to the _To encoding without by form of bit copying.

Template Parameters

- **_From** – The encoding that is going to decode the input code units into the intermediate code points.
- **_To** – The encoding that is going to encode the intermediate code points into the final code units.

template<typename _From, typename _To>

constexpr bool ztd::text::is_bitwise_transcoding_compatible_v =
is_bitwise_transcoding_compatible<::ztd::remove_cvref_t<_From>, ::ztd::remove_cvref_t<_To>>::value

An alias of the inner value for *ztd::text::is_transcoding_compatible*.

is_input_error_skippable

For an encoding object *encoding*, it checks that there exists a function that can be called with the format *encoding.skip_input_error(result)*, where *result* is either a *ztd::text::decode_result<...>* (for decoding operations which have failed) and *ztd::text::encode_result<...>* (for encoding operations which have failed). This allows an encoding to control precisely how to move ahead with the input when a problem is encountered.

template<typename _Encoding, typename _Result, typename _InputProgress, typename _OutputProgress>

class **is_input_error_skippable** : public std::integral_constant<bool,
 is_detected_v<__txt_detail::__detect_skip_input_error, _Encoding, _Result, _InputProgress, _OutputProgress>>

Whether or not the given _Encoding has a function called *skip_input_error* that takes the given _Result type with the given _InputProgress and _OutputProgress types.

Remark

This is used by *ztd::text::replacement_handler* and *ztd::text::skip_handler* to pass over malformed input when it happens.

Template Parameters

- **_Encoding** – The encoding that may contain the *skip_input_error* function.
- **_Result** – The result type to check if the input is callable.
- **_InputProgress** – The input progress type passed in to the error handler to be forwarded to the skip input error.
- **_OutputProgress** – The output progress type passed in to the error handler to be forwarded to the skip input error.

```
template<typename _Encoding, typename _Result, typename _InputProgress, typename _OutputProgress>
constexpr bool ztd::text::is_input_error_skippable_v = is_input_error_skippable<_Encoding, _Result,
    _InputProgress, _OutputProgress>::value
```

An alias of the inner value for `ztd::text::is_input_error_skippable`.

is_self_synchronizing_code

An encoding – after experiencing an error or when being dropped into the middle – can seek out the start of the next sequence of well-formed input unambiguously, compared with other encodings that reuse bit patterns from the first matching code unit / byte in subsequent code units / bytes in that pattern. This becomes a property of the encoding, and is therefore called *self synchronizing*. Self synchronizing codes are frequently considered superior when there is a lack of context.

The primary *Unicode encodings* are self synchronizing, but other versions both proprietary and not may fail to be self-synchronizing such as UTF-7.

```
template<typename _Type>
```

```
class is_self_synchronizing_code : public
    __is_self_synchronizing_code_sfinae<::ztd::remove_cvref_t<_Type>>
```

Checks whether not an encoding has distinct sequences that can be identified unambiguously from anywhere within a larger sequence. This implies that the start of any given sequence — including sequences that are a single input unit — can be reliably identified even in a stream full of errors.

Template Parameters

_Type –

```
template<typename _Type>
```

```
constexpr bool ztd::text::is_self_synchronizing_code_v =
    is_self_synchronizing_code<::ztd::remove_cvref_t<_Type>>::value
```

An alias for `ztd::is_self_synchronizing_code`'s inner value.

Template Parameters

_Type – The encoding type to check.

default_code_point_encoding

Picks the default encoding for the given code point type. In all cases, this just points a given code point type to `ztd::text::utf8`. Errors if there is no default association.

Note: User Specializations: ✓ Okay! You can add other types to this classification by specializing the class template. Your specialization must have a type definition named `type` (as in, `using type = ...;` or `typedef... type;`) inside of the class specialization that is `public`:ly accessible. Note that specializing any type not explicitly marked with this notice is Undefined Behavior.

```
template<typename _Type>
```

```
class default_code_point_encoding : public __default_code_point_encoding<_Type, false>
```

The default encoding associated with a given code point type, that serves as either input to an encode operation or output from decode operation.

Template Parameters

_Type – The code point type, with no cv-qualifiers

```
template<typename _Type>
```

```
using ztd::text::default_code_point_encoding_t = typename default_code_point_encoding<_Type>::type
    A typename alias for ztd::text::default_code_point_encoding.
```

Template Parameters

_Type – The code point type, with no cv-qualifiers

```
template<typename _Type>
```

```
class default_consteval_code_point_encoding : public __default_code_point_encoding<_Type, true>
```

The default encoding associated with a given code point type, that serves as either input to an encode operation or output from decode operation. This uses additional information that this is at compile time, not run time, to help make a decision as to what to do.

Template Parameters

_Type – The code point type, with no cv-qualifiers

```
template<typename _Type>
```

```
using ztd::text::default_consteval_code_point_encoding_t = typename
    default_consteval_code_point_encoding<_Type>::type
```

A typename alias for *ztd::text::default_consteval_code_point_encoding*.

Template Parameters

_Type – The code point type, with no cv-qualifiers

default_code_unit_encoding

Picks the default encoding for the given code unit type (for both run time, and compile time with the appropriately selected version of this property). The default association table is below. Errors if there is no default association.

Note: User Specializations: ✓ Okay! You can add other types to this classification by specializing the class template. Your specialization must have a type definition named `type` (as in, `using type = ...;` or `typedef... type;`) inside of the class specialization that is publicly accessible. Note that specializing any type not explicitly marked with this notice is Undefined Behavior.

Type	Encoding
signed char	<i>ztd::text::basic_ascii<signed char></i>
char	<i>ztd::text::execution</i>
char (compile time)	<i>ztd::text::literal</i>
wchar_t	<i>ztd::text::wide_execution</i>
wchar_t (compile time)	<i>ztd::text::wide_literal</i>
char8_t	<i>ztd::text::basic_utf8<char8_t></i>
ztd::uchar8_t	<i>ztd::text::basic_utf8<uchar8_t></i>
std::byte	<i>ztd::text::basic_utf8<std::byte></i>
char16_t	<i>ztd::text::utf16</i>
char32_t	<i>ztd::text::utf32</i>

```
template<typename _Type>
```

```
class default_code_unit_encoding : public __default_code_unit_encoding<_Type, false>
```

The default encoding associated with a given code unit type, that serves as either input to a decode operation or output from an encode operation.

Template Parameters

_Type – The code unit type, with no cv-qualifiers

```
template<typename _Type>
```

```
using ztd::text::default_code_unit_encoding_t = typename default_code_unit_encoding<_Type>::type
```

A typename alias for `ztd::text::default_code_unit_encoding`.

Template Parameters

_Type – The code unit type, with no cv-qualifiers

```
template<typename _Type>
```

```
class default_consteval_code_unit_encoding : public __default_code_unit_encoding<_Type, true>
```

The default encoding associated with a given code unit type, that serves as either input to a decode operation or output from an encode operation. This uses the additional information that this is compiletime, not runtime, to help make the decision on what to do.

Template Parameters

_Type – The code unit type, with no cv-qualifiers

```
template<typename _Type>
```

```
using ztd::text::default_consteval_code_unit_encoding_t = typename  
default_consteval_code_unit_encoding<_Type>::type
```

A typename alias for `ztd::text::default_consteval_code_unit_encoding`.

Template Parameters

_Type – The code unit type, with no cv-qualifiers

1.8.7 Result Types, Status Codes and Quality Aides

pivot

```
template<typename>
```

```
class pivot
```

encoding_error

```
enum class ztd::text::encoding_error : int
```

Describes a failure to encode, decode, transcode, or count, for four core various reasons.

Remark

This does not cover specific failures, like if a sequence was overlong (e.g., UTF-8) or if an encode operation produced an unpaired surrogate value (e.g. UTF-16).

Values:

enumerator `ok`

The okay status; everything is fine.

Remark

This does not necessarily mean an error handler was not called. An error handler can set the error code to `ztd::text::encoding_error::ok` after performing corrective action: see `ztd::text::replacement_handler_t` for an example.

enumerator `invalid_sequence`

Input contains ill-formed sequences. This means there were available units of input to read, but what was read resulted in an error.

enumerator `incomplete_sequence`

Input contains incomplete sequences. This means that the input was exhausted, without finding an invalid sequence, and therefore more input may be required.

Remark

Depending on context, this may or may not be an error in your use case (e.g., reading part of an incomplete network buffer and waiting for more). See `ztd::text::basic_incomplete_handler` as a way to aid with this use case.

enumerator `insufficient_output_space`

Output cannot receive the successfully encoded or decoded sequence. This means that, while there were no invalid or incomplete sequences in the input, the output ran out of space to receive it.

Remark

Provide a bigger storage area or guarantee that it meets the minimum required size for potential output. This can be queried for an encoding by using `ztd::text::max_code_points_v<the_encoding>` for code points, and `ztd::text::max_code_units_v<the_encoding>` for code units.

```
inline constexpr ::std::string_view ztd::text::to_name(encoding_error __error_code)
```

Converts an `encoding_error` to a string value.

Remark

If a value outside of the allowed `encoding_error` is passed, then undefined behavior happens.

Returns

A null-terminated `string_view` to the data.

make_decode_state

This detects when the `decode_state` of a given `encoding` requires the `encoding` itself to make said state. If so, it will call the `decode_state`'s constructor with the `encoding` passed in. Otherwise, it simply default-constructs a state. In either case, the constructed value is returned to the user.

The classification for this is done by `ztd::text::is_decode_state_independent`.

```
template<typename _Encoding>
constexpr decode_state_t<remove_cvref_t<Encoding>> ztd::text::make_decode_state(Encoding
                                                                    &__encoding)
                                                                    noexcept
```

Constructs the `decode_state` of the given `encoding`, based on whether or not the `encoding` and state meet the criteria of `ztd::text::is_decode_state_independent_v`.

Parameters

__encoding – [in] The `encoding` object to use, if applicable, for the construction of the state.

```
template<typename _Encoding>
constexpr decode_state_t<remove_cvref_t<Encoding>> ztd::text::make_decode_state_with(Encoding
                                                                    &__encoding,
                                                                    const en-
                                                                    code_state_t<remove_cvref_t<i
                                                                    &__en-
                                                                    code_state)
                                                                    noexcept
```

Constructs the `decode_state` of the given `encoding`, based on whether or not the `encoding` and state meet the criteria of `ztd::text::is_decode_state_independent_v` or whether it can be created by copy construction from the given `__encode_state`.

Parameters

- **__encoding** – [in] The `encoding` object to use, if applicable, for the construction of the state.
- **__encode_state** – [in] A preexisting state from the encoder.

make_encode_state

This detects when the `encode_state` of a given `encoding` requires the `encoding` itself to make said state. If so, it will call the `encode_state`'s constructor with the `encoding` passed in. Otherwise, it simply default-constructs a state. In either case, the constructed value is returned to the user.

The classification for this is done by `ztd::text::is_encode_state_independent`.

```
template<typename _Encoding>
constexpr encode_state_t<remove_cvref_t<Encoding>> ztd::text::make_encode_state(Encoding
                                                                    &__encoding)
                                                                    noexcept
```

Constructs the `encode_state` of the given `encoding`, based on whether or not the `encoding` and state meet the criteria of `ztd::text::is_encode_state_independent_v`.

Parameters

__encoding – [in] The `encoding` object to use, if applicable, for the construction of the state.

```
template<typename _Encoding>
```

```
constexpr encode_state_t<remove_cvref_t<Encoding>> ztd::text::make_encode_state_with(Encoding
                                                                    &__encoding,
                                                                    const de-
                                                                    code_state_t<remove_cvref_t<...
                                                                    &__de-
                                                                    code_state)
                                                                    noexcept
```

Constructs the *encode_state* of the given encoding, based on whether or not the encoding and state meet the criteria of *ztd::text::is_encode_state_independent_v* or whether it can be created by copy construction from the given *__decode_state*.

Parameters

- **__encoding** – [in] The encoding object to use, if applicable, for the construction of the state.
- **__decode_state** – [in] A preexisting state from the decoder.

unicode_code_point

If *ZTD_TEXT_UNICODE_CODE_POINT_DISTINCT_TYPE* is turned on, this type definition points to an internal class which implements the invariant of being a *unicode code point*. Otherwise, it is simply *char32_t*.

A unicode code point is stored as an at least 32-bit value, but may occupy more space depending on the architecture. It requires 21 bits of space to fit the required unicode code point definition. If the distinct type is used, then this type will trap (abort/assert) if the value is greater than the allowed 21 bits.

```
typedef char32_t ztd::text::unicode_code_point
```

Internal Type

Warning: Names with double underscores, and within the *__*detail* and *__*impl* namespaces are reserved for the implementation. Referencing this entity directly is bad, and the name/functionality can be changed at any point in the future. Relying on anything not guaranteed by the documentation is Undefined Behavior.

```
class __unicode_code_point
```

A 32-bit value that is within the allowed 21 bits of Unicode. Can be one of the surrogate values.

Public Functions

```
__unicode_code_point() noexcept = default
```

Constructs a code point value of indeterminate value (if no parentheses/brackets are provided) or with the value 0 (if parentheses/brackets are provided for intentional value initialization).

```
inline constexpr __unicode_code_point(char32_t __code_point) noexcept
```

Constructs a code point value with the given code point value.

Remark

inline explicit constexpr **operator char32_t**() const noexcept

An explicit conversion to a typical char32_t value, bit-compatible with a normal code point value.

inline constexpr const char32_t &**value**() const & noexcept

Retrieves the underlying value.

inline constexpr char32_t &**value**() & noexcept

Retrieves the underlying value.

inline constexpr char32_t &&**value**() && noexcept

Retrieves the underlying value.

unicode_scalar_value

If `ZTD_TEXT_UNICODE_SCALAR_VALUE_DISTINCT_TYPE` is turned on, this type definition points to an internal class which implements the invariant of being a *unicode scalar value*. Otherwise, it is simply `char32_t`.

A unicode scalar value is stored as an at least 32-bit value, but may occupy more space depending on the architecture. It requires 21 bits of space to fit the required unicode code point definition. If the distinct type is used, then this type will trap (`abort/assert`) if the value is greater than the allowed 21 bits, or if the value results in one of the Unicode Surrogate Pair values used for UTF-16 encoding and decoding. Not recommended for `ztd::text::wtf8` usage, as that encoding produces Unicode Surrogate Pair values intentionally.

typedef char32_t ztd::text::**unicode_scalar_value**

Internal Type

Warning: Names with double underscores, and within the `__*detail` and `__*impl` namespaces are reserved for the implementation. Referencing this entity directly is bad, and the name/functionality can be changed at any point in the future. Relying on anything not guaranteed by the documentation is Undefined Behavior.

class **__unicode_scalar_value**

A 32-bit value that is within the allowed 21 bits of Unicode and is not one of the Surrogate values.

Remark

The invariant is enforced with an assertion in normal modes, and can optionally be enforced by turning on `ZTD_TEXT_UNICODE_SCALAR_VALUE_INVARIANT_ABORT`.

Public Functions

`__unicode_scalar_value()` noexcept = default

Constructs a scalar value of indeterminate value (if no parentheses/brackets are provided) or with the value 0 (if parentheses/brackets are provided for intentional value initialization).

inline constexpr `__unicode_scalar_value(char32_t __code_point)` noexcept

Constructs a scalar value with the given code point value.

Remark

inline explicit constexpr `operator char32_t()` const noexcept

An explicit conversion to a typical char32_t value, bit-compatible with a normal code point value.

inline constexpr const char32_t &`value()` const & noexcept

Retrieves the underlying value.

inline constexpr char32_t &`value()` & noexcept

Retrieves the underlying value.

inline constexpr char32_t &&`value()` && noexcept

Retrieves the underlying value.

stateless_decode_result

template<typename `_Input`, typename `_Output`>

class `stateless_decode_result`

The result of all decode operations from encoding objects and higher-level calls (such as `ztd_text_decode`).

Subclassed by `decode_result<_Input, _Output, _State >`

Public Functions

template<typename `_ArgInput`, typename `_ArgOutput`,
 ::std::enable_if_t<__txt_detail::__result_type_copy_constraint<::ztd::text::stateless_decode_result, `_Input`,
`_ArgInput`, `_Output`, `_ArgOutput`>()* = nullptr>

inline constexpr `stateless_decode_result`(const `stateless_decode_result<_ArgInput, _ArgOutput>`
 &`__other`) noexcept
 cept(__txt_detail::__result_type_copy_noexcept<::ztd::text::stateless_decode_res
`_Input, _ArgInput, _Output, _ArgOutput`>)

Constructs a `ztd::text::decode_result` with the provided parameters and information, including whether or not an error was handled.

Parameters

`__other` – [in] A different but related result type.

template<typename `_ArgInput`, typename `_ArgOutput`,
 ::std::enable_if_t<__txt_detail::__result_type_move_constraint<::ztd::text::stateless_decode_result, `_Input`,
`_ArgInput`, `_Output`, `_ArgOutput`>()* = nullptr>

```
inline constexpr stateless_decode_result(stateless_decode_result<_ArgInput, _ArgOutput>
&&__other) noexcept(
__txt_detail::result_type_move_noexcept<::ztd::text::stateless_decode_re-
_Input, _ArgInput, _Output, _ArgOutput>)
```

Constructs a *ztd::text::decode_result* with the provided parameters and information, including whether or not an error was handled.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgState>
inline constexpr stateless_decode_result(_ArgInput &&__input, _ArgOutput &&__output,
encoding_error __error_code = encoding_error::ok) noexcept(
noexcept(stateless_decode_result(::std::forward<_ArgInput>(__input),
::std::forward<_ArgOutput>(__output), __error_code,
__error_code != encoding_error::ok)))
```

Constructs a *ztd::text::decode_result*, defaulting the error code to *ztd::text::encoding_error::ok* if not provided.

Parameters

- **__input** – [in] The input range to store.
- **__output** – [in] The output range to store.
- **__error_code** – [in] The error code for the decoding operation, if any.

```
template<typename _ArgInput, typename _ArgOutput>
inline constexpr stateless_decode_result(_ArgInput &&__input, _ArgOutput &&__output,
encoding_error __error_code, ::std::size_t __error_count)
noexcept(::std::is_nothrow_constructible_v<_Input,
_ArgInput> && ::std::is_nothrow_constructible_v<_Output,
_ArgOutput>)
```

Constructs a *ztd::text::decode_result* with the provided parameters and information, including whether or not an error was handled.

Parameters

- **__input** – [in] The input range to store.
- **__output** – [in] The output range to store.
- **__error_code** – [in] The error code for the decode operation, taken as the first of either the decode operation that failed.
- **__error_count** – [in] Whether or not an error was handled. Some error handlers are corrective (see *ztd::text::replacement_handler_t*), and so the error code is not enough to determine if the handler was invoked. This allows the value to be provided directly when constructing this result type.

```
inline constexpr bool errors_were_handled() const noexcept
```

Whether or not any errors were handled.

Returns

Simply checks whether *error_count* is greater than 0.

Public Members

_Input **input**

The reconstructed `input_view` object, with its `.begin()` incremented by the number of code units successfully read (can be identical to `.begin()` on original range on failure).

_Output **output**

The reconstructed `output_view` object, with its `.begin()` incremented by the number of code units successfully written (can be identical to `.begin()` on original range on failure).

encoding_error **error_code**

The kind of error that occurred, if any.

`::std::size_t` **error_count**

The number of times an error occurred in the processed input text.

decode_result

```
template<typename _Input, typename _Output, typename _State>
```

```
class decode_result : public ztd::text::stateless_decode_result<_Input, _Output>
```

The result of all decode operations from encoding objects and higher-level calls (such as `ztd_text_decode`).

Public Functions

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgState,
::std::enable_if_t<__txt_detail::__result_type_copy_constraint<::ztd::text::decode_result, _Input, _ArgInput,
_Output, _ArgOutput, _State, _ArgState>()>* = nullptr>
inline constexpr decode_result(const decode_result<_ArgInput, _ArgOutput, _ArgState> &__other) noexcept(
    __txt_detail::__result_type_copy_noexcept<::ztd::text::decode_result,
    _Input, _ArgInput, _Output, _ArgOutput, _State, _ArgState>)
```

Constructs a `ztd::text::decode_result` from a previous `decode_result`.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgState,
::std::enable_if_t<__txt_detail::__result_type_move_constraint<::ztd::text::decode_result, _Input, _ArgInput,
_Output, _ArgOutput, _State, _ArgState>()>* = nullptr>
inline constexpr decode_result(decode_result<_ArgInput, _ArgOutput, _ArgState> &&__other) noexcept(
    __txt_detail::__result_type_move_noexcept<::ztd::text::decode_result,
    _Input, _ArgInput, _Output, _ArgOutput, _State, _ArgState>)
```

Constructs a `ztd::text::decode_result` from a previous `decode_result`.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgState>
```

```
inline constexpr decode_result(_ArgInput &&__input, _ArgOutput &&__output, _ArgState &&__state,  
                                encoding_error __error_code = encoding_error::ok)
```

Constructs a `ztd::text::decode_result`, defaulting the error code to `ztd::text::encoding_error::ok` if not provided.

Parameters

- **__input** – [in] The input range to store.
- **__output** – [in] The output range to store.
- **__state** – [in] The state related to the Encoding that performed the decode operation.
- **__error_code** – [in] The error code for the decoding operation, if any.

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgState>  
inline constexpr decode_result(_ArgInput &&__input, _ArgOutput &&__output, _ArgState &&__state,  
                                encoding_error __error_code, ::std::size_t __error_count)
```

Constructs a `ztd::text::decode_result` with the provided parameters and information, including whether or not an error was handled.

Parameters

- **__input** – [in] The input range to store.
- **__output** – [in] The output range to store.
- **__state** – [in] The state related to the Encoding that performed the decode operation.
- **__error_code** – [in] The error code for the decode operation, taken as the first of either the decode operation that failed.
- **__error_count** – [in] Whether or not an error was handled. Some error handlers are corrective (see `ztd::text::replacement_handler_t`), and so the error code is not enough to determine if the handler was invoked. This allows the value to be provided directly when constructing this result type.

```
inline constexpr bool errors_were_handled() const noexcept
```

Whether or not any errors were handled.

Returns

Simply checks whether `error_count` is greater than 0.

Public Members

```
::ztd::reference_wrapper<_State> state
```

The state of the associated Encoding used for decoding input code units to code points.

_Input **input**

The reconstructed `input_view` object, with its `.begin()` incremented by the number of code units successfully read (can be identical to `.begin()` on original range on failure).

_Output **output**

The reconstructed `output_view` object, with its `.begin()` incremented by the number of code units successfully written (can be identical to `.begin()` on original range on failure).

***encoding_error* error_code**

The kind of error that occurred, if any.

::std::size_t error_count

The number of times an error occurred in the processed input text.

stateless_encode_result

```
template<typename _Input, typename _Output>
```

```
class stateless_encode_result
```

The result of all encode operations from encoding objects and higher-level calls (such as `ztd_text_encode`).

Subclassed by `encode_result<_Input, _Output, _State >`

Public Functions

```
template<typename _ArgInput, typename _ArgOutput,
::std::enable_if_t<__txt_detail::__result_type_copy_constraint<::ztd::text::stateless_encode_result, _Input,
_ArgInput, _Output, _ArgOutput>()* = nullptr>
```

```
inline constexpr stateless_encode_result(const stateless_encode_result<_ArgInput, _ArgOutput>
&__other) noexcept
cept(__txt_detail::__result_type_copy_noexcept<::ztd::text::stateless_encode_re
_Input, _ArgInput, _Output, _ArgOutput>())
```

Constructs a `ztd::text::encode_result` with the provided parameters and information, including whether or not an error was handled.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput,
::std::enable_if_t<__txt_detail::__result_type_move_constraint<::ztd::text::stateless_encode_result, _Input,
_ArgInput, _Output, _ArgOutput>()* = nullptr>
```

```
inline constexpr stateless_encode_result(stateless_encode_result<_ArgInput, _ArgOutput>
&&__other) noexcept
cept(__txt_detail::__result_type_move_noexcept<::ztd::text::stateless_encode_re
_Input, _ArgInput, _Output, _ArgOutput>())
```

Constructs a `ztd::text::encode_result` with the provided parameters and information, including whether or not an error was handled.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput>
inline constexpr stateless_encode_result(_ArgInput &&__input, _ArgOutput &&__output,
encoding_error __error_code = encoding_error::ok) noexcept
cept(noexcept(stateless_encode_result::std::forward<_ArgInput>(__input),
::std::forward<_ArgOutput>(__output), __error_code,
__error_code != encoding_error::ok)))
```

Constructs a `ztd::text::encode_result`, defaulting the error code to `ztd::text::encoding_error::ok` if not provided.

Parameters

- **__input** – [in] The input range to store.
- **__output** – [in] The output range to store.
- **__error_code** – [in] The error code for the decoding operation, if any.

```
template<typename _ArgInput, typename _ArgOutput>
inline constexpr stateless_encode_result(_ArgInput &&__input, _ArgOutput &&__output,
                                          encoding_error __error_code, ::std::size_t __error_count)
    noexcept(::std::is_nothrow_constructible_v<_Input,
                                                _ArgInput> && ::std::is_nothrow_constructible_v<_Output,
                                                _ArgOutput>)
```

Constructs a `ztd::text::encode_result` with the provided parameters and information, including whether or not an error was handled.

Parameters

- **__input** – [in] The input range to store.
- **__output** – [in] The output range to store.
- **__error_code** – [in] The error code for the encode operation, if any.
- **__error_count** – [in] Whether or not an error was handled. Some error handlers are corrective (see `ztd::text::replacement_handler_t`), and so the error code is not enough to determine if the handler was invoked. This allows the value to be provided directly when constructing this result type.

```
inline constexpr bool errors_were_handled() const noexcept
```

Whether or not any errors were handled.

Returns

Simply checks whether `error_count` is greater than 0.

Public Members

_Input **input**

The reconstructed `input_view` object, with its `.begin()` incremented by the number of code units successfully read (can be identical to `.begin()` on original range on failure).

_Output **output**

The reconstructed `output_view` object, with its `.begin()` incremented by the number of code units successfully written (can be identical to `.begin()` on original range on failure).

encoding_error **error_code**

The kind of error that occurred, if any.

::std::size_t **error_count**

Whether or not the error handler was invoked, regardless of if the `error_code` is set or not set to `ztd::text::encoding_error::ok`.

encode_result

```
template<typename _Input, typename _Output, typename _State>
```

```
class encode_result : public ztd::text::stateless_encode_result<_Input, _Output>
```

The result of all encode operations from encoding objects and higher-level calls (such as `ztd_text_encode`).

Public Functions

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgState,
::std::enable_if_t<__txt_detail::__result_type_copy_constraint<::ztd::text::encode_result, _Input, _ArgInput,
_Output, _ArgOutput, _State, _ArgState>()>* = nullptr>
inline constexpr encode_result(const encode_result<_ArgInput, _ArgOutput, _ArgState> &__other) noexcept(
__txt_detail::__result_type_copy_noexcept<::ztd::text::encode_result,
_Input, _ArgInput, _Output, _ArgOutput, _State, _ArgState>())
```

Constructs a `ztd::text::encode_result` from a previous `encode_result`.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgState,
::std::enable_if_t<__txt_detail::__result_type_move_constraint<::ztd::text::encode_result, _Input, _ArgInput,
_Output, _ArgOutput, _State, _ArgState>()>* = nullptr>
inline constexpr encode_result(encode_result<_ArgInput, _ArgOutput, _ArgState> &&__other) noexcept(
__txt_detail::__result_type_move_noexcept<::ztd::text::encode_result,
_Input, _ArgInput, _Output, _ArgOutput, _State, _ArgState>())
```

Constructs a `ztd::text::encode_result` from a previous `encode_result`.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgState>
inline constexpr encode_result(_ArgInput &&__input, _ArgOutput &&__output, _ArgState &&__state,
encoding_error __error_code = encoding_error::ok)
```

Constructs a `ztd::text::encode_result`, defaulting the error code to `ztd::text::encoding_error::ok` if not provided.

Parameters

- **__input** – [in] The input range to store.
- **__output** – [in] The output range to store.
- **__state** – [in] The state related to the Encoding that performed the encode operation.
- **__error_code** – [in] The error code for the decoding operation, if any.

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgState>
inline constexpr encode_result(_ArgInput &&__input, _ArgOutput &&__output, _ArgState &&__state,
encoding_error __error_code, ::std::size_t __error_count) noexcept
```

Constructs a `ztd::text::encode_result` with the provided parameters and information, including whether or not an error was handled.

Parameters

- **__input** – [in] The input range to store.
- **__output** – [in] The output range to store.

- **__state** – [in] The state related to the Encoding that performed the encode operation.
- **__error_code** – [in] The error code for the encode operation, if any.
- **__error_count** – [in] Whether or not an error was handled. Some error handlers are corrective (see *ztd::text::replacement_handler_t*), and so the error code is not enough to determine if the handler was invoked. This allows the value to be provided directly when constructing this result type.

inline constexpr bool **errors_were_handled**() const noexcept

Whether or not any errors were handled.

Returns

Simply checks whether `error_count` is greater than 0.

Public Members

`::ztd::reference_wrapper<_State>` **state**

The state of the associated Encoding used for decoding input code points to code units.

_Input **input**

The reconstructed `input_view` object, with its `.begin()` incremented by the number of code units successfully read (can be identical to `.begin()` on original range on failure).

_Output **output**

The reconstructed `output_view` object, with its `.begin()` incremented by the number of code units successfully written (can be identical to `.begin()` on original range on failure).

encoding_error **error_code**

The kind of error that occurred, if any.

`::std::size_t` **error_count**

Whether or not the error handler was invoked, regardless of if the `error_code` is set or not set to *ztd::text::encoding_error::ok*.

stateless_transcode_result

template<typename **_Input**, typename **_Output**>

class **stateless_transcode_result**

The result of transcoding operations (such as *ztd::text::transcode*) that specifically do not include a reference to the state.

Subclassed by *pivotless_transcode_result*< *_Input*, *_Output*, *_FromState*, *_ToState* >

Public Functions

```
template<typename _ArgInput, typename _ArgOutput,
::std::enable_if_t<__txt_detail::__result_type_copy_constraint<::ztd::text::stateless_transcode_result, _Input,
_ArgInput, _Output, _ArgOutput>()* = nullptr>
```

```
inline constexpr stateless_transcode_result(const stateless_transcode_result<_ArgInput, _ArgOutput>
&&_other) noexcept
cept(__txt_detail::__result_type_copy_noexcept<::ztd::text::stateless_transcode_result,
_Input, _ArgInput, _Output, _ArgOutput>())
```

Constructs a *ztd::text::stateless_transcode_result* with the provided parameters and information, including whether or not an error was handled.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput,
::std::enable_if_t<__txt_detail::__result_type_move_constraint<::ztd::text::stateless_transcode_result, _Input,
_ArgInput, _Output, _ArgOutput>()* = nullptr>
```

```
inline constexpr stateless_transcode_result(stateless_transcode_result<_ArgInput, _ArgOutput>
&&_other) noexcept
cept(__txt_detail::__result_type_move_noexcept<::ztd::text::stateless_transcode_result,
_Input, _ArgInput, _Output, _ArgOutput>())
```

Constructs a *ztd::text::stateless_transcode_result* with the provided parameters and information, including whether or not an error was handled.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput>
```

```
inline constexpr stateless_transcode_result(_ArgInput &&_input, _ArgOutput &&_output,
encoding_error _error_code = encoding_error::ok) noexcept
cept(noexcept(stateless_transcode_result::std::forward<_ArgInput>(_input),
::std::forward<_ArgOutput>(_output), _error_code,
_error_code != encoding_error::ok)))
```

Constructs a *ztd::text::stateless_transcode_result*, defaulting the error code to *ztd::text::encoding_error::ok* if not provided.

Parameters

- **__input** – [in] The input range to store.
- **__output** – [in] The output range to store.
- **__error_code** – [in] The error code for the encode operation, taken as the first of either the encode or decode operation that failed.

```
template<typename _ArgInput, typename _ArgOutput>
```

```
inline constexpr stateless_transcode_result(_ArgInput &&_input, _ArgOutput &&_output,
encoding_error _error_code, ::std::size_t _error_count)
noexcept(::std::is_nothrow_constructible_v<_Input,
_ArgInput> &&
::std::is_nothrow_constructible_v<_Output, _ArgOutput>)
```

Constructs a *ztd::text::stateless_transcode_result* with the provided parameters and information, including whether or not an error was handled.

Parameters

- **__input** – [in] The input range to store.

- **__output** – [in] The output range to store.
- **__error_code** – [in] The error code for the encode operation, taken as the first of either the encode or decode operation that failed.
- **__error_count** – [in] Whether or not an error was handled. Some error handlers are corrective (see *ztd::text::replacement_handler_t*), and so the error code is not enough to determine if the handler was invoked. This allows the value to be provided directly when constructing this result type.

inline constexpr bool **errors_were_handled**() const noexcept

Whether or not any errors were handled.

Returns

Simply checks whether `error_count` is greater than 0.

Public Members

_Input **input**

The reconstructed `input_view` object, with its `.begin()` incremented by the number of code units successfully read (can be identical to `.begin()` on original range on failure).

_Output **output**

The reconstructed `output_view` object, with its `.begin()` incremented by the number of code units successfully written (can be identical to `.begin()` on original range on failure).

encoding_error **error_code**

The kind of error that occurred, if any.

`::std::size_t` **error_count**

Whether or not the error handler was invoked, regardless of if the `error_code` is set or not set to *ztd::text::encoding_error::ok*.

pivotless_transcode_result

template<typename **_Input**, typename **_Output**, typename **_FromState**, typename **_ToState**>

class **pivotless_transcode_result** : public *ztd::text::stateless_transcode_result*<*_Input*, *_Output*>

The result of transcoding operations (such as *ztd::text::transcode* with the state argument provided).

Subclassed by *transcode_result*<*_Input*, *_Output*, *_FromState*, *_ToState*, *_Pivot*>

Public Functions

template<typename **_ArgInput**, typename **_ArgOutput**, typename **_ArgFromState**, typename **_ArgToState**,

`::std::enable_if_t<__txt_detail::__result_type_copy_constraint<::ztd::text::pivotless_transcode_result, _Input, _ArgInput, _Output, _ArgOutput, _FromState, _ArgFromState, _ToState, _ArgToState>()* = nullptr>`

```
inline constexpr pivotless_transcode_result(const pivotless_transcode_result<_ArgInput, _ArgOutput,
                                             _ArgFromState, _ArgToState> &__other) noexcept(
    __txt_detail::__result_type_copy_noexcept<::ztd::text::pivotless_transcode_result,
    _Input, _ArgInput, _Output, _ArgOutput, _FromState,
    _ArgFromState, _ToState, _ArgToState>())
```

Constructs a *ztd::text::pivotless_transcode_result* from a previous *pivotless_transcode_result*.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgFromState, typename
    _ArgToState,
    ::std::enable_if_t<__txt_detail::__result_type_move_constraint<::ztd::text::pivotless_transcode_result,
    _Input,
    _ArgInput, _Output, _ArgOutput, _FromState, _ArgFromState, _ToState, _ArgToState>()* = nullptr>
inline constexpr pivotless_transcode_result(pivotless_transcode_result<_ArgInput, _ArgOutput,
                                             _ArgFromState, _ArgToState> &&__other) noexcept(
    __txt_detail::__result_type_move_noexcept<::ztd::text::pivotless_transcode_result,
    _Input, _ArgInput, _Output, _ArgOutput, _FromState,
    _ArgFromState, _ToState, _ArgToState>())
```

Constructs a *ztd::text::pivotless_transcode_result* from a previous *pivotless_transcode_result*.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgFromState, typename
    _ArgToState>
inline constexpr pivotless_transcode_result(_ArgInput &&__input, _ArgOutput &&__output,
                                             _ArgFromState &&__from_state, _ArgToState
                                             &&__to_state, encoding_error __error_code =
                                             encoding_error::ok)
```

Constructs a *ztd::text::pivotless_transcode_result*, defaulting the error code to *ztd::text::encoding_error::ok* if not provided.

Parameters

- **__input** – [in] The input range to store.
- **__output** – [in] The output range to store.
- **__from_state** – [in] The state related to the “From Encoding” that performed the decode half of the operation.
- **__to_state** – [in] The state related to the “To Encoding” that performed the encode half of the operation.
- **__error_code** – [in] The error code for the transcoding operation, taken as the first of either the encode or decode operation that failed.

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgFromState, typename
    _ArgToState>
inline constexpr pivotless_transcode_result(_ArgInput &&__input, _ArgOutput &&__output,
                                             _ArgFromState &&__from_state, _ArgToState
                                             &&__to_state, encoding_error __error_code, ::std::size_t
                                             __error_count)
```

Constructs a *ztd::text::pivotless_transcode_result* with the provided parameters and information, including whether or not an error was handled.

Parameters

- **__input** – [in] The input range to store.
- **__output** – [in] The output range to store.
- **__from_state** – [in] The state related to the “From Encoding” that performed the decode half of the operation.
- **__to_state** – [in] The state related to the “To Encoding” that performed the encode half of the operation.
- **__error_code** – [in] The error code for the encode operation, taken as the first of either the encode or decode operation that failed.
- **__error_count** – [in] Whether or not an error was handled. Some error handlers are corrective (see *ztd::text::replacement_handler_t*), and so the error code is not enough to determine if the handler was invoked. This allows the value to be provided directly when constructing this result type.

inline constexpr bool **errors_were_handled**() const noexcept

Whether or not any errors were handled.

Returns

Simply checks whether `error_count` is greater than 0.

Public Members

`::ztd::reference_wrapper<_FromState>` **from_state**

A reference to the state of the associated Encoding used for decoding input code units to intermediate code points.

`::ztd::reference_wrapper<_ToState>` **to_state**

A reference to the state of the associated Encoding used for encoding intermediate code points to code units.

_Input **input**

The reconstructed `input_view` object, with its `.begin()` incremented by the number of code units successfully read (can be identical to `.begin()` on original range on failure).

_Output **output**

The reconstructed `output_view` object, with its `.begin()` incremented by the number of code units successfully written (can be identical to `.begin()` on original range on failure).

encoding_error **error_code**

The kind of error that occurred, if any.

`::std::size_t` **error_count**

Whether or not the error handler was invoked, regardless of if the `error_code` is set or not set to *ztd::text::encoding_error::ok*.

transcode_result

```
template<typename _Input, typename _Output, typename _FromState, typename _ToState, typename _Pivot>
```

```
class transcode_result : public ztd::text::pivotless_transcode_result<_Input, _Output, _FromState, _ToState>
```

The result of low-level transcoding operations (such as `ztd::text::transcode_into` with the pivot provided as an argument).

Public Functions

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgFromState, typename
  _ArgToState, typename _ArgPivot,
  ::std::enable_if_t<__txt_detail::__result_type_copy_constraint<::ztd::text::transcode_result, _Input,
  _ArgInput, _Output, _ArgOutput, _FromState, _ArgFromState, _ToState, _ArgToState, _Pivot, _ArgPivot>()>*
  = nullptr>
inline constexpr transcode_result(const transcode_result<_ArgInput,
  _ArgOutput, _ArgFromState, _ArgToState, _ArgPivot> &__other) noexcept(
  __txt_detail::__result_type_copy_noexcept<::ztd::text::transcode_result,
  _Input, _ArgInput, _Output, _ArgOutput, _FromState, _ArgFromState,
  _ToState, _ArgToState, _Pivot, _ArgPivot>())
```

Constructs a `ztd::text::pivotless_transcode_result` from a previous `pivotless_transcode_result`.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgFromState, typename
  _ArgToState, typename _ArgPivot,
  ::std::enable_if_t<__txt_detail::__result_type_move_constraint<::ztd::text::transcode_result, _Input,
  _ArgInput, _Output, _ArgOutput, _FromState, _ArgFromState, _ToState, _ArgToState, _Pivot, _ArgPivot>()>*
  = nullptr>
inline constexpr transcode_result(transcode_result<_ArgInput, _ArgOutput, _ArgFromState,
  _ArgToState, _ArgPivot> &&__other) noexcept(
  __txt_detail::__result_type_move_noexcept<::ztd::text::transcode_result,
  _Input, _ArgInput, _Output, _ArgOutput, _FromState, _ArgFromState,
  _ToState, _ArgToState, _Pivot, _ArgPivot>())
```

Constructs a `ztd::text::pivotless_transcode_result` from a previous `pivotless_transcode_result`.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgFromState, typename
  _ArgToState, typename _ArgPivot>
inline constexpr transcode_result(_ArgInput &&__input, _ArgOutput &&__output, _ArgFromState
  &&__from_state, _ArgToState &&__to_state, encoding_error
  __error_code, ::std::size_t __error_count, _ArgPivot &&__pivot,
  encoding_error __pivot_error_code, ::std::size_t __pivot_error_count)
```

Constructs a `ztd::text::pivotless_transcode_result` with the provided parameters and information, including whether or not an error was handled.

Parameters

- **__input** – [in] The input range to store.
- **__output** – [in] The output range to store.

- **__from_state** – [in] The state related to the “From Encoding” that performed the decode half of the operation.
- **__to_state** – [in] The state related to the “To Encoding” that performed the encode half of the operation.
- **__error_code** – [in] The error code for the transcode operation, taken as the first of either the encode or decode operation that failed.
- **__error_count** – [in] Whether or not an error was handled. Some error handlers are corrective (see `ztd::text::replacement_handler_t`), and so the error code is not enough to determine if the handler was invoked. This allows the value to be provided directly when constructing this result type.
- **__pivot** – [in] The pivot for this transcode operation.
- **__pivot_error_code** – [in] The error code for the decode step of the transcode operation, if it failed.
- **__pivot_error_count** – [in] Whether or not an error was handled during the decode step of the transcode operation. Some error handlers are corrective (see `ztd::text::replacement_handler_t`), and so the error code is not enough to determine if the handler was invoked. This allows the value to be provided directly when constructing this result type.

inline constexpr bool **errors_were_handled**() const noexcept

Whether or not any errors were handled.

Returns

Simply checks whether `error_count` is greater than 0.

Public Members

_Pivot **pivot**

The range used to hold the intermediate pivot transcoding units.

encoding_error **pivot_error_code**

The kind of error that occurred, if any, for the intermediate pivot.

::std::size_t **pivot_error_count**

Whether or not the error handler for the pivot point was invoked, regardless of if the `pivot_error_code` is set or not set to `ztd::text::encoding_error::ok`.

::ztd::reference_wrapper<*_FromState*> **from_state**

A reference to the state of the associated Encoding used for decoding input code units to intermediate code points.

::ztd::reference_wrapper<*_ToState*> **to_state**

A reference to the state of the associated Encoding used for encoding intermediate code points to code units.

_Input **input**

The reconstructed `input_view` object, with its `.begin()` incremented by the number of code units successfully read (can be identical to `.begin()` on original range on failure).

***_Output* output**

The reconstructed `output_view` object, with its `.begin()` incremented by the number of code units successfully written (can be identical to `.begin()` on original range on failure).

***encoding_error* error_code**

The kind of error that occurred, if any.

`::std::size_t` error_count

Whether or not the error handler was invoked, regardless of if the `error_code` is set or not set to `ztd::text::encoding_error::ok`.

stateless_recode_result

```
template<typename _Input, typename _Output>
```

```
class stateless_recode_result
```

The result of transcoding operations (such as `ztd::text::recode`) that specifically do not include a reference to the state.

Subclassed by `pivotless_recode_result< _Input, _Output, _FromState, _ToState >`

Public Functions

```
template<typename _ArgInput, typename _ArgOutput,
::std::enable_if_t<__txt_detail::__result_type_copy_constraint<::ztd::text::stateless_recode_result, _Input,
_ArgInput, _Output, _ArgOutput>()>* = nullptr>
```

```
inline constexpr stateless_recode_result(const stateless_recode_result<_ArgInput, _ArgOutput>
&&__other) noexcept(
__txt_detail::__result_type_copy_noexcept<::ztd::text::stateless_recode_res
_Input, _ArgInput, _Output, _ArgOutput>())
```

Constructs a `ztd::text::stateless_recode_result` with the provided parameters and information, including whether or not an error was handled.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput,
::std::enable_if_t<__txt_detail::__result_type_move_constraint<::ztd::text::stateless_recode_result, _Input,
_ArgInput, _Output, _ArgOutput>()>* = nullptr>
```

```
inline constexpr stateless_recode_result(stateless_recode_result<_ArgInput, _ArgOutput>
&&__other) noexcept(
__txt_detail::__result_type_move_noexcept<::ztd::text::stateless_recode_res
_Input, _ArgInput, _Output, _ArgOutput>)
```

Constructs a `ztd::text::stateless_recode_result` with the provided parameters and information, including whether or not an error was handled.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput>
```

```
inline constexpr stateless_recode_result(_ArgInput &&__input, _ArgOutput &&__output,
                                         encoding_error __error_code = encoding_error::ok) noexcept(
    noexcept(stateless_recode_result::std::forward<_ArgInput>(__input),
            ::std::forward<_ArgOutput>(__output), __error_code,
            __error_code != encoding_error::ok))
```

Constructs a *ztd::text::stateless_recode_result*, defaulting the error code to *ztd::text::encoding_error::ok* if not provided.

Parameters

- **__input** – [in] The input range to store.
- **__output** – [in] The output range to store.
- **__error_code** – [in] The error code for the encode operation, taken as the first of either the encode or decode operation that failed.

```
template<typename _ArgInput, typename _ArgOutput>
inline constexpr stateless_recode_result(_ArgInput &&__input, _ArgOutput &&__output,
                                         encoding_error __error_code, ::std::size_t __error_count)
    noexcept(::std::is_nothrow_constructible_v<_Input,
        _ArgInput> && ::std::is_nothrow_constructible_v<_Output,
        _ArgOutput>)
```

Constructs a *ztd::text::stateless_recode_result* with the provided parameters and information, including whether or not an error was handled.

Parameters

- **__input** – [in] The input range to store.
- **__output** – [in] The output range to store.
- **__error_code** – [in] The error code for the encode operation, taken as the first of either the encode or decode operation that failed.
- **__error_count** – [in] Whether or not an error was handled. Some error handlers are corrective (see *ztd::text::replacement_handler_t*), and so the error code is not enough to determine if the handler was invoked. This allows the value to be provided directly when constructing this result type.

```
inline constexpr bool errors_were_handled() const noexcept
```

Whether or not any errors were handled.

Returns

Simply checks whether `error_count` is greater than 0.

Public Members

_Input **input**

The reconstructed `input_view` object, with its `.begin()` incremented by the number of code units successfully read (can be identical to `.begin()` on original range on failure).

_Output **output**

The reconstructed `output_view` object, with its `.begin()` incremented by the number of code units successfully written (can be identical to `.begin()` on original range on failure).

encoding_error error_code

The kind of error that occurred, if any.

::std::size_t error_count

Whether or not the error handler was invoked, regardless of if the error_code is set or not set to *ztd::text::encoding_error::ok*.

recode_result

```
template<typename _Input, typename _Output, typename _FromState, typename _ToState, typename _Pivot>
```

```
class recode_result : public ztd::text::pivotless_recode_result<_Input, _Output, _FromState, _ToState>
```

The result of low-level transcoding operations (such as *ztd::text::recode_into* with the pivot provided as an argument).

Public Functions

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgFromState, typename
  _ArgToState, typename _ArgPivot,
  ::std::enable_if_t<__txt_detail::__result_type_copy_constraint<::ztd::text::recode_result, _Input, _ArgInput,
  _Output, _ArgOutput, _FromState, _ArgFromState, _ToState, _ArgToState, _Pivot, _ArgPivot>()* = nullptr>
inline constexpr recode_result(const recode_result<_ArgInput, _ArgOutput, _ArgFromState, _ArgToState,
  _ArgPivot> &__other) noexcept
  cept(__txt_detail::__result_type_copy_noexcept<::ztd::text::recode_result,
  _Input, _ArgInput, _Output, _ArgOutput, _FromState, _ArgFromState,
  _ToState, _ArgToState, _Pivot, _ArgPivot>())
```

Constructs a *ztd::text::pivotless_recode_result* from a previous *pivotless_recode_result*.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgFromState, typename
  _ArgToState, typename _ArgPivot,
  ::std::enable_if_t<__txt_detail::__result_type_move_constraint<::ztd::text::recode_result, _Input, _ArgInput,
  _Output, _ArgOutput, _FromState, _ArgFromState, _ToState, _ArgToState, _Pivot, _ArgPivot>()* = nullptr>
inline constexpr recode_result(recode_result<_ArgInput, _ArgOutput, _ArgFromState, _ArgToState,
  _ArgPivot> &&__other) noexcept
  cept(__txt_detail::__result_type_move_noexcept<::ztd::text::recode_result,
  _Input, _ArgInput, _Output, _ArgOutput, _FromState, _ArgFromState,
  _ToState, _ArgToState, _Pivot, _ArgPivot>())
```

Constructs a *ztd::text::pivotless_recode_result* from a previous *pivotless_recode_result*.

Parameters

__other – [in] A different but related result type.

```
template<typename _ArgInput, typename _ArgOutput, typename _ArgFromState, typename
  _ArgToState, typename _ArgPivot>
inline constexpr recode_result(_ArgInput &&__input, _ArgOutput &&__output, _ArgFromState
  &&__from_state, _ArgToState &&__to_state, encoding_error
  __error_code, ::std::size_t __error_count, _ArgPivot &&__pivot,
  encoding_error __pivot_error_code, ::std::size_t __pivot_error_count)
```

Constructs a `ztd::text::pivotless_recode_result` with the provided parameters and information, including whether or not an error was handled.

Parameters

- **__input** – [in] The input range to store.
- **__output** – [in] The output range to store.
- **__from_state** – [in] The state related to the “From Encoding” that performed the decode half of the operation.
- **__to_state** – [in] The state related to the “To Encoding” that performed the encode half of the operation.
- **__error_code** – [in] The error code for the recode operation, taken as the first of either the encode or decode operation that failed.
- **__error_count** – [in] Whether or not an error was handled. Some error handlers are corrective (see `ztd::text::replacement_handler_t`), and so the error code is not enough to determine if the handler was invoked. This allows the value to be provided directly when constructing this result type.
- **__pivot** – [in] The pivot that was used for the recode operation.
- **__pivot_error_code** – [in] The error code for the decode step of the recode operation, if it failed.
- **__pivot_error_count** – [in] Whether or not an error was handled during the decode step of the recode operation. Some error handlers are corrective (see `ztd::text::replacement_handler_t`), and so the error code is not enough to determine if the handler was invoked. This allows the value to be provided directly when constructing this result type.

inline constexpr bool **errors_were_handled**() const noexcept

Whether or not any errors were handled.

Returns

Simply checks whether `error_count` is greater than 0.

Public Members

_Pivot pivot

The range used to hold the intermediate pivot transcoding units.

encoding_error pivot_error_code

The kind of error that occurred, if any, for the intermediate pivot.

::std::size_t pivot_error_count

Whether or not the error handler for the pivot point was invoked, regardless of if the `pivot_error_code` is set or not set to `ztd::text::encoding_error::ok`.

::ztd::reference_wrapper<_FromState> from_state

A reference to the state of the associated Encoding used for decoding input code units to intermediate code points.

`::ztd::reference_wrapper<_ToState> to_state`

A reference to the state of the associated Encoding used for encoding intermediate code points to code units.

`_Input input`

The reconstructed `input_view` object, with its `.begin()` incremented by the number of code units successfully read (can be identical to `.begin()` on original range on failure).

`_Output output`

The reconstructed `output_view` object, with its `.begin()` incremented by the number of code units successfully written (can be identical to `.begin()` on original range on failure).

`encoding_error error_code`

The kind of error that occurred, if any.

`::std::size_t error_count`

Whether or not the error handler was invoked, regardless of if the `error_code` is set or not set to `ztd::text::encoding_error::ok`.

stateless_count_result

template<typename `_Input`>

class `stateless_count_result`

The result of counting operations (such as `ztd_text_count_as_encoded` and `ztd_text_count_as_decoded`) that specifically do not include a reference to the state.

Subclassed by `count_result<_Input, _State >`, `count_transcode_result<_Input, _FromState, _ToState >`

Public Functions

template<typename `_ArgInput`>

inline constexpr `stateless_count_result`(`_ArgInput` &&__input, ::std::size_t __count, `encoding_error` __error_code = `encoding_error::ok`)

Constructs a `ztd::text::stateless_count_result`, defaulting the error code to `ztd::text::encoding_error::ok` if not provided.

Parameters

- `__input` – [in] The input range to store.
- `__count` – [in] The number of code points or code units successfully counted.
- `__error_code` – [in] The error code for the encode operation, taken as the first of either the encode or decode operation that failed.

template<typename `_ArgInput`>

inline constexpr `stateless_count_result`(`_ArgInput` &&__input, ::std::size_t __count, `encoding_error` __error_code, ::std::size_t __error_count)

Constructs a `ztd::text::stateless_count_result` with the provided parameters and information, including whether or not an error was handled.

Parameters

- **__input** – [in] The input range to store.
- **__count** – [in] The number of code points or code units successfully counted.
- **__error_code** – [in] The error code for the encode operation, taken as the first of either the encode or decode operation that failed.
- **__error_count** – [in] Whether or not an error was handled. Some error handlers are corrective (see *ztd::text::replacement_handler_t*), and so the error code is not enough to determine if the handler was invoked. This allows the value to be provided directly when constructing this result type.

inline constexpr bool **errors_were_handled**() const noexcept

Whether or not any errors were handled.

Returns

Simply checks whether `error_count` is greater than 0.

Public Members

_Input **input**

The reconstructed `input_view` object, with its `.begin()` incremented by the number of code units successfully read (can be identical to `.begin()` on original range on failure).

`::std::size_t` **count**

The number of code units or code points counted successfully, so far.

encoding_error **error_code**

The kind of error that occurred, if any.

`::std::size_t` **error_count**

The number of times an error occurred in the processed input text.

Remark

This number may be greater than one despite `error_code` being *ztd::text::encoding_error::ok*, as some error handlers will encounter an error but “fix” the text (e.g. *ztd::text::skip_handler_t* or *ztd::text::replacement_handler_t*).

count_result

```
template<typename _Input, typename _State>
```

```
class count_result : public ztd::text::stateless_count_result<_Input>
```

The result of counting operations (such as `ztd_text_count_as_encoded` and `ztd_text_count_as_decoded`).

Public Functions

```
template<typename _ArgInput, typename _ArgState>
```

```
inline constexpr count_result(_ArgInput &&__input, ::std::size_t __count, _ArgState &&__state,
                               encoding_error __error_code = encoding_error::ok)
```

Constructs a `ztd::text::count_result`, defaulting the error code to `ztd::text::encoding_error::ok` if not provided.

Parameters

- **__input** – [in] The input range to store.
- **__count** – [in] The number of code points or code units successfully counted.
- **__state** – [in] The state related to the encoding for the counting operation.
- **__error_code** – [in] The error code for the encode operation, taken as the first of either the encode or decode operation that failed.

```
template<typename _ArgInput, typename _ArgState>
```

```
inline constexpr count_result(_ArgInput &&__input, ::std::size_t __count, _ArgState &&__state,
                               encoding_error __error_code, ::std::size_t __error_count)
```

Constructs a `ztd::text::count_result` with the provided parameters and information, including whether or not an error was handled.

Parameters

- **__input** – [in] The input range to store.
- **__count** – [in] The number of code points or code units successfully counted.
- **__state** – [in] The state related to the encode operation that counted the code units.
- **__error_code** – [in] The error code for the encode operation, taken as the first of either the encode or decode operation that failed.
- **__error_count** – [in] Whether or not an error was handled. Some error handlers are corrective (see `ztd::text::replacement_handler_t`), and so the error code is not enough to determine if the handler was invoked. This allows the value to be provided directly when constructing this result type.

```
inline constexpr bool errors_were_handled() const noexcept
```

Whether or not any errors were handled.

Returns

Simply checks whether `error_count` is greater than 0.

Public Members

`::ztd::reference_wrapper<_State> state`

A reference to the state of the associated Encoding used for counting.

`_Input input`

The reconstructed `input_view` object, with its `.begin()` incremented by the number of code units successfully read (can be identical to `.begin()` on original range on failure).

`::std::size_t count`

The number of code units or code points counted successfully, so far.

`encoding_error error_code`

The kind of error that occurred, if any.

`::std::size_t error_count`

The number of times an error occurred in the processed input text.

Remark

This number may be greater than one despite `error_code` being `ztd::text::encoding_error::ok`, as some error handlers will encounter an error but “fix” the text (e.g. `ztd::text::skip_handler_t` or `ztd::text::replacement_handler_t`).

stateless_validate_result

template<typename **_Input**>

class **stateless_validate_result**

The result of validation operations (such as `ztd_text_validate_decodable_as` and `ztd_text_validate_encodable_as`) that specifically do not include a reference to the state.

Subclassed by `validate_pivotless_transcode_result<_Input, _DecodeState, _EncodeState >`, `validate_result<_Input, _State >`

Public Functions

template<typename **_ArgInput**>

inline constexpr **stateless_validate_result**(*_ArgInput* &&__input, bool __is_valid)

Constructs a `ztd::text::validate_result`, defaulting the error code to `ztd::text::encoding_error::ok` if not provided.

Parameters

- `__input` – [in] The input range to store.
- `__is_valid` – [in] Whether or not the validation succeeded.

inline explicit constexpr **operator bool**() const noexcept

A conversion for use in if statements and conditional operators.

Returns

Whether or not the result is valid or not.

Public Members

_Input input

The reconstructed input_view object, with its .begin() incremented by the number of code units successfully read (can be identical to .begin() on original range on failure).

bool **valid**

Whether or not the specified input is valid or not.

validate_result

template<typename **_Input**, typename **_State**>

class **validate_result** : public ztd::text::stateless_validate_result<*_Input*>

The result of validation operations (such as ztd_text_validate_decodable_as and ztd_text_validate_encodable_as).

Public Functions

template<typename **_ArgInput**, typename **_ArgState**>

inline constexpr **validate_result**(*_ArgInput* &&__input, bool __is_valid, *_ArgState* &&__state)

Constructs a *ztd::text::validate_result*, defaulting the error code to *ztd::text::encoding_error::ok* if not provided.

Parameters

- **__input** – [in] The input range to store.
- **__is_valid** – [in] Whether or not the validation succeeded.
- **__state** – [in] The state related to the encoding that was used to do validation.

inline explicit constexpr **operator bool**() const noexcept

A conversion for use in if statements and conditional operators.

Returns

Whether or not the result is valid or not.

Public Members

`ztd::reference_wrapper<_State> state`

A reference to the state of the associated Encoding used for validating the input.

`_Input input`

The reconstructed `input_view` object, with its `.begin()` incremented by the number of code units successfully read (can be identical to `.begin()` on original range on failure).

bool `valid`

Whether or not the specified input is valid or not.

`validate_pivotless_transcode_result`

template<typename `_Input`, typename `_DecodeState`, typename `_EncodeState`>

class `validate_pivotless_transcode_result` : public `ztd::text::stateless_validate_result<_Input>`

The result of a transcoding validation operations (e.g. from `ztd_text_validate_transcodable_as`).

Subclassed by `validate_transcode_result<_Input, _DecodeState, _EncodeState, _Pivot >`

Public Functions

template<typename `_ArgInput`, typename `_ArgFromState`, typename `_ArgToState`>

```
inline constexpr validate_pivotless_transcode_result(_ArgInput &&__input, bool __is_valid,  
                                                    _ArgFromState &&__from_state, _ArgToState  
                                                    &&__to_state)
```

Constructs a `ztd::text::validate_result`, defaulting the error code to `ztd::text::encoding_error::ok` if not provided.

Parameters

- `__input` – [in] The input range to store.
- `__is_valid` – [in] Whether or not the validation succeeded.
- `__from_state` – [in] The state related to the encoding that was used to do validation.
- `__to_state` – [in] The state related to the encoding that was used to do validation.

inline explicit constexpr `operator bool`() const noexcept

A conversion for use in if statements and conditional operators.

Returns

Whether or not the result is valid or not.

Public Members

`::ztd::reference_wrapper<_DecodeState> from_state`

A reference to the state of the associated Encoding used for validating the input.

`::ztd::reference_wrapper<_EncodeState> to_state`

A reference to the state of the associated Encoding used for validating the input.

`_Input input`

The reconstructed `input_view` object, with its `.begin()` incremented by the number of code units successfully read (can be identical to `.begin()` on original range on failure).

bool **valid**

Whether or not the specified input is valid or not.

validate_transcode_result

template<typename **_Input**, typename **_DecodeState**, typename **_EncodeState**, typename **_Pivot**>

class **validate_transcode_result** : public ztd::text::*validate_pivotless_transcode_result*<**_Input**, **_DecodeState**, **_EncodeState**>

The result of a transcoding validation operations (e.g. from `ztd_text_validate_transcodable_as`).

Public Functions

template<typename **_ArgInput**, typename **_ArgFromState**, typename **_ArgToState**, typename **_ArgPivot**>

inline constexpr **validate_transcode_result**(*_ArgInput* &&__input, bool __is_valid, *_ArgFromState* &&__from_state, *_ArgToState* &&__to_state, *_ArgPivot* &&__pivot)

Constructs a `ztd::text::pivot_validate_result`.

Parameters

- **__input** – [in] The input range to store.
- **__is_valid** – [in] Whether or not the validation succeeded.
- **__from_state** – [in] The state related to the encoding that was used to do validation.
- **__to_state** – [in] The state related to the encoding that was used to do validation.
- **__pivot** – [in] The pivot range to store.

inline explicit constexpr **operator bool**() const noexcept

A conversion for use in if statements and conditional operators.

Returns

Whether or not the result is valid or not.

Public Members

_Pivot pivot

The range used to hold the intermediate pivot transcoding units.

`::ztd::reference_wrapper<_DecodeState> from_state`

A reference to the state of the associated Encoding used for validating the input.

`::ztd::reference_wrapper<_EncodeState> to_state`

A reference to the state of the associated Encoding used for validating the input.

_Input input

The reconstructed `input_view` object, with its `.begin()` incremented by the number of code units successfully read (can be identical to `.begin()` on original range on failure).

bool valid

Whether or not the specified input is valid or not.

skip_input_error

Utilizes `ztd::text::is_input_error_skippable` to check if a hypothetical encoding object `encoding` and a hypothetical result object `result` can be utilized to call `encoding.skip_input_error(result)`. Otherwise, it only skips forward by

It is particularly used with `ztd::text::replacement_handler` and `ztd::text::skip_handler`. You can use this function to perform encoding-aware and encoding-specific skips for a given encode and decode operation. This is particularly useful for Unicode encodings, as well as other variable-width encodings in the wild, which may be good to accommodate for in your own error handlers.

```
template<typename _Encoding, typename _Result, typename _InputProgress, typename _OutputProgress>
constexpr auto ztd::text::skip_input_error(const _Encoding &__encoding, _Result &&__result, const
    _InputProgress &__input_progress, const _OutputProgress
    &__output_progress)
    noexcept(::ztd::text::is_nothrow_skip_input_error_v<const
    _Encoding&, _Result, const _InputProgress&, const
    _OutputProgress&>)
```

Attempts to skip over an input error in the text.

```
"\xC0\x9F\x8D\xB7meow"
```

Remark

If there exists a well-formed function call of the form `__encoding.skip_input_error(__result)`, it will call that function. Otherwise, it will attempt to grab the input iterator and pre-increment it exactly once. The goal for this is to provide functionality which can smartly skip over a collection of ill-formed code units or bytes in an input sequence, rather than generated e.g. 3 different replacement characters for a mal-formed UTF-8 sequence. For example, given this malformed wineglass code point as an input UTF-8 sequence:

when used in conjunction with `ztd::text::utf8` (and similar), a proper decode/transcode call will error on `\xC0'`. Then, this function skips until the `'m'` input code unit, resulting in a leftover sequence of `"meow"`.

Parameters

- **__encoding** – [in] The Encoding that experienced the error.
- **__result** – [in] The current result state of the encode or decode operation.
- **__input_progress** – [in] A contiguous range containing all of the (potentially) irreversibly read input from an encoding operation.
- **__output_progress** – [in] A contiguous range containing all of the (potentially) irreversibly written output from an encoding operation.

```
template<typename _Result, typename _InputProgress, typename _OutputProgress>
constexpr auto ztd::text::skip_utf32_input_error(_Result &&__result, const _InputProgress
                                                &__input_progress, const _OutputProgress
                                                &__output_progress) noexcept
```

Attempts to skip over an input error in the text.

Remark

This function is specifically for UTF-32 input, where e.g. multiple surrogates may be part of the incoming text and the target encoding does not support that. Therefore, it will skip over every too-large codepoint, and every surrogate pair codepoint, before stopping.

Parameters

- **__result** – [in] The current result state of the encode or decode operation.
- **__input_progress** – [in] A contiguous range containing all of the (potentially) irreversibly read input from an encoding operation.
- **__output_progress** – [in] A contiguous range containing all of the (potentially) irreversibly written output from an encoding operation.

```
template<typename _Result, typename _InputProgress, typename _OutputProgress>
constexpr auto ztd::text::skip_utf32_with_surrogates_input_error(_Result &&__result, const
                                                                _InputProgress &__input_progress,
                                                                const _OutputProgress
                                                                &__output_progress) noexcept
```

Attempts to skip over an input error in the text.

Remark

This function is specifically for UTF-32 input that also includes surrogate values as a valid option. Therefore, it will skip over every too-large codepoint.

Parameters

- **__result** – [in] The current result state of the encode or decode operation.
- **__input_progress** – [in] A contiguous range containing all of the (potentially) irreversibly read input from an encoding operation.

- **__output_progress** – [in] A contiguous range containing all of the (potentially) irreversibly written output from an encoding operation.

propagate_(transcode|transcode)_error

This helper function processes an error for a transcoding operation and shuffles a result through its decode step and encode step *error handlers*. Nominally used after a solely decode portion of a transcode operation fails.

If the user is doing a direct conversion and can simply call the encode portion of the error handler directly, calling this function can be skipped entirely by the user.

```
template<typename _Result, typename _Output, typename _FromEncoding, typename _ToEncoding, typename
_EncodeErrorHandler, typename _DecodeErrorHandler, typename _ToState, typename
_FromInputProgress, typename _FromOutputProgress, typename _ToInputProgress, typename
_ToOutputProgress, typename _ResultInput, typename _Intermediate, typename _FromState>
constexpr auto propagate_recode_encode_error(_Output &&__output, _FromEncoding &&__from_encoding,
_ToEncoding &&__to_encoding, encode_result<_ResultInput,
_Intermediate, _FromState> &&__encode_result,
_EncodeErrorHandler &&__encode_error_handler,
_DecompileErrorHandler &&__decode_error_handler, _ToState
&__to_state, _FromInputProgress &&__from_input_progress,
_FromOutputProgress &&__from_output_progress,
_ToInputProgress &&__to_input_progress,
_ToOutputProgress &&__to_output_progress) noexcept
```

Transcoding helper. Takes the given `__from_encoding`, `__to_encoding`, `__encode_error_handler`, and `__decode_error_handler` and launders the `ztd::text::encode_result` through the `__encode_error_handler`. The transformed encode result is then transformed to a `ztd::text::decode_result` before transforming that into the desired `ztd::text::recode_result` type.

Remark

This function is a helper whose sole purpose is to ensure that the other half of error handling is called by recode-style functions written by the end user (e.g., writing overriding hooks for `ztd::text::recode`). This function attempts to take care of any unread/unwritten characters and other minor points in its pursuit of properly making sure the error manifests on the other side.

Template Parameters

_Result – The exact recode result type to use.

Parameters

- **__output** – [in] The output view to be writing into.
- **__from_encoding** – [in] The desired encoding that performs the decode portion of the transcoding step.
- **__to_encoding** – [in] The desired encoding that performs the decode portion of the transcoding step.
- **__encode_result** – [in] The result value that has an error in it.
- **__encode_error_handler** – [in] The error handler to mill the `__result` and other relevant information through.

- **__decode_error_handler** – [in] The error handler to mill the `__encode_error_handler`'s invoked result and other relevant information through.
- **__to_state** – [in] The current state of the encoding step of the recode operation.
- **__from_input_progress** – [in] Any unread input characters in any intermediate between the (failed) encode and decode operations.
- **__from_output_progress** – [in] Any unread intermediate output characters in any intermediates between the (failed) encode and decode operations.
- **__to_input_progress** – [in] Any unread intermediate input characters in any intermediate between the (failed) encode and decode operations.
- **__to_output_progress** – [in] Any unread output characters in any intermediates between the (failed) encode and decode operations.

```
template<typename _Output, typename _FromEncoding, typename _ToEncoding, typename
_EncodeErrorHandler, typename _DecodeErrorHandler, typename _ToState, typename
_FromInputProgress, typename _FromOutputProgress, typename _ToInputProgress, typename
_ToOutputProgress, typename _ResultInput, typename _ResultIntermediate, typename _FromState>
constexpr auto propagate_recode_encode_error(_Output &&__output, _FromEncoding &&__from_encoding,
                                           _ToEncoding &&__to_encoding, encode_result<_ResultInput,
                                           _ResultIntermediate, _FromState> &&__encode_result,
                                           _EncodeErrorHandler &&__encode_error_handler,
                                           _DecodeErrorHandler &&__decode_error_handler, _ToState
                                           &&__to_state, _FromInputProgress &&__from_input_progress,
                                           _FromOutputProgress &&__from_output_progress,
                                           _ToInputProgress &&__to_input_progress,
                                           _ToOutputProgress &&__to_output_progress) noexcept
```

Transcoding helper. Takes the given `__from_encoding`, `__to_encoding`, `__encode_error_handler`, and `__decode_error_handler` and launders the `ztd::text::encode_result` through the `__encode_error_handler`. The transformed encode result is then transformed to a `ztd::text::decode_result` before transforming that into the desired `ztd::text::recode_result` type.

Remark

This function is a helper whose sole purpose is to ensure that the other half of error handling is called by recode-style functions written by the end user (e.g., writing overriding hooks for `ztd::text::recode`). This function attempts to take care of any unread/unwritten characters and other minor points in its pursuit of properly making sure the error manifests on the other side.

Template Parameters

_Result – The exact recode result type to use.

Parameters

- **__output** – [in] The output view to be writing into.
- **__from_encoding** – [in] The desired encoding that performs the decode portion of the transcoding step.
- **__to_encoding** – [in] The desired encoding that performs the decode portion of the transcoding step.
- **__encode_result** – [in] The result value that has an error in it.

- **__encode_error_handler** – [in] The error handler to mill the `__result` and other relevant information through.
- **__decode_error_handler** – [in] The error handler to mill the `__encode_error_handler`'s invoked result and other relevant information through.
- **__to_state** – [in] The current state of the encoding step of the recode operation.
- **__from_input_progress** – [in] Any unread input characters in any intermediate between the (failed) encode and decode operations.
- **__from_output_progress** – [in] Any unread intermediate output characters in any intermediates between the (failed) encode and decode operations.
- **__to_input_progress** – [in] Any unread intermediate input characters in any intermediate between the (failed) encode and decode operations.
- **__to_output_progress** – [in] Any unread output characters in any intermediates between the (failed) encode and decode operations.

```
template<typename _Result, typename _ToEncoding, typename _DecodeErrorHandler, typename
_ToInputProgress, typename _ToOutputProgress, typename _ResultInput, typename _ResultPivot,
typename _FromState, typename _ResultIntermediate, typename _ResultOutput, typename _ToState>
constexpr auto propagate_recode_decode_error(
    _ToEncoding &&__to_encoding, encode_result<_ResultInput,
    _ResultPivot, _FromState> &&__encode_result,
    decode_result<_ResultIntermediate, _ResultOutput, _ToState>
    &&__decode_result, _DecodeErrorHandler
    &&__decode_error_handler, _ToInputProgress
    &&__to_input_progress, _ToOutputProgress
    &&__to_output_progress) noexcept
```

Transcoding helper. Takes the given `__to_encoding` and `__decode_error_handler` and launders the failed `ztd::text::encode_result` through it, producing a `ztd::text::decode_result` and transforming that into the desired `ztd::text::recode_result` type.

Remark

This function is a helper whose sole purpose is to ensure that the other half of error handling is called by recode-style functions written by the end user (e.g., writing overriding hooks for `ztd::text::recode`). This function attempts to take care of any unread/unwritten characters and other minor points in its pursuit of properly making sure the error manifests on the other side.

Template Parameters

_Result – The exact recode result type to use.

Parameters

- **__to_encoding** – [in] The desired encoding that performs the decode portion of the transcoding step.
- **__encode_result** – [in] The encode result value that has an error in it.
- **__decode_result** – [in] The decode result value that has not yet been processed by the decode error handler.
- **__decode_error_handler** – [in] The error handler to mill the `__result` and other relevant information through.

- **__to_input_progress** – [in] Any unread output characters in any intermediate between the (failed) encode and decode operations.
- **__to_output_progress** – [in] Any unread output characters in any intermediates between the (failed) encode and decode operations.

```
template<typename _ToEncoding, typename _DecodeErrorHandler, typename _ToInputProgress, typename
_ToOutputProgress, typename _ResultInput, typename _ResultPivot, typename _FromState, typename
_ResultIntermediate, typename _ResultOutput, typename _ToState>
constexpr auto propagate_recode_decode_error(_ToEncoding &&__to_encoding, encode_result<_ResultInput,
_ResultPivot, _FromState> &&__encode_result,
decode_result<_ResultIntermediate, _ResultOutput, _ToState>
&&__decode_result, _DecodeErrorHandler
&&__decode_error_handler, _ToInputProgress
&&__to_input_progress, _ToOutputProgress
&&__to_output_progress) noexcept
```

Takes the given `__to_encoding` and `__decode_error_handler` and launders the failed `ztd::text::encode_result` through it, producing a `ztd::text::decode_result` and transforming that into the desired `ztd::text::recode_result` type.

Remark

This function is a helper whose sole purpose is to ensure that the other half of error handling is called by recode-style functions written by the end user (e.g., writing overriding hooks for `ztd::text::recode`). This function attempts to take care of any unread/unwritten characters and other minor points in its pursuit of properly making sure the error manifests on the other side. Unlike its counterpart, this function does not take an `_Result` template parameter and instead deduces the returned recode result type from inputs.

Parameters

- **__to_encoding** – [in] The desired encoding that performs the decode portion of the transcoding step.
- **__encode_result** – [in] The result value that has an error on it.
- **__decode_result** – [in] The result value that has an error on it.
- **__decode_error_handler** – [in] The error handler to mill the `__result` and other relevant information through.
- **__to_input_progress** – [in] Any unread output characters in any intermediate between the (failed) encode and decode operations.
- **__to_output_progress** – [in] Any unread output characters in any intermediates between the (failed) encode and decode operations.

```
template<typename _Result, typename _Input, typename _Output, typename _FromEncoding, typename
_ToEncoding, typename _EncodeErrorHandler, typename _DecodeErrorHandler, typename _ToState,
typename _FromInputProgress, typename _FromOutputProgress, typename _ToInputProgress, typename
_ToOutputProgress, typename _ResultInput, typename _Intermediate, typename _FromState>
```

```
constexpr auto propagate_recode_encode_error_with(_Input &&__input, _Output &&__output,
                                                _FromEncoding &&__from_encoding, _ToEncoding
                                                &&__to_encoding, encode_result<_ResultInput,
                                                _Intermediate, _FromState> &&__encode_result,
                                                _EncodeErrorHandler &&__encode_error_handler,
                                                _DecodeErrorHandler &&__decode_error_handler,
                                                _ToState &__to_state, _FromInputProgress
                                                &&__from_input_progress, _FromOutputProgress
                                                &&__from_output_progress, _ToInputProgress
                                                &&__to_input_progress, _ToOutputProgress
                                                &&__to_output_progress) noexcept
```

Transcoding helper. Takes the given `__from_encoding`, `__to_encoding`, `__encode_error_handler`, and `__decode_error_handler` and launders the `ztd::text::encode_result` through the `__encode_error_handler`. The transformed encode result is then transformed to a `ztd::text::decode_result` before transforming that into the desired `ztd::text::recode_result` type.

Remark

This function is a helper whose sole purpose is to ensure that the other half of error handling is called by recode-style functions written by the end user (e.g., writing overriding hooks for `ztd::text::recode`). This function attempts to take care of any unread/unwritten characters and other minor points in its pursuit of properly making sure the error manifests on the other side.

Template Parameters

_Result – The exact recode result type to use.

Parameters

- **__input** – [in] The input view to be reading from.
- **__output** – [in] The output view to be writing into.
- **__from_encoding** – [in] The desired encoding that performs the decode portion of the transcoding step.
- **__to_encoding** – [in] The desired encoding that performs the decode portion of the transcoding step.
- **__result** – [in] The result value that has an error in it.
- **__encode_error_handler** – [in] The error handler to mill the `__result` and other relevant information through.
- **__decode_error_handler** – [in] The error handler to mill the `__encode_error_handler`'s invoked result and other relevant information through.
- **__to_state** – [in] The current state of the encoding step of the recode operation.
- **__from_input_progress** – [in] Any unread input characters in any intermediate between the (failed) encode and decode operations.
- **__from_output_progress** – [in] Any unread intermediate output characters in any intermediates between the (failed) encode and decode operations.
- **__to_input_progress** – [in] Any unread intermediate input characters in any intermediate between the (failed) encode and decode operations.

- **__to_output_progress** – [in] Any unread output characters in any intermediates between the (failed) encode and decode operations.

```
template<typename _Input, typename _Output, typename _FromEncoding, typename _ToEncoding, typename
_EncodeErrorHandler, typename _DecodeErrorHandler, typename _ToState, typename
_FromInputProgress, typename _FromOutputProgress, typename _ToInputProgress, typename
_ToOutputProgress, typename _ResultInput, typename _ResultIntermediate, typename _FromState>
constexpr auto propagate_recode_encode_error_with(_Input && __input, _Output && __output,
    _FromEncoding && __from_encoding, _ToEncoding
    && __to_encoding, encode_result<_ResultInput,
    _ResultIntermediate, _FromState> && __encode_result,
    _EncodeErrorHandler && __encode_error_handler,
    _DecodeErrorHandler && __decode_error_handler,
    _ToState & __to_state, _FromInputProgress
    && __from_input_progress, _FromOutputProgress
    && __from_output_progress, _ToInputProgress
    && __to_input_progress, _ToOutputProgress
    && __to_output_progress) noexcept
```

Transcoding helper. Takes the given `__from_encoding`, `__to_encoding`, `__encode_error_handler`, and `__decode_error_handler` and launders the `ztd::text::encode_result` through the `__encode_error_handler`. The transformed encode result is then transformed to a `ztd::text::decode_result` before transforming that into the desired `ztd::text::recode_result` type.

Remark

This function is a helper whose sole purpose is to ensure that the other half of error handling is called by recode-style functions written by the end user (e.g., writing overriding hooks for `ztd::text::recode`). This function attempts to take care of any unread/unwritten characters and other minor points in its pursuit of properly making sure the error manifests on the other side.

Template Parameters

_Result – The exact recode result type to use.

Parameters

- **__input** – [in] The input view to be reading from.
- **__output** – [in] The output view to be writing into.
- **__from_encoding** – [in] The desired encoding that performs the decode portion of the transcoding step.
- **__to_encoding** – [in] The desired encoding that performs the encode portion of the transcoding step.
- **__result** – [in] The result value that has an error in it.
- **__encode_error_handler** – [in] The error handler to mill the `__result` and other relevant information through.
- **__decode_error_handler** – [in] The error handler to mill the `__encode_error_handler`'s invoked result and other relevant information through.
- **__to_state** – [in] The current state of the encoding step of the recode operation.

- **__from_input_progress** – [in] Any unread input characters in any intermediate between the (failed) encode and decode operations.
- **__from_output_progress** – [in] Any unread intermediate output characters in any intermediates between the (failed) encode and decode operations.
- **__to_input_progress** – [in] Any unread intermediate input characters in any intermediate between the (failed) encode and decode operations.
- **__to_output_progress** – [in] Any unread output characters in any intermediates between the (failed) encode and decode operations.

```
template<typename _Result, typename _Input, typename _ToEncoding, typename _DecodeErrorHandler,
typename _ToInputProgress, typename _ToOutputProgress, typename _ResultInput, typename
_ResultPivot, typename _FromState, typename _ResultIntermediate, typename _ResultOutput, typename
_ToState>
```

```
constexpr auto propagate_recode_decode_error_with(_Input &&__input, _ToEncoding &&__to_encoding,
encode_result<_ResultInput, _ResultPivot, _FromState>
&&__encode_result,
decode_result<_ResultIntermediate, _ResultOutput,
_ToState> &&__decode_result, _DecodeErrorHandler
&&__decode_error_handler, _ToInputProgress
&&__to_input_progress, _ToOutputProgress
&&__to_output_progress) noexcept
```

Transcoding helper. Takes the given `__to_encoding` and `__decode_error_handler` and launders the failed `ztd::text::encode_result` through it, producing a `ztd::text::decode_result` and transforming that into the desired `ztd::text::recode_result` type.

Remark

This function is a helper whose sole purpose is to ensure that the other half of error handling is called by recode-style functions written by the end user (e.g., writing overriding hooks for `ztd::text::recode`). This function attempts to take care of any unread/unwritten characters and other minor points in its pursuit of properly making sure the error manifests on the other side.

Template Parameters

_Result – The exact recode result type to use.

Parameters

- **__input** – [in] The input view to be read from.
- **__to_encoding** – [in] The desired encoding that performs the decode portion of the transcoding step.
- **__encode_result** – [in] The result value that has an error on it.
- **__decode_result** – [in] The result value that has an error on it.
- **__decode_error_handler** – [in] The error handler to mill the `__result` and other relevant information through.
- **__to_state** – [in] The current state of the encoding step of the recode operation.
- **__to_input_progress** – [in] Any unread output characters in any intermediate between the (failed) encode and decode operations.

- **__to_output_progress** – [in] Any unread output characters in any intermediates between the (failed) encode and decode operations.

```
template<typename _Input, typename _ToEncoding, typename _DecodeErrorHandler, typename
_ToInputProgress, typename _ToOutputProgress, typename _ResultInput, typename _ResultPivot,
typename _FromState, typename _ResultIntermediate, typename _ResultOutput, typename _ToState>
constexpr auto propagate_recode_decode_error_with(_Input &&__input, _ToEncoding &&__to_encoding,
encode_result<_ResultInput, _ResultPivot, _FromState>
&&__encode_result,
decode_result<_ResultIntermediate, _ResultOutput,
_ToState> &&__decode_result, _DecodeErrorHandler
&&__decode_error_handler, _ToInputProgress
&&__to_input_progress, _ToOutputProgress
&&__to_output_progress) noexcept
```

Takes the given `__to_encoding` and `__decode_error_handler` and launders the failed `ztd::text::encode_result` through it, producing a `ztd::text::decode_result` and transforming that into the desired `ztd::text::recode_result` type.

Remark

This function is a helper whose sole purpose is to ensure that the other half of error handling is called by recode-style functions written by the end user (e.g., writing overriding hooks for `ztd::text::recode`). This function attempts to take care of any unread/unwritten characters and other minor points in its pursuit of properly making sure the error manifests on the other side. Unlike its counterpart, this function does not take an `_Result` template parameter and instead deduces the returned recode result type from inputs.

Parameters

- **__input** – [in] The input view to be read from.
- **__to_encoding** – [in] The desired encoding that performs the decode portion of the transcoding step.
- **__encode_result** – [in] The result value that has an error on it.
- **__decode_result** – [in] The result value that has an error on it.
- **__decode_error_handler** – [in] The error handler to mill the `__result` and other relevant information through.
- **__to_state** – [in] The current state of the encoding step of the recode operation.
- **__to_input_progress** – [in] Any unread output characters in any intermediate between the (failed) encode and decode operations.
- **__to_output_progress** – [in] Any unread output characters in any intermediates between the (failed) encode and decode operations.

```
template<typename _Result, typename _Output, typename _FromEncoding, typename _ToEncoding, typename
_DecompileErrorHandler, typename _EncodeErrorHandler, typename _ToState, typename
_FromInputProgress, typename _FromOutputProgress, typename _ToInputProgress, typename
_ToOutputProgress, typename _ResultInput, typename _Intermediate, typename _FromState>
```

```
constexpr auto propagate_transcode_decode_error(_Output &&__output, _FromEncoding
&&__from_encoding, _ToEncoding &&__to_encoding,
decode_result<_ResultInput, _Intermediate, _FromState>
&&__decode_result, _DecodeErrorHandler
&&__decode_error_handler, _EncodeErrorHandler
&&__encode_error_handler, _ToState &__to_state,
_FromInputProgress &&__from_input_progress,
_FromOutputProgress &&__from_output_progress,
_ToInputProgress &&__to_input_progress,
_ToOutputProgress &&__to_output_progress) noexcept
```

Transcoding helper. Takes the given `__from_encoding`, `__to_encoding`, `__decode_error_handler`, and `__encode_error_handler` and launders the `ztd::text::decode_result` through the `__decode_error_handler`. The transformed decode result is then transformed to a `ztd::text::encode_result` before transforming that into the desired `ztd::text::transcode_result` type.

Remark

This function is a helper whose sole purpose is to ensure that the other half of error handling is called by transcode-style functions written by the end user (e.g., writing overriding hooks for `ztd::text::transcode`). This function attempts to take care of any unread/unwritten characters and other minor points in its pursuit of properly making sure the error manifests on the other side.

Template Parameters

_Result – The exact transcode result type to use.

Parameters

- **__output** – [in] The output view to be writing into.
- **__from_encoding** – [in] The desired encoding that performs the encode portion of the transcoding step.
- **__to_encoding** – [in] The desired encoding that performs the decode portion of the transcoding step.
- **__result** – [in] The result value that has an error in it.
- **__decode_error_handler** – [in] The error handler to mill the `__result` and other relevant information through.
- **__encode_error_handler** – [in] The error handler to mill the `__decode_error_handler`'s invoked result and other relevant information through.
- **__to_state** – [in] The current state of the encoding step of the transcode operation.
- **__from_input_progress** – [in] Any unread input characters in any intermediate between the (failed) encode and decode operations.
- **__from_output_progress** – [in] Any unread intermediate output characters in any intermediates between the (failed) encode and decode operations.
- **__to_input_progress** – [in] Any unread intermediate input characters in any intermediate between the (failed) decode and encode operations.
- **__to_output_progress** – [in] Any unread output characters in any intermediates between the (failed) decode and encode operations.

```

template<typename _Output, typename _FromEncoding, typename _ToEncoding, typename
_DecodeErrorHandler, typename _EncodeErrorHandler, typename _ToState, typename
_FromInputProgress, typename _FromOutputProgress, typename _ToInputProgress, typename
_ToOutputProgress, typename _ResultInput, typename _ResultIntermediate, typename _FromState>
constexpr auto propagate_transcode_decode_error(_Output &&__output, _FromEncoding
&&__from_encoding, _ToEncoding &&__to_encoding,
decode_result<_ResultInput, _ResultIntermediate,
_FromState> &&__decode_result, _DecodeErrorHandler
&&__decode_error_handler, _EncodeErrorHandler
&&__encode_error_handler, _ToState &__to_state,
_FromInputProgress &&__from_input_progress,
_FromOutputProgress &&__from_output_progress,
_ToInputProgress &&__to_input_progress,
_ToOutputProgress &&__to_output_progress) noexcept

```

Transcoding helper. Takes the given `__from_encoding`, `__to_encoding`, `__decode_error_handler`, and `__encode_error_handler` and launders the `ztd::text::decode_result` through the `__decode_error_handler`. The transformed decode result is then transformed to a `ztd::text::encode_result` before transforming that into the desired `ztd::text::transcode_result` type.

Remark

This function is a helper whose sole purpose is to ensure that the other half of error handling is called by transcode-style functions written by the end user (e.g., writing overriding hooks for `ztd::text::transcode`). This function attempts to take care of any unread/unwritten characters and other minor points in its pursuit of properly making sure the error manifests on the other side.

Template Parameters

_Result – The exact transcode result type to use.

Parameters

- **__output** – [in] The output view to be writing into.
- **__from_encoding** – [in] The desired encoding that performs the encode portion of the transcoding step.
- **__to_encoding** – [in] The desired encoding that performs the encode portion of the transcoding step.
- **__result** – [in] The result value that has an error in it.
- **__decode_error_handler** – [in] The error handler to mill the `__result` and other relevant information through.
- **__encode_error_handler** – [in] The error handler to mill the `__decode_error_handler`'s invoked result and other relevant information through.
- **__to_state** – [in] The current state of the encoding step of the transcode operation.
- **__to_input_progress** – [in] Any unread output characters in any intermediate between the (failed) decode and encode operations.
- **__to_output_progress** – [in] Any unread output characters in any intermediates between the (failed) decode and encode operations.

```
template<typename _Result, typename _ToEncoding, typename _EncodeErrorHandler, typename
_ToInputProgress, typename _ToOutputProgress, typename _ResultInput, typename _ResultPivot,
typename _FromState, typename _ResultIntermediate, typename _ResultOutput, typename _ToState>
constexpr auto propagate_transcode_encode_error(_ToEncoding &&__to_encoding,
                                               decode_result<_ResultInput, _ResultPivot, _FromState>
                                               &&__decode_result, encode_result<_ResultIntermediate,
                                               _ResultOutput, _ToState> &&__encode_result,
                                               _EncodeErrorHandler &&__encode_error_handler,
                                               _ToInputProgress &&__to_input_progress,
                                               _ToOutputProgress &&__to_output_progress) noexcept
```

Transcoding helper. Takes the given `__to_encoding` and `__encode_error_handler` and launders the failed `ztd::text::decode_result` through it, producing a `ztd::text::encode_result` and transforming that into the desired `ztd::text::transcode_result` type.

Remark

This function is a helper whose sole purpose is to ensure that the other half of error handling is called by transcode-style functions written by the end user (e.g., writing overriding hooks for `ztd::text::transcode`). This function attempts to take care of any unread/unwritten characters and other minor points in its pursuit of properly making sure the error manifests on the other side.

Template Parameters

_Result – The exact transcode result type to use.

Parameters

- **__output** – [in] The output view to be writing into.
- **__to_encoding** – [in] The desired encoding that performs the encode portion of the transcoding step.
- **__result** – [in] The result value that has an error on it.
- **__encode_error_handler** – [in] The error handler to mill the `__result` and other relevant information through.
- **__to_state** – [in] The current state of the encoding step of the transcode operation.
- **__to_input_progress** – [in] Any unread output characters in any intermediate between the (failed) decode and encode operations.
- **__to_output_progress** – [in] Any unread output characters in any intermediates between the (failed) decode and encode operations.

```
template<typename _ToEncoding, typename _EncodeErrorHandler, typename _ToInputProgress, typename
_ToOutputProgress, typename _ResultInput, typename _ResultPivot, typename _FromState, typename
_ResultIntermediate, typename _ResultOutput, typename _ToState>
constexpr auto propagate_transcode_encode_error(_ToEncoding &&__to_encoding,
                                               decode_result<_ResultInput, _ResultPivot, _FromState>
                                               &&__decode_result, encode_result<_ResultIntermediate,
                                               _ResultOutput, _ToState> &&__encode_result,
                                               _EncodeErrorHandler &&__encode_error_handler,
                                               _ToInputProgress &&__to_input_progress,
                                               _ToOutputProgress &&__to_output_progress) noexcept
```

Takes the given `__to_encoding` and `__encode_error_handler` and launders the failed

`ztd::text::decode_result` through it, producing a `ztd::text::encode_result` and transforming that into the desired `ztd::text::transcode_result` type.

Remark

This function is a helper whose sole purpose is to ensure that the other half of error handling is called by transcode-style functions written by the end user (e.g., writing overriding hooks for `ztd::text::transcode`). This function attempts to take care of any unread/unwritten characters and other minor points in its pursuit of properly making sure the error manifests on the other side. Unlike its counterpart, this function does not take an `_Result` template parameter and instead deduces the returned transcode result type from inputs.

Parameters

- **__output** – [in] The output view to be writing into.
- **__to_encoding** – [in] The desired encoding that performs the encode portion of the transcoding step.
- **__decode_result** – [in] The decode result value that has an error on it.
- **__encode_result** – [in] The encode result value that represents what the next step would be if the decode did not work.
- **__encode_error_handler** – [in] The error handler to mill the `__result` and other relevant information through.
- **__to_state** – [in] The current state of the encoding step of the transcode operation.
- **__to_input_progress** – [in] Any unread output characters in any intermediate between the (failed) decode and encode operations.
- **__to_output_progress** – [in] Any unread output characters in any intermediates between the (failed) decode and encode operations.

```
template<typename _Result, typename _Input, typename _Output, typename _FromEncoding, typename
    _ToEncoding, typename _DecodeErrorHandler, typename _EncodeErrorHandler, typename _ToState,
    typename _FromInputProgress, typename _FromOutputProgress, typename _ToInputProgress, typename
    _ToOutputProgress, typename _ResultInput, typename _Intermediate, typename _FromState>
constexpr auto propagate_transcode_decode_error_with(
    _Input &&__input, _Output &&__output,
    _FromEncoding &&__from_encoding,
    _ToEncoding &&__to_encoding,
    decode_result<_ResultInput, _Intermediate,
    _FromState> &&__decode_result,
    _DecodeErrorHandler
    &&__decode_error_handler, _EncodeErrorHandler
    &&__encode_error_handler, _ToState &__to_state,
    _FromInputProgress &&__from_input_progress,
    _FromOutputProgress &&__from_output_progress,
    _ToInputProgress &&__to_input_progress,
    _ToOutputProgress &&__to_output_progress)
noexcept
```

Transcoding helper. Takes the given `__from_encoding`, `__to_encoding`, `__decode_error_handler`, and `__encode_error_handler` and launders the `ztd::text::decode_result` through the `__decode_error_handler`. The transformed decode result is then transformed to a `ztd::text::encode_result` before transforming that into the desired `ztd::text::transcode_result` type.

Remark

This function is a helper whose sole purpose is to ensure that the other half of error handling is called by transcode-style functions written by the end user (e.g., writing overriding hooks for `ztd::text::transcode`). This function attempts to take care of any unread/unwritten characters and other minor points in its pursuit of properly making sure the error manifests on the other side.

Template Parameters

_Result – The exact transcode result type to use.

Parameters

- **__output** – [in] The output view to be writing into.
- **__from_encoding** – [in] The desired encoding that performs the encode portion of the transcoding step.
- **__to_encoding** – [in] The desired encoding that performs the decode portion of the transcoding step.
- **__decode_result** – [in] The decode result value that has an error on it.
- **__decode_error_handler** – [in] The error handler to mill the `__result` and other relevant information through.
- **__encode_error_handler** – [in] The error handler to mill the `__decode_error_handler`'s invoked result and other relevant information through.
- **__to_state** – [in] The current state of the encoding step of the transcode operation.
- **__to_input_progress** – [in] Any unread output characters in any intermediate between the (failed) decode and encode operations.
- **__to_output_progress** – [in] Any unread output characters in any intermediates between the (failed) decode and encode operations.

```
template<typename _Input, typename _Output, typename _FromEncoding, typename _ToEncoding, typename
    _DecodeErrorHandler, typename _EncodeErrorHandler, typename _ToState, typename
    _FromInputProgress, typename _FromOutputProgress, typename _ToInputProgress, typename
    _ToOutputProgress, typename _ResultInput, typename _ResultIntermediate, typename _FromState>
constexpr auto propagate_transcode_decode_error_with(_Input &&__input, _Output &&__output,
    _FromEncoding &&__from_encoding,
    _ToEncoding &&__to_encoding,
    decode_result<_ResultInput, _ResultIntermediate,
    _FromState> &&__decode_result,
    _DecodeErrorHandler
    &&__decode_error_handler, _EncodeErrorHandler
    &&__encode_error_handler, _ToState &__to_state,
    _FromInputProgress &&__from_input_progress,
    _FromOutputProgress &&__from_output_progress,
    _ToInputProgress &&__to_input_progress,
    _ToOutputProgress &&__to_output_progress)
    noexcept
```

Transcoding helper. Takes the given `__from_encoding`, `__to_encoding`, `__decode_error_handler`, and `__encode_error_handler` and launders the `ztd::text::decode_result` through the `__decode_error_handler`.

The transformed decode result is then transformed to a `ztd::text::encode_result` before transforming that into the desired `ztd::text::transcode_result` type.

Remark

This function is a helper whose sole purpose is to ensure that the other half of error handling is called by transcode-style functions written by the end user (e.g., writing overriding hooks for `ztd::text::transcode`). This function attempts to take care of any unread/unwritten characters and other minor points in its pursuit of properly making sure the error manifests on the other side.

Template Parameters

_Result – The exact transcode result type to use.

Parameters

- **__output** – [in] The output view to be writing into.
- **__from_encoding** – [in] The desired encoding that performs the encode portion of the transcoding step.
- **__to_encoding** – [in] The desired encoding that performs the encode portion of the transcoding step.
- **__decode_result** – [in] The decode result value that has an error on it.
- **__decode_error_handler** – [in] The error handler to mill the `__result` and other relevant information through.
- **__encode_error_handler** – [in] The error handler to mill the `__decode_error_handler`'s invoked result and other relevant information through.
- **__to_state** – [in] The current state of the encoding step of the transcode operation.
- **__to_input_progress** – [in] Any unread output characters in any intermediate between the (failed) decode and encode operations.
- **__to_output_progress** – [in] Any unread output characters in any intermediates between the (failed) decode and encode operations.

```
template<typename _Result, typename _Input, typename _ToEncoding, typename _EncodeErrorHandler,
typename _ToInputProgress, typename _ToOutputProgress, typename _ResultInput, typename
_ResultPivot, typename _FromState, typename _ResultIntermediate, typename _ResultOutput, typename
_ToState>
```

```
constexpr auto propagate_transcode_encode_error_with(_Input &&__input, _ToEncoding
&&__to_encoding, decode_result<_ResultInput,
_ResultPivot, _FromState> &&__decode_result,
encode_result<_ResultIntermediate, _ResultOutput,
_ToState> &&__encode_result,
_EncodeErrorHandler &&__encode_error_handler,
_ToInputProgress &&__to_input_progress,
_ToOutputProgress &&__to_output_progress)
noexcept
```

Transcoding helper. Takes the given `__to_encoding` and `__encode_error_handler` and launders the failed `ztd::text::decode_result` through it, producing a `ztd::text::encode_result` and transforming that into the desired `ztd::text::transcode_result` type.

Remark

This function is a helper whose sole purpose is to ensure that the other half of error handling is called by transcode-style functions written by the end user (e.g., writing overriding hooks for `ztd::text::transcode`). This function attempts to take care of any unread/unwritten characters and other minor points in its pursuit of properly making sure the error manifests on the other side.

Template Parameters

_Result – The exact transcode result type to use.

Parameters

- **__output** – [in] The output view to be writing into.
- **__to_encoding** – [in] The desired encoding that performs the encode portion of the transcoding step.
- **__decode_result** – [in] The decode result value that has an error on it.
- **__encode_result** – [in] The encode result value that represents .
- **__encode_error_handler** – [in] The error handler to mill the `__result` and other relevant information through.
- **__to_state** – [in] The current state of the encoding step of the transcode operation.
- **__to_input_progress** – [in] Any unread output characters in any intermediate between the (failed) decode and encode operations.
- **__to_output_progress** – [in] Any unread output characters in any intermediates between the (failed) decode and encode operations.

```
template<typename _Input, typename _ToEncoding, typename _EncodeErrorHandler, typename
    _ToInputProgress, typename _ToOutputProgress, typename _ResultInput, typename _ResultPivot,
    typename _FromState, typename _ResultIntermediate, typename _ResultOutput, typename _ToState>
constexpr auto propagate_transcode_encode_error_with(_Input &&__input, _ToEncoding
    &&__to_encoding, decode_result<_ResultInput,
    _ResultPivot, _FromState> &&__decode_result,
    encode_result<_ResultIntermediate, _ResultOutput,
    _ToState> &&__encode_result,
    _EncodeErrorHandler &&__encode_error_handler,
    _ToInputProgress &&__to_input_progress,
    _ToOutputProgress &&__to_output_progress)
noexcept
```

Takes the given `__to_encoding` and `__encode_error_handler` and launders the failed `ztd::text::decode_result` through it, producing a `ztd::text::encode_result` and transforming that into the desired `ztd::text::transcode_result` type.

Remark

This function is a helper whose sole purpose is to ensure that the other half of error handling is called by transcode-style functions written by the end user (e.g., writing overriding hooks for `ztd::text::transcode`). This function attempts to take care of any unread/unwritten characters and other minor points in its pursuit of properly making

sure the error manifests on the other side. Unlike its counterpart, this function does not take an `_Result` template parameter and instead deduces the returned transcode result type from inputs.

Parameters

- `__output` – [in] The input view to be reading from.
- `__output` – [in] The output view to be writing into.
- `__to_encoding` – [in] The desired encoding that performs the encode portion of the transcoding step.
- `__decode_result` – [in] The decode result value that has an error on it.
- `__encode_result` – [in] The encode result value that represents .
- `__encode_error_handler` – [in] The error handler to mill the `__result` and other relevant information through.
- `__to_state` – [in] The current state of the encoding step of the transcode operation.
- `__to_input_progress` – [in] Any unread output characters in any intermediate between the (failed) decode and encode operations.
- `__to_output_progress` – [in] Any unread output characters in any intermediates between the (failed) decode and encode operations.

1.9 Progress & Future Work

This is where the status and progress of the library will be kept up to date. You can also check the [Issue Tracker](#) for specific issues and things being worked on! We also maintain a *very large list of encodings*, so you can check if a specific encoding you are looking for is supported (and if you will need to implement an *Encoding Object* for it).

1.9.1 Copyable State

Right now, all state parameters are assumed to be move-only. This is detrimental to creating cheap views like `.code_points()` on `basic_text_view`, and harms other types as well. Work should be done either to make copyable state, or allow passing state in more effectively (we currently do the passing technique at the moment).

- Do all states need to be copyable? Can it be done selectively? (At the moment: `basic_text_view` and `text_view` very well may need it, and as more Shift-State encodings become a part of the library, even more need...)

1.9.2 Transcoding Iterators/Transcode View

Right now these types would not work especially well for input and output ranges. They should be modified just like the internal `ztd::text::__txt_detail::__encoding_iterator` class types, so that they work with `input_iterator` and `output_iterator` types.

- Improve constructor delegation and make sure to explicitly implement default construction vs. letting it happen with `=default` (which does not work for some of the base types present).
- Modify implementation to cache data and position when an input or output iterator is detected.
- Return `const value_type&` for reference to enable C++20 ranges to work properly.
- Mark as `enable_borrowed_range` when C++20 is detected.

1.9.3 Normalization

`ztd::text::nfkd/nfk/nfc/nfkc/fcc` are all skeletons right now that need to be filled out for the purposes of giving this library normalization views.

- `nfkc`
- `nfc`
- `nfkd`
- `nfd`
- Hook up to `basic_text_view` and `basic_text` when finished

1.9.4 `basic_text_view`

`ztd::text::basic_text_view<Encoding, NormalizationForm, Range, ...>` is to be the premiere view for looking at text and preserving both the normalization and encoding form during insertion and erasure. It is not fully implemented yet, even though basic skeletons exist for it in the code base.

- Grapheme Cluster Iterators
- Code Point iterators
- Grapheme Cluster Iterators
- Comparison operators (If the normalization form is the same and *is_bitwise_transcoding_compatible*, then `memcmp`. If just normalization form and encoding is same, `memcmp`. Otherwise, code point by code point comparison.)

1.9.5 `basic_text`

`ztd::text::basic_text<Encoding, NormalizationForm, Storage, ...>` is to be the premiere container for storing text and preserving both the normalization and encoding form during insertion and erasure. It is not fully implemented yet, even though basic skeletons exist for it in the code base.

- Code Point iterators/ranges
- Grapheme Cluster Iterators
- Comparison operators (If the normalization form is the same and *is_bitwise_transcoding_compatible*, then `memcmp`. If just normalization form and encoding is same, `memcmp`. Otherwise, code point by code point comparison.)
- Insertion (Fast normalization-preserving splicing/inserting algorithm)
- Deletion
- Converting Constructors between compatible types (errors the same way *lossy conversion protection* describes if they are not compatible, forcing a user to pass in an error handler.)

1.10 Benchmarks

Below is a all of the benchmarks currently conducted and built-in to the code of this repository for the purposes of testing and improving the implementation. For further detail, read the article [here](#).

The specification for these benchmarks is as follows:

- The latest of each library was used as of 05 January, 2024.
- Windows 10 Pro machine, general user processes running in the background (but machine not being used).
- AMD Ryzen 9 5950X @ 3400 MHz (16 Core Processor), 32.0 GB Physical Memory
- Clang 15.0.3, latest available Clang at the time of generation with MSVC ABI.
- Entire software stack for every dependency build under default CMake flags (including ICU and libiconv from vcpkg).
- Anywhere from 150 to 10million samples per iteration, with mean (average) of 100 iterations forming transparent dots on graph.
- Each bar graph is mean of the 150 iterations, with provided standard deviation-based error bars.
- For the sake of keeping an almost identical set of bars in each graph, sometimes a library is explicitly shown as “unsupported”. “Unsupported” is different from doing a conversion but then failing, or doing a conversion and producing the wrong output.
- If an error occurs during the benchmark, its graph will instead feature a short text blurb explaining what went wrong. The benchmarking code can be read to understand further what happened.
- **In general, unless explicitly noted, the fastest possible API under the constraints was used to produce the data.**
 - “Unbounded” means that, where shown, the available space left for writing was not considered.
 - “Unchecked” means that, where shown, the input was not validated before being converted.
 - “Well-Formed”, in the title, means that the input was well-formed.
 - (We do not do error benchmarks (yet).)

The categories of benchmarks are as follows:

1.10.1 Function Form

The following benchmarks test the conversion of the entire set of valid Unicode Scalar Values (all Unicode code points, except the surrogate values used for UTF-16). The transcoding done is UTF-32 to UTF-8, with as-identical an internal conversion routine as possible. The only differences in the internal workings of the conversion are in reaction to the inputs and outputs given.

The goal of these benchmarks is to measure how using a basic, single (indivisible unit of work) conversion run in a loop can affect speed based on how the function is structured. This is mostly relevant in the case of libraries like [musl-libc](#), where the maintainers expressly declared they would NOT optimize the bulk-conversion functions to do anything and would rather write the base conversion loop:


...

On musl (where I’m familiar with performance properties), byte-at-a-time conversion is roughly half the speed of bulk, which looks big but is diminishingly so if you’re actually doing something with the result (just converting to `wchar_t` for its own sake is not very useful).

—Rich Felker, December 30th, 2019, [musl libc mailing list](#).

Here, we can see how writing the bulk conversion functions in terms of the single functions are affected by a given API design.

All Unicode Code Points



C Basic Source Character Set

1.10.2 INTERNAL Transcoding - Unicode Encodings


Warning: The benchmarks in this section are solely for tracking the behavior and runtime of effectively niche or internal behaviors, such as single conversion from bulk functionality built into ztd.cuneicode’s registry or how much it costs to run a basic loop.

Please keep this in mind as you browse.

The purpose of these graphs is to see how expensive it is for various styles of encoding. It includes all of the other benchmarks, but adds a few more for ztd.cuneicode and ztd.text. These labels are the more important ones:

- “single from bulk loop”
- “basic”

These mirror the points documented here; specifically, using a limiting technique to recreate a one-at-a-time, indivisible unit of work from a single loop, or using a technique to process an entire set of input by using the one-by-one functions. The latter technique is the foundation of both ztd.text and ztd.cuneicode, so it is illuminating to see how (poorly) the former technique (“single from bulk”) performs against the latter technique (“basic”, the bulk-from-single functionality). This described [:doc:here](#).



All Unicode Code Points

The following benchmarks test the conversion of the basic source character set (from C and C++), going from one UTF encoding to another UTF encoding. It helps test speed under larger conversions.

All Unicode Code Points, With Initialization



The following benchmarks measure the same conversion, but with any initialization object included within the conversion (e.g., for modeling a library that cannot store a registry/conversion descriptor somewhere).



C Basic Source Character Set



The following benchmarks test a much smaller conversion on the basic source character set, checking not only ASCII but how well the conversion works for a much smaller inputs.



C Basic Source Character Set, With Initialization



The following benchmarks measure the same conversion, but with any initialization object included within the conversion (e.g., for modeling a library that cannot store a registry/conversion descriptor somewhere).
























































1.10.3 Transcoding - Unicode Encodings

Conversion speed is one of the biggest points of a transcoding API. The benchmarks here are meant to test how fast a conversion could potentially be, taking into account any affordances the API can give for speed (such as not checking the output write, not validating for input, or doing an indivisible unit of conversion in a loop/a range conversion/etc.). All the input text right now is completely valid and well-formed input; some of the benchmarks will take advantage of this to assume the input is valid. Such benchmarks are presented as separate graphs, and only for the APIs that allow it.



All Unicode Code Points



The following benchmarks test the conversion of the basic source character set (from C and C++), going from one UTF encoding to another UTF encoding. It helps test speed under larger conversions.







All Unicode Code Points, With Initialization



The following benchmarks measure the same conversion, but with any initialization object included within the conversion (e.g., for modeling a library that cannot store a registry/conversion descriptor somewhere).






















C Basic Source Character Set

The following benchmarks test a much smaller conversion on the basic source character set, checking not only ASCII but how well the conversion works for a much smaller inputs.

C Basic Source Character Set, With Initialization

The following benchmarks measure the same conversion, but with any initialization object included within the conversion (e.g., for modeling a library that cannot store a registry/conversion descriptor somewhere).

1.11 Licenses, Thanks and Attribution



ztd.text is dual-licensed under either the Apache 2 License, or a corporate license if you bought it with special support. See the LICENSE file or your copy of the corporate license agreement for more details!



1.11.1 Third-party Dependencies and Code



All third-party code is listed in the NOTICE file. It is also reproduced here. In particular:



- Martin Moene; [span-lite](#) (Boost 1.0 License) - Code included directly and made available if a C++20 `` is not present.



We thank Martin Moene for their hard work.























1.11.2 Previous and Related Works

Previous attempts at text and text handling libraries were made by various authors. We note them here:

- Tom Honermann; [text_view](#).
- Zach Laine; [Boost.Text](#).
- Henri Sivonen; [encoding_rs](#).
- rmf; [libogonek](#).

Their work was groundbreaking when it first came about and employed similar concepts found in this library. We thank them for their efforts in moving Text Encoding, Unicode, and Systems Programming forward.

1.11.3 Helping Hands

Whether it's just a little bit of time, a point towards the right direction, or some ideas, this library builds upon a lot of collective knowledge and effort. Here we list some of the folks who have spent some time doing this best to make sure we have the greatest text library on the planet for C++:

- CopperSpice; Talking over many of their design struggles with trying to make better text in CopperSpice/Qt (https://www.youtube.com/watch?v=w_kD-qAkoH0)
- Luna & Lambda Kitten: Kick-starting better support for Clang / Apple (<https://twitter.com/lambdakitten/status/1418240846638485510>)
- Much of rmf and [Henri Sivonen's](#) writings and thoughts on the subjects of Unicode.
- All of [Tom Honermann's](#) previous work on Unicode, Text Processing, and Standardization.

1.11.4 Charitable Contributions

ztd.text has been made possible by charitable contributions from patrons and sponsors around the world:

- Shepherd's Oasis, LLC (<https://soasis.org>)
- Jane Lusby
- Orfeas Zafeiris
- Tom Honermann
- Lily Foster
- Camilla Löwy
- Leonardo Lima
- Piotr Piatkowski
- Cynthia Coan
- Johan Andersson
- Erekose Craft
- Christopher Crouzet
- Michael Schellenberger Costa
- Turig Eret
- Brent Beer

- Matt Godbolt
- Erica Brescia
- Carol Chen
- Jeremy Jung
- Max Stoiber
- Evan Lock
- Anil Kumar
- Vincent Weevers
- Ólafur Waage
- Jeff Trull
- Davide Faconti
- Anthony Nandaa
- Christ Drozdowski
- Douglas Creager
- superfunc
- Michael Caisse
- Joshua Fisher
- Billy O’Neal
- Sy Brand
- Eric Tremblay
- Michał Dominiak
- Zach Toogood
- beluga
- Alex Gilding
- Kirk Shoop
- Alex Hadd
- Jimmy “junoravin”
- Joel Falcou
- Pascal Menuet
- Elias Daler
- Randomnetcat
- Robert Maynard
- Martin Hořeňovský
- Hana Dusíková
- 7 more private sponsors
- And many, many more!

(If you are new to being a patron, sponsor, or donator and you don't see your name here, I may have bungled the export list, so please e-mail opensource@soasis.org!)

1.12 Bibliography

These are all the resources that this documentation links to, in alphabetical order.

cuneicode

JeanHeyd Meneide & Shepherd's Oasis, LLC. cuneicode. September 2022. URL: <https://savannah.gnu.org/git/?group=libiconv>. A software library for working with and converting text. Typically ships on most, if not all, POSIX and Linux systems.

encoding_rs

Henri Sivonen. "encoding_rs". February 2021. URL: <https://github.com/libogonek/ogonek>. A Rust library for performing encoding and decoding tasks. Takes a byte-based approach to handling encodings and decodings. The developer of this library worked on text for a very long time on Mozilla Firefox, and has great insight into the field of text [on their blog, https://hsivonen.fi](https://hsivonen.fi).

Fast UTF-8

Bob Steagall. "Fast Conversion from UTF-8 with C++, DFAs, and SSE Intrinsics". September 26th, 2019. URL: <https://www.youtube.com/watch?v=5FQ87-Ecb-A>. This presentation demonstrates one of the ways an underlying fast decoder for UTF-8 can be written, rather than just letting the default work. This work can be hooked into the *conversion function extension points* location.

Fast UTF-8 Validation

Daniel Lemire. "Ridiculously fast unicode (UTF-8) validation". October 20th, 2020. URL: <https://lemire.me/blog/2020/10/20/ridiculously-fast-unicode-utf-8-validation/>. This blog post is one of many that presents a faster, more optimized way to validate that UTF-8 is in its correctly form.

glibc-25744

Tom Honermann and Carlos O'Donnell. *mbrtowc* with Big5-HKSCS returns 2 instead of 1 when consuming the second byte of certain double byte characters. https://sourceware.org/bugzilla/show_bug.cgi?id=25744. This bug report details the problem with the C standard library's ability to handle multiwide characters. This problem is also present in the "1:N" and "N:1" rules in the C++ standard library.

iconv

Bruno Haible and Daiki Ueno. libiconv. August 2020. URL: <https://savannah.gnu.org/git/?group=libiconv>. A software library for working with and converting text. Typically ships on most, if not all, POSIX and Linux systems.

ICU

Unicode Consortium. "International Components for Unicode". April 17th, 2019. URL: https://github.com/hsivonen/encoding_rs The premiere library for not only performing encoding conversions, but performing other Unicode-related algorithms on sequences of text.

libogonek

R. Martinho Fernandes. "libogonek: A C++11 Library for Unicode". September 29th, 2019. URL: <http://site.icu-project.org/> One of the first influential C++11 libraries to bring the concept of iterators and ranges to not only encoding, but normalization and others. It's great design was only limited by how incapable C++11 as a language was for what its author was trying to do.

n2282

Philip K. Krause. "N2282 - Additional multibyte/wide string conversion functions". June 2018. URL: <http://www.open-std.org/jtc1/sc22/wg14/www/docs/n2282.htm>. This paper attempted to add a few unicode functions to the list of things to do without changing anything.

Non-Unicode in C++

Henri Sivonen. “P0244 - Text_view: A C++ concepts and range based character encoding and code point enumeration library”. URL: <https://hsivonen.fi/non-unicode-in-cpp/>. A rebuttal to P0244’s “strong code points” and “strong code units” opinion. This is talked about in depth in the design documentation for *strong vs. weak code point and code unit types*.

p0244

Tom Honermann. “P0244 - Text_view: A C++ concepts and range based character encoding and code point enumeration library”. URL: <https://wg21.link/p0244>. A C++ proposal written by Tom Honermann, proposing some of the first ideas for an extensible text encoding interface and lightweight ranges built on top of that. Reference implementation: https://github.com/tahonermann/text_view.

p1041

R. Martinho Fernandes. “P1041: Make char16_t/char32_t string literals be UTF-16/32”. February 2019. URL: <https://wg21.link/p1041>. This accepted paper enabled C++ to strongly associate all char16_t and char32_t string literals with UTF-16 and UTF-32. This is not the case for C.

1.13 Troubleshooting / Compilation Errors / Runtime Problems (In Progress)

Warning: This isn’t finished yet! Come check back by the next major or minor version update.

This is a section that contains troubleshooting, typical compilation errors, and FAQs/fixes for common problems. It is meant to be mostly for linking to answers for repeated existing problems when using the library. It is barren at the moment, but hopefully will be filled out more as the library’s lifetime increases. If you would like to see something here, please do not hesitate to [file an issue at the repository](#).

1.13.1 Common Compile/Runtime Errors

- Passing a non-borrowed range (a range which, effectively, cannot be cheaply copied) is considered an error since it has grace performance impacts. If you know that you are passing a range into the *_into class of functions, please mark that range as a borrowed range using `std::ranges::enable_borrowed_range` (C++20) or `ztd::ranges::enable_borrowed_range` (C++17 and lower) so that ztd.text knows how to handle it.

INDICES & SEARCH

2.1 Index

Symbols

- `__execution_mac_os` (C++ class), 143
- `__execution_mac_os::code_point` (C++ type), 143
- `__execution_mac_os::code_unit` (C++ type), 143
- `__execution_mac_os::decode_one` (C++ function), 144, 145
- `__execution_mac_os::decode_state` (C++ type), 143
- `__execution_mac_os::encode_one` (C++ function), 144, 145
- `__execution_mac_os::encode_state` (C++ type), 143
- `__execution_mac_os::is_decode_injective` (C++ type), 143
- `__execution_mac_os::is_encode_injective` (C++ type), 143
- `__execution_mac_os::is_unicode_encoding` (C++ type), 143
- `__execution_mac_os::max_code_points` (C++ member), 144
- `__execution_mac_os::max_code_units` (C++ member), 145
- `__unicode_code_point` (C++ class), 375
- `__unicode_code_point::__unicode_code_point` (C++ function), 375
- `__unicode_code_point::operator char32_t` (C++ function), 376
- `__unicode_code_point::value` (C++ function), 376
- `__unicode_scalar_value` (C++ class), 376
- `__unicode_scalar_value::__unicode_scalar_value` (C++ function), 377
- `__unicode_scalar_value::operator char32_t` (C++ function), 377
- `__unicode_scalar_value::value` (C++ function), 377
- `__wide_execution_cwchar` (C++ class), 191
- `__wide_execution_cwchar::code_point` (C++ type), 191
- `__wide_execution_cwchar::code_unit` (C++ type), 191
- `__wide_execution_cwchar::contains_unicode_encoding` (C++ function), 192
- `__wide_execution_cwchar::decode_one` (C++ function), 193
- `__wide_execution_cwchar::decode_state` (C++ type), 191
- `__wide_execution_cwchar::encode_one` (C++ function), 193
- `__wide_execution_cwchar::encode_state` (C++ type), 191
- `__wide_execution_cwchar::is_decode_injective` (C++ type), 192
- `__wide_execution_cwchar::is_encode_injective` (C++ type), 192
- `__wide_execution_cwchar::is_unicode_encoding` (C++ type), 192
- `__wide_execution_cwchar::max_code_points` (C++ member), 194
- `__wide_execution_cwchar::max_code_units` (C++ member), 194
- `__wide_execution_iso10646` (C++ class), 194
- `__wide_execution_iso10646::code_point` (C++ type), 195
- `__wide_execution_iso10646::code_unit` (C++ type), 195
- `__wide_execution_iso10646::decode_one` (C++ function), 195, 196
- `__wide_execution_iso10646::decode_state` (C++ type), 195
- `__wide_execution_iso10646::encode_one` (C++ function), 195, 197
- `__wide_execution_iso10646::encode_state` (C++ type), 195
- `__wide_execution_iso10646::is_decode_injective` (C++ type), 195
- `__wide_execution_iso10646::is_encode_injective` (C++ type), 195
- `__wide_execution_iso10646::is_unicode_encoding` (C++ type), 195
- `__wide_execution_iso10646::max_code_points` (C++ member), 196
- `__wide_execution_iso10646::max_code_units` (C++ member), 196
- `__wide_execution_windows` (C++ class), 197

__wide_execution_windows::code_point (C++ any_encoding (C++ type), 115
 type), 198 any_encoding_with (C++ class), 120
 __wide_execution_windows::code_unit (C++ any_encoding_with::any_decode_state (C++
 type), 198 class), 125
 __wide_execution_windows::decode_one (C++ any_encoding_with::any_decode_state::any_decode_state
 function), 198 (C++ function), 125
 __wide_execution_windows::decode_state (C++ any_encoding_with::any_decode_state::operator=
 type), 198 (C++ function), 125
 __wide_execution_windows::encode_one (C++ any_encoding_with::any_encode_state (C++
 function), 198 class), 125
 __wide_execution_windows::encode_state (C++ any_encoding_with::any_encode_state::any_encode_state
 type), 198 (C++ function), 126
 __wide_execution_windows::is_decode_injective any_encoding_with::any_encode_state::operator=
 (C++ type), 198 (C++ function), 126
 __wide_execution_windows::is_encode_injective any_encoding_with::any_encoding_with (C++
 (C++ type), 198 function), 122, 123
 __wide_execution_windows::is_unicode_encoding any_encoding_with::code_point (C++ type), 121
 (C++ type), 198 any_encoding_with::code_unit (C++ type), 121
 __wide_execution_windows::max_code_points any_encoding_with::contains_unicode_encoding
 (C++ member), 199 (C++ function), 123
 __wide_execution_windows::max_code_units any_encoding_with::decode_one (C++ function),
 (C++ member), 199 124
 any_encoding_with::decode_state (C++ type), 121
 any_encoding_with::decoded_id (C++ member),
 125
 any_encoding_with::encode_one (C++ function),
 124
 any_encoding_with::encode_state (C++ type), 121
 any_encoding_with::encoded_id (C++ member),
 125
 any_encoding_with::is_decode_injective (C++
 type), 122
 any_encoding_with::is_encode_injective (C++
 type), 122
 any_encoding_with::max_code_points (C++ mem-
 ber), 125
 any_encoding_with::max_code_units (C++ mem-
 ber), 125
 any_encoding_with::maybe_replacement_code_points
 (C++ function), 123
 any_encoding_with::maybe_replacement_code_units
 (C++ function), 123
 any_encoding_with::operator= (C++ function), 123
 ascii (C++ member), 126
 ascii_t (C++ type), 126
 assume_valid_handler (C++ member), 206
 assume_valid_handler_t (C++ class), 206
 assume_valid_handler_t::assume_valid (C++
 type), 207
 assume_valid_handler_t::operator() (C++ func-
 tion), 207
 atari_st (C++ member), 166
 atascii (C++ member), 166

A

any_byte_encoding (C++ class), 115
 any_byte_encoding::any_byte_encoding (C++
 function), 116–118
 any_byte_encoding::code_point (C++ type), 116
 any_byte_encoding::code_unit (C++ type), 116
 any_byte_encoding::contains_unicode_encoding
 (C++ function), 118
 any_byte_encoding::decode_one (C++ function),
 119
 any_byte_encoding::decode_state (C++ type), 115
 any_byte_encoding::decoded_id (C++ member),
 120
 any_byte_encoding::encode_one (C++ function),
 119
 any_byte_encoding::encode_state (C++ type), 115
 any_byte_encoding::encoded_id (C++ member),
 120
 any_byte_encoding::is_decode_injective (C++
 type), 116
 any_byte_encoding::is_encode_injective (C++
 type), 116
 any_byte_encoding::max_code_points (C++ mem-
 ber), 120
 any_byte_encoding::max_code_units (C++ mem-
 ber), 120
 any_byte_encoding::maybe_replacement_code_points
 (C++ function), 118
 any_byte_encoding::maybe_replacement_code_units
 (C++ function), 118
 any_byte_encoding::operator= (C++ function), 118

B

- basic_any_punycode (C++ class), 160
- basic_any_punycode::code_point (C++ type), 161
- basic_any_punycode::code_unit (C++ type), 161
- basic_any_punycode::decode_one (C++ function), 161
- basic_any_punycode::encode_one (C++ function), 161
- basic_any_punycode::is_decode_injective (C++ type), 161
- basic_any_punycode::is_encode_injective (C++ type), 161
- basic_any_punycode::max_code_points (C++ member), 162
- basic_any_punycode::max_code_units (C++ member), 162
- basic_ascii (C++ class), 126
- basic_ascii::code_point (C++ type), 127
- basic_ascii::code_unit (C++ type), 127
- basic_ascii::decode_one (C++ function), 127
- basic_ascii::encode_one (C++ function), 128
- basic_ascii::is_decode_injective (C++ type), 127
- basic_ascii::is_encode_injective (C++ type), 127
- basic_ascii::max_code_points (C++ member), 129
- basic_ascii::max_code_units (C++ member), 129
- basic_ascii::replacement_code_units (C++ function), 127
- basic_ascii::state (C++ type), 127
- basic_atari_st (C++ class), 168
- basic_atascii (C++ class), 168
- basic_big5_hkscs (C++ class), 130
- basic_big5_hkscs::code_point (C++ type), 130
- basic_big5_hkscs::code_unit (C++ type), 130
- basic_big5_hkscs::decode_one (C++ function), 131
- basic_big5_hkscs::encode_one (C++ function), 131
- basic_big5_hkscs::is_decode_injective (C++ type), 130
- basic_big5_hkscs::max_code_points (C++ member), 132
- basic_big5_hkscs::max_code_units (C++ member), 132
- basic_big5_hkscs::replacement_code_units (C++ function), 130
- basic_big5_hkscs::state (C++ type), 130
- basic_count_as_decoded (C++ function), 215
- basic_count_as_transcoded (C++ function), 219
- basic_decode_into (C++ function), 229
- basic_decode_into_raw (C++ function), 227
- basic_encode_into (C++ function), 248
- basic_encode_into_raw (C++ function), 246
- basic_euc_kr_uhc (C++ class), 140
- basic_euc_kr_uhc::code_point (C++ type), 140
- basic_euc_kr_uhc::code_unit (C++ type), 140
- basic_euc_kr_uhc::decode_one (C++ function), 140
- basic_euc_kr_uhc::encode_one (C++ function), 141
- basic_euc_kr_uhc::is_decode_injective (C++ type), 140
- basic_euc_kr_uhc::max_code_points (C++ member), 142
- basic_euc_kr_uhc::max_code_units (C++ member), 142
- basic_euc_kr_uhc::replacement_code_units (C++ function), 140
- basic_euc_kr_uhc::state (C++ type), 140
- basic_gb18030 (C++ class), 146
- basic_gb18030::code_point (C++ type), 147
- basic_gb18030::code_unit (C++ type), 147
- basic_gb18030::decode_one (C++ function), 147
- basic_gb18030::encode_one (C++ function), 148
- basic_gb18030::is_decode_injective (C++ type), 147
- basic_gb18030::is_encode_injective (C++ type), 147
- basic_gb18030::is_unicode_encoding (C++ type), 147
- basic_gb18030::max_code_points (C++ member), 148
- basic_gb18030::max_code_units (C++ member), 148
- basic_gb18030::replacement_code_points (C++ function), 147
- basic_gb18030::replacement_code_units (C++ function), 147
- basic_gb18030::state (C++ type), 147
- basic_gbk (C++ class), 149
- basic_gbk::code_point (C++ type), 149
- basic_gbk::code_unit (C++ type), 149
- basic_gbk::decode_one (C++ function), 150
- basic_gbk::encode_one (C++ function), 150
- basic_gbk::is_decode_injective (C++ type), 149
- basic_gbk::is_encode_injective (C++ type), 149
- basic_gbk::is_unicode_encoding (C++ type), 149
- basic_gbk::max_code_points (C++ member), 151
- basic_gbk::max_code_units (C++ member), 151
- basic_gbk::replacement_code_points (C++ function), 150
- basic_gbk::replacement_code_units (C++ function), 150
- basic_gbk::state (C++ type), 149
- basic_ibm_1006_urdu (C++ class), 169
- basic_ibm_424_hebrew_bulletin (C++ class), 169
- basic_ibm_856_hebrew (C++ class), 169
- basic_ibm_866_cyrillic (C++ class), 169
- basic_iconv (C++ class), 129
- basic_incomplete_handler (C++ class), 208

basic_incomplete_handler::base (C++ *function*), 209
 basic_incomplete_handler::basic_incomplete_handler (C++ *function*), 209
 basic_incomplete_handler::code_points (C++ *function*), 210
 basic_incomplete_handler::code_units (C++ *function*), 210
 basic_incomplete_handler::error_handler (C++ *type*), 208
 basic_incomplete_handler::operator() (C++ *function*), 209, 210
 basic_iso_8859_1 (C++ *class*), 170
 basic_iso_8859_10 (C++ *class*), 173
 basic_iso_8859_13 (C++ *class*), 174
 basic_iso_8859_14 (C++ *class*), 174
 basic_iso_8859_15 (C++ *class*), 174
 basic_iso_8859_16 (C++ *class*), 174
 basic_iso_8859_1::code_point (C++ *type*), 170
 basic_iso_8859_1::code_unit (C++ *type*), 170
 basic_iso_8859_1::decode_one (C++ *function*), 171
 basic_iso_8859_1::encode_one (C++ *function*), 171
 basic_iso_8859_1::is_decode_injective (C++ *type*), 170
 basic_iso_8859_1::is_encode_injective (C++ *type*), 171
 basic_iso_8859_1::max_code_points (C++ *member*), 172
 basic_iso_8859_1::max_code_units (C++ *member*), 172
 basic_iso_8859_1::replacement_code_units (C++ *function*), 171
 basic_iso_8859_1::state (C++ *type*), 170
 basic_iso_8859_1_1985 (C++ *class*), 169
 basic_iso_8859_1_1998 (C++ *class*), 170
 basic_iso_8859_2 (C++ *class*), 172
 basic_iso_8859_3 (C++ *class*), 172
 basic_iso_8859_4 (C++ *class*), 172
 basic_iso_8859_5 (C++ *class*), 173
 basic_iso_8859_6 (C++ *class*), 173
 basic_iso_8859_7 (C++ *class*), 173
 basic_iso_8859_8 (C++ *class*), 173
 basic_kamenicky (C++ *class*), 174
 basic_kazakh_strk1048 (C++ *class*), 175
 basic_koi8_r (C++ *class*), 175
 basic_koi8_u (C++ *class*), 175
 basic_mutf8 (C++ *class*), 155
 basic_mutf8::code_point (C++ *type*), 156
 basic_mutf8::code_unit (C++ *type*), 156
 basic_mutf8::decode_one (C++ *function*), 157
 basic_mutf8::decode_state (C++ *type*), 155
 basic_mutf8::decoded_id (C++ *member*), 158
 basic_mutf8::encode_one (C++ *function*), 157
 basic_mutf8::encode_state (C++ *type*), 156
 basic_mutf8::encoded_id (C++ *member*), 158
 basic_mutf8::is_decode_injective (C++ *type*), 156
 basic_mutf8::is_encode_injective (C++ *type*), 156
 basic_mutf8::is_unicode_encoding (C++ *type*), 155
 basic_mutf8::max_code_points (C++ *member*), 158
 basic_mutf8::max_code_units (C++ *member*), 158
 basic_mutf8::replacement_code_points (C++ *function*), 156
 basic_mutf8::replacement_code_units (C++ *function*), 156
 basic_mutf8::self_synchronizing_code (C++ *type*), 155
 basic_mutf8::skip_input_error (C++ *function*), 156
 basic_petscii (C++ *class*), 159
 basic_petscii_shifted (C++ *class*), 176
 basic_petscii_unshifted (C++ *class*), 175
 basic_punycode (C++ *type*), 159
 basic_punycode_idna (C++ *type*), 160
 basic_recode_into_raw (C++ *function*), 265
 basic_recode_one_into (C++ *function*), 290
 basic_recode_one_into_raw (C++ *function*), 285
 basic_shift_jis (C++ *type*), 163
 basic_shift_jis_x0208 (C++ *class*), 163
 basic_shift_jis_x0208::code_point (C++ *type*), 164
 basic_shift_jis_x0208::code_unit (C++ *type*), 164
 basic_shift_jis_x0208::decode_one (C++ *function*), 164
 basic_shift_jis_x0208::encode_one (C++ *function*), 164
 basic_shift_jis_x0208::is_decode_injective (C++ *type*), 164
 basic_shift_jis_x0208::max_code_points (C++ *member*), 165
 basic_shift_jis_x0208::max_code_units (C++ *member*), 165
 basic_shift_jis_x0208::replacement_code_units (C++ *function*), 164
 basic_shift_jis_x0208::state (C++ *type*), 164
 basic_tatar_ansi (C++ *class*), 176
 basic_tatar_ascii (C++ *class*), 176
 basic_text (C++ *class*), 79
 basic_text_view (C++ *class*), 80
 basic_text_view::base (C++ *function*), 82
 basic_text_view::code_points (C++ *function*), 81, 82
 basic_text_view::encoding_type (C++ *type*), 81
 basic_text_view::error_handler_type (C++ *type*), 81

basic_text_view::normalization_type (C++ type), 81
 basic_text_view::range_type (C++ type), 81
 basic_text_view::state_type (C++ type), 81
 basic_transcode_into_raw (C++ function), 308
 basic_transcode_one_into (C++ function), 333
 basic_transcode_one_into_raw (C++ function), 328
 basic_utf16 (C++ class), 179
 basic_utf16::code_point (C++ type), 180
 basic_utf16::code_unit (C++ type), 180
 basic_utf16::decode_one (C++ function), 181
 basic_utf16::decoded_id (C++ member), 182
 basic_utf16::encode_one (C++ function), 181
 basic_utf16::encoded_id (C++ member), 182
 basic_utf16::is_decode_injective (C++ type), 180
 basic_utf16::is_encode_injective (C++ type), 180
 basic_utf16::is_unicode_encoding (C++ type), 179
 basic_utf16::max_code_points (C++ member), 182
 basic_utf16::max_code_units (C++ member), 182
 basic_utf16::replacement_code_points (C++ function), 180
 basic_utf16::replacement_code_units (C++ function), 180
 basic_utf16::self_synchronizing_code (C++ type), 179
 basic_utf16::skip_input_error (C++ function), 180, 181
 basic_utf16::state (C++ type), 180
 basic_utf16_be (C++ type), 132
 basic_utf16_le (C++ type), 132
 basic_utf16_ne (C++ type), 133
 basic_utf32 (C++ class), 183
 basic_utf32::code_point (C++ type), 183
 basic_utf32::code_unit (C++ type), 183
 basic_utf32::decode_one (C++ function), 184
 basic_utf32::decoded_id (C++ member), 185
 basic_utf32::encode_one (C++ function), 184
 basic_utf32::encoded_id (C++ member), 185
 basic_utf32::is_decode_injective (C++ type), 183
 basic_utf32::is_encode_injective (C++ type), 184
 basic_utf32::is_unicode_encoding (C++ type), 183
 basic_utf32::max_code_points (C++ member), 185
 basic_utf32::max_code_units (C++ member), 185
 basic_utf32::self_synchronizing_code (C++ type), 183
 basic_utf32::skip_input_error (C++ function), 184
 basic_utf32::state (C++ type), 183
 basic_utf32_be (C++ type), 133
 basic_utf32_le (C++ type), 133
 basic_utf32_ne (C++ type), 133
 basic_utf8 (C++ class), 186
 basic_utf8::code_point (C++ type), 187
 basic_utf8::code_unit (C++ type), 187
 basic_utf8::decode_one (C++ function), 189
 basic_utf8::decode_state (C++ type), 187
 basic_utf8::decoded_id (C++ member), 189
 basic_utf8::encode_one (C++ function), 188
 basic_utf8::encode_state (C++ type), 187
 basic_utf8::encoded_id (C++ member), 189
 basic_utf8::is_decode_injective (C++ type), 187
 basic_utf8::is_encode_injective (C++ type), 187
 basic_utf8::is_unicode_encoding (C++ type), 187
 basic_utf8::max_code_points (C++ member), 189
 basic_utf8::max_code_units (C++ member), 189
 basic_utf8::replacement_code_points (C++ function), 188
 basic_utf8::replacement_code_units (C++ function), 188
 basic_utf8::self_synchronizing_code (C++ type), 187
 basic_utf8::skip_input_error (C++ function), 188
 basic_validate_decodable_as (C++ function), 349
 basic_validate_encodable_as (C++ function), 352
 basic_validate_transcodable_as (C++ function), 355
 basic_windows_1251 (C++ class), 177
 basic_windows_1252 (C++ class), 177
 basic_windows_1253 (C++ class), 177
 basic_windows_1254 (C++ class), 177
 basic_windows_1255 (C++ class), 178
 basic_windows_1256 (C++ class), 178
 basic_windows_1257 (C++ class), 178
 basic_windows_1258 (C++ class), 178
 basic_windows_437_dos_latin_us (C++ class), 176
 basic_windows_865_dos_nordic (C++ class), 176
 basic_windows_874 (C++ class), 177
 basic_wtf8 (C++ class), 203
 basic_wtf8::code_point (C++ type), 204
 basic_wtf8::code_unit (C++ type), 204
 basic_wtf8::decode_one (C++ function), 205
 basic_wtf8::decode_state (C++ type), 204
 basic_wtf8::decoded_id (C++ member), 206
 basic_wtf8::encode_one (C++ function), 205
 basic_wtf8::encode_state (C++ type), 204
 basic_wtf8::encoded_id (C++ member), 206
 basic_wtf8::is_decode_injective (C++ type), 204
 basic_wtf8::is_encode_injective (C++ type), 204
 basic_wtf8::is_unicode_encoding (C++ type), 203
 basic_wtf8::max_code_points (C++ member), 206
 basic_wtf8::max_code_units (C++ member), 206

- basic_wtf8::replacement_code_points (C++ function), 204
 basic_wtf8::replacement_code_units (C++ function), 204
 basic_wtf8::self_synchronizing_code (C++ type), 203
 basic_wtf8::skip_input_error (C++ function), 204
 big5_hksks (C++ member), 130
- ## C
- character, 20
 code point, 20
 code unit, 20
 code_point (C++ class), 358
 code_point::type (C++ type), 358
 code_point_t (C++ type), 358
 code_unit (C++ class), 358
 code_unit::type (C++ type), 358
 code_unit_t (C++ type), 358
 compat_utf8 (C++ member), 186
 compat_utf8_t (C++ type), 186
 contains_unicode_encoding (C++ function), 366
 count_as_decoded (C++ function), 216, 217
 count_as_transcoded (C++ function), 220–224
 count_result (C++ class), 397
 count_result::count (C++ member), 398
 count_result::count_result (C++ function), 397
 count_result::error_code (C++ member), 398
 count_result::error_count (C++ member), 398
 count_result::errors_were_handled (C++ function), 397
 count_result::input (C++ member), 398
 count_result::state (C++ member), 398
 cuneicode, 459
- ## D
- decode, 20
 decode (C++ function), 234, 235
 decode_into (C++ function), 230, 231
 decode_into_raw (C++ function), 227–229
 decode_iterator (C++ class), 85
 decode_iterator::decode_iterator (C++ function), 87, 88
 decode_iterator::difference_type (C++ type), 86
 decode_iterator::encoding_type (C++ type), 86
 decode_iterator::error_handler_type (C++ type), 86
 decode_iterator::iterator (C++ type), 86
 decode_iterator::iterator_category (C++ type), 86
 decode_iterator::iterator_concept (C++ type), 86
 decode_iterator::operator= (C++ function), 89
 decode_iterator::pointer (C++ type), 86
 decode_iterator::range_type (C++ type), 86
 decode_iterator::reference (C++ type), 86
 decode_iterator::state_type (C++ type), 86
 decode_iterator::value_type (C++ type), 86
 decode_one (C++ function), 241–243
 decode_one_into (C++ function), 237–239
 decode_one_into_raw (C++ function), 236, 237
 decode_one_to (C++ function), 239–241
 decode_result (C++ class), 379
 decode_result::decode_result (C++ function), 379, 380
 decode_result::error_code (C++ member), 380
 decode_result::error_count (C++ member), 381
 decode_result::errors_were_handled (C++ function), 380
 decode_result::input (C++ member), 380
 decode_result::output (C++ member), 380
 decode_result::state (C++ member), 380
 decode_state (C++ class), 358
 decode_state::type (C++ type), 359
 decode_state_t (C++ type), 359
 decode_to (C++ function), 232, 233
 decode_view (C++ class), 83
 decode_view::begin (C++ function), 85
 decode_view::decode_view (C++ function), 84, 85
 decode_view::encoding_type (C++ type), 83
 decode_view::end (C++ function), 85
 decode_view::error_handler_type (C++ type), 83
 decode_view::iterator (C++ type), 83
 decode_view::operator= (C++ function), 85
 decode_view::range_type (C++ type), 83
 decode_view::sentinel (C++ type), 83
 decode_view::state_type (C++ type), 84
 decode_view::value_type (C++ type), 83
 default_code_point_encoding (C++ class), 370
 default_code_point_encoding_t (C++ type), 370
 default_code_unit_encoding (C++ class), 371
 default_code_unit_encoding_t (C++ type), 372
 default_consteval_code_point_encoding (C++ class), 371
 default_consteval_code_point_encoding_t (C++ type), 371
 default_consteval_code_unit_encoding (C++ class), 372
 default_consteval_code_unit_encoding_t (C++ type), 372
 default_handler (C++ member), 207
 default_handler_t (C++ class), 207
 default_handler_t::error_handler (C++ type), 208
- ## E
- encode, 20
 encode (C++ function), 252–254

encode_into (C++ function), 249, 250
 encode_into_raw (C++ function), 246–248
 encode_iterator (C++ class), 91
 encode_iterator::difference_type (C++ type), 93
 encode_iterator::encode_iterator (C++ function), 93, 94
 encode_iterator::encoding_type (C++ type), 92
 encode_iterator::error_handler_type (C++ type), 92
 encode_iterator::iterator (C++ type), 92
 encode_iterator::iterator_category (C++ type), 92
 encode_iterator::iterator_concept (C++ type), 92
 encode_iterator::operator= (C++ function), 95
 encode_iterator::pointer (C++ type), 93
 encode_iterator::range_type (C++ type), 92
 encode_iterator::reference (C++ type), 93
 encode_iterator::state_type (C++ type), 92
 encode_iterator::value_type (C++ type), 92
 encode_one (C++ function), 260–262
 encode_one_into (C++ function), 256–258
 encode_one_into_raw (C++ function), 255, 256
 encode_one_to (C++ function), 258–260
 encode_result (C++ class), 383
 encode_result::encode_result (C++ function), 383
 encode_result::error_code (C++ member), 384
 encode_result::error_count (C++ member), 384
 encode_result::errors_were_handled (C++ function), 384
 encode_result::input (C++ member), 384
 encode_result::output (C++ member), 384
 encode_result::state (C++ member), 384
 encode_state (C++ class), 359
 encode_state::type (C++ type), 359
 encode_state_t (C++ type), 359
 encode_to (C++ function), 250–252
 encode_view (C++ class), 89
 encode_view::begin (C++ function), 91
 encode_view::encode_view (C++ function), 90, 91
 encode_view::encoding_type (C++ type), 90
 encode_view::end (C++ function), 91
 encode_view::error_handler_type (C++ type), 90
 encode_view::iterator (C++ type), 90
 encode_view::operator= (C++ function), 91
 encode_view::range_type (C++ type), 90
 encode_view::sentinel (C++ type), 90
 encode_view::state_type (C++ type), 90
 encoding, 21
 encoding_error (C++ enum), 372
 encoding_error::incomplete_sequence (C++ enumerator), 373
 encoding_error::insufficient_output_space (C++ enumerator), 373
 encoding_error::invalid_sequence (C++ enumerator), 373
 encoding_error::ok (C++ enumerator), 372
 encoding_rs, 459
 encoding_scheme (C++ class), 134
 encoding_scheme::base (C++ function), 136, 137
 encoding_scheme::code_point (C++ type), 134
 encoding_scheme::code_unit (C++ type), 134
 encoding_scheme::contains_unicode_encoding (C++ function), 137
 encoding_scheme::decode_one (C++ function), 138
 encoding_scheme::decode_state (C++ type), 134
 encoding_scheme::decoded_id (C++ member), 139
 encoding_scheme::encode_one (C++ function), 138
 encoding_scheme::encode_state (C++ type), 135
 encoding_scheme::encoded_id (C++ member), 139
 encoding_scheme::encoding_scheme (C++ function), 135, 136
 encoding_scheme::encoding_type (C++ type), 134
 encoding_scheme::is_decode_injective (C++ type), 135
 encoding_scheme::is_encode_injective (C++ type), 135
 encoding_scheme::max_code_points (C++ member), 139
 encoding_scheme::max_code_units (C++ member), 139
 encoding_scheme::maybe_replacement_code_points (C++ function), 137
 encoding_scheme::maybe_replacement_code_units (C++ function), 137
 encoding_scheme::operator= (C++ function), 136
 encoding_scheme::replacement_code_points (C++ function), 137
 encoding_scheme::replacement_code_units (C++ function), 137
 encoding_scheme::skip_input_error (C++ function), 138
 euc_kr_uhc (C++ member), 140
 execution (C++ member), 142
 execution encoding, 21
 execution_t (C++ class), 142

F

Fast UTF-8, 459
 Fast UTF-8 Validation, 459

G

gb18030 (C++ member), 146
 gbk (C++ member), 149
 glibc-25744, 459
 grapheme cluster, 21

I

ibm_1006_urdu (C++ member), 166
 ibm_424_hebrew_bulletin (C++ member), 166
 ibm_856_hebrew (C++ member), 166
 ibm_866_cyrillic (C++ member), 166
 iconv, 459
 ICU, 459
 indivisible unit of work, 21
 injective, 21
 is_bitwise_transcoding_compatible (C++ class), 369
 is_bitwise_transcoding_compatible_v (C++ member), 369
 is_code_points_maybe_replaceable (C++ class), 364
 is_code_points_maybe_replaceable_v (C++ member), 365
 is_code_points_replaceable (C++ class), 364
 is_code_points_replaceable_v (C++ member), 364
 is_code_units_maybe_replaceable (C++ class), 363
 is_code_units_maybe_replaceable_v (C++ member), 363
 is_code_units_replaceable (C++ class), 363
 is_code_units_replaceable_v (C++ member), 363
 is_decode_injective (C++ class), 362
 is_decode_injective_v (C++ member), 362
 is_decode_state_independent_v (C++ member), 361
 is_encode_injective (C++ class), 362
 is_encode_injective_v (C++ member), 362
 is_encode_state_independent_v (C++ member), 361
 is_ignorable_error_handler (C++ class), 365
 is_ignorable_error_handler_v (C++ member), 365
 is_input_error_skippable (C++ class), 369
 is_input_error_skippable_v (C++ member), 369
 is_self_synchronizing_code (C++ class), 370
 is_self_synchronizing_code_v (C++ member), 370
 is_state_complete (C++ function), 365
 is_state_independent_v (C++ member), 361
 is_transcoding_compatible (C++ class), 368
 is_transcoding_compatible_v (C++ member), 368
 is_unicode_code_point (C++ class), 367
 is_unicode_code_point_v (C++ member), 367
 is_unicode_encoding (C++ class), 366
 is_unicode_encoding_v (C++ member), 366
 is_unicode_scalar_value (C++ class), 367
 is_unicode_scalar_value_v (C++ member), 367
 iso_8859_1 (C++ member), 166
 iso_8859_10 (C++ member), 167
 iso_8859_13 (C++ member), 167
 iso_8859_14 (C++ member), 167
 iso_8859_15 (C++ member), 167

iso_8859_16 (C++ member), 167
 iso_8859_1_1985 (C++ member), 166
 iso_8859_1_1998 (C++ member), 166
 iso_8859_2 (C++ member), 166
 iso_8859_3 (C++ member), 166
 iso_8859_4 (C++ member), 166
 iso_8859_5 (C++ member), 166
 iso_8859_6 (C++ member), 166
 iso_8859_7 (C++ member), 166
 iso_8859_8 (C++ member), 167

K

kamenicky (C++ member), 167
 kazakh_strk1048 (C++ member), 167
 koi8_r (C++ member), 167
 koi8_u (C++ member), 167

L

libogonek, 459
 literal (C++ member), 152
 literal encoding, 21
 literal_t (C++ class), 152
 literal_t::code_point (C++ type), 152
 literal_t::code_unit (C++ type), 152
 literal_t::decode_one (C++ function), 153
 literal_t::decode_state (C++ type), 152
 literal_t::decoded_id (C++ member), 154
 literal_t::encode_one (C++ function), 153
 literal_t::encode_state (C++ type), 152
 literal_t::encoded_id (C++ member), 154
 literal_t::is_decode_injective (C++ type), 152
 literal_t::is_encode_injective (C++ type), 152
 literal_t::is_unicode_encoding (C++ type), 152
 literal_t::literal_t (C++ function), 153
 literal_t::max_code_points (C++ member), 154
 literal_t::max_code_units (C++ member), 154
 literal_t::operator= (C++ function), 153

M

make_decode_state (C++ function), 374
 make_decode_state_with (C++ function), 374
 make_encode_state (C++ function), 374
 make_encode_state_with (C++ function), 374
 max_code_points_v (C++ member), 359
 max_code_units_v (C++ member), 360
 max_recode_code_points_v (C++ member), 360
 max_transcode_code_units_v (C++ member), 360
 mojibake, 21
 mutf8 (C++ member), 155
 mutf8_t (C++ type), 155

N

n2282, 459

nltext (C++ type), 79
 nltext_view (C++ type), 82
 Non-Unicode in C++, 460
 ntext (C++ type), 79
 ntext_view (C++ type), 82

P

p0244, 460
 p1041, 460
 pass_handler (C++ member), 211
 pass_handler_t (C++ class), 211
 petSCII (C++ member), 159
 petSCII_shift (C++ enum), 158
 petSCII_shift::shifted (C++ enumerator), 158
 petSCII_shift::unshifted (C++ enumerator), 158
 petSCII_shifted (C++ member), 167
 petSCII_state (C++ class), 158
 petSCII_unshifted (C++ member), 167
 pivot (C++ class), 372
 pivotless_transcode_result (C++ class), 386
 pivotless_transcode_result::error_code (C++ member), 388
 pivotless_transcode_result::error_count (C++ member), 388
 pivotless_transcode_result::errors_were_handled (C++ function), 388
 pivotless_transcode_result::from_state (C++ member), 388
 pivotless_transcode_result::input (C++ member), 388
 pivotless_transcode_result::output (C++ member), 388
 pivotless_transcode_result::pivotless_transcode_result (C++ function), 386, 387
 pivotless_transcode_result::to_state (C++ member), 388
 propagate_recode_decode_error (C++ function), 406, 407
 propagate_recode_decode_error_with (C++ function), 410, 411
 propagate_recode_encode_error (C++ function), 404, 405
 propagate_recode_encode_error_with (C++ function), 407, 409
 propagate_transcode_decode_error (C++ function), 411, 412
 propagate_transcode_decode_error_with (C++ function), 415, 416
 propagate_transcode_encode_error (C++ function), 413, 414
 propagate_transcode_encode_error_with (C++ function), 417, 418
 punycode (C++ member), 159
 punycode_idna (C++ member), 159

punycode_idna_t (C++ type), 159
 punycode_t (C++ type), 159

R

recode (C++ function), 280–284
 recode_into (C++ function), 271–275
 recode_into_raw (C++ function), 266–270
 recode_iterator (C++ class), 98
 recode_iterator::difference_type (C++ type), 100
 recode_iterator::error_code (C++ function), 103
 recode_iterator::from_encoding (C++ function), 102
 recode_iterator::from_encoding_type (C++ type), 99
 recode_iterator::from_error_handler_type (C++ type), 99
 recode_iterator::from_handler (C++ function), 103
 recode_iterator::from_state (C++ function), 102
 recode_iterator::from_state_type (C++ type), 99
 recode_iterator::iterator_category (C++ type), 99
 recode_iterator::iterator_concept (C++ type), 99
 recode_iterator::iterator_type (C++ type), 99
 recode_iterator::operator* (C++ function), 104
 recode_iterator::operator++ (C++ function), 104
 recode_iterator::operator= (C++ function), 102
 recode_iterator::pivot_error_code (C++ function), 103
 recode_iterator::pointer (C++ type), 100
 recode_iterator::range (C++ function), 103
 recode_iterator::range_type (C++ type), 99
 recode_iterator::recode_iterator (C++ function), 100, 101
 recode_iterator::reference (C++ type), 100
 recode_iterator::to_encoding (C++ function), 102
 recode_iterator::to_encoding_type (C++ type), 99
 recode_iterator::to_error_handler_type (C++ type), 99
 recode_iterator::to_handler (C++ function), 103
 recode_iterator::to_state (C++ function), 102
 recode_iterator::to_state_type (C++ type), 99
 recode_iterator::value_type (C++ type), 100
 recode_one (C++ function), 301–305
 recode_one_into (C++ function), 291–296
 recode_one_into_raw (C++ function), 286–290
 recode_one_to (C++ function), 296–300
 recode_result (C++ class), 393
 recode_result::error_code (C++ member), 395
 recode_result::error_count (C++ member), 395

recode_result::errors_were_handled (C++ function), 394
 recode_result::from_state (C++ member), 394
 recode_result::input (C++ member), 395
 recode_result::output (C++ member), 395
 recode_result::pivot (C++ member), 394
 recode_result::pivot_error_code (C++ member), 394
 recode_result::pivot_error_count (C++ member), 394
 recode_result::recode_result (C++ function), 393
 recode_result::to_state (C++ member), 394
 recode_to (C++ function), 275–280
 recode_view (C++ class), 95
 recode_view::begin (C++ function), 98
 recode_view::end (C++ function), 98
 recode_view::from_encoding_type (C++ type), 96
 recode_view::from_error_handler_type (C++ type), 96
 recode_view::from_state_type (C++ type), 96
 recode_view::iterator (C++ type), 96
 recode_view::range_type (C++ type), 96
 recode_view::recode_view (C++ function), 97
 recode_view::sentinel (C++ type), 96
 recode_view::to_encoding_type (C++ type), 96
 recode_view::to_error_handler_type (C++ type), 96
 recode_view::to_state_type (C++ type), 96
 replacement_handler (C++ member), 211
 replacement_handler_t (C++ class), 212
 replacement_handler_t::operator() (C++ function), 212

S

shift_jis (C++ member), 163
 shift_jis_t (C++ type), 163
 shift_jis_x0208 (C++ member), 163
 skip_handler (C++ member), 213
 skip_handler_t (C++ class), 213
 skip_handler_t::operator() (C++ function), 213
 skip_input_error (C++ function), 402
 skip_utf32_input_error (C++ function), 403
 skip_utf32_with_surrogates_input_error (C++ function), 403
 stateless_count_result (C++ class), 395
 stateless_count_result::count (C++ member), 396
 stateless_count_result::error_code (C++ member), 396
 stateless_count_result::error_count (C++ member), 396
 stateless_count_result::errors_were_handled (C++ function), 396
 stateless_count_result::input (C++ member), 396
 stateless_count_result::stateless_count_result (C++ function), 395
 stateless_decode_result (C++ class), 377
 stateless_decode_result::error_code (C++ member), 379
 stateless_decode_result::error_count (C++ member), 379
 stateless_decode_result::errors_were_handled (C++ function), 378
 stateless_decode_result::input (C++ member), 379
 stateless_decode_result::output (C++ member), 379
 stateless_decode_result::stateless_decode_result (C++ function), 377, 378
 stateless_encode_result (C++ class), 381
 stateless_encode_result::error_code (C++ member), 382
 stateless_encode_result::error_count (C++ member), 382
 stateless_encode_result::errors_were_handled (C++ function), 382
 stateless_encode_result::input (C++ member), 382
 stateless_encode_result::output (C++ member), 382
 stateless_encode_result::stateless_encode_result (C++ function), 381, 382
 stateless_recode_result (C++ class), 391
 stateless_recode_result::error_code (C++ member), 392
 stateless_recode_result::error_count (C++ member), 393
 stateless_recode_result::errors_were_handled (C++ function), 392
 stateless_recode_result::input (C++ member), 392
 stateless_recode_result::output (C++ member), 392
 stateless_recode_result::stateless_recode_result (C++ function), 391, 392
 stateless_transcode_result (C++ class), 384
 stateless_transcode_result::error_code (C++ member), 386
 stateless_transcode_result::error_count (C++ member), 386
 stateless_transcode_result::errors_were_handled (C++ function), 386
 stateless_transcode_result::input (C++ member), 386
 stateless_transcode_result::output (C++ member), 386

stateless_transcode_result::stateless_transcode_result (C++ function), 385
 stateless_validate_result (C++ class), 398
 stateless_validate_result::input (C++ member), 399
 stateless_validate_result::operator bool (C++ function), 398
 stateless_validate_result::stateless_validate_result (C++ function), 398
 stateless_validate_result::valid (C++ member), 399

T

tatar_ansi (C++ member), 167
 tatar_ascii (C++ member), 167
 text (C++ type), 79
 text_view (C++ type), 82
 throw_handler (C++ member), 214
 throw_handler_t (C++ class), 214
 throw_handler_t::operator() (C++ function), 214
 to_name (C++ function), 373
 transcode, 21
 transcode (C++ function), 323–327
 transcode_into (C++ function), 314–318
 transcode_into_raw (C++ function), 309–313
 transcode_iterator (C++ class), 108
 transcode_iterator::difference_type (C++ type), 110
 transcode_iterator::error_code (C++ function), 113
 transcode_iterator::from_encoding (C++ function), 112
 transcode_iterator::from_encoding_type (C++ type), 109
 transcode_iterator::from_error_handler_type (C++ type), 109
 transcode_iterator::from_handler (C++ function), 112
 transcode_iterator::from_state (C++ function), 112
 transcode_iterator::from_state_type (C++ type), 109
 transcode_iterator::iterator_category (C++ type), 109
 transcode_iterator::iterator_concept (C++ type), 109
 transcode_iterator::iterator_type (C++ type), 109
 transcode_iterator::operator* (C++ function), 113
 transcode_iterator::operator++ (C++ function), 113
 transcode_iterator::operator= (C++ function), 112
 transcode_iterator::pivot_error_code (C++ function), 113
 transcode_iterator::pointer (C++ type), 109
 transcode_iterator::range (C++ function), 112, 113
 transcode_iterator::range_type (C++ type), 109
 transcode_iterator::reference (C++ type), 109
 transcode_iterator::to_encoding (C++ function), 112
 transcode_iterator::to_encoding_type (C++ type), 109
 transcode_iterator::to_error_handler_type (C++ type), 109
 transcode_iterator::to_handler (C++ function), 112
 transcode_iterator::to_state (C++ function), 112
 transcode_iterator::to_state_type (C++ type), 109
 transcode_iterator::transcode_iterator (C++ function), 110, 111
 transcode_iterator::value_type (C++ type), 109
 transcode_one (C++ function), 344–348
 transcode_one_into (C++ function), 334–339
 transcode_one_into_raw (C++ function), 329–333
 transcode_one_to (C++ function), 339–343
 transcode_result (C++ class), 389
 transcode_result::error_code (C++ member), 391
 transcode_result::error_count (C++ member), 391
 transcode_result::errors_were_handled (C++ function), 390
 transcode_result::from_state (C++ member), 390
 transcode_result::input (C++ member), 390
 transcode_result::output (C++ member), 391
 transcode_result::pivot (C++ member), 390
 transcode_result::pivot_error_code (C++ member), 390
 transcode_result::pivot_error_count (C++ member), 390
 transcode_result::to_state (C++ member), 390
 transcode_result::transcode_result (C++ function), 389
 transcode_to (C++ function), 318–323
 transcode_view (C++ class), 105
 transcode_view::begin (C++ function), 107, 108
 transcode_view::end (C++ function), 108
 transcode_view::from_encoding_type (C++ type), 106
 transcode_view::from_error_handler_type (C++ type), 106
 transcode_view::from_state_type (C++ type), 106
 transcode_view::iterator (C++ type), 106
 transcode_view::range_type (C++ type), 106
 transcode_view::sentinel (C++ type), 106

- transcode_view::to_encoding_type (C++ type), 106
 transcode_view::to_error_handler_type (C++ type), 106
 transcode_view::to_state_type (C++ type), 106
 transcode_view::transcode_view (C++ function), 106, 107
- ## U
- u16text (C++ type), 79
 u16text_view (C++ type), 82
 u32text (C++ type), 80
 u32text_view (C++ type), 82
 u8text (C++ type), 79
 u8text_view (C++ type), 82
 unicode code point, 21
 unicode scalar value, 22
 unicode_code_point (C++ type), 375
 unicode_scalar_value (C++ type), 376
 utf16 (C++ member), 179
 utf16_be_t (C++ type), 133
 utf16_le_t (C++ type), 132
 utf16_ne_t (C++ type), 133
 utf16_t (C++ type), 179
 utf32 (C++ member), 182
 utf32_be_t (C++ type), 133
 utf32_le_t (C++ type), 133
 utf32_ne_t (C++ type), 133
 utf32_t (C++ type), 182
 utf8 (C++ member), 186
 utf8_t (C++ type), 186
- ## V
- validate_decodable_as (C++ function), 350, 351
 validate_encodable_as (C++ function), 353, 354
 validate_pivotless_transcode_result (C++ class), 400
 validate_pivotless_transcode_result::from_state (C++ member), 401
 validate_pivotless_transcode_result::input (C++ member), 401
 validate_pivotless_transcode_result::operator bool (C++ function), 400
 validate_pivotless_transcode_result::to_state (C++ member), 401
 validate_pivotless_transcode_result::valid (C++ member), 401
 validate_pivotless_transcode_result::validate (C++ function), 400
 validate_result (C++ class), 399
 validate_result::input (C++ member), 400
 validate_result::operator bool (C++ function), 399
 validate_result::state (C++ member), 400
 validate_result::valid (C++ member), 400
 validate_result::validate_result (C++ function), 399
 validate_transcodable_as (C++ function), 355–357
 validate_transcode_result (C++ class), 401
 validate_transcode_result::from_state (C++ member), 402
 validate_transcode_result::input (C++ member), 402
 validate_transcode_result::operator bool (C++ function), 401
 validate_transcode_result::pivot (C++ member), 402
 validate_transcode_result::to_state (C++ member), 402
 validate_transcode_result::valid (C++ member), 402
 validate_transcode_result::validate_transcode_result (C++ function), 401
- ## W
- wide execution encoding, 22
 wide literal encoding, 22
 wide_execution (C++ member), 190
 wide_execution_t (C++ class), 190
 wide_literal (C++ member), 200
 wide_literal_t (C++ class), 200
 wide_literal_t::code_point (C++ type), 200
 wide_literal_t::code_unit (C++ type), 200
 wide_literal_t::decode_one (C++ function), 201
 wide_literal_t::decode_state (C++ type), 200
 wide_literal_t::decoded_id (C++ member), 202
 wide_literal_t::encode_one (C++ function), 201
 wide_literal_t::encode_state (C++ type), 200
 wide_literal_t::encoded_id (C++ member), 202
 wide_literal_t::is_decode_injective (C++ type), 200
 wide_literal_t::is_encode_injective (C++ type), 200
 wide_literal_t::is_unicode_encoding (C++ type), 200
 wide_literal_t::max_code_points (C++ member), 202
 wide_literal_t::max_code_units (C++ member), 202
 wide_literal_t::operator= (C++ function), 201
 wide_literal_t::wide_literal_t (C++ function), 201
 wide_pivotless_transcode_result (C++ class), 401
 wide_utf16 (C++ member), 179
 wide_utf16_t (C++ type), 179
 wide_utf32 (C++ member), 182
 wide_utf32_t (C++ type), 182
 windows_1251 (C++ member), 168
 windows_1252 (C++ member), 168

windows_1253 (C++ member), 168
windows_1254 (C++ member), 168
windows_1255 (C++ member), 168
windows_1256 (C++ member), 168
windows_1257 (C++ member), 168
windows_1258 (C++ member), 168
windows_437_dos_latin_us (C++ member), 167
windows_865_dos_nordic (C++ member), 168
windows_874 (C++ member), 168
wltex (C++ type), 79
wltex_view (C++ type), 82
wtext (C++ type), 79
wtext_view (C++ type), 82
wtf8 (C++ member), 203
wtf8_t (C++ type), 203